

# SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

## Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities\*

10-20-2000 Rev. 0  
12-5-2003 Rev. 1  
7-14-2006 Rev 2  
2-2-2018 Rev 3  
XX-XX-2019 Rev 4

Equipment or Process: Printing (Graphic Arts)

Subcategory	Criteria Pollutants					
	VOC	NO <sub>x</sub>	SO <sub>x</sub>	CO	PM <sub>10</sub>	Inorganic
Flexographic	Inks with ≤ 1.5 Lbs VOC/Gal, Less Water and Less Exempt Compounds (1990); or use of UV/EB or water-based inks/coatings ≤ 180 g VOC/L. Compliance with SCAQMD Rules 1130 and 1171 (2-2-2018)					
Control	For add-on control required by SCAQMD Rule 1130(c)(5) or other District requirement: EPA M. 204 Permanent Total Enclosure (100% collection) vented to <del>afterburner</del> <u>RTO</u> with 95% overall control efficiency; Combustion Chamber: Temp ≥ 1500°F <sup>1</sup> , Retention Time > 0.3 seconds (2-2-2018)	Compliance with SCAQMD Rule 1147 at time of applicability (2-2-2018)				
Letterpress	Compliance with SCAQMD Rules 1130 and 1171 (12-5-2003)					
Lithographic or Offset, Heatset	Low VOC Fountain Solution (≤ 8% by Vol. VOC); Low VOC (≤ 100 g/l) Blanket and Roller Washes; Oil-Based or UV-Curable Inks; and Compliance with SCAQMD Rules 1130 and 1171 ( <del>7-14-2006</del> )(2-2-18)				<u>Venting to an afterburner (≥ 0.3 sec. Retention Time at ≥ 1400 °F; 95% Overall Efficiency) (10-20-2000)</u>	
Control	Oven Venting to an Afterburner (≥ 0.3 Sec.	<u>Compliance</u>				

\* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

**SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT**  
**Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities\***

Subcategory	Criteria Pollutants					
	VOC	NO <sub>x</sub>	SO <sub>x</sub>	CO	PM <sub>10</sub>	Inorganic
	Retention Time at $\geq 1400^{\circ}\text{F}$ ; 95% Overall Efficiency) (10-20-2000)	<u>with SCAQMD Rule 1147</u>				

(Continued on next page)

Lithographic or Offset, Non-Heatset	<del>Same As Above</del> <u>Low VOC Fountain Solution (<math>\leq 8\%</math> by Vol. VOC); Low VOC (<math>\leq 100</math> g/l) Blanket and Roller Washes; Oil-Based or UV-Curable Inks; and Compliance with SCAQMD Rules 1130 and 1171. (XX-XX-2019)</u>					
Rotogravure or Gravure—Publication and Packaging	Compliance with SCAQMD Rules 1130 and 1171 (10-20-2000)					
Screen Printing and Drying	Compliance with SCAQMD Rules 1130.1 and 1171; or use of Rule 1130.1 and 1171 compliant UV/EB or water-based inks/coatings. (2-2-2018).					

1) or temperature demonstrating equivalent overall control efficiency in a District-approved source test.

\* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions