SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

10-20-2000 Rev. 0 12-5-2003 Rev. 1 7-14-2006 Rev 2 2-2-2018 Rev 3 XX-XX-2019 Rev 4

Equipment or Process: Printing (Graphic Arts)

Criteria Pollutants						
Subcategory	VOC	NOx	SOx	CO	PM10	Inorganic
Flexographic	Inks with ≤ 1.5 Lbs VOC/Gal, Less Water and Less Exempt Compounds (1990); or use of UV/EB or water-based inks/coatings ≤ 180 g VOC/L. Compliance with SCAQMD Rules 1130 and 1171 (2-2-2018)					
Control	For add-on control required by SCAQMD Rule 1130(c)(5) or other District requirement: EPA M. 204 Permanent Total Enclosure (100% collection) vented to <u>afterburner RTO</u> with 95% overall control efficiency; Combustion Chamber: Temp ≥ 1500°F¹, Retention Time > 0.3 seconds (2-2-2018)	Compliance with SCAQMD Rule 1147 at time of applicability (2- 2-2018)				
Letterpress	Compliance with SCAQMD Rules 1130 and 1171 (12-5-2003)					
Lithographic or Offset, Heatset	Low VOC Fountain Solution (≤ 8% by Vol. VOC); Low VOC (≤ 100 g/l) Blanket and Roller Washes; Oil-Based or UV-Curable Inks; and Compliance with SCAQMD Rules 1130 and 1171 (7-14-2006) (2-2-18)				Venting to an afterburner (≥ 0.3 sec. Retention Time at ≥ 1400 °F; 95% Overall Efficiency) (10-20-2000)	
Control	Oven Venting to an Afterburner (≥ 0.3 Sec.	Compliance				

^{*} Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

	Criteria Pollutants					
Subcategory	VOC	NOx	SOx	CO	PM10	Inorganic
	Retention Time at $\geq 1400 {}^{0}\text{F}$; 95% Overall	with SCAQMD				
	Efficiency)	Rule 1147				
	(10-20-2000)					

Lithographic or	Same As Above			
Offset, Non-	Low VOC Fountain Solution (\leq 8% by Vol.			
Heatset	VOC); Low VOC (≤ 100 g/l) Blanket and Roller			
	Washes; Oil-Based or UV-Curable Inks; and			
	Compliance with SCAQMD Rules 1130 and 1171.			
	(XX-XX-2019)			
Rotogravure or	Compliance with SCAQMD Rules 1130 and 1171			
Gravure—	(10-20-2000)			
Publication and				
Packaging				
Screen Printing	Compliance with SCAQMD Rules 1130.1 and			
and Drying	1171; or use of Rule 1130.1 and 1171 compliant			
	UV/EB or water-based inks/coatings. (2-2-2018).			

¹⁾ or temperature demonstrating equivalent overall control efficiency in a District-approved source test.

^{*} Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions