



Part D, SCAQMD BACT Determination

Source Type: **Minor**

Application No.: **548863**

Equipment Category: **Food Oven**

Equipment Subcategory: **Ribbon Burner \leq 500°F**

Date: **March 24, 2017**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: International Multifood		B. MODEL: 1400
C. DESCRIPTION: Griddle Type oven with ribbon burners		
D. FUNCTION: Food oven with griddle type trays used to bake English muffins		
E. SIZE/DIMENSIONS/CAPACITY: 6' W X 70'L x 5'-4"H		
COMBUSTION SOURCES		
F. MAXIMUM HEAT INPUT: 2.59 MMBtu/hr		
G. BURNER INFORMATION		
TYPE	INDIVIDUAL HEAT INPUT	NUMBER
FLYNN MODEL 122HN SERIES 856	.	63
H. PRIMARY FUEL: NATURAL GAS		I. OTHER FUEL:
J. OPERATING SCHEDULE: 24 HRS/DAY 7 DAYS/WEEK 52 WKS/YR		
K. EQUIPMENT COST: TBD		
L. EQUIPMENT INFORMATION COMMENTS: PERMITTED LIMIT OF < 49 LB VOC/DAY		

2. COMPANY INFORMATION

A. COMPANY: Aryzta, LLC		B. FAC ID: 173864
C. ADDRESS: 1220 S. Baker St. CITY: Ontario STATE: CA ZIP: 91761		D. NAICS CODE: 311812
E. CONTACT PERSON: Michael Wu		F. TITLE: Asst Dir. of Engineering
G. PHONE NO.: 714-256-6900	H. EMAIL: michael.wu@aryzta.com	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: OTHER
C. SCAQMD ENGINEER: Tracy Nguyen	
D. PERMIT INFORMATION: PC ISSUANCE DATE: 9/4/13 P/O NO.: G26836 PO ISSUANCE DATE: 9/4/2013	
E. START-UP DATE:	
F. OPERATIONAL TIME: > 5years	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM₁₀	INORGANIC
BACT Limit		30 ppmvd	Natural Gas	Compliance with SCAQMD Rule 1153.1	Natural Gas	
Averaging Time		1 HR				
Correction		3% O2				
B. OTHER BACT REQUIREMENTS:						
C. BASIS OF THE BACT/LAER DETERMINATION: Achieved in Practice/New Technology						
D. EMISSION INFORMATION COMMENTS: Enter any additional comments regarding Emissions Information.						

5. CONTROL TECHNOLOGY

A. MANUFACTURER:		B. MODEL:	
C. DESCRIPTION:			
D. SIZE/DIMENSIONS/CAPACITY:			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. PC ISSUANCE DATE: PO NO.: PO ISSUANCE DATE:			
F. REQUIRED CONTROL EFFICIENCIES:			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	%	%	%
NO _x	%	%	%
SO _x	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS .			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source Tests R12019 and R11208
B. DATE(S) OF SOURCE TEST: 3/9/2011 and 11/9/2011 when facility was named Fresh Start Bakeries (Fac ID: 149457) and Application # 513897
C. COLLECTION EFFICIENCY METHOD:
D. COLLECTION EFFICIENCY PARAMETERS:
E. SOURCE TEST/PERFORMANCE DATA: CO ₂ equivalency used due to high O ₂ content, highest zone concentration 27.76 ppmvd NO _x @3%O ₂ .
F. TEST OPERATING PARAMETERS AND CONDITIONS: Test conducted during "normal operations."
G. TEST METHODS (SPECIFY AGENCY): SCAQMD Method 100.1

H. MONITORING AND TESTING REQUIREMENTS:
I. DEMONSTRATION OF COMPLIANCE COMMENTS:

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT: 000255	B. CCAT:	C. APPLICATION TYPE CODE: 40	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	F. SOURCE TEST ID(S): R12019, R11208	
G. SCAQMD SOURCE SPECIFIC RULES: 1153, 1153.1			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5. HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:



Part D, SCAQMD BACT Determination

Source Type: **Minor**
 Application No.: **548869**
 Equipment Category: **Food Ovens**
 Equipment Subcategory: **Ribbon Burners with CatOx**
 Date: **March 24, 2017**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: Baking Technology (2 identical ovens)		B. MODEL: Baketech Maxisaver Bun Oven
C. DESCRIPTION: Two identical food ovens vented to a 2.7 MMBtu/hr Catalytic Oxidizer		
D. FUNCTION: Two food oven with ribbon burners used to bake buns		
E. SIZE/DIMENSIONS/CAPACITY: 33'-0" L X 48'-4" W X 11'-0"H		
COMBUSTION SOURCES		
F. MAXIMUM HEAT INPUT: 7.3 MMBtu/hr each oven		
G. BURNER INFORMATION		
TYPE	INDIVIDUAL HEAT INPUT	NUMBER
FLYNN 1622HN	.	24 each oven
MAXON MPAKT EB4	2.7 MMBtu/hr	1 Cat Ox
H. PRIMARY FUEL: NATURAL GAS	I. OTHER FUEL:	
J. OPERATING SCHEDULE: 24 HRS/DAY 7 DAYS/WEEK 52 WKS/YR		
K. EQUIPMENT COST: TBD		
L. EQUIPMENT INFORMATION COMMENTS: TEMP RANGE $\leq 500^{\circ}\text{F}$		

2. COMPANY INFORMATION

A. COMPANY: Aryzta, LLC		B. FAC ID: 173864
C. ADDRESS: 1220 S. Baker St. CITY: Ontario STATE: CA ZIP: 91761		D. NAICS CODE:
E. CONTACT PERSON: Michael Wu		F. TITLE: Asst. Dir. of Engineering
G. PHONE NO.: 714-256-6900	H. EMAIL: michael.wu@aryzta.com	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: OTHER
C. SCAQMD ENGINEER: Marilyn Potter	
D. PERMIT INFORMATION: PC ISSUANCE DATE: P/O NO.: G14787 PO ISSUANCE DATE: 9/13/2013	
E. START-UP DATE:	
F. OPERATIONAL TIME: > 9 years. Prev. operated under Fresh Start Bakeries	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM₁₀	INORGANIC
BACT Limit	95% overall control (mass basis)	30 ppmvd (both ovens and Catalytic Oxidizer)	Natural Gas	Compliance with SCAQMD Rules 407 and 1153.1	Natural Gas	
Averaging Time	1 HR	1 HR				
Correction		3% O2				
B. OTHER BACT REQUIREMENTS:						
C. BASIS OF THE BACT/LAER DETERMINATION: Achieved in Practice/New Technology						
D. EMISSION INFORMATION COMMENTS: Enter any additional comments regarding Emissions Information.						

5. CONTROL TECHNOLOGY

A. MANUFACTURER: CSM Worldwide		B. MODEL: 180A	
C. DESCRIPTION: Catalytic oxidizer used to control VOC emissions vented from two burners			
D. SIZE/DIMENSIONS/CAPACITY: 25 Catalyst module with 2.7 MMBtu/hr			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. 548869 PC ISSUANCE DATE: PO NO.: G27030 PO ISSUANCE DATE: 9/13/2016			
F. REQUIRED CONTROL EFFICIENCIES:			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	95%	%	%
NO _x	%	%	%
SO _x	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS. Minimum catalyst inlet temperature 600°F			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source Test PR07086
B. DATE(S) OF SOURCE TEST: 4/3/2011 NO _x cat ox burner (Appl file 518219), NO _x Ovens 1 and 2 (Appl file 460942, 460943) – 9/24/2007, VOC control of cat ox (Appl file 460945) - 9/20/2007.
C. COLLECTION EFFICIENCY METHOD:
D. COLLECTION EFFICIENCY PARAMETERS:
E. SOURCE TEST/PERFORMANCE DATA: 96.6% overall VOC control eff. Highest concentration 28.2 ppmvd NO _x @ 3% O ₂
F. TEST OPERATING PARAMETERS AND CONDITIONS: Test conducted during normal load.
G. TEST METHODS (SPECIFY AGENCY): SCAQMD Methods 100.1, 25.1, 25.3

H. MONITORING AND TESTING REQUIREMENTS:

I. DEMONSTRATION OF COMPLIANCE COMMENTS:

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT: 000255	B. CCAT: 16	C. APPLICATION TYPE CODE: 30	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	F. SOURCE TEST ID(S): PR07086	
G. SCAQMD SOURCE SPECIFIC RULES: 1153, 1153.1			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5: HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:



Part D, SCAQMD BACT Determination

Source Type: **Minor**
Application No.: **548341**
Equipment Category: **Flexographic Printing Press**
Equipment Subcategory: **w/ Regenerative Thermal Oxidizer**
Date: **March 28, 2017**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: Hot Jin Ironworks		B. MODEL: HJ-222
C. DESCRIPTION: Flexographic Printing Press 4 color. Demonstrates compliance with Rule 1130(c)(1) through provisions of 1130(c)(5).		
D. FUNCTION: Printing of food packaging		
E. SIZE/DIMENSIONS/CAPACITY: Two identical presses contained in enclosure. Second press operating under Appl. 548337		
COMBUSTION SOURCES		
F. MAXIMUM HEAT INPUT: Press electric heater; RTO 1.35 MMBtu/hr		
G. BURNER INFORMATION		
TYPE	INDIVIDUAL HEAT INPUT	NUMBER
MAXON KINEDIZER	1.35 MMBtu/hr	1
H. PRIMARY FUEL: NATURAL GAS		I. OTHER FUEL:
J. OPERATING SCHEDULE: 24 HRS/DAY 5 DAYS/WEEK 52 WKS/YR		
K. EQUIPMENT COST: TBD		
L. EQUIPMENT INFORMATION COMMENTS:		

2. COMPANY INFORMATION

A. COMPANY: Asia Plastics		B. FAC ID: 103149
C. ADDRESS: 9347 Rush St. CITY: S. El Monte STATE: CA ZIP: 91733		D. NAICS CODE: 32311
E. CONTACT PERSON: Kent Ung		F. TITLE: President
G. PHONE NO.: 626-448-8100	H. EMAIL: asiaplasticsinc@yahoo.com	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: NEW CONSTRUCTION
C. SCAQMD ENGINEER: Farah Milner	
D. PERMIT INFORMATION: PC ISSUANCE DATE: 7/10/13 P/O NO.: G43434 PO ISSUANCE DATE: 10/21/2016	
E. START-UP DATE:	
F. OPERATIONAL TIME: 12/9/2013 source test date. > 3 years	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM₁₀	INORGANIC
BACT Limit	Overall Control Efficiency 95%	RTO: Compliance with SCAQMD Rule 1147				
Averaging Time	1 HR	30 MIN				
Correction	Mass basis	@ 3% O ₂				
B. OTHER BACT REQUIREMENTS: Method 204 Permanent Total Enclosure, Combustion Chamber Temperature $\geq 1500^{\circ}\text{F}$, Chamber Retention Time ≥ 0.3 seconds, chamber temperature interlock system						
C. BASIS OF THE BACT/LAER DETERMINATION: Achieved in Practice/New Technology						
D. EMISSION INFORMATION COMMENTS: Flexographic press has an electric heater						

5. CONTROL TECHNOLOGY

A. MANUFACTURER: Ship and Shore		B. MODEL: SSE-3K-95X-RTO	
C. DESCRIPTION: RTO to vent and combust VOC emissions from a flexographic printing press			
D. SIZE/DIMENSIONS/CAPACITY: 1.35 MMBtu/hr natural gas fired with two ceramic heat exchanger beds			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. 548337 PC ISSUANCE DATE: 7/10/13 PO NO.: G43432 PO ISSUANCE DATE: 10/21/2016			
F. REQUIRED CONTROL EFFICIENCIES:			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	95%	95%	100%
NO _x	%	%	%
SO _x	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS NO _x emissions in compliance with SCAQMD Rule 1147			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source Test
B. DATE(S) OF SOURCE TEST: December 9, 2013
C. COLLECTION EFFICIENCY METHOD: EPA Method 204
D. COLLECTION EFFICIENCY PARAMETERS: PTE Static Pressure ≤ 0.01 " H ₂ O
E. SOURCE TEST/PERFORMANCE DATA: VOC: Inlet 1.5 lb C1/hr, Exhaust 0.075 lb C/hr, Exhaust 0.081 lb VOC/hr. NO _x : Startup 0.064 lb NO _x /hr, Normal 0.026 lb NO _x /hr
F. TEST OPERATING PARAMETERS AND CONDITIONS: RTO Startup Burner at 99.9%, Burner during normal operation 52-66%; Oxidizer inlet 2730 acfm; oxidizer exh 3680 acfm; Press 1 1100 ft/hr; Press 2 7000 ft/hr
G. TEST METHODS (SPECIFY AGENCY): SCAQMD 25.1, 25.3, 100.1

H. MONITORING AND TESTING REQUIREMENTS:
I. DEMONSTRATION OF COMPLIANCE COMMENTS: Rule 1130 minimum requirement is 70% overall control, equipment permitted at 95% overall control

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT: 000276	B. CCAT: 12	C. APPLICATION TYPE CODE: 10	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	F. SOURCE TEST ID(S):	
G. SCAQMD SOURCE SPECIFIC RULES:			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5. HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:



Part D, SCAQMD BACT Determination

Source Type: **Minor**
Application No.: **515931**
Equipment Category: **Heatset Lithographic Printing Press**
Equipment Subcategory: **w/ Regenerative Thermal Oxidizer**
Date: **March 28, 2017**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: Beiren		B. MODEL: 3845
C. DESCRIPTION: Heatset lithographic press with two Megtec 3.2 MMBtu/hr ovens vented to a 1.2 MMBtu/hr Adwest RTO.		
D. FUNCTION: Printing of newspaper inserts		
E. SIZE/DIMENSIONS/CAPACITY: Press: 8 color 38" wide, RTO two ceramic heat exchangers and a 40 HP exhaust blower		
COMBUSTION SOURCES		
F. MAXIMUM HEAT INPUT: Press: 6.4 MMBtu/hr; RTO 1.2 MMBtu/hr		
G. BURNER INFORMATION		
TYPE	INDIVIDUAL HEAT INPUT	NUMBER
MAXON CYCLOMAX	1.6 MMBtu/hr	4
MAXON KINEMAX	1.2 MMBtu/hr	1
H. PRIMARY FUEL: NATURAL GAS		I. OTHER FUEL:
J. OPERATING SCHEDULE: 24 HRS/DAY 7 DAYS/WEEK 52 WKS/YR		
K. EQUIPMENT COST: TBD		
L. EQUIPMENT INFORMATION COMMENTS:		

2. COMPANY INFORMATION

A. COMPANY: Freedom Communications		B. FAC ID: 81797
C. ADDRESS: 1701 S. Lewis CITY: Anaheim STATE: CA ZIP: 92801		D. NAICS CODE: 511110
E. CONTACT PERSON: Greg Engler		F. TITLE: Pressroom Mgr
G. PHONE NO.: 714-953-7882	H. EMAIL:	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: NEW CONSTRUCTION
C. SCAQMD ENGINEER: Emmanuel Quizon	
D. PERMIT INFORMATION: PC ISSUANCE DATE: P/O NO.: G17024 PO ISSUANCE DATE: 3/6/2012	
E. START-UP DATE:	
F. OPERATIONAL TIME: 11/8/2007 source test date. > 9 years	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM₁₀	INORGANIC
BACT Limit	Overall Control Efficiency 99%	Ovens:30 ppmv RTO: Compliance with SCAQMD Rule 1147				
Averaging Time	1 HR	30 MIN				
Correction	Mass basis	All @ 3% O ₂				
B. OTHER BACT REQUIREMENTS: Combustion Chamber Temperature $\geq 1595^{\circ}\text{F}$, Chamber Retention Time ≥ 0.3 seconds, chamber temperature interlock system. Control efficiency only applies to ink usage (permitted condition)						
C. BASIS OF THE BACT/LAER DETERMINATION: Achieved in Practice/New Technology						
D. EMISSION INFORMATION COMMENTS: Equipment complies with VOC limits through provisions of SCAQMD Rule 1130(c)(5).						

5. CONTROL TECHNOLOGY

A. MANUFACTURER: Adwest		B. MODEL: RETOX 4.0 RTO95	
C. DESCRIPTION: RTO vents and combust VOC emissions from a lithographic printing press			
D. SIZE/DIMENSIONS/CAPACITY: 1.20 MMBtu/hr natural gas fired with two ceramic heat exchanger beds			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. 460266 PC ISSUANCE DATE: PO NO.: F99092 PO ISSUANCE DATE: 9/18/2008			
F. REQUIRED CONTROL EFFICIENCIES:			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	99%	99.5%	99.5%
NO _x	%	%	%
SO _x	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS NO _x emissions in compliance with SCAQMD Rule 1147. 99.5% collection efficiency assigned based on 1997 SCAQMD Compliance Advisory. 99% overall control efficiency chosen by applicant.			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source Test
B. DATE(S) OF SOURCE TEST: December 9, 2013
C. COLLECTION EFFICIENCY METHOD: Smoke Test
D. COLLECTION EFFICIENCY PARAMETERS: 99.5% collection efficiency assigned based on SCAQMD Permitting policy. Smoke test was conducted to verify collection of process air. Collection efficiency only applies to ink usage (permitted condition)
E. SOURCE TEST/PERFORMANCE DATA: Oven 19.8ppmvd NO _x @3% O ₂ . VOC 99.77% Dest. Eff, 99.27% overall eff.
F. TEST OPERATING PARAMETERS AND CONDITIONS:
G. TEST METHODS (SPECIFY AGENCY): SCAQMD 25.1, 25.3, 100.1
H. MONITORING AND TESTING REQUIREMENTS:
I. DEMONSTRATION OF COMPLIANCE COMMENTS:

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT: 000272	B. CCAT: 12	C. APPLICATION TYPE CODE: 10	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	F. SOURCE TEST ID(S):	
G. SCAQMD SOURCE SPECIFIC RULES:			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5. HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:



Part D, SCAQMD BACT Determination

Source Type: **Minor**
 Application No.: **487295**
 Equipment Category: **Food Oven**
 Equipment Subcategory: **Direct Fired**
 Date: **March 24, 2017**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: Werner Ppfleiderer		B. MODEL: 1F62837/1
C. DESCRIPTION: Two zone 48" wide oven		
D. FUNCTION: Food oven with low NOx burners used to bake almond cookies		
E. SIZE/DIMENSIONS/CAPACITY: 20'-7" L X 7'-4" W X 6'-9"H		
COMBUSTION SOURCES		
F. MAXIMUM HEAT INPUT: 2.4 MMBtu/hr		
G. BURNER INFORMATION		
TYPE	INDIVIDUAL HEAT INPUT	NUMBER
LOW NOX	1.2 MMBtu/hr	2
H. PRIMARY FUEL: NATURAL GAS		I. OTHER FUEL:
J. OPERATING SCHEDULE: 24 HRS/DAY 7 DAYS/WEEK 52 WKS/YR		
K. EQUIPMENT COST: TBD		
L. EQUIPMENT INFORMATION COMMENTS: TEMP RANGE 500-560°F		

2. COMPANY INFORMATION

A. COMPANY: JSL Foods Inc.		B. FAC ID: 136986
C. ADDRESS: 2222 ½ Davie Ave. CITY: Los Angeles STATE: CA ZIP: 90040		D. NAICS CODE:
E. CONTACT PERSON: Gregorio Torres		F. TITLE: Plant Mgr
G. PHONE NO.: 323-797-9999	H. EMAIL: gtorres@jslfoods.com	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: PO NO PC
C. SCAQMD ENGINEER: Kim Le	
D. PERMIT INFORMATION: PC ISSUANCE DATE: P/O NO.: G5819 PO ISSUANCE DATE: 1/1/2010	
E. START-UP DATE:	
F. OPERATIONAL TIME: > 7 years	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM ₁₀	INORGANIC
BACT Limit		30 ppmvd	Natural Gas	Compliance with SCAQMD Rules 407 and 1153.1	Natural Gas	
Averaging Time		1 HR				
Correction		3% O2				
B. OTHER BACT REQUIREMENTS:						
C. BASIS OF THE BACT/LAER DETERMINATION: Achieved in Practice/New Technology						
D. EMISSION INFORMATION COMMENTS: Enter any additional comments regarding Emissions Information.						

5. CONTROL TECHNOLOGY

A. MANUFACTURER:		B. MODEL:	
C. DESCRIPTION:			
D. SIZE/DIMENSIONS/CAPACITY:			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. PC ISSUANCE DATE: PO NO.: PO ISSUANCE DATE:			
F. REQUIRED CONTROL EFFICIENCIES:			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	%	%	%
NO _x	%	%	%
SO _x	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS.			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source Tests PR10302
B. DATE(S) OF SOURCE TEST: 10/22/2010
C. COLLECTION EFFICIENCY METHOD:
D. COLLECTION EFFICIENCY PARAMETERS:
E. SOURCE TEST/PERFORMANCE DATA: 2 zones, Highest zone concentration 22.3 ppmvd NO _x , 111 ppmvd CO both at 3%O ₂ .
F. TEST OPERATING PARAMETERS AND CONDITIONS: Test conducted during normal load.
G. TEST METHODS (SPECIFY AGENCY): SCAQMD M. 100.1

H. MONITORING AND TESTING REQUIREMENTS:
I. DEMONSTRATION OF COMPLIANCE COMMENTS:

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT: 000255	B. CCAT:	C. APPLICATION TYPE CODE: 30	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	F. SOURCE TEST ID(S): PR10302	
G. SCAQMD SOURCE SPECIFIC RULES: 1153, 1153.1			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5. HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:



Part D: NonSCAQMD BACT Determination

Source Type: **Minor**
Application No.: **533039**
Equipment Category: **I.C. Engine, Stationary, Non-Emergency, Electrical Generators**
Equipment Subcategory:

Date: **April 26, 2012**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: GM/Tecogen		B. MODEL: TECODRIVE 7400	
C. DESCRIPTION: Spark Ignition, Rich Burn, Four-Cycle, 8 cylinders.			
D. FUNCTION: On-site electrical power generation			
E. SIZE/DIMENSIONS/CAPACITY: 108 HP, driving 75 KW generator			
COMBUSTION SOURCES			
F. MAXIMUM HEAT INPUT: ---			
G. BURNER INFORMATION			
TYPE	INDIVIDUAL HEAT INPUT	NUMBER	
---	<input type="text"/>	<input type="text"/>	
H. PRIMARY FUEL: NATURAL GAS		I. OTHER FUEL: ---	
J. OPERATING SCHEDULE: 24 HRS/DAY 7 DAYS/WEEK 52 WKS/YR			
K. EQUIPMENT COST: Not Available			
L. EQUIPMENT INFORMATION COMMENTS: Engine is equipped with emission control consisting of non-selective catalytic converter.			

2. COMPANY INFORMATION

A. COMPANY: Lake Forest II Master Assoc.		B. FAC ID: 170558	
C. ADDRESS: 24752 Toledo Way CITY: Lake Forest STATE: CA ZIP: 92630		D. NAICS CODE:	
E. CONTACT PERSON: JoAnn Burrows		F. TITLE: General Manager	
G. PHONE NO.: 949-586-0860		H. EMAIL: jburrows@lf2.org	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: PO NO PC
C. SCAQMD ENGINEER: Chingli Lin	
D. PERMIT INFORMATION: PC ISSUANCE DATE: 4/26/12 P/O NO.: G17651 PO ISSUANCE DATE: 4/26/2012	
E. START-UP DATE: 1/29/2013	
F. OPERATIONAL TIME: 4+ years	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM₁₀	INORGANIC
BACT Limit	0.1 LB/MW-HR	0.07 LB/MW-HR		0.2 LB/MW-HR	RULE 404	
Averaging Time	Per 1110.2 requirements	Per 1110.2 requirements		Per 1110.2 requirements		
Correction						
B. OTHER BACT REQUIREMENTS: Compliance with emission requirements of Rule 1110.2(d)(1)(L)						
C. BASIS OF THE BACT/LAER DETERMINATION: Compliance with Rule 1110.2(d)(1)(L) and achieved in practiceOther (add comment)						
D. EMISSION INFORMATION COMMENTS: Enter any additional comments regarding Emissions Information.						

5. CONTROL TECHNOLOGY

A. MANUFACTURER: SUD-CHEMIE NSCR		B. MODEL: ENVICAT 7319	
C. DESCRIPTION: Non-Selective Catalytic Converter with automatic air/fuel ratio controller, Tecogen, model Teconet Stoichiometric AFRC.			
D. SIZE/DIMENSIONS/CAPACITY: ---			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. 533039 PC ISSUANCE DATE: 4/26/12 PO NO.: G17651 PO ISSUANCE DATE: 4/26/2012			
F. REQUIRED CONTROL EFFICIENCIES: Maintain compliance with Rule 1110.2(d)(1)(L) for engine emissions.			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	%	%	%
NO _x	%	%	%
SO _x	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS two stage system with three way catalyst followed by air injection and additional catalyst. Manages air/fuel ratio slightly rich of stoichiometric via oxygen sensors located before and after the first stage three way catalyst.			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source test.
B. DATE(S) OF SOURCE TEST: January 29, 2013
C. COLLECTION EFFICIENCY METHOD:
D. COLLECTION EFFICIENCY PARAMETERS:
E. SOURCE TEST/PERFORMANCE DATA: NO _x = 0.027 lb/MWe-hr, CO = 0.067 lb/MWe-hr, VOC = 0.04 lb/MWe-hr.
F. TEST OPERATING PARAMETERS AND CONDITIONS:
G. TEST METHODS (SPECIFY AGENCY): NO _x , CO and O ₂ determined using SCAQMD Method 100.1. VOC determined using SCAQMD Method 25.3.

H. MONITORING AND TESTING REQUIREMENTS: Compliance with Rule 1110.2(f)
I. DEMONSTRATION OF COMPLIANCE COMMENTS:

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT:	B. CCAT:	C. APPLICATION TYPE CODE:	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input type="checkbox"/>	F. SOURCE TEST ID(S):	
G. SCAQMD SOURCE SPECIFIC RULES:			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5. HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:



Part D, SCAQMD BACT Determination

Source Type: **Minor**
Application No.: **475618**
Equipment Category: **Food Oven**
Equipment Subcategory: **Ribbon Burner > 500°F**
Date: **March 24, 2017**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: Tecnomaz		B. MODEL: T-1200 NG
C. DESCRIPTION: Corn Tortilla Oven No. 1		
D. FUNCTION: Food oven with ribbon type burners used to bake corn tortillas		
E. SIZE/DIMENSIONS/CAPACITY: 20'-7" L X 7'-4" W X 6'-9"H		
COMBUSTION SOURCES		
F. MAXIMUM HEAT INPUT: 2.7 MMBtu/hr		
G. BURNER INFORMATION		
TYPE	INDIVIDUAL HEAT INPUT	NUMBER
RIBBON	0.079 MMBtu/hr	34
H. PRIMARY FUEL: NATURAL GAS		I. OTHER FUEL:
J. OPERATING SCHEDULE: 24 HRS/DAY 7 DAYS/WEEK 52 WKS/YR		
K. EQUIPMENT COST: TBD		
L. EQUIPMENT INFORMATION COMMENTS:		

2. COMPANY INFORMATION

A. COMPANY: Mission Foods		B. FAC ID: 153640
C. ADDRESS: 14200 Arminta St. CITY: Panorama City STATE: CA ZIP: 91402		D. NAICS CODE: 31183
E. CONTACT PERSON: Kelli Kimberly		F. TITLE: Environmental Director
G. PHONE NO.: 909-980-3566	H. EMAIL: kelli_kimberly@missionfoods.com	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: NEW CONSTRUCTION
C. SCAQMD ENGINEER: Hassan Namaki	
D. PERMIT INFORMATION: PC ISSUANCE DATE: 1/1/10 P/O NO.: G19902 PO ISSUANCE DATE: 8/16/2012	
E. START-UP DATE:	
F. OPERATIONAL TIME: > 5years	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM₁₀	INORGANIC
BACT Limit		60 ppmvd	Natural Gas	Compliance with SCAQMD Rules 407 and 1153.1	Natural Gas	
Averaging Time		1 HR				
Correction		3% O2				
B. OTHER BACT REQUIREMENTS:						
C. BASIS OF THE BACT/LAER DETERMINATION: Achieved in Practice/New Technology						
D. EMISSION INFORMATION COMMENTS: Enter any additional comments regarding Emissions Information.						

5. CONTROL TECHNOLOGY

A. MANUFACTURER:		B. MODEL:	
C. DESCRIPTION:			
D. SIZE/DIMENSIONS/CAPACITY:			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. PC ISSUANCE DATE: PO NO.: PO ISSUANCE DATE:			
F. REQUIRED CONTROL EFFICIENCIES:			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	%	%	%
NO _x	%	%	%
SO _x	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS.			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source Tests PR10242
B. DATE(S) OF SOURCE TEST: 1/12/2012
C. COLLECTION EFFICIENCY METHOD:
D. COLLECTION EFFICIENCY PARAMETERS:
E. SOURCE TEST/PERFORMANCE DATA: 2 zones, Highest zone concentration 52.6 ppmvd NO _x , 915 ppmvd CO both at 3%O ₂ .
F. TEST OPERATING PARAMETERS AND CONDITIONS: Test conducted during "normal load," 89.1% firing rate
G. TEST METHODS (SPECIFY AGENCY): SCAQMD M. 100.1

H. MONITORING AND TESTING REQUIREMENTS:
I. DEMONSTRATION OF COMPLIANCE COMMENTS:

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT: 000264	B. CCAT:	C. APPLICATION TYPE CODE: 40	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	F. SOURCE TEST ID(S): PR10242	
G. SCAQMD SOURCE SPECIFIC RULES: 1153, 1153.1			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5. HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:



Part D: NonSCAQMD BACT Determination

Source Type: **Minor**
Application No.: **558783**
Equipment Category: **I.C. Engine, Stationary, Non-Emergency, Electrical Generators**
Equipment Subcategory:

Date: **April 14, 2015**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: GM/Tecogen		B. MODEL: TECODRIVE 7400	
C. DESCRIPTION: Spark Ignition, Rich Burn, Four-Cycle, 8 cylinders.			
D. FUNCTION: On-site electrical power generation			
E. SIZE/DIMENSIONS/CAPACITY: 108 HP, driving 75 KW generator			
COMBUSTION SOURCES			
F. MAXIMUM HEAT INPUT: ---			
G. BURNER INFORMATION			
TYPE	INDIVIDUAL HEAT INPUT		NUMBER
---	<input type="text"/>		<input type="text"/>
H. PRIMARY FUEL: NATURAL GAS		I. OTHER FUEL: ---	
J. OPERATING SCHEDULE: 24 HRS/DAY 7 DAYS/WEEK 52 WKS/YR			
K. EQUIPMENT COST: Not Available			
L. EQUIPMENT INFORMATION COMMENTS: Engine is equipped with emission control consisting of non-selective catalytic converter.			

2. COMPANY INFORMATION

A. COMPANY: Playa Capital Company LLC		B. FAC ID: 176353	
C. ADDRESS: 12852 Runway Road CITY: Playa Vista STATE: CA ZIP: 90094		D. NAICS CODE:	
E. CONTACT PERSON: Derek Fraychineaud		F. TITLE: VP Residential Dev.	
G. PHONE NO.: 310-448-4682		H. EMAIL: derek.fraychineaud@brookfieldrp.com	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: NEW CONSTRUCTION PERMIT TO OPERATE
C. SCAQMD ENGINEER: Jason Taylor	
D. PERMIT INFORMATION: PC ISSUANCE DATE: 3/18/14 P/O NO.: G39943 PO ISSUANCE DATE: 4/14/2015	
E. START-UP DATE: 8/21/2015	
F. OPERATIONAL TIME: 1+ years	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM₁₀	INORGANIC
BACT Limit	0.222 LB/MW-HR	0.156 LB/MW-HR		0.444 LB/MW-HR	RULE 404	
Averaging Time	Per Rule 1110.2 requirements	Per Rule 1110.2 requirements		Per Rule 1110.2 requirements		
Correction						
B. OTHER BACT REQUIREMENTS: Compliance with emission requirements of Rule 1110.2(d)(1)(L)						
C. BASIS OF THE BACT/LAER DETERMINATION: Compliance with Rule 1110.2(d)(1)(L) and achieved in practiceOther (add comment)						
D. EMISSION INFORMATION COMMENTS: Enter any additional comments regarding Emissions Information.						

5. CONTROL TECHNOLOGY

A. MANUFACTURER: SUD-CHEMIE NSCR		B. MODEL: ENVICAT 7319	
C. DESCRIPTION: Non-Selective Catalytic Converter with automatic air/fuel ratio controller, Tecogen, model Teconet Stoichiometric AFRC.			
D. SIZE/DIMENSIONS/CAPACITY: ---			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. 558783 PC ISSUANCE DATE: 3/18/14 PO NO.: G39943 PO ISSUANCE DATE: 4/14/2015			
F. REQUIRED CONTROL EFFICIENCIES: Maintain compliance with Rule 1110.2(d)(1)(L) for engine emissions.			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	%	%	%
NO _x	%	%	%
SO _x	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS two stage system with three way catalyst followed by air injection and additional catalyst. Manages air/fuel ratio slightly rich of stoichiometric via oxygen sensors located before and after the first stage three way catalyst.			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source test.
B. DATE(S) OF SOURCE TEST: August 21, 2015
C. COLLECTION EFFICIENCY METHOD:
D. COLLECTION EFFICIENCY PARAMETERS:
E. SOURCE TEST/PERFORMANCE DATA: NO _x = 0.014 lb/MWe-hr, CO = 0.083 lb/MWe-hr, VOC = 0.116 lb/MWe-hr.
F. TEST OPERATING PARAMETERS AND CONDITIONS:
G. TEST METHODS (SPECIFY AGENCY): NO _x , CO and O ₂ determined using SCAQMD Method 100.1. VOC determined using SCAQMD Method 25.3.

H. MONITORING AND TESTING REQUIREMENTS: Compliance with Rule 1110.2(f)
I. DEMONSTRATION OF COMPLIANCE COMMENTS:

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT:	B. CCAT:	C. APPLICATION TYPE CODE:	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input type="checkbox"/>	F. SOURCE TEST ID(S):	
G. SCAQMD SOURCE SPECIFIC RULES:			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5. HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:



Part D, SCAQMD BACT Determination

Source Type: **Minor**
Application No.: **Oven - 567948, CatOx - 569302**
Equipment Category: **Food Oven**
Equipment Subcategory: **Infrared burners**
Date: **March 24, 2017**

1. EQUIPMENT INFORMATION

A. MANUFACTURER: Custom		B. MODEL:	
C. DESCRIPTION: Food oven with only infrared burners vented to a catalytic oxidizer to control VOC emissions			
D. FUNCTION: Food oven equipped with infrared burners used to bake pita and other flat breads			
E. SIZE/DIMENSIONS/CAPACITY: 7' W x 19' L x 11'H with a 0.5 HP combustion blower			
COMBUSTION SOURCES			
F. MAXIMUM HEAT INPUT: 2.198 MMBtu/hr			
G. BURNER INFORMATION			
TYPE		INDIVIDUAL HEAT INPUT	NUMBER
		.	314
H. PRIMARY FUEL: NATURAL GAS		I. OTHER FUEL:	
J. OPERATING SCHEDULE: 24 HRS/DAY 7 DAYS/WEEK 52 WKS/YR			
K. EQUIPMENT COST: TBD			
L. EQUIPMENT INFORMATION COMMENTS: UNCONTROLLED (INLET) VOC EMISSIONS 1.038 LB/HR (PERMIT EVALUATION) IS EQUAL TO 24.9 LB VOC/DAY. PERMIT LIMITS TO 1440 TON BAKERY PROD/MONTH AND 0.7752% YEAST			

2. COMPANY INFORMATION

A. COMPANY: Rich Products Corporation		B. FAC ID: 178261	
C. ADDRESS: 3401 W. Segerstrom Ave. CITY: Santa Ana STATE: CA ZIP: 92704		D. NAICS CODE: 311812	
E. CONTACT PERSON: Jim Niemeyer		F. TITLE: Maintenance Manager	
G. PHONE NO.: 714-559-6826		H. EMAIL: jniemeyer@rich.com	

3. PERMIT INFORMATION

A. AGENCY: SCAQMD	B. APPLICATION TYPE: MODIFICATION
C. SCAQMD ENGINEER: Tracy Nguyen	
D. PERMIT INFORMATION: PC ISSUANCE DATE: P/O NO.: G43298 PO ISSUANCE DATE: 10/14/2016	
E. START-UP DATE: 10/14/2014	
F. OPERATIONAL TIME: > 1 year (10/14/14 source test date)	

4. EMISSION INFORMATION

A. BACT EMISSION LIMITS AND AVERAGING TIMES:						
	VOC	NOx	SOx	CO	PM OR PM₁₀	INORGANIC
BACT Limit	95% BY WEIGHT OVERALL CONTROL	Oven: 30 ppm CatOx: 30 ppm	Nat Gas	Compliance with SCAQMD Rules 407 and 1153.1	Nat Gas	
Averaging Time	1 HR	1 HR				
Correction	TGNMO as CH4	Oven: 3%O2 Cat Ox: 3%O2				
B. OTHER BACT REQUIREMENTS:						
C. BASIS OF THE BACT/LAER DETERMINATION: Achieved in Practice/New Technology						
D. EMISSION INFORMATION COMMENTS: Enter any additional comments regarding Emissions Information.						

5. CONTROL TECHNOLOGY

A. MANUFACTURER: Western Combustion		B. MODEL: 30	
C. DESCRIPTION: Catalytic oxidizer with low NOx burner venting Oven No. 2 and control VOC emission released by yeast in baking products			
D. SIZE/DIMENSIONS/CAPACITY: Maxon Oven Pak LE13 burner, 1.3 MMBTu/hr burner. 4 Pt catalyst Modules.			
E. CONTROL EQUIPMENT PERMIT INFORMATION: APPLICATION NO. 569302 PC ISSUANCE DATE: Change ownership PO NO.: G43249 PO ISSUANCE DATE: 10/12/2016			
F. REQUIRED CONTROL EFFICIENCIES:			
CONTAMINANT	OVERALL CONTROL EFFICIENCY	CONTROL DEVICE EFFICIENCY	COLLECTION EFFICIENCY
VOC	95%	95%	%
NOx	%	%	%
SOx	%	%	%
CO	%	%	%
PM	%	%	%
PM ₁₀	%	%	%
INORGANIC	%	%	%
G. CONTROL TECHNOLOGY COMMENTS Permitted limit minimum 600°F catalyst inlet temperature. 100% collection efficiency required to meet efficiency limits.			

6. DEMONSTRATION OF COMPLIANCE

A. COMPLIANCE DEMONSTRATED BY: Source test PR14211
B. DATE(S) OF SOURCE TEST: 10/14-16/2014 when the Cat Ox was Appl # 557729
C. COLLECTION EFFICIENCY METHOD: EPA M.204
D. COLLECTION EFFICIENCY PARAMETERS:
E. SOURCE TEST/PERFORMANCE DATA: 98.4% destruction eff, Inlet VOC to Cat Ox 2.4 lb/hr, Exh VOC 0.03 lb/hr. Exhaust of cat ox: Normal load NOx with production 22.1 ppmvd @ 3%O ₂ (0.05 lb NOx/hr) and 21.2 ppmvd CO @ 3%O ₂ (0.14 lb CO/hr)
F. TEST OPERATING PARAMETERS AND CONDITIONS: Cat Bed inlet Temp 650°F.
G. TEST METHODS (SPECIFY AGENCY): SCAQMD 25.1, 25.3, 100.1

H. MONITORING AND TESTING REQUIREMENTS:

I. DEMONSTRATION OF COMPLIANCE COMMENTS:

7. ADDITIONAL SCAQMD REFERENCE DATA

A. BCAT: 000255	B. CCAT: 06	C. APPLICATION TYPE CODE:	
D. RECLAIM FAC? YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	E. TITLE V FAC: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	F. SOURCE TEST ID(S): PR14211	
G. SCAQMD SOURCE SPECIFIC RULES:			
H. HEALTH RISK FOR PERMIT UNIT			
H1. MICR:	H2. MICR DATE:	H3. CANCER BURDEN:	H4. CB DATE:
H5. HIA:	H6. HIA DATE:	H7. HIC:	H8. HIC DATE:

Lithographic Printing Press Cost Effectiveness Calculations for Regenerative Thermal Oxidizer as control - Freedom Communications

Litho Printing Presses Info

Manufacturer: Beiren
Model: 3845, 8-Color, Oven Dry
Oven: MegTech Systems, Model 350, 2x3.2MMBtu/hr & 2x1.6MMBtu/hr
Operation Schedule: 24 hr/day, 365 days/yr (Avg.)

Control Technology

RTO - Adwest Technologies
Model SSE-3K-95X-RTO, 1.2MMBtu/hr

Capital Cost

Equipment	\$	207,100
Direct & Indirect Installation	\$	200,000
Total Capital	\$	407,100

Operating Cost

Direct & Indirect	\$	135,000
Total Average Annual	\$	135,000

Present Value of Capital Costs	\$	407,100
Present Value of Annual Costs (10 years @ 4%)	\$	1,094,850
Total 10-Year Capital Cost	\$	1,501,950

Uncontrolled Emissions (lbs/day)	181.6
Overall Control Efficiency	99%
Controlled Emissions (lbs/day)	180
Controlled Emissions (tons/10 years)	328
Cost per ton of VOC controlled	\$ 4,578

MSBACT maximum cost effectiveness (\$/ton)	\$ 28,886	COST EFFECTIVE
	\$ 23,484	
MSBACT maximum cost effectiveness (\$/ton)	\$ 86,658	COST EFFECTIVE
	\$ 70,451	

AVERAGE
<i>1st quarter 2006 M&S cost effectiveness (1302.3)</i>
INCREMENTAL
<i>1st quarter 2006 M&S cost effectiveness (1302.3)</i>

Notes:

- Calculations were based on Regenerative Thermal Oxidizer permit application no. 460266 submitted by applicant controlling VOC emissions from a Lithographic Printing Press drying oven and cost info provided by RTO manufacturer.
- 181.59 lbs/day of uncontrolled VOC emissions was the baseline used in determining cost effectiveness
- Maximum allowed cost effectiveness was based on 1st quarter 2017 Marshall & Swift index
- Incremental costs are assumed to be the same since there is no more stringent control technology

Flexographic Printing Press Cost Effectiveness Calculations for Regenerative Thermal Oxidizer as control - Asia Plastics

Flexo Printing Presses Info

Manufacturer: Hon Jin Iron Works
Model: HJ-222, 4-Color, Air Dry
Model HJ-HS6001, 6-Color, Air Dry
Operation Schedule: 16 hr/day, 365 days/yr

Control Technology

RTO - Ship & Shore
Model SSE-3K-95X-RTO, 1.35MMBtu/hr

Capital Cost

Equipment	\$	160,000
Direct & Indirect Installation	\$	140,000
Total Capital	\$	300,000

Operating Cost

Direct & Indirect	\$	124,720
Total Average Annual	\$	124,720

Present Value of Capital Costs	\$	300,000
Present Value of Annual Costs (10 years @ 4%)	\$	1,011,479
Total 10-Year Capital Cost	\$	1,311,479

Uncontrolled Emissions (lbs/day)	133
Control Efficiency	95%
Controlled Emissions (lbs/day)	127
Controlled Emissions (tons/10 years)	231
Cost per ton of VOC controlled	\$ 5,675

MSBACT maximum cost effectiveness ROG (\$/ton)	\$ 28,886	AVERAGE
	COST EFFECTIVE	
	\$ 28,107	1st quarter 2013 M&S cost effectiveness (1558.7)
MSBACT maximum cost effectiveness ROG (\$/ton)	\$ 86,658	INCREMENTAL
	COST EFFECTIVE	
	\$ 84,322	1st quarter 2013 M&S cost effectiveness (1558.7)

Notes:

- Calculations were based on Regenerative Thermal Oxidizer permit application no. 548337 submitted by applicant controlling VOC emissions from two Flexographic Printing Presses, 6-color and 4-color. In addition to cost information provided by applicant.
- 133.3 lbs/day of uncontrolled VOC emissions was the baseline used in determining cost effectiveness
- Maximum allowed cost effectiveness was based on 1st quarter 2017 Marshall & Swift index
- Incremental costs are assumed to be the same since there is no more stringent control technology

Bakery Oven Cost Effectiveness Calculations for Regenerative Thermal Oxidizer (RTO) as control - Bon Appetit

Oven Information

Manufacturer: GPA Orlandi
Model: Turbo termo oven 25
Rating/Fuel: 5,000,000 Btu/hr
4 Burners, 3x1MM Btu/hr & 1x2MM Btu/hr
Outside Dimensions: 86'-5"L, 15'-5"W, 6'-3"H
Operation Schedule: 24 hr/day, 360 days/yr

Control Technology

RTO - Alliance Corporation
Model Boxidizer 2-bed, .96 therms/hr

Capital Cost

Equipment	\$	150,166
Direct Installation	\$	85,600
Indirect Installation	\$	18,020
Total Capital	\$	253,786

Operating Cost

Direct & Indirect	\$	42,046
Total Average Annual	\$	42,046

Present Value of Capital Costs	\$	253,786
Present Value of Annual Costs (10 years @ 4%)	\$	340,993
Total 10-Year Capital Cost	\$	594,779

Uncontrolled Emissions (lbs/day)	30
Control Efficiency	95%
Controlled Emissions (lbs/day)	29
Controlled Emissions (tons/10 years)	52
Cost per ton of VOC controlled	\$ 11,435

MSBACT maximum cost effectiveness ROG (\$/ton)	\$ 28,886	
	COST EFFECTIVE	AVERAGE

MSBACT maximum cost effectiveness ROG (\$/ton)	\$ 86,658	
	COST EFFECTIVE	INCREMENTAL

Notes:

- Calculations were based on cost effectiveness analysis submitted by applicant in April 2017 for Bakery Oven permit application no. 523867 that was evaluated for cost-effectiveness for expected 15.56 lbs/day of uncontrolled VOC emissions and cost estimates from another RTO manufacturer.
- 30 lbs/day of uncontrolled VOC emissions was the baseline used in determining cost effectiveness
- Maximum allowed cost effectiveness was based on 1st quarter 2017 Marshall & Swift index
- Incremental costs are assumed to be the same since there is no more stringent control technology

Bakery Oven Cost Effectiveness Calculations for Catalytic Oxidizer as control- Bon Appetit**Oven Information**

Manufacturer: GPA Orlandi
 Model: Turbo termo oven 25
 Rating/Fuel: 5,000,000 Btu/hr
 4 Burners, 3x1MM Btu/hr & 1x2MM Btu/hr
 Outside Dimensions: 86'-5"L, 15'-5"W, 6'-3"H
 Operation Schedule: 24 hr/day, 360 days/yr

Control Technology

CSM
 Cat-Ox Model 30A, 0.80MMBtu/hr

Capital Cost

Equipment	\$	460,438
Direct Installation	\$	277,455
Indirect Installation	\$	56,416
Total Capital	\$	794,309

Operating Cost

Direct	\$	75,136
Indirect	\$	2,000
Total Average Annual	\$	77,136

Present Value of Capital Costs	\$	794,309
Present Value of Annual Costs (10 years @ 4%)	\$	625,573
Total 10-Year Capital Cost	\$	1,419,882

Uncontrolled Emissions (lbs/day)	30
Control Efficiency	95%
Controlled Emissions (lbs/day)	28.50
Controlled Emissions (tons/10 years)	51.30
Cost per ton of VOC controlled	\$ 27,678

MSBACT maximum cost effectiveness (\$/ton)	\$ 28,886
	COST EFFECTIVE

MSBACT maximum cost effectiveness (\$/ton)	\$ 86,658
	COST EFFECTIVE

Notes:

- Calculations were based on cost effectiveness analysis submitted by applicant in April 2017 for Bakery Oven permit application no. 523867 that was evaluated for cost-effectiveness for expected 15.56 lbs/day of uncontrolled VOC emissions.
- 30 lbs/day of uncontrolled VOC emissions was the baseline used in determining cost effectiveness
- Maximum allowed cost effectiveness was based on 1st quarter 2017 Marshall & Swift index
- Incremental costs are assumed to be the same since there is no more stringent control technology

Bakery Oven Cost Effectiveness Calculations for Catalytic Oxidizer as control - Aryzta, Ontario

Oven Information (two identical ovens vented)

Manufacturer: Baking Technology
Model: Baketech Maxisaver bun oven
Rating/Fuel: 7,300,000 Btu/hr
24 Burners, Flynn no. 162HN, 30ppm NOx
Outside Dimensions: 48'-4"L, 33'-0"W, 11'-0"H
Operation Schedule: 24 hr/day, 360 days/yr

Control Technology

CSM
Cat-Ox Model 180A, 2.7MMBtu/hr

Capital Cost

Equipment	\$	709,769
Direct Installation	\$	45,000
Indirect Installation	\$	71,000
Total Capital	\$	825,769

Operating Cost

Direct and Indirect	\$	37,178
Total Average Annual	\$	37,178

Present Value of Capital Costs	\$	825,769
Present Value of Annual Costs (10 years @ 4%)	\$	301,514
Total 10-Year Capital Cost	\$	1,127,283

Uncontrolled Emissions (lbs/day)	114
Control Efficiency	95%
Controlled Emissions (lbs/day)	108.64
Controlled Emissions (tons/10 years)	195.56
Cost per ton of VOC controlled	\$ 5,765

MSBACT maximum cost effectiveness ROG (\$/ton)	\$ 28,886
	COST EFFECTIVE
	\$ 24,573
MSBACT maximum cost effectiveness ROG (\$/ton)	\$ 86,658
	COST EFFECTIVE
	\$ 73,719

AVERAGE
<i>1st quarter 2007 M&S cost effectiveness (1362.7)</i>
INCREMENTAL
<i>1st quarter 2007 M&S cost effectiveness (1362.7)</i>

Notes:

- Calculations were based on cost effectiveness analysis provided by applicant for Cat-Ox under application no. 548869 venting two bakery ovens appl. Nos. 548863 & 548866 for expected 114.36 lbs/day of uncontrolled VOC emissions.
- Since applicant stated that these costs are almost 10 years old, cost effectiveness based on 1st quarter 2007 Marshall & Swift index was also used.
- Incremental costs are assumed to be the same since there is no more stringent control technology

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

DRAFT

10-20-2000 Rev. 0
[1-5-2018 Rev. 1](#)

Equipment or Process: Dryer or Oven

Subcategory/ Rating/Size	Criteria Pollutants					Inorganic
	VOC	NO _x	SO _x	CO	PM ₁₀	
Carpet Oven		80 ppmvd, corrected to 3% O ₂ (10-20-2000)	Natural Gas (1990)		Natural Gas (1990)	
Rotary, Spray and Flash Dryers ¹⁾		Natural Gas with Low NO _x Burner (10-20-2000)	Natural Gas (1990)		Natural Gas with Baghouse (1990)	
Tray, Agitated Pan, and Rotary Vacuum Dryers		Natural Gas with Low NO _x Burner (10-20-2000)	Natural Gas (1990)		Natural Gas (1990)	
Tenter Frame Fabric Dryer		60 ppmvd Corrected to 3% O ₂ (10-20-2000)	Natural Gas (10-20-2000)		Natural Gas (10-20-2000)	
Other Dryers and Ovens – Direct and Indirect Fired ²⁾		30 ppmvd corrected to 3% O ₂ (04-10-98)	Natural Gas (10-20-2000)		Natural Gas (10-20-2000)	

1. Dryers for foodstuff, pharmaceuticals, aggregate & chemicals.
~~1-2.~~ Does not include food or bakery ovens. See listing for “Food Oven.”

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

DRAFT

1-5-2018 Rev. 0

Equipment or Process:

Food Oven

		<u>Criteria Pollutants</u>					
<u>Subcategory¹</u>	<u>Rating/ Size</u>	<u>VOC</u>	<u>NO_x</u>	<u>SO_x</u>	<u>CO</u>	<u>PM₁₀</u>	<u>Inorganic</u>
<u>Ribbon Burner</u>	<u>> 500°F</u>		<u>60 ppmvd @ 3% O₂ (1-5-2018)</u>	<u>Natural Gas (1-5-2018)</u>	<u>Compliance with applicable SCAQMD Rules 407 or 1153.1(1-5-2018)</u>	<u>Natural Gas (1- 5-2018)</u>	
	<u>≤ 500°F</u>		<u>30 ppmvd @ 3% O₂ (1-5-2018)</u>	<u>Same as above</u>	<u>Same as above</u>	<u>Same as above</u>	
<u>Direct Fired Burner</u>			<u>30 ppmvd @ 3% O₂ (1-5-2018)</u>				
<u>Infrared Burner</u>			<u>30 ppmvd @ 3% O₂ (1-5-2018)</u>				
<u>Add-on Control for Bakery Oven processing yeast leavened products with emissions ≥ 30 lb VOC/day</u>		<u>Catalytic oxidizer with 95% overall control efficiency (mass basis); catalyst inlet temperature ≥ 600°F; ceramic prefilter (1-5-2018)</u>	<u>Compliance with SCAQMD Rule 1147 (1-5-2018)</u>				

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

(Continued on next page)

¹[Indirect Fired units may be subject to Rules 1146 and 1146.1 and BACT for Process Heater](#)

		Criteria Pollutants					Inorganic
Subcategory	Rating/ Size	VOC	NOx	SOx	CO	PM10	
Other Burners		Compliance with SCAQMD Rules and Regulations					

* [Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions](#)

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

10-20-2000 Rev. 0
7-14-2006 Rev. 1
12-02-2016 Rev. 2
[1-5-2018 Rev. 3](#)

Equipment or Process: I.C. Engine, Portable ¹

		Criteria Pollutants					
Subcategory	Rating/Size	VOC	NO _x	NO _x + NMHC ²	SO _x	CO	PM
Compression-Ignition ³	50 ≤ HP < 75			Tier 4 Final: 4.7 grams/kW-hr (3.5 grams/bhp-hr) (12-02-2016)	Diesel fuel with a sulfur content no greater than 0.0015% by weight (Rule 431.2). (6-6-2003)	Tier 4 Final: 5.0 grams/kW-hr (3.7 grams/bhp-hr) (12-02-2016)	Tier 4 Final: 0.03 grams/kW-hr (0.02 grams/bhp-hr) and CARB ATCM for portable diesel engines ⁴ (12-02-2016)
	75 ≤ HP < 175 ⁵		Tier 4 FinalInterim: 3.40 0.40 grams/kW-hr (2.50 0.30 grams/bhp-hr) (1-5-2018)	Tier 4 FinalInterim: NMHC only: 0.19 grams/kW-hr (0.14 grams/bhp-hr) (1-5-2018)		Tier 4 FinalInterim: 5.0 grams/kW-hr (3.7 grams/bhp-hr) (1-5-2018)	Tier 4 FinalInterim: 0.02 grams/kW-hr (0.01 grams/bhp-hr) and CARB ATCM for portable diesel engines ⁴ (1-5-2018)
	175 ≤ HP < 750		Tier 4 Final: 0.40 grams/kW-hr (0.30 grams/bhp-hr) (12-02-2016)	Tier 4 Final: NMHC only: 0.19 grams/kW-hr (0.14 grams/bhp-hr) (12-02-2016)		Tier 4 Final: 3.5 grams/kW-hr (2.6 grams/bhp-hr) (12-02-2016)	Tier 4 Final: 0.02 grams/kW-hr (0.01 grams/bhp-hr) and CARB ATCM for portable diesel engines ⁴ (12-02-2016)

* [Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions](#)

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

Subcategory	Rating/Size	Criteria Pollutants					
		VOC	NO _x	NO _x + NMHC ²	SO _x	CO	PM

(Continued on Next Page)

Compression-Ignition ³	≥750 HP ⁵		<u>Tier 4 Interim:</u> For Generator Sets > 1200 HP: 0.67 grams/kW-hr (0.50 grams/bhp-hr) For All Engines Except “Generator Sets > 1200 HP”: 3.5 grams/kW-hr (2.6 grams/bhp-hr) (12-02-2016)	<u>Tier 4 Interim:</u> NMHC only: 0.4 grams/kW-hr (0.30 grams/bhp-hr) (12-02-2016)	Diesel fuel with a sulfur content no greater than 0.0015% by weight (Rule 431.2). (6-6-2003)	<u>Tier 4 Interim:</u> 3.5 grams/kW-hr (2.6 grams/bhp-hr) (12-02-2016)	<u>Tier 4 Interim:</u> 0.10 grams/kW-hr (0.07 grams/bhp-hr)and CARB ATCM for portable diesel engines ⁴ (12-02-2016)
Spark Ignition	All	1.5 grams/bhp-hr, or 240 ppmvd as methane @ 15% O ₂ (4-10-1998)	1.5 grams/bhp-hr, or 80 ppmvd @ 15% O ₂ (4-10-1998)			2.0 grams/bhp-hr, or 176 ppmvd @ 15% O ₂ (4-10-1998)	

Notes:

- 1) BACT for “I.C. Engine, Portable” is determined by deemed complete date of permit application not date of manufacture or installation.
- 2) NMHC + NO_x means the sum of non-methane hydrocarbons and oxides of nitrogen emissions, unless specified as “NMHC only”, which only includes NMHC emissions.
- 3) The engine must be certified by U.S. EPA or CARB to meet the Tier 4 emission requirements of 40 CFR Part 89 – Control of Emissions from New and In-use Nonroad Compression-Ignition Engines shown in the table– or otherwise demonstrate that it meets the Tier 4 emission limits. If, because of the averaging, banking, and trading program, there is no new engine from any manufacturer that meets the above standards, then the engine must meet the family emission limits established by the manufacturer and approved by U.S. EPA. Based on the model year, the CARB Airborne Toxic Control Measure (ATCM) for Portable Diesel Engines (see www.arb.ca.gov/diesel/peatcm/peatcm.htm) requires in-use portable diesel engines to be certified to Tier 1, 2, 3 or 4 by their respective deadlines, all of which have passed. All exceptions allowed in the ATCM are also allowed in this guideline.

* [Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions](#)

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

- 4) The CARB ATCM also requires in-use portable diesel engines to meet fleet-average PM standards beginning 1/1/2013. The PM limits in the table apply only to filterable PM.
- 5) CARB has extended the Tier 4 Final requirements deadline “until further notice” for Portable, Compression-Ignition Engines for ~~75 ≤ HP < 175~~
~~and~~ HP ≥ 750.

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

DRAFT

1-5-2018 Rev. 0

Equipment or Process: I.C. Engine, Stationary, Non-Emergency, Electrical Generators ¹

<u>Subcategory/ Rating/Size</u>	<u>Criteria Pollutants</u>					<u>Inorganic</u>
	<u>VOC</u>	<u>NO_x</u>	<u>SO_x</u>	<u>CO</u>	<u>PM₁₀</u>	
<u>> 50 bhp</u>	<u>Compliance with SCAQMD Rule 1110.2 (1-5-2018)</u>	<u>Compliance with SCAQMD Rule 1110.2 (1-5-2018)</u>	<u>See Clean Fuels Policy in Part C of the BACT Guidelines (1-5-2018)</u>	<u>Compliance with SCAQMD Rule 1110.2 (1-5-2018)</u>	<u>See Clean Fuels Policy in Part C of the BACT Guidelines (1-5-2018) Compliance with Rule 1470 (1-5-2018)</u>	
<u>Landfill or Digester Gas Fired</u>	<u>Compliance with SCAQMD Rule 1110.2 (1-5-2018)</u>	<u>Compliance with SCAQMD Rule 1110.2 (1-5-2018)</u>	<u>Compliance with SCAQMD Rule 431.1 (1-5-2018)</u>	<u>Compliance with SCAQMD Rule 1110.2 (1-5-2018)</u>		

1) This BACT listing was adapted from the previous "I.C. Engine, Stationary, Non-Emergency," Part D BACT listing.

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

DRAFT

12-02-2016 Rev. 0
[1-5-2018 Rev. 1](#)

Equipment or Process: - I.C. Engine, Stationary, Non-Emergency, Non-Electrical Generators ⁺

Subcategory/ Rating/Size	Criteria Pollutants					Inorganic
	VOC	NO _x	SO _x	CO	PM ₁₀	
> 50 bhp	Compliance with SCAQMD Rule 1110.2 (12-02-2016)	Compliance with SCAQMD Rule 1110.2 (12-02-2016)	See Clean Fuels Policy in Part C of the BACT Guidelines (12-02-2016)	Compliance with SCAQMD Rule 1110.2 (12-02-2016)	See Clean Fuels Policy in Part C of the BACT Guidelines (12-02-2016) Compliance with Rule 1470 (12-02-2016)	
Landfill or Digester Gas Fired ²¹	Compliance with SCAQMD Rule 1110.2 0-8 grams/bhp-hr (12-02-2016)(1-5-2018)	Compliance with SCAQMD Rule 1110.2 0-60 grams/bhp-hr (12-02-2016)(1-5-2018)	Compliance with SCAQMD Rule 431.1 (12-02-2016)	Compliance with SCAQMD Rule 1110.22-5 grams/bhp-hr (12-02-2016)(1-5-2018)		

1) ~~This BACT listing was adapted from the “I.C. Engine, Stationary, Non-Emergency.” An additional listing for “I.C. Engine, Stationary, Non-Emergency, Electrical Generators,” is currently under development. Until the amendment is developed, Stationary, Non-Emergency, Electrical Generators will be subject to “I.C. Engine, Stationary, Non-Emergency.”~~

2) 1) For the adoption of this new listing, the requirements for this subcategory were transferred directly from the existing requirements under “I.C. Engine, Stationary, Non-Emergency.” The requirements are not new, but the date listed was updated to reflect the date of adoption of the new listing.

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

DRAFT

~~10-20-2000 Rev. 0~~
~~7-9-2004 Rev. 1~~
~~12-3-2004 Rev. 2~~
1-5-2018 Rev. 3

Equipment or Process: ~~I.C. Engine, Stationary, Non-Emergency~~

Subcategory/ Rating/Size	Criteria Pollutants					Inorganic
	VOC	NO _x	SO _x	CO	PM ₁₀	
<2064 bhp	0.15 grams/bhp-hr (4-10-98)	0.15 grams/bhp-hr (4-10-98)	See Clean Fuels Policy in Part C of the BACT Guidelines (10-20-2000)	0.60 grams/bhp-hr (4-10-98)	See Clean Fuels Policy in Part C of the BACT Guidelines (10-20-2000) Compliance with Rule 1470: (12-3-2004)	
≥2064 bhp	25 ppm @ 15% O ₂ (7-9-2004)	9 ppmvd @ 15% O ₂ (7-9-2004)	Same as Above (10-20-2000)	33 ppmvd @ 15% O ₂ (5-8-98)	Same as Above (7-9-2004)	Ammonia: 10 ppmvd @ 15% O ₂ (7-9-2004)
Landfill or Digester Gas Fired	0.8 grams/bhp-hr (4-10-98)	0.60 grams/bhp-hr (4-10-98)	Compliance with Rule 431.1 (10-20-2000)	2.5 grams/bhp-hr (4-10-98)		

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

DRAFT

10-20-2000 Rev. 0

12-5-2003 Rev. 1

7-14-2006 Rev 2

[1-5-2018 Rev 3](#)

Equipment or Process: Printing (Graphic Arts)

Subcategory	Criteria Pollutants					
	VOC	NO _x	SO _x	CO	PM ₁₀	Inorganic
Flexographic	Inks with ≤ 1.5 Lbs VOC/Gal, Less Water and Less Exempt Compounds (1990); or use of UV/EB or water-based inks/coatings ≤ 180 g VOC/L. Compliance with SCAQMD Rules 1130 and 1171 (12-5-2003) (1-5-2018)					
Control	For add-on control required by SCAQMD Rule 1130(c)(5) or other District requirement: EPA M. 204 Permanent Total Enclosure (100% collection) vented to RTO with 95% overall control efficiency; Combustion Chamber: Temp ≥ 1500°F¹, Retention Time > 0.3 seconds (1-5-2018)	Compliance with SCAQMD Rule 1147 (1-5-2018)				
Letterpress	Compliance with SCAQMD Rules 1130 and 1171 (12-5-2003)					
Lithographic or Offset, Heatset	Low VOC Fountain Solution (≤ 8% by Vol. VOC); Low Vapor Pressure (≤ 10 mm Hg VOC Composite Partial Pressure¹) or Low VOC (≤ 100 g/l) Blanket and Roller Washes; Oil-Based or UV-Curable Inks; and Compliance with SCAQMD Rules 1130 and 1171 (7-14-2006) (1-5-18)				Oven Venting to an Afterburner (≥ 0.3 Sec. Retention Time at ≥ 1400-°F; 95% Overall Efficiency) (10-20-2000)	
Control	Oven Venting to an Afterburner (≥ 0.3 Sec.	Compliance				

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

Subcategory	Criteria Pollutants					
	VOC	NO _x	SO _x	CO	PM ₁₀	Inorganic
	Retention Time at ≥ 1595°F¹; 99% Overall Efficiency (10-20-2000)(1-5-2018)	with SCAQMD Rule 1147 (1-5-2018)				

(Continued on next page)

Lithographic or Offset, Non-Heatset	Same As Above					
Rotogravure or Gravure—Publication and Packaging	Compliance with SCAQMD Rules 1130 and 1171 (10-20-2000)					
Screen Printing and Drying	Compliance with SCAQMD Rules 1130.1 and 1171 (12-5-2003) ; or use of Rule 1130.1 and 1171 compliant UV/EB or water-based inks/coatings. (1-5-2018).					

(Continued on Next Page)

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Best Available Control Technology (BACT) Guidelines for Non-Major Polluting Facilities*

~~1) VOC COMPOSITE PARTIAL PRESSURE is the sum of the partial pressures of the compounds defined as VOCs. VOC Composite Partial Pressure is calculated as follows:~~

$$PP_c = \frac{\sum_{i=1}^n \frac{(W_i)(VP_i)}{MW_i}}{\frac{W_w}{MW_w} + \frac{W_e}{MW_e} + \sum_{i=1}^n \frac{W_i}{MW_i}}$$

Where:	PP _c	=	VOC composite partial pressure at 20°C in mm Hg
	W _i	=	Weight of the "i"th VOC compound in grams
	MW _i	=	Molecular weight of "i"th VOC compound in grams per gram mole
	VP _i	=	Vapor pressure of the "i"th VOC compound at 20°C in mm Hg
	W _w	=	Weight of water in grams
	MW _w	=	Molecular weight of water in grams per gram mole
	W _e	=	Weight of exempt compound in grams
	MW _e	=	Molecular weight of exempt compound in grams per gram mole

~~For multiple exempt compounds: $W_e / MW_e = \sum_{j=1}^n W_{ej} / MW_{ej}$~~

12) or temperature demonstrating equivalent overall control efficiency in a District-approved source test.

* Means those facilities that are not major polluting facilities as defined by Rule 1302 - Definitions