

APPENDIX E

TRAFFIC IMPACT ANALYSIS

This page intentionally left blank.

Submitted by:



TESORO LOS ANGELES REFINERY INTEGRATION
AND COMPLIANCE PROJECT
Traffic Impact Analysis
Draft Report

Submitted to:

South Coast Air Quality Management District

April 27, 2015

17J14-17B0

This page intentionally left blank.

TABLE OF CONTENTS

Table of Contents	i
Appendices.....	i
List of Tables.....	ii
List of Figures	iii
1.0 Introduction.....	1
1.1 PROJECT DESCRIPTION.....	1
1.2 STUDY AREA.....	3
1.3 STUDY ANALYSIS PERIODS	7
2.0 Baseline Conditions.....	8
2.1 ROADWAY CONFIGURATIONS.....	8
2.2 BASELINE TRANSIT OPERATIONS	8
2.3 BASELINE TRAFFIC VOLUMES	9
2.4 TRAFFIC OPERATIONS ANALYSIS METHODOLOGY	9
2.5 BASELINE INTERSECTION LEVELS OF SERVICE	12
3.0 Construction Conditions.....	13
3.1 PROJECT CONSTRUCTION TRIP GENERATION AND DISTRIBUTION.....	14
3.2 CONSTRUCTION PERIOD INTERSECTION LEVELS OF SERVICE	18
4.0 Year 2021 Conditions	22
4.1 YEAR 2021 WITHOUT PROJECT INTERSECTION LEVELS OF SERVICE.....	22
4.2 YEAR 2021 WITH PROJECT INTERSECTION LEVELS OF SERVICE	25
5.0 Conclusions.....	31

APPENDICES

Appendix A: Traffic Counts

Appendix B: LOS Calculation Sheets

LIST OF TABLES

Table 1: Intersection Level of Service Definitions.....	10
Table 2: Baseline Existing Conditions (2014) Intersection Levels of Service	13
Table 3: Construction Period Daily Trip Generation	14
Table 4: Construction Period Peak Hour Trip Generation	15
Table 5: Baseline Existing Conditions Plus Project Construction Conditions (Pre- I-405/Wilmington Interchange) Intersection LOS.....	20
Table 6: Year 2021 Without Project Conditions Intersection LOS.....	23
Table 7: Proposed Project Operation Peak Hour Trips	25
Table 8: Year 2021 With Project Intersection LOS.....	30

LIST OF FIGURES

Figure 1: Proposed Project Site Plan.....	4
Figure 2: Study Intersection Locations.....	5
Figure 3: Baseline Intersection Lane Configurations	6
Figure 4: Baseline Peak Hour Intersection Volumes.....	11
Figure 5: Proposed Project Construction Trip Distribution	16
Figure 6: Proposed Project Construction Trip Assignment.....	17
Figure 7: Proposed Project Construction Period Intersection Volumes.....	19
Figure 8: Year 2021 Without Project Intersection Volumes	24
Figure 9: Proposed Project Operations Distribution	27
Figure 10: Proposed Project Operations Trip Assignment	28
Figure 11: Year 2021 Proposed Project Operations Peak Hour Intersection Volumes	29

1.0 INTRODUCTION

This report summarizes the methodology and results of a traffic impact analysis for the proposed Tesoro Refining & Marketing Company LLC (Tesoro) Los Angeles Refinery Integration and Compliance Project (proposed Project) located in the Cities of Los Angeles and Carson, California. This report follows guidelines provided by the South Coast Air Quality Management District, the California Department of Transportation, Los Angeles County and the Cities of Los Angeles and Carson.

The traffic study will look at several scenarios to describe baseline and future conditions without the project, during the construction of the project, and in the operational phase of the project. This includes analysis of baseline conditions, peak construction activities, and year 2021 traffic conditions which represent future traffic growth and operating conditions at study locations due to ambient growth, a cumulative interchange realignment project at I-405/Wilmington Avenue, and traffic generated by the proposed project. Therefore this analysis addresses the proposed project's contribution to cumulative traffic growth and congestion.

1.1 PROJECT DESCRIPTION

In June 2013, Tesoro purchased the BP West Coast Products LLC (BP) Carson Refinery, which will be further integrated with the adjacent Tesoro Los Angeles Refinery – Wilmington Operations to form the Tesoro Los Angeles Refinery (Refinery). The Refinery includes: (1) the Wilmington Operations located at 2101 East Pacific Coast Highway in the Wilmington District of the City of Los Angeles; and (2) the Carson Operations, which is the former BP Carson Refinery located at 2350 East 223rd Street in the City of Carson. The proposed project will be designed to better integrate the Tesoro Wilmington Operations and Tesoro Carson Operations.

The proposed project will occur at both the Wilmington and Carson Operations of the Tesoro Los Angeles Refinery. Tesoro will further integrate the recently purchased adjacent BP Carson Refinery (currently referred to as the Tesoro Los Angeles Refinery Carson Operations) with the existing Tesoro Los Angeles Refinery (currently referred to as the Tesoro Los Angeles Refinery Wilmington Operations). Together, the Wilmington and Carson Operations comprise the complete Tesoro Los Angeles Refinery (the Refinery).

The Tesoro Los Angeles Refinery is approximately 950 contiguous acres in size and operates within the Cities of Los Angeles and Carson. The Tesoro Wilmington Operations is located within Wilmington, a community under the jurisdiction of the City of Los Angeles, at 2101 East Pacific Coast Highway, Wilmington, Los Angeles County, California 90744. The Tesoro Carson Operations is located at 2350 East 223rd Street, Carson, California, 90745.

As part of the proposed project, both new and modified equipment, as well as connecting piping, will be located within portions of the Refinery under both the City of Carson jurisdiction and the City of Los Angeles jurisdiction.

The Wilmington Operations are bounded to the north by Sepulveda Boulevard, to the west by Alameda Street, to the south by railroad tracks, and to the east by the Dominguez Channel. The Wilmington Operations are bisected by Pacific Coast Highway, with the larger portion of the Wilmington Operations to the north of Pacific Coast Highway and the smaller portion to the south. The Refinery and all adjacent areas in the Cities of Carson and Los Angeles are zoned for heavy industrial use.

The Carson Operations are bounded by Wilmington Avenue to the west, 223rd Avenue to the north, Alameda Street to the east, and Sepulveda Boulevard to the south. The Dominguez Channel flows through the Carson Operations, dividing the property into two sections: Northeastern and Southern. Several industrial/commercial facilities and the 405 Freeway border the Carson Operations to the north. The Alameda Corridor and other industrial facilities, including the Tesoro Coke Barn, the Air Products Hydrogen Plant, and the Tesoro Sulfur Recovery Plant (SRP), are located to the east of the Carson Operations. Commercial and residential areas are located to the west of the Carson Operations. The Phillips 66 Refinery and tank farms occupy the area located to the south of the Tesoro Carson Operations. Additionally, the SRP (considered to be a portion of the Tesoro Wilmington Operations) is located at 23208 South Alameda Street in the City of Carson.

Construction activities for the proposed Project are expected to begin in third quarter of 2015 and are expected to be completed by first quarter of 2021, based on preliminary project engineering. The preliminary construction schedule for each component of the proposed project varies. The construction activities for most of the components are expected to overlap from about December 2015 to February 2017. Construction work shifts are expected to last about ten hours per day during most portions of the construction schedule. During normal construction periods, one work shift per day is expected.

Construction period employee trips will access the proposed Project site at three parking lots: parking for 550 workers will be provided from 223rd street at the northern portion of the proposed Project site, parking for 200 workers will be provided off of Alameda Street to the immediate north of Sepulveda Boulevard, and parking for 200 workers will be provided from Sepulveda Boulevard to the east of Alameda Street.

Completion of the proposed Project will result in the permanent addition of approximately ten daily truck roundtrips from the proposed Project site:

- There will be no increase in workers as compared to baseline conditions following completion of the construction phase
- Eight trucks per day will transport spent sulfuric acid from the Carson Plant to the new Sulfuric Acid Plant at Wilmington
- One truck per day will transport other materials and supplies to or from the Refinery

The project site location as well as the location of the construction worker parking lots is shown in **Figure 1**.

1.2 STUDY AREA

The following thirteen (13) intersections were identified for inclusion in the traffic impact analysis:


1. Wilmington Avenue/I-405 Northbound Ramps;
2. Wilmington Avenue/I-405 Southbound Ramps;
3. Wilmington Avenue/223rd Street;
4. Alameda Street/I-405 Northbound Ramps;
5. Alameda Street/223rd Street (along Alameda Street);
6. Alameda Street/223rd Street (along 223rd Street);
7. Alameda Street/Sepulveda Boulevard (along Alameda Street);
8. Alameda Street/Sepulveda Boulevard (along Sepulveda Boulevard);
9. I-405 Southbound Ramps/223rd Street;
10. Terminal Island Freeway (SR-103)/Sepulveda Boulevard;
11. Santa Fe Avenue/Sepulveda Boulevard;
12. SR-710 SB Ramps/Willow Street; and
13. SR-710 NB Ramps/Willow Street.

Figure 2 illustrates the study area including the locations of the study intersections analyzed in this report. The existing lane configurations of the study intersections are illustrated in **Figure 3**.



Tesoro Los Angeles Refinery
Integration & Compliance Project
Traffic Study

FIGURE 1
Proposed Project Site Plan



Tesoro Los Angeles Refinery
Integration & Compliance Project
Traffic Study

FIGURE 2
Study Intersection Locations




FIGURE 3
Baseline Intersection Lane Configurations

1.3 STUDY ANALYSIS PERIODS

Traffic Operations are evaluated for each of the following scenarios during the weekday a.m. peak hour and the p.m. peak hour:

- Baseline (Existing) Conditions
- Baseline Conditions Plus Construction Conditions (2015)
- Year 2021 Without Project
- Year 2021 With Project Operations

Baseline (existing) conditions are obtained from turning movement traffic counts taken in August 2014 during the peak hours of operations (6:00 a.m. to 9:00 a.m. and 4:00 p.m. to 6:00 p.m.) as well as existing roadway signal and geometric conditions. These conditions include the trips to and from the proposed Project site and the parking lots to be used for the construction trips associated with the proposed Project. Based on traffic counts of those driveways, there are a total of 1,312 daily trips generated by these parking areas in the baseline conditions: 135 daily trips from the 223rd Street parking lot, 912 daily trips from the Alameda Street parking lot, and 265 daily trips from the Sepulveda Boulevard parking lot.

The trips associated with the construction of the proposed Project were added to the baseline traffic counts to evaluate construction conditions. The proposed Project will have several phases requiring a variable number of construction-related trips. For this analysis, the peak number of trips to be generated over the two-year construction period was used to determine the potential for significant impacts at the study locations¹. It was assumed the trips associated with current operations on the proposed Project site would occur at the same rate as in the baseline conditions.

The I-405/Wilmington Avenue Interchange began a major improvement project in November 2013 which is expected to be completed by late 2015 or early 2016. The geometrics at the study locations associated with the interchange are assumed to be the pre-construction configuration in the near-term construction period analysis—the construction activities prior to the traffic counts did not change the number of lanes or connections provided by the interchange. The I-405/Wilmington Avenue Interchange construction involves periodic closures and openings of geometric and operational improvements on a constant (daily, weekly, and monthly) but inconsistent basis over the course of its construction period, and while these many iterations of the I-405/Wilmington Avenue interchange construction period conditions were not specifically analyzed in this study, it is recommended that the construction schedule of the Interchange be integrated into the traffic management planning and scheduling for trips associated with the proposed Project for the duration of the overlapping construction periods.

Ambient (background traffic) Year 2021 Conditions were forecasted based on the annualized ambient growth as determined from the Southern California Association of Governments (SCAG) regional travel

¹ As explained in more detail in *Section 3.0 Construction Conditions*, below, during the majority of the construction period, only one work shift per day is expected. However, during peak construction activities, the project is expected to require two shifts per day, a day and night shift.

demand model. The proposed Project area annualized growth was calculated based on the growth between the two analysis years of the travel demand model (2012 to 2035) along Wilmington Avenue and Alameda Street from 223rd to Sepulveda Boulevard and along Sepulveda Boulevard and 223rd Street from Wilmington Avenue to Alameda Street. The annualized growth rate was calculated to be 0.4 percent per year. The completion of the I-405/Wilmington Avenue Interchange improvement project is assumed in the 2021 Project Operations scenario. The proposed Project operations are estimated to not increase the number of on-site workers after the opening of the proposed project, however approximately ten additional truck round-trips per work day would result from the proposed Project to support its operations.

2.0 BASELINE CONDITIONS

This section presents an overview of the existing roadway system and transit operations within the study area and the methodology used to determine existing traffic volumes.

2.1 ROADWAY CONFIGURATIONS

The existing configurations of the roadways within the study area are described as follows:

Wilmington Avenue, oriented in a north-south direction, is a four-lane roadway with a raised median. Wilmington Avenue provides access to the project site as well as regional access through its connection to the I-405 freeway. On-street parking is prohibited along Wilmington Avenue in the study area.

Alameda Street, oriented in a north-south direction, consists of two lanes in each direction. On-street parking is prohibited along Alameda Street in the study area. Alameda Street bisects and provides direct access to the project site.

Santa Fe Avenue, oriented in a north-south direction, consists of two lanes in each direction with a raised median and on-street parking permitted in the study area. Santa Fe Avenue runs parallel to the I-710 freeway and consists of multiple bus routes.

223rd Street, oriented in an east-west direction, consists of two lanes in each direction with on-street parking allowed in some sections of the study area. 223rd Street provides access to the project site. East of the project site, 223rd Street transitions to Wardlow Road.

Sepulveda Boulevard, oriented in an east-west direction, consists of two lanes in each direction. On-street parking is prohibited along Sepulveda Boulevard in the study area. East of the I-710 freeway, Sepulveda Boulevard transitions to Willow Street.

2.2 BASELINE TRANSIT OPERATIONS

The Los Angeles County Metropolitan Transportation Authority (Metro) and the Long Beach Transit (LBT) operate bus lines within the area of the project site. A description of the transit service follows:

Metro Line 202 – This line operates between Wilmington and Watts. Within the study area, this line travels north and south along Alameda Street. Service is provided at 60 minute headways during weekday peak periods, late night, and owl service. Weekend and holiday service is not provided.

Long Beach Line 191/192 – These lines operate between Downtown Long Beach and Lakewood. Within the study area, the lines travel north and south along Santa Fe Avenue. Service is provided on weekdays, weekends, and holidays. They currently provide 20 minute headways during peak periods.

Long Beach Line 101/102/103/104 – These lines operate between Wilmington and Long Beach. Within the study area, the lines travel east and west along Sepulveda Boulevard beginning at Santa Fe Avenue. Service is provided at 20 minute headways during weekday peak periods. Weekend and holiday service is limited.

2.3 BASELINE TRAFFIC VOLUMES

Vehicle turning movement counts at the study intersections were collected in August 2014 during the a.m. (6:00a.m. to 9:00 a.m.) and p.m. (4:00p.m. and 6:00 p.m.) peak periods. The traffic counts are a reasonable estimate of conditions during the baseline period. Detailed traffic count sheets are provided in **Appendix A**. **Figure 4** shows the existing peak hour volumes at the study intersections.

2.4 TRAFFIC OPERATIONS ANALYSIS METHODOLOGY

The efficiency of traffic operations on a facility can be described in terms of Level of Service (LOS). The level of service concept is a measure of average operating conditions at an intersection during an hour. Levels range from 'A' to 'F', with 'A' representing excellent (free-flow) conditions and 'F' representing a roadway operating at its design capacity.

Traffic operating conditions in the vicinity of the project were evaluated using methodologies described in each project area agencies' traffic analysis guidelines. The non-freeway ramp study intersections are analyzed using the Intersection Capacity Utilization (ICU) methodology for intersection analysis. ICU methodology defines the LOS by the volume-to-capacity (V/C) ratio for the turning movements and intersection characteristics at the signalized intersections. The ICU value is determined by summing the V/C ratio of the critical movements, plus a factor for a yellow signal time. Intersections located in the City of Los Angeles are also analyzed with the Circular 212 methodology which calculates the delay of critical movements in the intersection—those results are similar to the ICU calculation and are included in the appendix. The Caltrans ramp intersections are under Caltrans' jurisdiction and are analyzed using the Highway Capacity Manual (HCM) methodology. HCM methodology defines the LOS by the average vehicle delay experienced by all vehicles traveling through the intersection. **Table 1** presents the both the V/C ratio and average delay associated with each LOS grade as well as a qualitative description of intersection operations at that grade.

TABLE 1: INTERSECTION LEVEL OF SERVICE DEFINITIONS

Level of Service	Description	Signalized Intersection Volume-to-Capacity Ratio (V/C)	Signalized Intersection Delay (seconds)
A	Free flowing, virtually no delay. Minimal Traffic.	≤ 0.600	≤ 10
B	Free flow and choice of lanes. Delays are minimal. All cars clear intersection easily.	>0.600 to 0.699	>10 and ≤ 20
C	Good operation. Delays starting to become a factor but still within acceptable limits.	>0.700 to 0.799	>20 and ≤ 35
D	Approaching unstable flow. Queues at intersection are quite long but most cars clear intersection on their green signal. Occasionally, several vehicles must wait for a second green signal. Congestion is moderate.	>0.800 to 0.899	>35 and ≤ 55
E	Severe Congestion and delay. Most of the available capacity is used. Many cars must wait through a complete signal cycle to clear the intersection.	>0.900 to 0.999	>55 and ≤ 80
F	Excessive delay and congestion. Most cars must wait through more than one on one signal cycle. Queues are very long and drivers are obviously irritated.	> 1.000	> 80

Study location significance criteria are based on the location of each analyzed facility. The Cities in the study area consider LOS D to be the minimum acceptable LOS. The threshold of significance is considered to be a Project-related change in V/C ratio of 0.02 or greater if the final LOS is 'E' or 'F'.²

The City of Los Angeles has a sliding scale of acceptable effects for service levels 'C', 'D', 'E' and 'F'.³ For example, a greater effect is allowed under LOS 'C' than LOS 'D' before being considered significant. Thus, a project would have a significant impact on transportation/circulation during construction if it would increase an intersection's V/C ratio in accordance with the following guidelines:

- V/C ratio increase greater than or equal to 0.040 if final LOS is 'C',
- V/C ratio increase greater than or equal to 0.020 if final LOS is 'D', or
- V/C ratio increase greater than or equal to 0.010 if final LOS is 'E' or 'F'.

However since the analysis intersection located in the City of Los Angeles is forecasted to operate at no worse than LOS 'B' in any of the analysis scenarios, there is no impact determined at the intersection of Alameda Street Ramp at 223rd Street in the City of Los Angeles.

² City of Carson General Plan Update Transportation and Infrastructure Element, October 11, 2004, City of Long Beach General Plan Transportation Element, 1991 based on Los Angeles County Congestion Management Program Guidelines.

³ City of Los Angeles Department of Transportation Traffic Study Policies and Procedures, August 2014




FIGURE 4
Baseline Intersection Volumes

Caltrans has not adopted specific thresholds of significance for determining whether an impact is significant and relies on the local-defined County and City standards for significance thresholds. The transportation/traffic questions on the CEQA checklist XVI: Transportation/Traffic a) and b) state:

- a) Conflict with an applicable plan, ordinance or policy establishing measures of effectiveness for the performance of the circulation system, taking into account all modes of transportation including mass transit and non-motorized travel and relevant components of the circulation system, including but not limited to intersections, streets, highways and freeways, pedestrian and bicycle paths, and mass transit?
- b) Conflict with an applicable congestion management program including, but not limited to level of service standards and travel demand measures, or other standards established by the county congestion management agency for designated roads or highways?

Therefore the Caltrans CEQA Checklist defers to locally defined thresholds. For the purposes of this analysis, intersection locations under the jurisdiction of Caltrans will use the significance threshold of the City in which it is located.

2.5 BASELINE INTERSECTION LEVELS OF SERVICE

LOS analysis was conducted to evaluate existing intersection operations during the a.m. and p.m. peak hours. **Table 2** summarizes the existing level of service at the study intersections. LOS calculation worksheets are included in **Appendix B**.

TABLE 2: BASELINE EXISTING CONDITIONS (2014) INTERSECTION LEVELS OF SERVICE

Intersection		Agency / LOS Methodology	AM Peak Hour			PM Peak Hour		
			V/C Ratio	Delay (sec)	LOS	V/C Ratio	Delay (sec)	LOS
1	Wilmington Ave/I-405 NB Ramps	Caltrans / HCM	0.499	21.4	C	0.395	18.5	B
2	Wilmington Ave/I-405 SB Ramps	Caltrans / HCM	0.355	44.2	D	0.629	15.7	B
3	Wilmington Ave/223 rd St	Carson / ICU	0.643	-	B	0.690	-	B
4	Alameda St/I-405 NB Ramps	Caltrans / HCM	0.690	21.2	C	0.665	23.2	C
5	Alameda St/223 rd St (along Alameda St)	Carson / ICU	0.460	-	A	0.570	-	A
6	Alameda St/223 rd St (along 223 rd St)	LA / ICU	0.349	-	A	0.634	-	B
7	Alameda St/Sepulveda Blvd (along Alameda St)	Carson / ICU	0.374	-	A	0.537	-	A
8	Alameda St/Sepulveda Blvd (along Sepulveda Blvd)	Carson / ICU	0.415	-	A	0.742	-	C
9	I-405 SB Ramps/223 rd St	Caltrans / HCM	0.472	23.4	C	0.327	24.3	C
10	Terminal Island Fwy (SR-103)/Sepulveda Blvd	Long Beach / ICU	0.390	-	A	0.579	-	A
11	Santa Fe Ave/Sepulveda Blvd	Long Beach / ICU	0.624	-	C	0.781	-	C
12	I-710 SB Ramps/Willow St	Uncontrolled Intersection						
13	I-710 NB Ramps/Willow St	Uncontrolled Intersection						

Notes:

V/C = Volume to Capacity Ratio, LOS = Level of Service, Delay = Average Vehicle Delay (Seconds)

As shown in **Table 2**, the study intersections are currently operating at LOS D or better.

3.0 CONSTRUCTION CONDITIONS

Construction activities for the proposed Project are expected to begin in fourth quarter of 2015 and are expected to be completed by fourth quarter, 2019, based on preliminary project engineering. The preliminary construction schedule for each component of the proposed project varies. The construction activities for most of the components are expected to overlap from about December 2015 to February 2017. Construction work shifts are expected to last about ten hours per day during most portions of the construction schedule. During normal construction periods, one work shift per day is expected. However, during peak construction activities, the proposed project is expected to require two work shifts – one day and one night shift.

Due to the temporary nature of construction trips, in general construction-related traffic is considered less than significant; however detailed analysis of construction period conditions were conducted due to several factors. First, the proposed Project is expected to involve a large number of workers and therefore generate a large number of worker trips as compared to typical development projects in

southern California. Second, a cumulative construction event at the I-405/Wilmington interchange will overlap with the first phases of the proposed Project construction. Since the I-405/Wilmington interchange is expected to be utilized by many of the proposed Project construction trips, construction period analysis of the proposed Project include analysis at the beginning of the construction of the I-405/Wilmington Interchange (baseline conditions) in its pre-construction geometry. For these reasons detailed analysis of construction period conditions for the peak construction period (2015) was conducted to identify potential significant impacts and recommend construction period traffic management strategies to mitigate those impacts.

3.1 PROJECT CONSTRUCTION TRIP GENERATION AND DISTRIBUTION

Construction conditions are analyzed for the construction phase with the maximum number of construction trips during the two-year construction period. The peak construction period trip generation is shown below in **Table 3**. In total 950 workers will travel to and from the proposed Project site during the highest trip-generation phase of construction of the proposed project. These include 875 day shift workers and 75 night shift workers. In addition to worker trips, 120 truck trips would be generated during the peak trip-generating construction phase throughout the work day.

TABLE 3: CONSTRUCTION PERIOD DAILY TRIP GENERATION

Type	Work Shift	Total Round Trips	Total One-Way Trips
Supervisors	6 am – 5:30 pm	40	80
Dayshift Workers	7:00 am – 5:30 pm	835	1,670
Nightshift Workers	7:00 pm – 7:00 am	75	150
Trucks	Throughout the day	120	240
Total		1,070	2,140

In converting daily trip generation values into peak hour analysis periods, two adjustments were made. First, it was assumed that auto trips had a 10 percent carpool rate. Second, given the work shift hours for each type of worker, not all project trips are expected to occur within the peak hour for overall traffic volume in the study area and the following peak hour project trip generation assumptions were made:

- Supervisors would arrive before the a.m. peak hour and 50 percent would leave in the p.m. peak hour
- 50 percent of day shift workers would arrive during the a.m. peak hour and 50 percent would leave in the p.m. peak hour
- 50 percent of night shift workers would leave in the a.m. peak hour and 50 percent would arrive in the p.m. peak hour
- Truck trips are distributed evenly throughout the ten hour work day with 12 inbound and 12 outbound trips per peak hour. A passenger car equivalency (PCE) factor of 2.0 is applied to the truck trips to account for their larger size and slower turning speeds at intersections.

Of the 2,140 total daily construction-related trips shown in **Table 3**, PCE trips occurring in the peak hours are forecasted to be 454 PCE in the a.m. peak hour and 472 PCE trips in the p.m. peak hour as shown in **Table 4**.

TABLE 4: CONSTRUCTION PERIOD PEAK HOUR TRIP GENERATION

Type	AM Peak Hour			PM Peak Hour		
	In	Out	Total	In	Out	Total
Auto	376	34	410	34	394	428
Truck (PCE)	24	24	48	24	24	48
Total	400	58	458	58	418	476

Trip distribution assumptions were used to determine the origin and destination of new vehicle trips associated with the project. Trip distribution for the employee trips of the proposed Project was developed using the weighted distribution of workers, from the 2010 United States Census, in Los Angeles, Orange, Riverside, and San Bernardino Counties via the arterial network to Cities near the study area (e.g. Carson, Compton, Long Beach, portions of Los Angeles, and Torrance) and the regional freeway network for Cities more than two miles from the proposed Project site. As shown in **Figure 5**, distribution of employee trips was approximately 30 percent from I-405 north of the proposed Project site, 25 percent from I-405 south of the proposed Project site, 30 percent from I-710 north of the proposed Project site and 15 percent from local access along arterials. Truck trip distribution was assumed to occur to/from the north along I-710. The assignment of project-related trips shown in **Figure 6** is based on the trip distribution percentages.



FIGURE 5
Proposed Project Construction Trip Distribution




FIGURE 6
Proposed Project Construction Trip Assignment

3.2 CONSTRUCTION PERIOD INTERSECTION LEVELS OF SERVICE

LOS analysis was conducted to evaluate existing plus construction intersection operations during the a.m. and p.m. peak hours. **Figure 7** shows the baseline plus construction peak hour volumes at the study intersections. **Table 5** summarizes the LOS at the study intersections as compared to baseline LOS to determine if a threshold of significance was exceeded. LOS calculation worksheets are included in **Appendix B**.

Caltrans has undertaken a major construction project to modify the I-405/Wilmington interchange starting November 2013. The interchange construction is expected to finish in late 2015 or early 2016—potentially overlapping with the construction period of the proposed Project. The project will reconfigure existing on- and off-ramps from northbound and southbound I-405, construct a new on-ramp to southbound I-405, reconstruct Wilmington Avenue and Lenardo Drive, and construct a new bridge over the Torrance Lateral Channel.

The construction of the I-405/Wilmington Interchange will have periodic lane and ramp closures that, while temporary, have the potential to effect the proposed Project-related construction trips' interaction with the roadway network and demand placed on study intersections. While the Year 2015 With Project Construction Conditions (Pre- I-405/Wilmington Interchange) does not account for each possible iteration of lane closures⁴, it does include the construction period analysis of the proposed Project at the beginning of the construction of the I-405/Wilmington Interchange (baseline conditions) in its pre-construction geometry. These conditions are shown in **Table 5**. Further the Year 2021 scenarios assume the completion of the interchange in its post-construction configuration. .

⁴ The I-405/Wilmington Avenue Interchange construction involves periodic closures and openings of geometric and operational improvements on a constant (daily, weekly, and monthly) but inconsistent basis over the course of its construction period

1. Wilmington Ave & I-405 NB Ramps ← 375/795 ← 21/71 ← 464/302 ← 693/428 ← 982/836 ← 9/363 ← 49/226 ← 9/363	2. Wilmington Ave & I-405 SB Ramps ← 910/889 ← 141/337 ← 317/485 ← 359/478 ← 123/260 ← 250/97 ← 147/38 ← 55/125
--	--




FIGURE 7
Proposed Project Construction Period Intersection Volumes

Tesoro Los Angeles Refinery
Integration & Compliance Project
Traffic Study



TABLE 5: BASELINE EXISTING CONDITIONS PLUS PROJECT CONSTRUCTION CONDITIONS (PRE- I-405/WILMINGTON INTERCHANGE)
INTERSECTION LOS

Intersection		Existing Conditions						Existing Plus Construction Conditions						a.m. Change in V/C or Delay	p.m. Change in V/C or Delay	Significant Impact?
		a.m. Peak Hour			p.m. Peak Hour			a.m. Peak Hour			p.m. Peak Hour					
		V/C Ratio	Delay (sec)	LOS	V/C Ratio	Delay (sec)	LOS	V/C Ratio	Delay (sec)	LOS	V/C Ratio	Delay (sec)	LOS			
1	Wilmington Ave/I-405 NB Ramps	0.499	21.4	C	0.395	18.5	B	0.500	21.5	C	0.395	18.6	B	0.1 s	No	
2	Wilmington Ave/I-405 SB Ramps	0.355	44.2	D	0.629	15.7	B	0.439	57.9	E	0.641	16.5	B	13.7 s	Yes ¹	
3	Wilmington Ave/223 rd St	0.643	-	B	0.690	-	B	0.653	-	B	0.696	-	B	0.010	No	
4	Alameda St/I-405 NB Ramps	0.690	21.2	C	0.665	23.2	C	0.807	25.6	C	0.683	23.8	C	4.4 s	No	
5	Alameda St/223 rd St (along Alameda St)	0.460	-	A	0.570	-	A	0.484	-	A	0.604	-	B	0.024	No	
6	Alameda St/223 rd St (along 223 rd St)	0.349	-	A	0.634	-	B	0.358	-	A	0.696	-	B	0.009	No	
7	Alameda St/Sepulveda Blvd (along Alameda St)	0.374	-	A	0.537	-	A	0.406	-	A	0.552	-	A	0.032	No	
8	Alameda St/Sepulveda Blvd (along Sepulveda Blvd)	0.415	-	A	0.742	-	C	0.452	-	A	0.751	-	C	0.037	No	
9	I-405 SB Ramps/223 rd St	0.472	23.4	C	0.327	24.3	C	0.502	24.6	C	0.395	23.7	C	1.2 s	No	
10	Terminal Island Fwy (SR-103)/Sepulveda Blvd	0.390	-	A	0.579	-	A	0.421	-	A	0.595	-	A	0.031	No	
11	Santa Fe Ave/Sepulveda Blvd	0.624	-	C	0.781	-	C	0.654	-	C	0.798	-	C	0.030	No	
12	I-710 SB Ramps/Willow St	Uncontrolled Intersection												No		
13	I-710 NB Ramps/Willow St	Uncontrolled Intersection												No		

¹ = Significant temporary impact based on LOS E operation with the addition of construction-related trips.

Notes:

V/C = Volume to Capacity Ratio, LOS = Level of Service, Delay = Average Vehicle Delay (Seconds), s = seconds

As shown in **Table 5**, construction-related trips are forecast to result in a significant impact during construction conditions at the Wilmington Ave/I-405 Southbound Ramps under their pre-construction configuration. This is due to the large number of project-related trips utilizing the Southbound ramp to access the proposed Project site in the a.m. peak hour.

It should be emphasized that this exceedance of the threshold of significance is temporary in nature and does not represent a significant impact that would require permanent mitigation by the applicant. However, it does indicate that inbound trips to the proposed Project during the construction period should avoid the I-405/Wilmington interchange while it is under construction.

In order to reduce the proposed Project's construction-related trips on the Wilmington Avenue/I-405 Southbound Ramps intersection prior to the completion of the I-405/Wilmington Avenue Interchange Modification Project, it is recommended that proposed Project workers be advised of the construction schedule and potential restrictions and closures associated with the Interchange Modification Project. It is recommended that the Project workers be encouraged to avoid the Wilmington Avenue/I-405 Southbound Ramps intersection during morning peak travel periods by traveling either outside of the morning peak travel time or along alternative routes. The operational conditions of all other study locations, operating at LOS C or better during peak hours, demonstrate the adequacy of several alternative routes for proposed Project construction period trips.

The I-405/Wilmington Avenue Interchange Modification Project maintains several sources of information about current construction conditions through a web site (<http://i405wilmington.com>), a bilingual, toll-free hotline (887) 481-0004 and an email notification system.

The protocols for the dissemination of information to proposed Project workers and potential alternative schedules or routing during construction activities for the proposed project should be provided in the form of a construction staging and/or traffic management plan, to be approved by the Cities of Carson and Los Angeles.

4.0 YEAR 2021 CONDITIONS

Year 2021 conditions were forecasted by applying ambient growth from year 2014 with the 0.4 percent per year growth as calculated from the SCAG travel demand model. The proposed Project operations are estimated to not increase the number of on-site workers after the construction phase, however approximately ten additional truck round-trips per work day would result from the proposed Project to support its operations. The peak hour estimates of these project-related trips were used to develop a year 2021 with proposed Project scenario that was compared against the year 2021 conditions without the proposed Project to determine if any significant impacts would occur due to the operation of the proposed Project.

4.1 YEAR 2021 WITHOUT PROJECT INTERSECTION LEVELS OF SERVICE

Figure 8 shows the year 2021 without project peak hour volumes at the study intersections. A level of service analysis was conducted to evaluate year 2021 without project intersection operations during the a.m. and p.m. peak hours. **Table 6** summarizes the year 2021 without project LOS at the study intersections. LOS calculation worksheets are included in **Appendix B**.

TABLE 6: YEAR 2021 WITHOUT PROJECT CONDITIONS INTERSECTION LOS

Intersection		Agency / LOS Methodology	a.m. Peak Hour			p.m. Peak Hour		
			V/C Ratio	Delay (sec)	LOS	V/C Ratio	Delay (sec)	LOS
1	Wilmington Ave/I-405 NB Ramps	Caltrans / HCM	0.512	21.7	C	0.420	18.4	B
2	Wilmington Ave/I-405 SB Ramps	Caltrans / HCM	0.364	21.8	C	0.362	15.7	B
3	Wilmington Ave/223 rd St	Carson / ICU	0.656	-	B	0.703	-	C
4	Alameda St/I-405 NB Ramps	Caltrans / HCM	0.687	23.4	C	0.681	23.5	C
5	Alameda St/223 rd St (along Alameda St)	Carson / ICU	0.470	-	A	0.581	-	A
6	Alameda St/223 rd St (along 223 rd St)	LA / ICU	0.355	-	A	0.647	-	B
7	Alameda St/Sepulveda Blvd (along Alameda St)	Carson / ICU	0.380	-	A	0.548	-	A
8	Alameda St/Sepulveda Blvd (along Sepulveda Blvd)	Carson / ICU	0.422	-	A	0.758	-	C
9	I-405 SB Ramps/223 rd St	Caltrans / HCM	0.484	23.5	C	0.514	19.1	B
10	Terminal Island Fwy (SR-103)/Sepulveda Blvd	Long Beach / ICU	0.396	-	A	0.590	-	A
11	Santa Fe Ave/Sepulveda Blvd	Long Beach / ICU	0.636	-	B	0.798	-	C
12	I-710 SB Ramps/Willow St	Uncontrolled Intersection						
13	I-710 NB Ramps/Willow St	Uncontrolled Intersection						


Notes:

V/C = Volume to Capacity Ratio, LOS = Level of Service, Delay = Average Vehicle Delay (Seconds)

Traffic Impact Analysis

Draft

1. Wilmington Ave & I-405 NB Ramps	2. Wilmington Ave & I-405 SB Ramps	3. Wilmington Ave & 223rd St	4. Alameda Ave & I-405 NB Ramps	5. Alameda Ave & 223rd St	6. Alameda Ave & 223rd St	7. Alameda Ave & Sepulveda Blvd
402/886 496/309 710/438 34/155 371/289	928/910 144/345 126/27 168/84 368/491 311/416	327/204 58/56 558/811 663/742 140/246 558/811 16/10 82/127 506/426 11/8	860/773 51/82 320/108 473/393 48/195 571/944	1149/1004 163/168 122/125 180/114 248/472 482/991	408/1212 82/141 765/290 228/94 272/506 146/99	785/877 235/266 203/417 50/95 51/85 438/1012
8. Alameda Ave & Sepulveda Blvd	9. I-405 SB Ramps & 223rd St	10. SR-103 & Sepulveda Blvd	11. Santa Fe Ave & Sepulveda Blvd	12. SR-710 SB Ramps & Willow St	13. SR-710 NB Ramps & Willow St	
147/176 9/12 128/131 121/235 364/958 4/9 19/13 2/4	126/37 0/2 56/128 362/660 309/617 4/18	4/0 324/1024 187/262 16/1 813/435 242/171 101/254 99/319	135/64 264/319 156/339 75/143 436/1006 33/44 82/205 188/438 78/84	1095/1835 163/261 446/979 177/94 1021/1304 197/413	936/1905 360/372 123/96 363/303 1074/1276 155/111	



Tesoro Los Angeles Refinery
Integration & Compliance Project
Traffic Study

FIGURE 8
Year 2021 Without Proposed Project Intersection Volumes

4.2 YEAR 2021 WITH PROJECT INTERSECTION LEVELS OF SERVICE

A level of service analysis was conducted to evaluate year 2021 with project conditions during the a.m. and p.m. peak hours. The following trip generation assumptions for the operation of the proposed Project were made:

- There will be no increase in workers as compared to baseline conditions following completion of the construction phase
- Eight trucks per day will transport spent sulfuric acid from the Carson Plant to the new Sulfuric Acid Plant at Wilmington
- One truck per day will transport other materials and supplies to or from the Refinery

Overall ten truck roundtrips over 10 daytime hours are estimated to occur with the completion of the proposed Project. Based on the above assumptions, the estimated worst-case a.m. and p.m. trips were estimated: two inbound and two outbound truck trips in each peak hour, resulting in four inbound and four outbound PCE trips per peak hour as shown in **Table 7**.

TABLE 7: PROPOSED PROJECT OPERATION PEAK HOUR TRIPS

Type	a.m. Peak Hour		p.m. Peak Hour	
	In	Out	In	Out
Auto	0	0	0	0
Truck (PCE)	4	4	4	4
Total	4	4	4	4

Trip distribution assumptions were used to determine the origin and destination of vehicle trips associated with the operation of the proposed Project. As shown in **Figure 9**, distribution of proposed Project trips was 25 percent from I-405 north of the proposed Project site, 25 percent from I-405 south of the proposed Project site, 25 percent from I-710 north of the proposed Project site and 25 percent from local access along Willow Street east of the proposed Project site based on the equitable distribution of trips to major destinations outside of the study area. The assignment of project-related trips shown in **Figure 10** is based on the trip distribution percentages.

The resulting year 2021 peak hour traffic volumes at the study intersections with the proposed project are shown in **Figure 11**. **Table 8** summarizes the year 2021 with project LOS compared to without project conditions at the study intersections. LOS calculation worksheets are included in **Appendix B**.

As shown in **Table 8**, the proposed Project is not forecasted to cause a study location to exceed a threshold of significance and therefore the project would have a less than significant impact on area roadway facilities.

It should be noted that an Existing Conditions plus Project Operations was not conducted in addition to the Year 2021 Plus Project Operations scenario since the Year 2021 Plus Project Operations scenario was developed in this study as an existing conditions plus ambient growth to Year 2021 plus Project Operations. If levels of significance are not exceeded under the Year 2021 levels of ambient traffic, they will not be under lower levels of existing traffic.

Traffic Impact Analysis

Draft




FIGURE 9
Proposed Project Operations Distribution



**Tesoro Los Angeles Refinery
Integration & Compliance Project
Traffic Study**



Page 27
Tesoro Los Angeles Refinery Reconfiguration
South Coast AQMD

1576303

Traffic Impact Analysis

Draft

1. Wilmington Ave & I-405 NB Ramps	2. Wilmington Ave & I-405 SB Ramps	3. Wilmington Ave & 223rd St	4. Alameda Ave & I-405 NB Ramps	5. Alameda Ave & 223rd St	6. Alameda Ave & 223rd St	7. Alameda Ave & Sepulveda Blvd
8. Alameda Ave & Sepulveda Blvd	9. I-405 SB Ramps & 223rd St	10. SR-103 & Sepulveda Blvd	11. Santa Fe Ave & Sepulveda Blvd	12. SR-710 SB Ramps & Willow St	13. SR-710 NB Ramps & Willow St	



Tesoro Los Angeles Refinery
Integration & Compliance Project
Traffic Study

FIGURE 10
Proposed Project Operations Trip Assignment

Traffic Impact Analysis

Draft

1. Wilmington Ave & I-405 NB Ramps 402/886 496/309 710/438 35/156 371/289 682/178	2. Wilmington Ave & I-405 SB Ramps 928/910 144/345 126/27 169/85 368/491 312/417 161/87 51/85	3. Wilmington Ave & 223rd St 327/204 664/743 58/56 140/246 558/811 16/10 82/127 507/427 11/8	4. Alameda Ave & I-405 NB Ramps 860/773 51/82 156/339 264/319 135/64 48/195 571/944 408/1212	5. Alameda Ave & 223rd St 1150/1005 163/168 447/980 177/94 1022/1305 249/473 482/991 82/141	6. Alameda Ave & 223rd St 765/290 228/94 408/1212 82/141 273/507 146/99 438/1012 51/85	7. Alameda Ave & Sepulveda Blvd 785/877 236/257 204/418 50/95 438/1012 51/85 438/1012
8. Alameda Ave & Sepulveda Blvd 148/177 9/12 128/131 100/244 610/549 8/2 19/13 4/6 6/1	9. I-405 SB Ramps & 223rd St 363/861 309/817 4/18 126/37 56/128 0/2 5/3 1/6 1/3	10. SR-103 & Sepulveda Blvd 40/0 326/1026 187/262 16/1 815/437 242/171 101/254 99/6319 1097/1837	11. Santa Fe Ave & Sepulveda Blvd 75/143 438/1008 33/44 156/339 264/319 135/64 82/205 188/438 78/84	12. SR-710 SB Ramps & Willow St 1097/1837 163/261 163/261 447/980 177/94 1022/1305 197/413 937/1906 361/373	13. SR-710 NB Ramps & Willow St 155/111 937/1906 361/373 123/96 363/303 1075/1277 155/111 937/1906 361/373	




FIGURE 11
Year 2021 With Proposed Project Operations Intersection Volumes

Tesoro Los Angeles Refinery
Integration & Compliance Project
Traffic Study

TABLE 8: YEAR 2021 WITH PROJECT INTERSECTION LOS

Intersection		Year 2021 Without Project						Year 2021 With Project Operations						a.m. Change in V/C or Delay	p.m. Change in V/C or Delay	Significant Impact?
		a.m. Peak Hour			p.m. Peak Hour			a.m. Peak Hour			p.m. Peak Hour					
		V/C Ratio	Delay (sec)	LOS	V/C Ratio	Delay (sec)	LOS	V/C Ratio	Delay (sec)	LOS	V/C Ratio	Delay (sec)	LOS			
1	Wilmington Ave/I-405 NB Ramps	0.512	21.7	C	0.420	18.4	B	0.512	21.7	C	0.420	18.4	B	0 s	No	
2	Wilmington Ave/I-405 SB Ramps	0.364	21.8	C	0.362	15.7	B	0.365	21.8	C	0.363	15.8	B	0 s	No	
3	Wilmington Ave/223 rd St	0.656	-	B	0.703	-	C	0.657	-	B	0.703	-	C	0.001	No	
4	Alameda St/I-405 NB Ramps	0.687	23.4	C	0.681	23.5	C	0.687	23.4	C	0.682	23.6	C	0 s	No	
5	Alameda St/223 rd St (along Alameda St)	0.470	-	A	0.581	-	A	0.471	-	A	0.581	-	A	0.001	No	
6	Alameda St/223 rd St (along 223 rd St)	0.355	-	A	0.647	-	B	0.355	-	A	0.647	-	B	0	No	
7	Alameda St/Sepulveda Blvd (along Alameda St)	0.380	-	A	0.548	-	A	0.381	-	A	0.549	-	A	0.001	No	
8	Alameda St/Sepulveda Blvd (along Sepulveda Blvd)	0.422	-	A	0.758	-	C	0.423	-	A	0.759	-	C	0.001	No	
9	I-405 SB Ramps/223 rd St	0.484	23.5	C	0.514	19.1	B	0.484	23.5	C	0.514	19.1	B	0 s	No	
10	Terminal Island Fwy (SR-103)/Sepulveda Blvd	0.396	-	A	0.590	-	A	0.397	-	A	0.591	-	A	0.001	No	
11	Santa Fe Ave/Sepulveda Blvd	0.636	-	B	0.798	-	C	0.637	-	B	0.799	-	C	0.001	No	
12	I-710 SB Ramps/Willow St	Uncontrolled Intersection														-
13	I-710 NB Ramps/Willow St	Uncontrolled Intersection														-

Notes:

V/C = Volume to Capacity Ratio, LOS = Level of Service, Delay = Average Vehicle Delay (Seconds)

5.0 CONCLUSIONS

As shown in **Table 5**, under the Baseline Existing Conditions (2014) Plus Project Construction Conditions scenario, temporary construction-related trips are forecast to result in a potentially significant impact at the Wilmington Ave/I-405 Southbound Ramps under the I-405/Wilmington Interchange pre-construction configuration. This is due to the large number of temporary project-related trips utilizing the southbound ramp to access the proposed Project site in the a.m. peak hour.

It should be emphasized that this exceedance of the threshold of significance is temporary in nature and does not represent a significant impact that would require permanent mitigation by the applicant. However, it does indicate that inbound trips to the proposed Project during the construction period should avoid the I-405/Wilmington interchange while it is under construction.

In order to reduce the proposed Project's construction-related trips on the Wilmington Avenue/I-405 Southbound Ramps intersection prior to the completion of the I-405/Wilmington Avenue Interchange Modification Project, it is recommended that proposed Project workers be advised of the construction schedule and potential restrictions and closures associated with the Interchange Modification Project. Workers should be encouraged to avoid the Wilmington Avenue/I-405 Southbound Ramps intersection during morning peak travel periods by traveling either outside of the morning peak travel time or along alternative routes. The operational conditions of all other study locations, operating at LOS C or better during peak hours, demonstrate the adequacy of several alternative routes for proposed Project construction period trips.

The protocols for the dissemination of information to proposed Project workers and potential alternative schedules or routing during construction activities for the proposed project should be provided in the form of a construction staging and/or traffic management plan, to be approved by the Cities of Carson and Los Angeles.

As shown in **Table 12**, the proposed Project is not forecasted to cause a study location to exceed a threshold of significance in year 2021 and therefore the project would have a less than significant impact on area roadway facilities.

It should be noted that an Existing Conditions plus Project Operations was not conducted in addition to the Year 2021 Plus Project Operations scenario since the Year 2021 Plus Project Operations scenario was developed in this study as an existing conditions plus ambient growth to Year 2021 plus Project Operations. If levels of significance are not exceeded under the Year 2021 levels of ambient traffic, they will not be under lower levels of existing traffic.

APPENDIX A: TRAFFIC COUNTS

CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

File Name : Wilmington_405NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	Wilmington Ave Southbound			405 NB Ramps Westbound			Wilmington Ave Northbound			Eastbound			Int. Total
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	10	78	0	159	0	78	0	46	24	0	0	0	395
06:15 AM	6	84	0	174	0	85	0	44	9	0	0	0	402
06:30 AM	1	80	0	172	0	94	0	96	14	0	0	0	457
06:45 AM	7	95	0	180	0	137	0	124	5	0	0	0	548
Total	24	337	0	685	0	394	0	310	52	0	0	0	1802
07:00 AM	4	75	0	187	0	111	0	71	10	0	0	0	458
07:15 AM	6	94	0	161	0	108	0	90	13	0	0	0	472
07:30 AM	4	107	0	165	0	128	0	77	5	0	0	0	486
07:45 AM	3	98	0	130	0	148	0	99	13	0	0	0	491
Total	17	374	0	643	0	495	0	337	41	0	0	0	1907
08:00 AM	3	105	0	161	0	109	0	95	18	0	0	0	491
08:15 AM	5	86	0	146	0	125	0	80	9	0	0	0	451
08:30 AM	7	105	0	118	0	110	0	80	14	0	0	0	434
08:45 AM	4	99	0	115	0	99	0	63	14	0	0	0	394
Total	19	395	0	540	0	443	0	318	55	0	0	0	1770
04:00 PM	18	195	0	99	0	71	0	59	24	0	0	0	466
04:15 PM	15	166	0	100	0	59	0	60	26	0	0	0	426
04:30 PM	16	190	0	105	0	78	0	67	39	0	0	0	495
04:45 PM	21	201	0	108	0	76	0	82	46	0	0	0	534
Total	70	752	0	412	0	284	0	268	135	0	0	0	1921
05:00 PM	20	190	0	111	0	76	0	61	32	0	0	0	490
05:15 PM	14	213	0	104	0	72	0	72	34	0	0	0	509
05:30 PM	9	174	0	102	0	66	0	74	33	0	0	0	458
05:45 PM	13	176	0	109	0	104	0	62	40	0	0	0	504
Total	56	753	0	426	0	318	0	269	139	0	0	0	1961
Grand Total	186	2611	0	2706	0	1934	0	1502	422	0	0	0	9361
Apprch %	6.6	93.4	0	58.3	0	41.7	0	78.1	21.9	0	0	0	
Total %	2	27.9	0	28.9	0	20.7	0	16	4.5	0	0	0	

CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Wilmington_405NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Wilmington Ave Southbound				405 NB Ramps Westbound				Wilmington Ave Northbound				Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 06:45 AM																	
06:45 AM	7	95	0	102	180	0	137	317	0	124	5	129	0	0	0	0	548
07:00 AM	4	75	0	79	187	0	111	298	0	71	10	81	0	0	0	0	458
07:15 AM	6	94	0	100	161	0	108	269	0	90	13	103	0	0	0	0	472
07:30 AM	4	107	0	111	165	0	128	293	0	77	5	82	0	0	0	0	486
Total Volume	21	371	0	392	693	0	484	1177	0	362	33	395	0	0	0	0	1964
% App. Total	5.4	94.6	0		58.9	0	41.1		0	91.6	8.4		0	0	0		
PHF	.750	.867	.000	.883	.926	.000	.883	.928	.000	.730	.635	.766	.000	.000	.000	.000	.896



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Wilmington_405NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Wilmington Ave Southbound				405 NB Ramps Westbound				Wilmington Ave Northbound				Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:30 PM																	
04:30 PM	16	190	0	206	105	0	78	183	0	67	39	106	0	0	0	0	495
04:45 PM	21	201	0	222	108	0	76	184	0	82	46	128	0	0	0	0	534
05:00 PM	20	190	0	210	111	0	76	187	0	61	32	93	0	0	0	0	490
05:15 PM	14	213	0	227	104	0	72	176	0	72	34	106	0	0	0	0	509
Total Volume	71	794	0	865	428	0	302	730	0	282	151	433	0	0	0	0	2028
% App. Total	8.2	91.8	0		58.6	0	41.4		0	65.1	34.9		0	0	0		
PHF	.845	.932	.000	.953	.964	.000	.968	.976	.000	.860	.821	.846	.000	.000	.000	.000	.949



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E

File Name : Wilmington_405SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	Wilmington Ave Southbound			405 SB Ramp Westbound			Wilmington Ave Northbound			405 SB Ramp Eastbound			Int. Total
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	38	198	0	0	0	0	0	53	100	15	0	31	435
06:15 AM	40	211	0	0	0	0	0	41	107	12	0	34	445
06:30 AM	35	227	0	0	0	0	0	84	98	27	0	43	514
06:45 AM	43	222	0	0	0	0	0	78	89	50	0	46	528
Total	156	858	0	0	0	0	0	256	394	104	0	154	1922
07:00 AM	25	240	0	0	0	0	0	62	81	19	0	35	462
07:15 AM	38	217	0	0	0	0	0	80	91	27	0	40	493
07:30 AM	46	217	0	0	0	0	0	64	79	18	0	37	461
07:45 AM	24	212	0	0	0	0	0	85	94	27	0	63	505
Total	133	886	0	0	0	0	0	291	345	91	0	175	1921
08:00 AM	48	210	0	0	0	0	0	98	103	23	0	47	529
08:15 AM	43	187	1	0	0	0	0	92	83	24	0	47	477
08:30 AM	46	181	0	0	0	0	0	66	79	27	0	51	450
08:45 AM	26	191	0	0	0	0	0	70	90	24	0	42	443
Total	163	769	1	0	0	0	0	326	355	98	0	187	1899
04:00 PM	86	212	0	0	0	0	0	81	117	10	0	19	525
04:15 PM	77	190	0	0	0	0	0	81	125	6	0	25	504
04:30 PM	79	218	0	0	0	0	0	98	142	6	0	17	560
04:45 PM	88	220	0	0	0	0	0	119	110	11	0	15	563
Total	330	840	0	0	0	0	0	379	494	33	0	76	2152
05:00 PM	83	220	0	0	0	0	0	84	105	7	0	29	528
05:15 PM	87	230	0	0	0	0	0	105	122	2	0	21	567
05:30 PM	75	203	0	0	0	0	0	97	125	11	0	10	521
05:45 PM	78	203	0	0	0	0	0	93	126	6	0	12	518
Total	323	856	0	0	0	0	0	379	478	26	0	72	2134
Grand Total	1105	4209	1	0	0	0	0	1631	2066	352	0	664	10028
Apprch %	20.8	79.2	0	0	0	0	0	44.1	55.9	34.6	0	65.4	
Total %	11	42	0	0	0	0	0	16.3	20.6	3.5	0	6.6	

CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : Wilmington_405SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Wilmington Ave Southbound				405 SB Ramp Westbound				Wilmington Ave Northbound				405 SB Ramp Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 06:30 AM																	
06:30 AM	35	227	0	262	0	0	0	0	0	84	98	182	27	0	43	70	514
06:45 AM	43	222	0	265	0	0	0	0	0	78	89	167	50	0	46	96	528
07:00 AM	25	240	0	265	0	0	0	0	0	62	81	143	19	0	35	54	462
07:15 AM	38	217	0	255	0	0	0	0	0	80	91	171	27	0	40	67	493
Total Volume	141	906	0	1047	0	0	0	0	0	304	359	663	123	0	164	287	1997
% App. Total	13.5	86.5	0		0	0	0		0	45.9	54.1		42.9	0	57.1		
PHF	.820	.944	.000	.988	.000	.000	.000	.000	.000	.905	.916	.911	.615	.000	.891	.747	.946



CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : Wilmington_405SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Wilmington Ave Southbound				405 SB Ramp Westbound				Wilmington Ave Northbound				405 SB Ramp Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:30 PM																	
04:30 PM	79	218	0	297	0	0	0	0	0	98	142	240	6	0	17	23	560
04:45 PM	88	220	0	308	0	0	0	0	0	119	110	229	11	0	15	26	563
05:00 PM	83	220	0	303	0	0	0	0	0	84	105	189	7	0	29	36	528
05:15 PM	87	230	0	317	0	0	0	0	0	105	122	227	2	0	21	23	567
Total Volume	337	888	0	1225	0	0	0	0	0	406	479	885	26	0	82	108	2218
% App. Total	27.5	72.5	0		0	0	0		0	45.9	54.1		24.1	0	75.9		
PHF	.957	.965	.000	.966	.000	.000	.000	.000	.000	.853	.843	.922	.591	.000	.707	.750	.978



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E

File Name : Wilmington_223rd

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	Wilmington Ave Southbound			223rd St Westbound			Wilmington Ave Northbound			223rd St Eastbound			Int. Total
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	11	152	49	35	33	15	3	125	7	28	36	0	494
06:15 AM	6	169	69	36	56	11	1	117	3	26	52	3	549
06:30 AM	6	185	74	42	148	12	3	138	4	33	64	0	709
06:45 AM	12	183	77	50	130	10	2	119	22	38	66	3	712
Total	35	689	269	163	367	48	9	499	36	125	218	6	2464
07:00 AM	13	169	82	51	132	12	7	109	8	27	99	7	716
07:15 AM	9	161	75	55	231	13	3	114	21	32	112	5	831
07:30 AM	22	148	90	54	235	12	3	117	14	33	140	5	873
07:45 AM	12	177	78	38	178	13	1	143	17	32	149	2	840
Total	56	655	325	198	776	50	14	483	60	124	500	19	3260
08:00 AM	14	161	76	53	150	15	4	120	28	40	144	4	809
08:15 AM	16	155	73	45	128	15	6	97	15	27	102	0	679
08:30 AM	14	149	58	34	102	12	3	108	23	42	78	5	628
08:45 AM	12	152	71	32	103	8	2	112	16	19	68	6	601
Total	56	617	278	164	483	50	15	437	82	128	392	15	2717
04:00 PM	18	166	47	25	62	21	1	109	23	69	213	5	759
04:15 PM	14	173	36	40	68	23	3	112	24	63	210	4	770
04:30 PM	8	167	58	43	87	64	4	86	20	70	184	4	795
04:45 PM	14	178	49	40	70	35	1	126	40	59	185	2	799
Total	54	684	190	148	287	143	9	433	107	261	792	15	3123
05:00 PM	20	190	42	50	101	28	1	83	38	48	191	1	793
05:15 PM	13	189	50	44	87	16	2	121	26	63	232	3	846
05:30 PM	16	148	51	22	56	26	2	126	35	63	226	5	776
05:45 PM	14	162	44	25	49	26	4	136	40	55	184	7	746
Total	63	689	187	141	293	96	9	466	139	229	833	16	3161
Grand Total	264	3334	1249	814	2206	387	56	2318	424	867	2735	71	14725
Apprch %	5.4	68.8	25.8	23.9	64.7	11.4	2	82.8	15.2	23.6	74.5	1.9	
Total %	1.8	22.6	8.5	5.5	15	2.6	0.4	15.7	2.9	5.9	18.6	0.5	

CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : Wilmington_223rd

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Wilmington Ave Southbound				223rd St Westbound				Wilmington Ave Northbound				223rd St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:15 AM																	
07:15 AM	9	161	75	245	55	231	13	299	3	114	21	138	32	112	5	149	831
07:30 AM	22	148	90	260	54	235	12	301	3	117	14	134	33	140	5	178	873
07:45 AM	12	177	78	267	38	178	13	229	1	143	17	161	32	149	2	183	840
08:00 AM	14	161	76	251	53	150	15	218	4	120	28	152	40	144	4	188	809
Total Volume	57	647	319	1023	200	794	53	1047	11	494	80	585	137	545	16	698	3353
% App. Total	5.6	63.2	31.2		19.1	75.8	5.1		1.9	84.4	13.7		19.6	78.1	2.3		
PHF	.648	.914	.886	.958	.909	.845	.883	.870	.688	.864	.714	.908	.856	.914	.800	.928	.960



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E


File Name : Wilmington_223rd

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Wilmington Ave Southbound				223rd St Westbound				Wilmington Ave Northbound				223rd St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:30 PM																	
04:30 PM	8	167	58	233	43	87	64	194	4	86	20	110	70	184	4	258	795
04:45 PM	14	178	49	241	40	70	35	145	1	126	40	167	59	185	2	246	799
05:00 PM	20	190	42	252	50	101	28	179	1	83	38	122	48	191	1	240	793
05:15 PM	13	189	50	252	44	87	16	147	2	121	26	149	63	232	3	298	846
Total Volume	55	724	199	978	177	345	143	665	8	416	124	548	240	792	10	1042	3233
% App. Total	5.6	74	20.3		26.6	51.9	21.5		1.5	75.9	22.6		23	76	1		
PHF	.688	.953	.858	.970	.885	.854	.559	.857	.500	.825	.775	.820	.857	.853	.625	.874	.955



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

File Name : Alameda_405NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	Alameda Ave Southbound			405 NB Ramps Westbound			Alameda Ave Northbound			405 NB Ramps Eastbound			
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Int. Total
06:00 AM	18	93	0	138	0	30	0	69	20	0	0	0	368
06:15 AM	8	133	0	144	0	31	0	65	13	0	0	0	394
06:30 AM	11	164	0	153	0	64	0	105	14	0	0	0	511
06:45 AM	17	137	0	132	0	51	0	99	15	0	0	0	451
Total	54	527	0	567	0	176	0	338	62	0	0	0	1724
07:00 AM	19	200	0	123	0	63	0	120	13	0	0	0	538
07:15 AM	12	207	0	104	0	64	0	124	13	0	0	0	524
07:30 AM	7	219	0	117	0	88	0	165	14	0	0	0	610
07:45 AM	12	214	0	118	0	97	0	148	7	0	0	0	596
Total	50	840	0	462	0	312	0	557	47	0	0	0	2268
08:00 AM	12	185	0	95	0	59	0	123	16	0	0	0	490
08:15 AM	8	133	0	84	0	61	0	111	13	0	0	0	410
08:30 AM	7	155	0	83	0	41	0	79	10	0	0	0	375
08:45 AM	6	146	0	92	0	37	0	85	14	0	0	0	380
Total	33	619	0	354	0	198	0	398	53	0	0	0	1655
04:00 PM	19	156	0	111	0	40	0	189	39	0	0	0	554
04:15 PM	21	179	0	121	0	32	0	198	37	0	0	0	588
04:30 PM	19	188	0	110	0	29	0	224	58	0	0	0	628
04:45 PM	17	175	0	106	0	28	0	255	53	0	0	0	634
Total	76	698	0	448	0	129	0	866	187	0	0	0	2404
05:00 PM	26	188	0	84	0	13	0	221	49	0	0	0	581
05:15 PM	18	204	0	84	0	35	0	222	30	0	0	0	593
05:30 PM	19	212	0	89	0	26	0	196	29	0	0	0	571
05:45 PM	10	141	0	105	0	37	0	157	39	0	0	0	489
Total	73	745	0	362	0	111	0	796	147	0	0	0	2234
Grand Total	286	3429	0	2193	0	926	0	2955	496	0	0	0	10285
Apprch %	7.7	92.3	0	70.3	0	29.7	0	85.6	14.4	0	0	0	
Total %	2.8	33.3	0	21.3	0	9	0	28.7	4.8	0	0	0	

CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : Alameda_405NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Alameda Ave Southbound				405 NB Ramps Westbound				Alameda Ave Northbound				405 NB Ramps Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:00 AM																	
07:00 AM	19	200	0	219	123	0	63	186	0	120	13	133	0	0	0	0	538
07:15 AM	12	207	0	219	104	0	64	168	0	124	13	137	0	0	0	0	524
07:30 AM	7	219	0	226	117	0	88	205	0	165	14	179	0	0	0	0	610
07:45 AM	12	214	0	226	118	0	97	215	0	148	7	155	0	0	0	0	596
Total Volume	50	840	0	890	462	0	312	774	0	557	47	604	0	0	0	0	2268
% App. Total	5.6	94.4	0		59.7	0	40.3		0	92.2	7.8		0	0	0		
PHF	.658	.959	.000	.985	.939	.000	.804	.900	.000	.844	.839	.844	.000	.000	.000	.000	.930



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Alameda_405NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Alameda Ave Southbound				405 NB Ramps Westbound				Alameda Ave Northbound				405 NB Ramps Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:30 PM																	
04:30 PM	19	188	0	207	110	0	29	139	0	224	58	282	0	0	0	0	628
04:45 PM	17	175	0	192	106	0	28	134	0	255	53	308	0	0	0	0	634
05:00 PM	26	188	0	214	84	0	13	97	0	221	49	270	0	0	0	0	581
05:15 PM	18	204	0	222	84	0	35	119	0	222	30	252	0	0	0	0	593
Total Volume	80	755	0	835	384	0	105	489	0	922	190	1112	0	0	0	0	2436
% App. Total	9.6	90.4	0		78.5	0	21.5		0	82.9	17.1		0	0	0		
PHF	.769	.925	.000	.940	.873	.000	.750	.879	.000	.904	.819	.903	.000	.000	.000	.000	.961



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E

File Name : 223rd_Alameda_onAlameda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	Alameda St Southbound			223rd St Westbound			Alameda St Northbound			Eastbound			Int. Total
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	30	195	0	31	0	12	0	63	38	0	0	0	369
06:15 AM	34	239	0	50	0	11	0	68	33	0	0	0	435
06:30 AM	30	277	0	43	0	21	0	92	50	0	0	0	513
06:45 AM	32	243	0	39	0	20	0	95	55	0	0	0	484
Total	126	954	0	163	0	64	0	318	176	0	0	0	1801
07:00 AM	31	290	0	39	0	28	0	99	62	0	0	0	549
07:15 AM	35	273	0	41	0	27	0	102	65	0	0	0	543
07:30 AM	42	280	0	47	0	31	0	145	63	0	0	0	608
07:45 AM	51	279	0	49	0	33	0	125	52	0	0	0	589
Total	159	1122	0	176	0	119	0	471	242	0	0	0	2289
08:00 AM	40	251	0	42	0	28	0	120	26	0	0	0	507
08:15 AM	33	181	0	37	0	32	0	92	23	0	0	0	398
08:30 AM	32	203	0	40	0	26	0	81	12	0	0	0	394
08:45 AM	26	207	0	27	0	26	0	77	18	0	0	0	381
Total	131	842	0	146	0	112	0	370	79	0	0	0	1680
04:00 PM	47	212	0	25	0	24	0	198	108	0	0	0	614
04:15 PM	25	240	0	27	0	17	0	212	107	0	0	0	628
04:30 PM	39	259	0	35	0	38	0	237	108	0	0	0	716
04:45 PM	39	235	0	27	0	26	0	277	112	0	0	0	716
Total	150	946	0	114	0	105	0	924	435	0	0	0	2674
05:00 PM	41	239	0	21	0	34	0	229	118	0	0	0	682
05:15 PM	45	247	0	28	0	24	0	225	123	0	0	0	692
05:30 PM	41	251	0	17	0	18	0	205	98	0	0	0	630
05:45 PM	28	209	0	16	0	21	0	177	95	0	0	0	546
Total	155	946	0	82	0	97	0	836	434	0	0	0	2550
Grand Total	721	4810	0	681	0	497	0	2919	1366	0	0	0	10994
Apprch %	13	87	0	57.8	0	42.2	0	68.1	31.9	0	0	0	
Total %	6.6	43.8	0	6.2	0	4.5	0	26.6	12.4	0	0	0	

CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : 223rd_Alameda_onAlameda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Alameda St Southbound				223rd St Westbound				Alameda St Northbound				Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:00 AM																	
07:00 AM	31	290	0	321	39	0	28	67	0	99	62	161	0	0	0	0	549
07:15 AM	35	273	0	308	41	0	27	68	0	102	65	167	0	0	0	0	543
07:30 AM	42	280	0	322	47	0	31	78	0	145	63	208	0	0	0	0	608
07:45 AM	51	279	0	330	49	0	33	82	0	125	52	177	0	0	0	0	589
Total Volume	159	1122	0	1281	176	0	119	295	0	471	242	713	0	0	0	0	2289
% App. Total	12.4	87.6	0		59.7	0	40.3		0	66.1	33.9		0	0	0		
PHF	.779	.967	.000	.970	.898	.000	.902	.899	.000	.812	.931	.857	.000	.000	.000	.000	.941



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : 223rd_Alameda_onAlameda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Alameda St Southbound				223rd St Westbound				Alameda St Northbound				Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:30 PM																	
04:30 PM	39	259	0	298	35	0	38	73	0	237	108	345	0	0	0	0	716
04:45 PM	39	235	0	274	27	0	26	53	0	277	112	389	0	0	0	0	716
05:00 PM	41	239	0	280	21	0	34	55	0	229	118	347	0	0	0	0	682
05:15 PM	45	247	0	292	28	0	24	52	0	225	123	348	0	0	0	0	692
Total Volume	164	980	0	1144	111	0	122	233	0	968	461	1429	0	0	0	0	2806
% App. Total	14.3	85.7	0		47.6	0	52.4		0	67.7	32.3		0	0	0		
PHF	.911	.946	.000	.960	.793	.000	.803	.798	.000	.874	.937	.918	.000	.000	.000	.000	.980



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

File Name : 223rd_Alameda_on223rd

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

Start Time	Southbound			223rd St Westbound			Alameda St Northbound			223rd St Eastbound			Int. Total
	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	0	0	0	34	78	0	18	0	49	0	53	10	242
06:15 AM	0	0	0	37	107	0	18	0	50	0	57	20	289
06:30 AM	0	0	0	40	158	0	29	0	50	0	57	19	353
06:45 AM	0	0	0	40	169	0	33	0	54	0	77	19	392
Total	0	0	0	151	512	0	98	0	203	0	244	68	1276
07:00 AM	0	0	0	53	179	0	35	0	59	0	79	16	421
07:15 AM	0	0	0	51	180	0	41	0	63	0	102	18	455
07:30 AM	0	0	0	63	207	0	40	0	67	0	110	19	506
07:45 AM	0	0	0	56	181	0	27	0	77	0	107	27	475
Total	0	0	0	223	747	0	143	0	266	0	398	80	1857
08:00 AM	0	0	0	48	148	0	28	0	39	0	120	26	409
08:15 AM	0	0	0	45	132	0	33	0	55	0	118	24	407
08:30 AM	0	0	0	41	106	0	28	0	28	0	105	24	332
08:45 AM	0	0	0	36	110	0	20	0	22	0	123	20	331
Total	0	0	0	170	496	0	109	0	144	0	466	94	1479
04:00 PM	0	0	0	22	62	0	32	0	124	0	268	20	528
04:15 PM	0	0	0	24	69	0	19	0	116	0	304	21	553
04:30 PM	0	0	0	27	45	0	30	0	112	0	307	48	569
04:45 PM	0	0	0	21	81	0	24	0	128	0	290	34	578
Total	0	0	0	94	257	0	105	0	480	0	1169	123	2228
05:00 PM	0	0	0	20	88	0	24	0	138	0	282	35	587
05:15 PM	0	0	0	26	74	0	24	0	144	0	248	27	543
05:30 PM	0	0	0	16	67	0	22	0	112	0	282	20	519
05:45 PM	0	0	0	19	65	0	15	0	111	0	274	20	504
Total	0	0	0	81	294	0	85	0	505	0	1086	102	2153
Grand Total	0	0	0	719	2306	0	540	0	1598	0	3363	467	8993
Apprch %	0	0	0	23.8	76.2	0	25.3	0	74.7	0	87.8	12.2	
Total %	0	0	0	8	25.6	0	6	0	17.8	0	37.4	5.2	

CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : 223rd_Alameda_on223rd

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Southbound				223rd St Westbound				Alameda St Northbound				223rd St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:00 AM																	
07:00 AM	0	0	0	0	53	179	0	232	35	0	59	94	0	79	16	95	421
07:15 AM	0	0	0	0	51	180	0	231	41	0	63	104	0	102	18	120	455
07:30 AM	0	0	0	0	63	207	0	270	40	0	67	107	0	110	19	129	506
07:45 AM	0	0	0	0	56	181	0	237	27	0	77	104	0	107	27	134	475
Total Volume	0	0	0	0	223	747	0	970	143	0	266	409	0	398	80	478	1857
% App. Total	0	0	0	0	23	77	0		35	0	65		0	83.3	16.7		
PHF	.000	.000	.000	.000	.885	.902	.000	.898	.872	.000	.864	.956	.000	.905	.741	.892	.917



CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : 223rd_Alameda_on223rd

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Southbound				223rd St Westbound				Alameda St Northbound				223rd St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:15 PM																	
04:15 PM	0	0	0	0	24	69	0	93	19	0	116	135	0	304	21	325	553
04:30 PM	0	0	0	0	27	45	0	72	30	0	112	142	0	307	48	355	569
04:45 PM	0	0	0	0	21	81	0	102	24	0	128	152	0	290	34	324	578
05:00 PM	0	0	0	0	20	88	0	108	24	0	138	162	0	282	35	317	587
Total Volume	0	0	0	0	92	283	0	375	97	0	494	591	0	1183	138	1321	2287
% App. Total	0	0	0	0	24.5	75.5	0		16.4	0	83.6		0	89.6	10.4		
PHF	.000	.000	.000	.000	.852	.804	.000	.868	.808	.000	.895	.912	.000	.963	.719	.930	.974



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

File Name : Sepulveda_Alameda_onAlameda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	Alameda St Southbound			Sepulveda Blvd Westbound			Alameda St Northbound			Eastbound			Int. Total
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	49	174	0	2	0	20	0	68	16	0	0	0	329
06:15 AM	52	181	0	6	0	31	0	80	10	0	0	0	360
06:30 AM	74	210	0	13	0	36	0	87	12	0	0	0	432
06:45 AM	60	212	0	15	0	53	0	103	7	0	0	0	450
Total	235	777	0	36	0	140	0	338	45	0	0	0	1571
07:00 AM	51	217	0	12	0	48	0	100	12	0	0	0	440
07:15 AM	50	184	0	11	0	46	0	86	15	0	0	0	392
07:30 AM	60	196	0	11	0	46	0	105	16	0	0	0	434
07:45 AM	62	196	0	14	0	49	0	117	11	0	0	0	449
Total	223	793	0	48	0	189	0	408	54	0	0	0	1715
08:00 AM	61	201	0	9	0	54	0	104	9	0	0	0	438
08:15 AM	46	173	0	15	0	49	0	102	14	0	0	0	399
08:30 AM	51	151	0	11	0	43	0	87	12	0	0	0	355
08:45 AM	50	142	0	13	0	39	0	92	13	0	0	0	349
Total	208	667	0	48	0	185	0	385	48	0	0	0	1541
04:00 PM	49	252	0	18	0	101	0	196	17	0	0	0	633
04:15 PM	59	218	0	27	0	98	0	144	14	0	0	0	560
04:30 PM	57	226	0	27	0	113	0	267	28	0	0	0	718
04:45 PM	54	211	0	26	0	112	0	240	21	0	0	0	664
Total	219	907	0	98	0	424	0	847	80	0	0	0	2575
05:00 PM	57	197	0	22	0	108	0	255	18	0	0	0	657
05:15 PM	82	222	0	18	0	74	0	226	16	0	0	0	638
05:30 PM	41	184	0	27	0	92	0	209	16	0	0	0	569
05:45 PM	59	177	0	18	0	58	0	147	20	0	0	0	479
Total	239	780	0	85	0	332	0	837	70	0	0	0	2343
Grand Total	1124	3924	0	315	0	1270	0	2815	297	0	0	0	9745
Apprch %	22.3	77.7	0	19.9	0	80.1	0	90.5	9.5	0	0	0	
Total %	11.5	40.3	0	3.2	0	13	0	28.9	3	0	0	0	

CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Sepulveda_Alameda_onAlameda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Alameda St Southbound				Sepulveda Blvd Westbound				Alameda St Northbound				Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:30 AM																	
07:30 AM	60	196	0	256	11	0	46	57	0	105	16	121	0	0	0	0	434
07:45 AM	62	196	0	258	14	0	49	63	0	117	11	128	0	0	0	0	449
08:00 AM	61	201	0	262	9	0	54	63	0	104	9	113	0	0	0	0	438
08:15 AM	46	173	0	219	15	0	49	64	0	102	14	116	0	0	0	0	399
Total Volume	229	766	0	995	49	0	198	247	0	428	50	478	0	0	0	0	1720
% App. Total	23	77	0		19.8	0	80.2		0	89.5	10.5		0	0	0		
PHF	.923	.953	.000	.949	.817	.000	.917	.965	.000	.915	.781	.934	.000	.000	.000	.000	.958



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Sepulveda_Alameda_onAlameda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Alameda St Southbound				Sepulveda Blvd Westbound				Alameda St Northbound				Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:30 PM																	
04:30 PM	57	226	0	283	27	0	113	140	0	267	28	295	0	0	0	0	718
04:45 PM	54	211	0	265	26	0	112	138	0	240	21	261	0	0	0	0	664
05:00 PM	57	197	0	254	22	0	108	130	0	255	18	273	0	0	0	0	657
05:15 PM	82	222	0	304	18	0	74	92	0	226	16	242	0	0	0	0	638
Total Volume	250	856	0	1106	93	0	407	500	0	988	83	1071	0	0	0	0	2677
% App. Total	22.6	77.4	0		18.6	0	81.4		0	92.3	7.7		0	0	0		
PHF	.762	.947	.000	.910	.861	.000	.900	.893	.000	.925	.741	.908	.000	.000	.000	.000	.932



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E

File Name : Sepulveda_Alameda_onSepulveda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	Alameda St Southbound			Sepulveda Blvd Westbound			Alameda St Northbound			Sepulveda Blvd Eastbound			Int. Total
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	21	8	34	4	66	14	0	1	0	9	36	0	193
06:15 AM	20	6	34	3	108	15	1	5	0	15	45	0	252
06:30 AM	34	7	44	0	154	30	0	3	0	16	67	1	356
06:45 AM	29	4	33	0	158	30	0	6	0	33	77	0	370
Total	104	25	145	7	486	89	1	15	0	73	225	1	1171
07:00 AM	33	2	26	1	125	26	0	2	1	29	88	1	334
07:15 AM	26	4	36	1	164	27	1	5	1	24	85	2	376
07:30 AM	38	2	33	2	152	26	0	3	1	28	83	3	371
07:45 AM	32	1	39	3	148	25	0	5	2	31	89	1	376
Total	129	9	134	7	589	104	1	15	5	112	345	7	1457
08:00 AM	29	2	36	2	130	20	1	6	0	35	98	0	359
08:15 AM	29	3	28	2	119	22	2	6	4	30	83	0	328
08:30 AM	39	3	23	1	103	30	0	2	0	24	83	0	308
08:45 AM	25	4	37	0	107	30	1	1	0	18	75	1	299
Total	122	12	124	5	459	102	4	15	4	107	339	1	1294
04:00 PM	32	4	28	1	101	68	2	5	2	46	186	1	476
04:15 PM	46	4	23	0	112	71	1	4	4	52	213	0	530
04:30 PM	44	1	39	1	103	69	1	6	5	64	247	0	580
04:45 PM	34	5	33	1	120	70	1	6	3	62	219	0	554
Total	156	14	123	3	436	278	5	21	14	224	865	1	2140
05:00 PM	32	4	40	0	130	69	2	2	3	59	243	0	584
05:15 PM	35	2	60	1	151	51	0	2	2	42	210	0	556
05:30 PM	27	1	39	0	133	48	1	3	1	66	263	1	583
05:45 PM	40	5	32	0	103	30	0	2	3	44	224	0	483
Total	134	12	171	1	517	198	3	9	9	211	940	1	2206
Grand Total	645	72	697	23	2487	771	14	75	32	727	2714	11	8268
Apprch %	45.6	5.1	49.3	0.7	75.8	23.5	11.6	62	26.4	21.1	78.6	0.3	
Total %	7.8	0.9	8.4	0.3	30.1	9.3	0.2	0.9	0.4	8.8	32.8	0.1	

CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Sepulveda_Alameda_onSepulveda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Alameda St Southbound				Sepulveda Blvd Westbound				Alameda St Northbound				Sepulveda Blvd Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:15 AM																	
07:15 AM	26	4	36	66	1	164	27	192	1	5	1	7	24	85	2	111	376
07:30 AM	38	2	33	73	2	152	26	180	0	3	1	4	28	83	3	114	371
07:45 AM	32	1	39	72	3	148	25	176	0	5	2	7	31	89	1	121	376
08:00 AM	29	2	36	67	2	130	20	152	1	6	0	7	35	98	0	133	359
Total Volume	125	9	144	278	8	594	98	700	2	19	4	25	118	355	6	479	1482
% App. Total	45	3.2	51.8		1.1	84.9	14		8	76	16		24.6	74.1	1.3		
PHF	.822	.563	.923	.952	.667	.905	.907	.911	.500	.792	.500	.893	.843	.906	.500	.900	.985



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Sepulveda_Alameda_onSepulveda

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Alameda St Southbound				Sepulveda Blvd Westbound				Alameda St Northbound				Sepulveda Blvd Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:45 PM																	
04:45 PM	34	5	33	72	1	120	70	191	1	6	3	10	62	219	0	281	554
05:00 PM	32	4	40	76	0	130	69	199	2	2	3	7	59	243	0	302	584
05:15 PM	35	2	60	97	1	151	51	203	0	2	2	4	42	210	0	252	556
05:30 PM	27	1	39	67	0	133	48	181	1	3	1	5	66	263	1	330	583
Total Volume	128	12	172	312	2	534	238	774	4	13	9	26	229	935	1	1165	2277
% App. Total	41	3.8	55.1		0.3	69	30.7		15.4	50	34.6		19.7	80.3	0.1		
PHF	.914	.600	.717	.804	.500	.884	.850	.953	.500	.542	.750	.650	.867	.889	.250	.883	.975



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E

File Name : Alameda_405SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

Start Time	405 SB Ramps Southbound			Alameda @ 223rd St Westbound			Driveway Northbound			Alameda @ 223rd St Eastbound			Int. Total
	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	2	1	33	0	79	6	2	3	7	62	35	3	233
06:15 AM	8	0	35	6	101	6	4	4	4	67	37	1	273
06:30 AM	8	1	31	2	165	7	0	3	3	66	40	1	327
06:45 AM	3	2	35	0	173	4	1	0	1	71	57	1	348
Total	21	4	134	8	518	23	7	10	15	266	169	6	1181
07:00 AM	6	0	27	0	202	7	1	0	2	79	56	0	380
07:15 AM	12	0	25	0	204	7	0	1	2	84	75	0	410
07:30 AM	22	0	37	2	231	15	0	0	0	95	83	2	487
07:45 AM	15	0	34	1	200	3	0	0	1	95	88	2	439
Total	55	0	123	3	837	32	1	1	5	353	302	4	1716
08:00 AM	12	0	28	2	162	4	3	0	0	86	70	4	371
08:15 AM	12	0	41	1	137	10	0	0	0	98	77	1	377
08:30 AM	7	0	31	0	109	4	1	1	0	78	63	2	296
08:45 AM	9	0	35	1	105	5	0	0	0	79	64	0	298
Total	40	0	135	4	513	23	4	1	0	341	274	7	1342
04:00 PM	13	0	8	3	74	14	1	0	2	186	199	0	500
04:15 PM	21	0	13	2	78	5	0	2	0	198	217	1	537
04:30 PM	26	1	8	0	65	19	1	0	1	210	204	14	549
04:45 PM	31	0	11	1	93	12	0	2	0	213	202	1	566
Total	91	1	40	6	310	50	2	4	3	807	822	16	2152
05:00 PM	36	1	6	1	100	25	1	3	2	227	192	2	596
05:15 PM	32	0	11	2	89	21	1	1	0	190	200	1	548
05:30 PM	24	0	7	4	77	18	0	1	2	185	208	0	526
05:45 PM	32	1	10	3	71	12	1	1	0	180	200	0	511
Total	124	2	34	10	337	76	3	6	4	782	800	3	2181
Grand Total	331	7	466	31	2515	204	17	22	27	2549	2367	36	8572
Apprch %	41.2	0.9	58	1.1	91.5	7.4	25.8	33.3	40.9	51.5	47.8	0.7	
Total %	3.9	0.1	5.4	0.4	29.3	2.4	0.2	0.3	0.3	29.7	27.6	0.4	

CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Alameda_405SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	405 SB Ramps Southbound				Alameda @ 223rd St Westbound				Driveway Northbound				Alameda @ 223rd St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:00 AM																	
07:00 AM	6	0	27	33	0	202	7	209	1	0	2	3	79	56	0	135	380
07:15 AM	12	0	25	37	0	204	7	211	0	1	2	3	84	75	0	159	410
07:30 AM	22	0	37	59	2	231	15	248	0	0	0	0	95	83	2	180	487
07:45 AM	15	0	34	49	1	200	3	204	0	0	1	1	95	88	2	185	439
Total Volume	55	0	123	178	3	837	32	872	1	1	5	7	353	302	4	659	1716
% App. Total	30.9	0	69.1		0.3	96	3.7		14.3	14.3	71.4		53.6	45.8	0.6		
PHF	.625	.000	.831	.754	.375	.906	.533	.879	.250	.250	.625	.583	.929	.858	.500	.891	.881



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Alameda_405SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	405 SB Ramps Southbound				Alameda @ 223rd St Westbound				Driveway Northbound				Alameda @ 223rd St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:30 PM																	
04:30 PM	26	1	8	35	0	65	19	84	1	0	1	2	210	204	14	428	549
04:45 PM	31	0	11	42	1	93	12	106	0	2	0	2	213	202	1	416	566
05:00 PM	36	1	6	43	1	100	25	126	1	3	2	6	227	192	2	421	596
05:15 PM	32	0	11	43	2	89	21	112	1	1	0	2	190	200	1	391	548
Total Volume	125	2	36	163	4	347	77	428	3	6	3	12	840	798	18	1656	2259
% App. Total	76.7	1.2	22.1		0.9	81.1	18		25	50	25		50.7	48.2	1.1		
PHF	.868	.500	.818	.948	.500	.868	.770	.849	.750	.500	.375	.500	.925	.978	.321	.967	.948



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

File Name : Sepulveda_TerminalIslandFrwy103

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

Start Time	Southbound			Sepulveda Blvd Westbound			Terminal Island Frwy 103 Northbound			Sepulveda Blvd Eastbound			Int. Total
	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	0	0	0	42	99	0	6	0	18	0	28	13	206
06:15 AM	0	0	0	50	143	0	17	0	10	0	34	11	265
06:30 AM	0	0	0	67	197	0	21	0	23	0	35	25	368
06:45 AM	0	0	0	55	186	4	20	0	21	0	66	27	379
Total	0	0	0	214	625	4	64	0	72	0	163	76	1218
07:00 AM	0	0	0	47	147	3	27	0	19	1	61	34	339
07:15 AM	0	0	0	73	194	0	23	0	22	2	67	44	425
07:30 AM	0	0	0	59	230	8	22	0	24	0	78	55	476
07:45 AM	0	0	0	66	206	5	34	0	28	2	93	39	473
Total	0	0	0	245	777	16	106	0	93	5	299	172	1713
08:00 AM	0	0	0	38	164	3	18	0	25	0	78	45	371
08:15 AM	0	0	0	29	128	1	20	0	24	0	75	32	309
08:30 AM	0	0	0	33	117	2	35	0	18	1	75	46	327
08:45 AM	0	0	0	19	109	1	39	0	27	1	70	33	299
Total	0	0	0	119	518	7	112	0	94	2	298	156	1306
04:00 PM	0	0	0	55	88	1	75	1	44	0	192	44	500
04:15 PM	0	0	0	45	96	1	88	1	59	0	232	56	578
04:30 PM	0	0	0	53	94	1	55	0	55	1	266	67	592
04:45 PM	0	0	0	55	103	1	102	0	55	0	248	63	627
Total	0	0	0	208	381	4	320	2	213	1	938	230	2297
05:00 PM	0	0	0	38	105	0	60	0	67	0	245	80	595
05:15 PM	0	0	0	37	111	0	82	0	78	0	226	58	592
05:30 PM	0	0	0	37	106	0	67	0	48	0	281	55	594
05:45 PM	0	0	0	35	96	0	37	0	30	0	229	63	490
Total	0	0	0	147	418	0	246	0	223	0	981	256	2271
Grand Total	0	0	0	933	2719	31	848	2	695	8	2679	890	8805
Apprch %	0	0	0	25.3	73.8	0.8	54.9	0.1	45	0.2	74.9	24.9	
Total %	0	0	0	10.6	30.9	0.4	9.6	0	7.9	0.1	30.4	10.1	

CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : Sepulveda_TerminalIslandFrwy103

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Southbound				Sepulveda Blvd Westbound				Terminal Island Frwy 103 Northbound				Sepulveda Blvd Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:15 AM																	
07:15 AM	0	0	0	0	73	194	0	267	23	0	22	45	2	67	44	113	425
07:30 AM	0	0	0	0	59	230	8	297	22	0	24	46	0	78	55	133	476
07:45 AM	0	0	0	0	66	206	5	277	34	0	28	62	2	93	39	134	473
08:00 AM	0	0	0	0	38	164	3	205	18	0	25	43	0	78	45	123	371
Total Volume	0	0	0	0	236	794	16	1046	97	0	99	196	4	316	183	503	1745
% App. Total	0	0	0	0	22.6	75.9	1.5		49.5	0	50.5		0.8	62.8	36.4		
PHF	.000	.000	.000	.000	.808	.863	.500	.880	.713	.000	.884	.790	.500	.849	.832	.938	.916



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Sepulveda_TerminalIslandFrwy103

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Southbound				Sepulveda Blvd Westbound				Terminal Island Frwy 103 Northbound				Sepulveda Blvd Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:45 PM																	
04:45 PM	0	0	0	0	55	103	1	159	102	0	55	157	0	248	63	311	627
05:00 PM	0	0	0	0	38	105	0	143	60	0	67	127	0	245	80	325	595
05:15 PM	0	0	0	0	37	111	0	148	82	0	78	160	0	226	58	284	592
05:30 PM	0	0	0	0	37	106	0	143	67	0	48	115	0	281	55	336	594
Total Volume	0	0	0	0	167	425	1	593	311	0	248	559	0	1000	256	1256	2408
% App. Total	0	0	0	0	28.2	71.7	0.2		55.6	0	44.4		0	79.6	20.4		
PHF	.000	.000	.000	.000	.759	.957	.250	.932	.762	.000	.795	.873	.000	.890	.800	.935	.960



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E

File Name : Sepulveda_SantaFe

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	Santa Fe Ave Southbound			Sepulveda Blvd Westbound			Santa Fe Ave Northbound			Sepulveda Blvd Eastbound			
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Int. Total
06:00 AM	14	24	14	9	114	15	11	22	10	6	55	4	298
06:15 AM	20	27	15	14	130	22	18	23	11	2	51	5	338
06:30 AM	28	37	27	9	194	17	18	35	15	4	68	6	458
06:45 AM	29	42	25	19	201	23	15	31	7	18	100	6	516
Total	91	130	81	51	639	77	62	111	43	30	274	21	1610
07:00 AM	24	38	26	15	184	24	23	36	8	12	84	2	476
07:15 AM	38	62	42	31	200	27	16	42	17	16	98	6	595
07:30 AM	30	56	38	45	201	21	22	40	23	27	106	4	613
07:45 AM	51	72	35	50	200	34	19	55	23	15	126	15	695
Total	143	228	141	141	785	106	80	173	71	70	414	27	2379
08:00 AM	33	68	17	33	166	26	19	47	17	15	96	7	544
08:15 AM	34	55	20	22	115	19	16	40	15	19	94	13	462
08:30 AM	34	47	16	19	120	36	20	37	31	10	97	8	475
08:45 AM	51	50	10	33	108	25	12	32	20	10	84	7	442
Total	152	220	63	107	509	106	67	156	83	54	371	35	1923
04:00 PM	70	76	23	41	111	43	24	72	40	33	202	10	745
04:15 PM	59	81	21	39	118	38	15	77	47	34	242	7	778
04:30 PM	70	69	16	31	129	42	17	112	45	31	270	13	845
04:45 PM	85	91	17	29	133	34	18	122	61	40	247	8	885
Total	284	317	77	140	491	157	74	383	193	138	961	38	3253
05:00 PM	82	71	21	30	90	34	21	98	49	40	228	9	773
05:15 PM	94	80	8	47	131	39	26	96	45	29	237	13	845
05:30 PM	81	71	15	45	116	31	21	85	41	29	238	6	779
05:45 PM	75	86	9	52	104	47	21	63	43	33	233	16	782
Total	332	308	53	174	441	151	89	342	178	131	936	44	3179
Grand Total	1002	1203	415	613	2865	597	372	1165	568	423	2956	165	12344
Apprch %	38.2	45.9	15.8	15	70.3	14.7	17.7	55.3	27	11.9	83.4	4.7	
Total %	8.1	9.7	3.4	5	23.2	4.8	3	9.4	4.6	3.4	23.9	1.3	

CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : Sepulveda_SantaFe

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	Santa Fe Ave Southbound				Sepulveda Blvd Westbound				Santa Fe Ave Northbound				Sepulveda Blvd Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:15 AM																	
07:15 AM	38	62	42	142	31	200	27	258	16	42	17	75	16	98	6	120	595
07:30 AM	30	56	38	124	45	201	21	267	22	40	23	85	27	106	4	137	613
07:45 AM	51	72	35	158	50	200	34	284	19	55	23	97	15	126	15	156	695
08:00 AM	33	68	17	118	33	166	26	225	19	47	17	83	15	96	7	118	544
Total Volume	152	258	132	542	159	767	108	1034	76	184	80	340	73	426	32	531	2447
% App. Total	28	47.6	24.4		15.4	74.2	10.4		22.4	54.1	23.5		13.7	80.2	6		
PHF	.745	.896	.786	.858	.795	.954	.794	.910	.864	.836	.870	.876	.676	.845	.533	.851	.880



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E


File Name : Sepulveda_SantaFe

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	Santa Fe Ave Southbound				Sepulveda Blvd Westbound				Santa Fe Ave Northbound				Sepulveda Blvd Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:30 PM																	
04:30 PM	70	69	16	155	31	129	42	202	17	112	45	174	31	270	13	314	845
04:45 PM	85	91	17	193	29	133	34	196	18	122	61	201	40	247	8	295	885
05:00 PM	82	71	21	174	30	90	34	154	21	98	49	168	40	228	9	277	773
05:15 PM	94	80	8	182	47	131	39	217	26	96	45	167	29	237	13	279	845
Total Volume	331	311	62	704	137	483	149	769	82	428	200	710	140	982	43	1165	3348
% App. Total	47	44.2	8.8		17.8	62.8	19.4		11.5	60.3	28.2		12	84.3	3.7		
PHF	.880	.854	.738	.912	.729	.908	.887	.886	.788	.877	.820	.883	.875	.909	.827	.928	.946



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E

File Name : Willow_710SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	710 SB Ramps Southbound			Willow St Westbound			710 SB Ramps Northbound			Willow St Eastbound			Int. Total
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	0	0	74	0	90	22	0	0	15	0	131	21	353
06:15 AM	0	0	81	0	134	18	0	0	30	0	184	28	475
06:30 AM	0	0	135	0	174	28	0	0	30	0	200	26	593
06:45 AM	0	0	112	0	193	23	0	0	34	0	221	39	622
Total	0	0	402	0	591	91	0	0	109	0	736	114	2043
07:00 AM	0	0	80	0	196	19	0	0	34	0	227	16	572
07:15 AM	0	0	137	0	215	42	0	0	50	0	242	39	725
07:30 AM	0	0	98	0	291	51	0	0	43	0	259	37	779
07:45 AM	0	0	111	0	261	48	0	0	47	0	323	42	832
Total	0	0	426	0	963	160	0	0	174	0	1051	134	2908
08:00 AM	0	0	89	0	230	32	0	0	52	0	245	41	689
08:15 AM	0	0	90	0	200	30	0	0	44	0	272	33	669
08:30 AM	0	0	68	0	179	29	0	0	54	0	269	51	650
08:45 AM	0	0	71	0	192	24	0	0	58	0	281	38	664
Total	0	0	318	0	801	115	0	0	208	0	1067	163	2672
04:00 PM	0	0	131	0	262	18	0	0	95	0	409	53	968
04:15 PM	0	0	161	0	261	21	0	0	93	0	426	55	1017
04:30 PM	0	0	139	0	288	30	0	0	129	0	462	55	1103
04:45 PM	0	0	118	0	290	26	0	0	99	0	441	48	1022
Total	0	0	549	0	1101	95	0	0	416	0	1738	211	4110
05:00 PM	0	0	211	0	317	31	0	0	109	0	475	70	1213
05:15 PM	0	0	254	0	299	22	0	0	103	0	451	57	1186
05:30 PM	0	0	196	0	340	16	0	0	104	0	446	73	1175
05:45 PM	0	0	295	0	317	23	0	0	87	0	420	55	1197
Total	0	0	956	0	1273	92	0	0	403	0	1792	255	4771
Grand Total	0	0	2651	0	4729	553	0	0	1310	0	6384	877	16504
Apprch %	0	0	100	0	89.5	10.5	0	0	100	0	87.9	12.1	
Total %	0	0	16.1	0	28.7	3.4	0	0	7.9	0	38.7	5.3	

CITY TRAFFIC COUNTERS

626.991.7522

Appendix E
www.ctcounters.com


File Name : Willow_710SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	710 SB Ramps Southbound				Willow St Westbound				710 SB Ramps Northbound				Willow St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:15 AM																	
07:15 AM	0	0	137	137	0	215	42	257	0	0	50	50	0	242	39	281	725
07:30 AM	0	0	98	98	0	291	51	342	0	0	43	43	0	259	37	296	779
07:45 AM	0	0	111	111	0	261	48	309	0	0	47	47	0	323	42	365	832
08:00 AM	0	0	89	89	0	230	32	262	0	0	52	52	0	245	41	286	689
Total Volume	0	0	435	435	0	997	173	1170	0	0	192	192	0	1069	159	1228	3025
% App. Total	0	0	100		0	85.2	14.8		0	0	100		0	87.1	12.9		
PHF	.000	.000	.794	.794	.000	.857	.848	.855	.000	.000	.923	.923	.000	.827	.946	.841	.909



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Willow_710SBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	710 SB Ramps Southbound				Willow St Westbound				710 SB Ramps Northbound				Willow St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 05:00 PM																	
05:00 PM	0	0	211	211	0	317	31	348	0	0	109	109	0	475	70	545	1213
05:15 PM	0	0	254	254	0	299	22	321	0	0	103	103	0	451	57	508	1186
05:30 PM	0	0	196	196	0	340	16	356	0	0	104	104	0	446	73	519	1175
05:45 PM	0	0	295	295	0	317	23	340	0	0	87	87	0	420	55	475	1197
Total Volume	0	0	956	956	0	1273	92	1365	0	0	403	403	0	1792	255	2047	4771
% App. Total	0	0	100		0	93.3	6.7		0	0	100		0	87.5	12.5		
PHF	.000	.000	.810	.810	.000	.936	.742	.959	.000	.000	.924	.924	.000	.943	.873	.939	.983



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com

Appendix E

File Name : Willow_710NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 1

Groups Printed- Unshifted

	710 NB Ramps Southbound			Willow St Westbound			710 NB Ramps Northbound			Willow St Eastbound			Int. Total
Start Time	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	
06:00 AM	0	0	15	0	97	73	0	0	18	0	91	52	346
06:15 AM	0	0	22	0	127	78	0	0	18	0	129	88	462
06:30 AM	0	0	21	0	185	117	0	0	20	0	150	95	588
06:45 AM	0	0	21	0	191	110	0	0	31	0	172	81	606
Total	0	0	79	0	600	378	0	0	87	0	542	316	2002
07:00 AM	0	0	22	0	196	105	0	0	25	0	172	89	609
07:15 AM	0	0	29	0	229	93	0	0	22	0	203	92	668
07:30 AM	0	0	35	0	304	92	0	0	44	0	215	87	777
07:45 AM	0	0	34	0	276	88	0	0	40	0	267	100	805
Total	0	0	120	0	1005	378	0	0	131	0	857	368	2859
08:00 AM	0	0	22	0	240	81	0	0	45	0	229	72	689
08:15 AM	0	0	21	0	210	66	0	0	28	0	225	90	640
08:30 AM	0	0	23	0	186	50	0	0	31	0	221	97	608
08:45 AM	0	0	27	0	188	75	0	0	26	0	258	79	653
Total	0	0	93	0	824	272	0	0	130	0	933	338	2590
04:00 PM	0	0	19	0	257	66	0	0	33	0	400	103	878
04:15 PM	0	0	24	0	260	54	0	0	29	0	409	112	888
04:30 PM	0	0	26	0	294	62	0	0	24	0	447	136	989
04:45 PM	0	0	21	0	297	63	0	0	26	0	460	81	948
Total	0	0	90	0	1108	245	0	0	112	0	1716	432	3703
05:00 PM	0	0	16	0	330	93	0	0	23	0	492	89	1043
05:15 PM	0	0	19	0	304	71	0	0	21	0	454	99	968
05:30 PM	0	0	38	0	315	69	0	0	38	0	454	94	1008
05:45 PM	0	0	32	0	307	73	0	0	19	0	416	94	941
Total	0	0	105	0	1256	306	0	0	101	0	1816	376	3960
Grand Total	0	0	487	0	4793	1579	0	0	561	0	5864	1830	15114
Apprch %	0	0	100	0	75.2	24.8	0	0	100	0	76.2	23.8	
Total %	0	0	3.2	0	31.7	10.4	0	0	3.7	0	38.8	12.1	

CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Willow_710NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 2

	710 NB Ramps Southbound				Willow St Westbound				710 NB Ramps Northbound				Willow St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 06:00 AM to 11:45 AM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 07:15 AM																	
07:15 AM	0	0	29	29	0	229	93	322	0	0	22	22	0	203	92	295	668
07:30 AM	0	0	35	35	0	304	92	396	0	0	44	44	0	215	87	302	777
07:45 AM	0	0	34	34	0	276	88	364	0	0	40	40	0	267	100	367	805
08:00 AM	0	0	22	22	0	240	81	321	0	0	45	45	0	229	72	301	689
Total Volume	0	0	120	120	0	1049	354	1403	0	0	151	151	0	914	351	1265	2939
% App. Total	0	0	100		0	74.8	25.2		0	0	100		0	72.3	27.7		
PHF	.000	.000	.857	.857	.000	.863	.952	.886	.000	.000	.839	.839	.000	.856	.878	.862	.913



CITY TRAFFIC COUNTERS

626.991.7522

www.ctcounters.com


File Name : Willow_710NBRamps

Site Code : 00000000

Start Date : 8/20/2014

Page No : 3

	710 NB Ramps Southbound				Willow St Westbound				710 NB Ramps Northbound				Willow St Eastbound				
Start Time	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Left	Thru	Right	App. Total	Int. Total
Peak Hour Analysis From 12:00 PM to 05:45 PM - Peak 1 of 1																	
Peak Hour for Entire Intersection Begins at 04:45 PM																	
04:45 PM	0	0	21	21	0	297	63	360	0	0	26	26	0	460	81	541	948
05:00 PM	0	0	16	16	0	330	93	423	0	0	23	23	0	492	89	581	1043
05:15 PM	0	0	19	19	0	304	71	375	0	0	21	21	0	454	99	553	968
05:30 PM	0	0	38	38	0	315	69	384	0	0	38	38	0	454	94	548	1008
Total Volume	0	0	94	94	0	1246	296	1542	0	0	108	108	0	1860	363	2223	3967
% App. Total	0	0	100		0	80.8	19.2		0	0	100		0	83.7	16.3		
PHF	.000	.000	.618	.618	.000	.944	.796	.911	.000	.000	.711	.711	.000	.945	.917	.957	.951



APPENDIX B: LOS CALCULATION SHEETS

EXISTING CONDITIONS (BASELINE)

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 3 North/South Street: WILMINGTON AVENUE East/West Street: 223RD STREET Scenario: Existing Conditions						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	319	1,600	0.114	N-S(1): 0.160
	TH	2.00	647	3,200	0.202 *	N-S(2): 0.209 *
	LT	1.00	57	1,600	0.036	E-W(1): 0.295
Westbound	RT	1.00	53	1,600	0.000	E-W(2): 0.334 *
	TH	2.00	794	3,200	0.248 *	
	LT	1.00	200	1,600	0.125	V/C: 0.543
Northbound	RT	0.50	80	800	0.000	Lost Time: 0.100
	TH	2.50	494	4,000	0.124	
	LT	1.00	11	1,600	0.007 *	
Eastbound	RT	1.00	16	1,600	0.003	ICU: 0.643
	TH	2.00	545	3,200	0.170	
	LT	1.00	137	1,600	0.086 *	LOS: B
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	199	1,600	0.000	N-S(1): 0.138
	TH	2.00	724	3,200	0.226 *	N-S(2): 0.231 *
	LT	1.00	55	1,600	0.034	E-W(1): 0.359 *
Westbound	RT	1.00	143	1,600	0.055	E-W(2): 0.258
	TH	2.00	345	3,200	0.108	
	LT	1.00	177	1,600	0.111 *	V/C: 0.590
Northbound	RT	0.50	124	800	0.000	Lost Time: 0.100
	TH	2.50	416	4,000	0.104	
	LT	1.00	8	1,600	0.005 *	
Eastbound	RT	1.00	10	1,600	0.001	ICU: 0.690
	TH	2.00	792	3,200	0.248 *	
	LT	1.00	240	1,600	0.150	LOS: B

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 5 North/South Street: 223rd Street Ramp (on Alameda Street) East/West Street: Alameda Street Scenario: Existing Conditions						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.250 *
	TH	3.00	1,122	4,800	0.234	N-S(2): 0.234
	LT	1.00	159	1,600	0.099 *	E-W(1): 0.110 *
Westbound	RT	1.00	119	1,600	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	
	LT	1.00	176	1,600	0.110 *	V/C: 0.360
Northbound	RT	0.00	242	1,600	0.151 *	Lost Time: 0.100
	TH	3.00	471	3,200	0.147	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.460
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.401 *
	TH	3.00	980	4,800	0.204	N-S(2): 0.204
	LT	1.00	164	1,600	0.103 *	E-W(1): 0.069 *
Westbound	RT	1.00	122	1,600	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	
	LT	1.00	111	1,600	0.069 *	V/C: 0.470
Northbound	RT	0.00	461	0	0.000	Lost Time: 0.100
	TH	3.00	968	4,800	0.298 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.570
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 6 North/South Street: 223rd Street East/West Street: Alameda Street Ramp Scenario: Existing Conditions						
Thru Lane: 1600 vph Left-Turn Lane: 1600 vph Dual LT Penalty: 10 %				N-S Split Phase : N E-W Split Phase : N Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.088 *
	TH	0.00	0	0	0.000	N-S(2): 0.081
	LT	0.00	0	0	0.000 *	E-W(1): 0.161 *
Westbound	RT	0.00	0	0	0.000	E-W(2): 0.141
	TH	3.00	747	5,280	0.141	V/C: 0.249 Lost Time: 0.100
	LT	2.00	223	3,168	0.070 *	
Northbound	RT	1.00	266	1,760	0.088 *	
	TH	0.00	0	0	0.000	
	LT	1.00	143	1,760	0.081	
Eastbound	RT	0.00	80	0	0.000	ICU: 0.349
	TH	3.00	398	5,280	0.091 *	LOS: A
	LT	0.00	0	0	0.000	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.255 *
	TH	0.00	0	0	0.000	N-S(2): 0.055
	LT	0.00	0	0	0.000 *	E-W(1): 0.279 *
Westbound	RT	0.00	0	0	0.000	E-W(2): 0.054
	TH	3.00	283	5,280	0.054	V/C: 0.534 Lost Time: 0.100
	LT	2.00	92	3,168	0.029 *	
Northbound	RT	1.00	494	1,760	0.255 *	
	TH	0.00	0	0	0.000	
	LT	1.00	97	1,760	0.055	
Eastbound	RT	0.00	138	0	0.000	ICU: 0.634
	TH	3.00	1,183	5,280	0.250 *	LOS: B
	LT	0.00	0	0	0.000	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 7 North/South Street: ALAMEDA STREET East/West Street: SEPULVEDA BOULEVARD-ALAMEDA RAMP Scenario: Existing Conditions						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.243 *
	TH	3.00	766	4,800	0.160	N-S(2): 0.160
	LT	1.00	229	1,600	0.143 *	E-W(1): 0.031 *
Westbound	RT	2.00	198	3,200	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	
	LT	1.00	49	1,600	0.031 *	V/C: 0.274
Northbound	RT	0.00	50	0	0.000	Lost Time: 0.100
	TH	3.00	428	4,800	0.100 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.374
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.379 *
	TH	3.00	856	4,800	0.178	N-S(2): 0.178
	LT	1.00	250	1,600	0.156 *	E-W(1): 0.058 *
Westbound	RT	2.00	407	3,200	0.049	E-W(2): 0.049
	TH	0.00	0	0	0.000	
	LT	1.00	93	1,600	0.058 *	V/C: 0.437
Northbound	RT	0.00	83	0	0.000	Lost Time: 0.100
	TH	3.00	988	4,800	0.223 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.537
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 8 North/South Street: SEPULVEDA BOULEVARD-ALAMEDA RAMP East/West Street: SEPULVEDA BOULEVARD Scenario: Existing Conditions						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	144	1,600	0.016	N-S(1): 0.055 *
	TH	0.13	9	215	0.042	N-S(2): 0.000
	LT	1.87	125	2,687	0.047 *	E-W(1): 0.227
Westbound	RT	1.00	98	1,600	0.019	E-W(2): 0.260 *
	TH	2.00	594	3,200	0.186 *	
	LT	1.00	8	1,600	0.005	V/C: 0.315
Northbound	RT	0.00	4	0	0.000	Lost Time: 0.100
	TH	2.00	19	3,200	0.008 *	
	LT	0.00	2	1,600	0.001	
Eastbound	RT	1.00	6	1,600	0.003	ICU: 0.415
	TH	1.00	355	1,600	0.222	
	LT	1.00	118	1,600	0.074 *	LOS: A
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	172	1,600	0.000	N-S(1): 0.057 *
	TH	0.17	12	274	0.044	N-S(2): 0.000
	LT	1.83	128	2,633	0.049 *	E-W(1): 0.585 *
Westbound	RT	1.00	238	1,600	0.105	E-W(2): 0.310
	TH	2.00	534	3,200	0.167	
	LT	1.00	2	1,600	0.001 *	V/C: 0.642
Northbound	RT	0.00	9	0	0.000	Lost Time: 0.100
	TH	2.00	13	3,200	0.008 *	
	LT	0.00	4	1,600	0.003	
Eastbound	RT	1.00	1	1,600	0.000	ICU: 0.742
	TH	1.00	935	1,600	0.584 *	
	LT	1.00	229	1,600	0.143	LOS: C

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 10 North/South Street: TERMINAL ISLAND FREEWAY (SR-103) East/West Street: WILLOW STREET Scenario: Existing Conditions						
Thru Lane: 1600 vph Left-Turn Lane: 1600 vph Dual LT Penalty: 10 %				N-S Split Phase : Y E-W Split Phase : N Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.034 *
	TH	1.00	0	1,600	0.000	N-S(2): 0.000
	LT	0.00	0	0	0.000 *	E-W(1): 0.181
Westbound	RT	0.00	16	0	0.000	E-W(2): 0.256 *
	TH	2.00	794	3,200	0.253 *	V/C: 0.290 Lost Time: 0.100
	LT	2.00	236	2,880	0.082	
Northbound	RT	2.00	97	3,200	0.000	
	TH	0.00	0	0	0.000	
	LT	2.00	99	2,880	0.034 *	
Eastbound	RT	1.00	183	1,600	0.083	LOS: A
	TH	2.00	316	3,200	0.099	
	LT	1.00	4	1,600	0.003 *	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.108 *
	TH	1.00	0	1,600	0.000	N-S(2): 0.000
	LT	0.00	0	0	0.000 *	E-W(1): 0.371 *
Westbound	RT	0.00	1	0	0.000	E-W(2): 0.133
	TH	2.00	425	3,200	0.133	V/C: 0.479 Lost Time: 0.100
	LT	2.00	167	2,880	0.058 *	
Northbound	RT	2.00	248	3,200	0.051	
	TH	0.00	0	0	0.000	
	LT	2.00	311	2,880	0.108 *	
Eastbound	RT	1.00	256	1,600	0.063	LOS: A
	TH	2.00	1,000	3,200	0.313 *	
	LT	1.00	0	1,600	0.000	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 11 North/South Street: SANTA FE AVE East/West Street: SEPULVEDA BOULEVARD Scenario: Existing Conditions						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	132	0	0.000	N-S(1): 0.205 *
	TH	2.00	258	3,200	0.122 *	N-S(2): 0.000
	LT	2.00	152	2,880	0.053	E-W(1): 0.198
Westbound	RT	0.00	108	0	0.000	E-W(2): 0.319 *
	TH	2.00	767	3,200	0.273 *	
	LT	2.00	159	2,880	0.055	V/C: 0.524
Northbound	RT	0.00	80	0	0.000	Lost Time: 0.100
	TH	2.00	184	3,200	0.083 *	
	LT	1.00	76	1,600	0.048	
Eastbound	RT	0.00	32	0	0.000	ICU: 0.624
	TH	2.00	426	3,200	0.143	
	LT	1.00	73	1,600	0.046 *	LOS: B
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	62	0	0.000	N-S(1): 0.313 *
	TH	2.00	311	3,200	0.117 *	N-S(2): 0.000
	LT	2.00	331	2,880	0.115	E-W(1): 0.368 *
Westbound	RT	0.00	149	0	0.000	E-W(2): 0.286
	TH	2.00	483	3,200	0.198	
	LT	2.00	137	2,880	0.048 *	V/C: 0.681
Northbound	RT	0.00	200	0	0.000	Lost Time: 0.100
	TH	2.00	428	3,200	0.196 *	
	LT	1.00	82	1,600	0.051	
Eastbound	RT	0.00	43	0	0.000	ICU: 0.781
	TH	2.00	982	3,200	0.320 *	
	LT	1.00	140	1,600	0.088	LOS: C

* = Critical Movement

I/S #: 31

PROJECT TITLE: ICTF Modification and Expansion Project EIR
 North-South Street: 223rd Street (on 223rd) East-West Street:
 Scenario: CEQA Baseline
 Count Date:

Alameda Street Ramp

Analyst: Iteris, Inc.

Date: 7/22/2014

		AM PEAK HOUR			MD PEAK HOUR			PM PEAK HOUR		
No. of Phases		3			3			3		
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?		2			2			2		
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB -- 3	SB -- 0		NB -- 3	SB -- 0		NB -- 0	SB -- 0	
ATSAC-1 or ATSAC+ATCS-2?		EB -- 0	WB -- 0		EB -- 0	WB -- 0		EB -- 3	WB -- 0	
Override Capacity		1500			1500			1500		
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	143	1	143	0	1	60	97	1	97
	Left-Through		0			0			0	
	Through	0	0	0	0	0	0	0	0	0
	Through-Right		0			0			0	
	Right	266	1	143	0	1	403	494	1	443
	Left-Through-Right		0			0			0	
SOUTHBOUND	Left	0	0	0	0	0	0	0	0	0
	Left-Through		0			0			0	
	Through	0	0	0	0	0	0	0	0	0
	Through-Right		0			0			0	
	Right	0	0	0	0	0	0	0	0	0
	Left-Through-Right		0			0			0	
EASTBOUND	Left	0	0	0	0	0	0	0	0	0
	Left-Through		0			0			0	
	Through	398	2	159	0	2	380	1,183	2	440
	Through-Right		1			1			1	
	Right	80	0	80	0	0	45	138	0	138
	Left-Through-Right		0			0			0	
WESTBOUND	Left	223	2	123	0	2	77	92	2	51
	Left-Through		0			0			0	
	Through	747	3	249	0	3	82	283	3	94
	Through-Right		0			0			0	
	Right	0	0	0	0	0	0	0	0	0
	Left-Through-Right		0			0			0	
CRITICAL VOLUMES		North-South: 143 East-West: 408 SUM: 551			North-South: 403 East-West: 462 SUM: 865			North-South: 443 East-West: 534 SUM: 977		
VOLUME/CAPACITY (V/C) RATIO:		0.387			0.577			0.686		
V/C LESS ATSAC/ATCS ADJUSTMENT:		0.287			0.477			0.586		
LEVEL OF SERVICE (LOS):		A			A			A		

EX AM EX_AM.out Fri Nov 14, 2014 09:29:31 Page 1-1

Tesoro Los Angeles Refinery
Integration & Compliance Project Traffic Study
Existing AM Peak Hour

Scenario Report

Scenario: EX AM
Command: Default Command
Volume: AM
Geometry: Default Geometry
Impact Fee: Default Impact Fee
Trip Generation: Default Trip Generation
Trip Distribution: Default Trip Distribution
Paths: Default Path
Routes: Default Route
Configuration: Default Configuration

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
EX AM Fri Nov 14, 2014 09:29:31 Page 2-1

Tesoro Los Angeles Refinery
Page 1

EX_AM.out
Integration & Compliance Project Traffic Study
Existing AM Peak Hour

Impact Analysis Report
Level Of Service

Intersection	LOS	Base		LOS	Future		Change in
		Del/ Veh	V/ C		Del/ Veh	V/ C	
# 1 Wilmington Ave / I-405 NB Ramp	C	20.0	0.478	C	20.0	0.478	+ 0.000 D/V
# 2 Wilmington Ave / I-405 SB Ramp	B	12.4	0.463	B	12.4	0.463	+ 0.000 D/V
# 4 Alameda Ave / I-405 NB Ramps	B	18.3	0.633	B	18.3	0.633	+ 0.000 D/V
# 9 I-405 SB Ramps / 223rd St	C	20.4	0.422	C	20.4	0.422	+ 0.000 D/V

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
EX AM Fri Nov 14, 2014 09:29:31 Page 3-1

Tesoro Los Angeles Refinery
Integration & Compliance Project Traffic Study
Existing AM Peak Hour

EX_AM.out

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

 Intersection #1 Wilmington Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.478
 Loss Time (sec): 4 (Y+R=4.0 sec) Average Delay (sec/veh): 20.0
 Optimal Cycle: 25 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Permitted					Permitted					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	3	0	0	0	0	0	0	0	2	0	0	0	1

Volume Module:	North Bound					South Bound					East Bound					West Bound				
Base Vol:	0	362	33	21	371	0	0	0	0	693	0	484	0	0	0	0	0	0	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	362	33	21	371	0	0	0	0	693	0	484	0	0	0	0	0	0	0	0
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	362	33	21	371	0	0	0	0	693	0	484	0	0	0	0	0	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
PHF Volume:	0	404	37	23	414	0	0	0	0	773	0	540	0	0	0	0	0	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	404	37	23	414	0	0	0	0	773	0	540	0	0	0	0	0	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	404	37	23	414	0	0	0	0	773	0	540	0	0	0	0	0	0	0	0

Saturation Flow Module:	North Bound					South Bound					East Bound					West Bound				
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.28	0.91	1.00	1.00	1.00	1.00	0.59	1.00	0.85	0.00	0.00	0.00	2.00	0.00	1.00	0.00	0.85
Lanes:	0.00	2.00	1.00	1.00	3.00	0.00	0.00	0.00	0.00	2.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00
Final Sat.:	0	3610	1615	536	5187	0	0	0	0	2226	0	1615	0	0	0	0	0	0	0	1615

Capacity Analysis Module:	North Bound					South Bound					East Bound					West Bound				
Vol/Sat:	0.00	0.11	0.02	0.04	0.08	0.00	0.00	0.00	0.00	0.35	0.00	0.33	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Crit Moves:	****					****					****					****				
Green/Cycle:	0.00	0.34	0.34	0.14	0.14	0.00	0.00	0.00	0.00	0.62	0.00	0.62	0.00	0.00	0.62	0.00	0.00	0.00	0.00	0.62
Volume/Cap:	0.00	0.33	0.07	0.31	0.56	0.00	0.00	0.00	0.00	0.56	0.00	0.56	0.00	0.00	0.54	0.00	0.00	0.00	0.00	0.54
Delay/Veh:	0.0	24.7	22.3	40.8	41.0	0.0	0.0	0.0	0.0	11.6	0.0	11.6	0.0	0.0	11.5	0.0	0.0	0.0	0.0	11.5
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	24.7	22.3	40.8	41.0	0.0	0.0	0.0	0.0	11.6	0.0	11.6	0.0	0.0	11.5	0.0	0.0	0.0	0.0	11.5
LOS by Move:	A	C	C	D	D	A	A	A	A	B	A	B	A	A	B	B	A	A	A	B
HCM2kAvgQ:	0	5	1	1	5	0	0	0	0	8	0	10	0	0	10	0	0	0	0	10

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX AM Fri Nov 14, 2014 09:29:32 Page 4-1

Tesoro Los Angeles Refinery
 Integration & Compliance Project Traffic Study
 Existing AM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

EX_AM.out

Intersection #2 Wilmington Ave / I-405 SB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.463
 Loss Time (sec): 4 (Y+R=4.0 sec) Average Delay (sec/veh): 12.4
 Optimal Cycle: 21 Level Of Service: B

Approach:	North Bound			South Bound			East Bound			West Bound			
Movement:	L	T	R	L	T	R	L	T	R	L	T	R	
Control:	Permitted			Prot+Permit			Permitted			Permitted			
Rights:	Include			Include			Include			Include			
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	
Lanes:	0	0	2	0	1	1	0	3	0	0	0	1	0

Volume Module:	North Bound			South Bound			East Bound			West Bound		
Base Vol:	0	304	359	141	906	0	123	0	164	0	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	304	359	141	906	0	123	0	164	0	0	0
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	304	359	141	906	0	123	0	164	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	0	321	379	149	958	0	130	0	173	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	321	379	149	958	0	130	0	173	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	321	379	149	958	0	130	0	173	0	0	0

Saturation Flow Module:	North Bound			South Bound			East Bound			West Bound		
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.95	0.91	1.00	0.72	0.95	0.72	1.00	1.00	1.00
Lanes:	0.00	2.00	1.00	1.00	3.00	0.00	1.00	0.00	1.00	0.00	0.00	0.00
Final Sat.:	0	3610	1615	1805	5187	0	1366	0	1366	0	0	0

Capacity Analysis Module:	North Bound			South Bound			East Bound			West Bound		
Vol/Sat:	0.00	0.09	0.23	0.08	0.18	0.00	0.10	0.00	0.13	0.00	0.00	0.00
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.51	0.51	0.69	0.69	0.00	0.27	0.00	0.27	0.00	0.00	0.00
Volume/Cap:	0.00	0.18	0.46	0.19	0.27	0.00	0.35	0.00	0.46	0.00	0.00	0.00
Delay/Veh:	0.0	13.4	16.3	5.7	6.1	0.0	29.4	0.0	30.7	0.0	0.0	0.0
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	13.4	16.3	5.7	6.1	0.0	29.4	0.0	30.7	0.0	0.0	0.0
LOS by Move:	A	B	B	A	A	A	C	A	C	A	A	A
HCM2kAvgQ:	0	3	8	2	4	0	4	0	5	0	0	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX AM Fri Nov 14, 2014 09:29:32 Page 5-1

Tesoro Los Angeles Refinery
 Integration & Compliance Project Traffic Study
 Existing AM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #4 Alameda Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.633
 Page 4

EX_AM.out

Loss Time (sec): 4 (Y+R=4.0 sec) Average Delay (sec/veh): 18.3
 Optimal Cycle: 30 Level Of Service: B

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Protected					Protected					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	1	1	0	0	0	0	0	0	1	0	0	0	1

Volume Module:

Base Vol:	0	557	47	0	840	50	0	0	0	462	0	312
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	557	47	0	840	50	0	0	0	462	0	312
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	557	47	0	840	50	0	0	0	462	0	312
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
PHF Volume:	0	599	51	0	903	54	0	0	0	497	0	335
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	599	51	0	903	54	0	0	0	497	0	335
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	599	51	0	903	54	0	0	0	497	0	335

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	1.00	0.94	0.94	1.00	1.00	1.00	0.77	1.00	0.85
Lanes:	0.00	2.00	1.00	1.00	1.89	0.11	0.00	0.00	0.00	1.00	0.00	1.00
Final Sat.:	0	3610	1615	1900	3380	201	0	0	0	1461	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.17	0.03	0.00	0.27	0.27	0.00	0.00	0.00	0.34	0.00	0.21
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.42	0.42	0.00	0.42	0.42	0.00	0.00	0.00	0.54	0.00	1.08
Volume/Cap:	0.00	0.39	0.07	0.00	0.63	0.63	0.00	0.00	0.00	0.63	0.00	0.19
Delay/Veh:	0.0	20.2	17.3	0.0	23.6	23.6	0.0	0.0	0.0	17.9	0.0	0.4
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	20.2	17.3	0.0	23.6	23.6	0.0	0.0	0.0	17.9	0.0	0.4
LOS by Move:	A	C	B	A	C	C	A	A	A	B	A	A
HCM2kAvgQ:	0	7	1	0	13	13	0	0	0	11	0	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX AM Fri Nov 14, 2014 09:29:32 Page 6-1

Tesoro Los Angeles Refinery
 Integration & Compliance Project Traffic Study
 Existing AM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #9 I-405 SB Ramps / 223rd St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.422

Loss Time (sec): 6 (Y+R=4.0 sec) Average Delay (sec/veh): 20.4

Optimal Cycle: 24 Level Of Service: C

EX_AM.out

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Permitted					Protected					Protected					Protected				
Rights:	Include					Include					Include					Include				
Min. Green:	0		0		0	0		0		0	0		0		0	0		0		0
Lanes:	0	0	1	0	0	1	0	0	1	0	2	0	2	1	0	1	0	2	1	0
Volume Module:																				
Base Vol:	1		1		5	55		0		123	353		302		4	3		837		32
Growth Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
Initial Bse:	1		1		5	55		0		123	353		302		4	3		837		32
Added Vol:	0		0		0	0		0		0	0		0		0	0		0		0
PasserByVol:	0		0		0	0		0		0	0		0		0	0		0		0
Initial Fut:	1		1		5	55		0		123	353		302		4	3		837		32
User Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
PHF Adj:	0.88		0.88		0.88	0.88		0.88		0.88	0.88		0.88		0.88	0.88		0.88		0.88
PHF Volume:	1		1		6	62		0		140	401		343		5	3		950		36
Reduct Vol:	0		0		0	0		0		0	0		0		0	0		0		0
Reduced Vol:	1		1		6	62		0		140	401		343		5	3		950		36
PCE Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
MLF Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
FinalVolume:	1		1		6	62		0		140	401		343		5	3		950		36
Saturation Flow Module:																				
Sat/Lane:	1900		1900		1900	1900		1900		1900	1900		1900		1900	1900		1900		1900
Adjustment:	0.90		0.90		0.90	0.95		1.00		0.85	0.92		0.91		0.91	0.95		0.90		0.90
Lanes:	0.14		0.14		0.72	1.00		0.00		1.00	2.00		2.96		0.04	1.00		2.89		0.11
Final Sat.:	245		245		1227	1805		0		1615	3502		5109		68	1805		4966		190
Capacity Analysis Module:																				
Vol/Sat:	0.00		0.00		0.00	0.03		0.00		0.09	0.11		0.07		0.07	0.00		0.19		0.19
Crit Moves:	****					****					****					****				
Green/Cycle:	0.01		0.01		0.01	0.20		0.00		0.22	0.27		0.70		0.70	0.02		0.45		0.45
Volume/Cap:	0.41		0.41		0.41	0.17		0.00		0.40	0.42		0.10		0.10	0.10		0.42		0.42
Delay/Veh:	62.9		62.9		62.9	33.0		0.0		34.4	30.3		4.7		4.7	49.3		18.6		18.6
User DelAdj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
AdjDel/Veh:	62.9		62.9		62.9	33.0		0.0		34.4	30.3		4.7		4.7	49.3		18.6		18.6
LOS by Move:	E		E		E	C		A		C	C		A		A	D		B		B
HCM2kAvgQ:	1		1		1	2		0		4	5		1		1	0		8		8

Note: Queue reported is the number of cars per lane.																				

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA

EX PM EX_PM.out Wed Nov 26, 2014 17:31:44 Page 1-1

Tesoro Los Angeles Refinery
Existing Conditionsq
PM Peak Hour

Scenario Report

Scenario: EX PM
Command: EX-PM
Volume: PM
Geometry: Existing
Impact Fee: Default Impact Fee
Trip Generation: Const-PM
Trip Distribution: Default Trip Distribution
Paths: Default Path
Routes: Default Route
Configuration: EX-PM

Traffic 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
EX PM Wed Nov 26, 2014 17:31:44 Page 2-1

Tesoro Los Angeles Refinery
Page 1

EX_PM.out
Existing Conditions
PM Peak Hour

Impact Analysis Report
Level Of Service

Intersection	LOS	Base		LOS	Future		Change in
		Del/ Veh	V/ C		Del/ Veh	V/ C	
# 1 Wilmington Ave / I-405 NB Ramp	B	18.5	0.395	B	18.5	0.395	+ 0.000 D/V
# 2 Wilmington Ave / I-405 SB Ramp	B	15.7	0.629	B	15.7	0.629	+ 0.000 D/V
# 4 Alameda Ave / I-405 NB Ramps	C	23.2	0.665	C	23.2	0.665	+ 0.000 D/V
# 9 I-405 SB Ramps / 223rd St	B	19.0	0.502	B	19.0	0.502	+ 0.000 D/V

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
EX PM Wed Nov 26, 2014 17:31:44 Page 3-1

Tesoro Los Angeles Refinery
Existing Conditions
PM Peak Hour

EX_PM.out

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

Intersection #1 Wilmington Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.395
Loss Time (sec): 8 (Y+R=4.0 sec) Average Delay (sec/veh): 18.5
Optimal Cycle: 27 Level Of Service: B

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Permitted					Permitted					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	3	0	0	0	0	0	0	0	2	0	0	0	1

Volume Module:

Base Vol:	0	282	151	71	794	0	0	0	0	428	0	302
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	282	151	71	794	0	0	0	0	428	0	302
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	282	151	71	794	0	0	0	0	428	0	302
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	0	297	159	75	837	0	0	0	0	451	0	318
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	297	159	75	837	0	0	0	0	451	0	318
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	297	159	75	837	0	0	0	0	451	0	318

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.52	0.91	1.00	1.00	1.00	1.00	0.59	1.00	0.85
Lanes:	0.00	2.00	1.00	1.00	3.00	0.00	0.00	0.00	0.00	2.00	0.00	1.00
Final Sat.:	0	3610	1615	979	5187	0	0	0	0	2234	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.08	0.10	0.08	0.16	0.00	0.00	0.00	0.00	0.20	0.00	0.20
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.41	0.41	0.41	0.41	0.00	0.00	0.00	0.00	0.51	0.00	0.51
Volume/Cap:	0.00	0.20	0.24	0.19	0.39	0.00	0.00	0.00	0.00	0.39	0.00	0.39
Delay/Veh:	0.0	19.1	19.6	19.2	21.0	0.0	0.0	0.0	0.0	15.2	0.0	15.2
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	19.1	19.6	19.2	21.0	0.0	0.0	0.0	0.0	15.2	0.0	15.2
LOS by Move:	A	B	B	B	C	A	A	A	A	B	A	B
HCM2kAvgQ:	0	3	3	2	7	0	0	0	0	5	0	6

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
EX PM Wed Nov 26, 2014 17:31:44 Page 4-1

Tesoro Los Angeles Refinery
Existing Conditionsq
PM Peak Hour

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

EX_PM.out

Intersection #2 Wilmington Ave / I-405 SB Ramps

```

*****
Cycle (sec):          100          Critical Vol./Cap.(X):          0.629
Loss Time (sec):      12 (Y+R=4.0 sec) Average Delay (sec/veh):      15.7
Optimal Cycle:        51          Level Of Service:          B
*****

```

```

Approach:      North Bound      South Bound      East Bound      West Bound
Movement:      L - T - R      L - T - R      L - T - R      L - T - R
-----|-----|-----|-----|
Control:      Permitted      Protected      Permitted      Permitted
Rights:      Include      Include      Include      Include
Min. Green:      0 0 0 0      0 0 0 0      0 0 0 0      0 0 0 0
Lanes:      0 0 2 0 1      1 0 3 0 0      0 1 0 1 0      0 0 0 0 0
-----|-----|-----|-----|

```

```

Volume Module:
Base Vol:      0 406 479 337 888 0 26 0 82 0 0 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 406 479 337 888 0 26 0 82 0 0 0
Added Vol: 0 0 0 0 0 0 0 0 0 0 0 0
PasserByVol: 0 0 0 0 0 0 0 0 0 0 0 0
Initial Fut: 0 406 479 337 888 0 26 0 82 0 0 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98
PHF Volume: 0 415 490 345 908 0 27 0 84 0 0 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 0 415 490 345 908 0 27 0 84 0 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 0 415 490 345 908 0 27 0 84 0 0 0
-----|-----|-----|-----|

```

```

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 1.00 0.95 0.85 0.95 0.91 1.00 0.74 0.95 0.74 1.00 1.00 1.00
Lanes: 0.00 2.00 1.00 1.00 3.00 0.00 1.00 0.00 1.00 0.00 0.00 0.00
Final Sat.: 0 3610 1615 1805 5187 0 1415 0 1415 0 0 0
-----|-----|-----|-----|

```

```

Capacity Analysis Module:
Vol/Sat: 0.00 0.11 0.30 0.19 0.18 0.00 0.02 0.00 0.06 0.00 0.00 0.00
Crit Moves: *****
Green/Cycle: 0.00 0.48 0.48 0.30 0.79 0.00 0.09 0.00 0.09 0.00 0.00 0.00
Volume/Cap: 0.00 0.24 0.63 0.63 0.22 0.00 0.20 0.00 0.63 0.00 0.00 0.00
Delay/Veh: 0.0 15.2 20.9 32.3 2.8 0.0 42.0 0.0 51.0 0.0 0.0 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 0.0 15.2 20.9 32.3 2.8 0.0 42.0 0.0 51.0 0.0 0.0 0.0
LOS by Move: A B C C A A D A D A A A
HCM2kAvgQ: 0 4 12 10 3 0 1 0 4 0 0 0
*****

```

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
EX PM Wed Nov 26, 2014 17:31:44 Page 5-1

Tesoro Los Angeles Refinery
Existing Conditions
PM Peak Hour

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

Intersection #4 Alameda Ave / I-405 NB Ramps

```

*****
Cycle (sec):          100          Critical Vol./Cap.(X):          0.665
Page 4

```

EX_PM.out

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 23.2
 Optimal Cycle: 55 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Protected					Protected					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	2	0	0	0	0	0	0	0	1	0	0	0	1

Volume Module:

Base Vol:	0	922	190	80	755	0	0	0	0	384	0	105
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	922	190	80	755	0	0	0	0	384	0	105
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	922	190	80	755	0	0	0	0	384	0	105
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
PHF Volume:	0	959	198	83	786	0	0	0	0	400	0	109
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	959	198	83	786	0	0	0	0	400	0	109
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	959	198	83	786	0	0	0	0	400	0	109

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.95	0.95	1.00	1.00	1.00	1.00	0.77	1.00	0.85
Lanes:	0.00	2.00	1.00	1.00	2.00	0.00	0.00	0.00	0.00	1.00	0.00	1.00
Final Sat.:	0	3610	1615	1805	3610	0	0	0	0	1461	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.27	0.12	0.05	0.22	0.00	0.00	0.00	0.00	0.27	0.00	0.07
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.40	0.40	0.07	0.47	0.00	0.00	0.00	0.00	0.41	0.00	0.82
Volume/Cap:	0.00	0.67	0.31	0.67	0.46	0.00	0.00	0.00	0.00	0.67	0.00	0.08
Delay/Veh:	0.0	25.7	20.8	58.2	18.2	0.0	0.0	0.0	0.0	26.7	0.0	1.7
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	25.7	20.8	58.2	18.2	0.0	0.0	0.0	0.0	26.7	0.0	1.7
LOS by Move:	A	C	C	E	B	A	A	A	A	C	A	A
HCM2kAvgQ:	0	13	4	4	9	0	0	0	0	11	0	1

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX PM Wed Nov 26, 2014 17:31:44 Page 6-1

Tesoro Los Angeles Refinery
 Existing Conditions
 PM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #9 I-405 SB Ramps / 223rd St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.502
 Loss Time (sec): 16 (Y+R=4.0 sec) Average Delay (sec/veh): 19.0
 Optimal Cycle: 49 Level Of Service: B

EX_PM.out

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Split Phase					Split Phase					Protected					Protected				
Rights:	Include					Include					Include					Include				
Min. Green:	0		0		0	0		0		0	0		0		0	0		0		0
Lanes:	0	0	1	0	0	1	0	0	1	0	2	0	2	1	0	1	0	2	1	0
Volume Module:																				
Base Vol:	3		6		3	125		2		36	840		798		18	4		347		77
Growth Adj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
Initial Bse:	3		6		3	125		2		36	840		798		18	4		347		77
Added Vol:	0		0		0	0		0		0	0		0		0	0		0		0
PasserByVol:	0		0		0	0		0		0	0		0		0	0		0		0
Initial Fut:	3		6		3	125		2		36	840		798		18	4		347		77
User Adj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
PHF Adj:	0.95	0.95	0.95			0.95	0.95	0.95			0.95	0.95	0.95			0.95	0.95	0.95		
PHF Volume:	3		6		3	132		2		38	886		842		19	4		366		81
Reduct Vol:	0		0		0	0		0		0	0		0		0	0		0		0
Reduced Vol:	3		6		3	132		2		38	886		842		19	4		366		81
PCE Adj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
MLF Adj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
FinalVolume:	3		6		3	132		2		38	886		842		19	4		366		81
Saturation Flow Module:																				
Sat/Lane:	1900		1900		1900	1900		1900		1900	1900		1900		1900	1900		1900		1900
Adjustment:	0.95	0.95	0.95			0.95	0.86	0.86			0.92	0.91	0.91			0.95	0.89	0.89		
Lanes:	0.25	0.50	0.25			1.00	0.05	0.95			2.00	2.93	0.07			1.00	2.46	0.54		
Final Sat.:	453		907		453	1805		86		1544	3502		5057		114	1805		4130		917
Capacity Analysis Module:																				
Vol/Sat:	0.01	0.01	0.01			0.07	0.02	0.02			0.25	0.17	0.17			0.00	0.09	0.09		
Crit Moves:	****					****					****					****				
Green/Cycle:	0.01	0.01	0.01			0.15	0.15	0.15			0.50	0.67	0.67			0.01	0.18	0.18		
Volume/Cap:	0.50	0.50	0.50			0.50	0.17	0.17			0.50	0.25	0.25			0.25	0.50	0.50		
Delay/Veh:	64.0	64.0	64.0			40.9	37.8	37.8			16.7	6.5	6.5			56.7	37.7	37.7		
User DelAdj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
AdjDel/Veh:	64.0	64.0	64.0			40.9	37.8	37.8			16.7	6.5	6.5			56.7	37.7	37.7		
LOS by Move:	E	E	E			D	D	D			B	A	A			E	D	D		
HCM2kAvgQ:	1		1		1	4		1		1	9		4		4	0		5		5

Note: Queue reported is the number of cars per lane.																				

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA

BASELINE PLUS PROJECT CONSTRUCTION

Project:		Tesoro Los Angeles Refinery Traffic Study					
Int #:		3					
North/South Street:		WILMINGTON AVENUE					
East/West Street:		223RD STREET					
Scenario:		Existing Plus Construction					
Thru Lane:		1600 vph			N-S Split Phase :		N
Left-Turn Lane:		1600 vph			E-W Split Phase :		N
Dual LT Penalty:		10 %			Lost Time (% of cycle) :		10
Peak Period:		AM PEAK HOUR					
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	1.00	319	1,600	0.114	N-S(1):	0.203
	TH	2.00	679	3,200	0.212 *	N-S(2):	0.219 *
	LT	1.00	125	1,600	0.078	E-W(1):	0.296
Westbound	RT	1.00	59	1,600	0.000	E-W(2):	0.334 *
	TH	2.00	794	3,200	0.248 *	V/C:	0.553
	LT	1.00	200	1,600	0.125	Lost Time:	0.100
Northbound	RT	0.50	84	800	0.000		
	TH	2.50	501	4,000	0.125		
	LT	1.00	11	1,600	0.007 *		
Eastbound	RT	1.00	17	1,600	0.004	ICU:	0.653
	TH	2.00	548	3,200	0.171		
	LT	1.00	137	1,600	0.086 *	LOS:	B
Peak Period:		PM PEAK HOUR					
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	1.00	199	1,600	0.000	N-S(1):	0.144
	TH	2.00	733	3,200	0.229 *	N-S(2):	0.234 *
	LT	1.00	61	1,600	0.038	E-W(1):	0.362 *
Westbound	RT	1.00	215	1,600	0.096	E-W(2):	0.259
	TH	2.00	349	3,200	0.109	V/C:	0.596
	LT	1.00	182	1,600	0.114 *	Lost Time:	0.100
Northbound	RT	0.50	124	800	0.000		
	TH	2.50	424	4,000	0.106		
	LT	1.00	8	1,600	0.005 *		
Eastbound	RT	1.00	10	1,600	0.001	ICU:	0.696
	TH	2.00	792	3,200	0.248 *		
	LT	1.00	240	1,600	0.150	LOS:	B

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study						
Int #: 5						
North/South Street: 223rd Street Ramp (on Alameda Street)						
East/West Street: Alameda Street						
Scenario: Existing Plus Construction						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.257 *
	TH	3.00	1,145	4,800	0.239	N-S(2): 0.239
	LT	1.00	159	1,600	0.099 *	E-W(1): 0.127 *
Westbound	RT	1.00	119	1,600	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	V/C: 0.384
	LT	1.00	203	1,600	0.127 *	
Northbound	RT	0.00	253	1,600	0.158 *	ICU: 0.484
	TH	3.00	489	3,200	0.153	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	LOS: A
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.433 *
	TH	3.00	1,001	4,800	0.209	N-S(2): 0.209
	LT	1.00	164	1,600	0.103 *	E-W(1): 0.071 *
Westbound	RT	1.00	122	1,600	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	V/C: 0.504
	LT	1.00	114	1,600	0.071 *	
Northbound	RT	0.00	528	1,600	0.330 *	ICU: 0.604
	TH	3.00	1,025	3,200	0.320	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	LOS: B
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study						
Int #: 6						
North/South Street: 223rd Street						
East/West Street: Alameda Street Ramp						
Scenario: Existing Plus Construction						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.086 *
	TH	0.00	0	0	0.000	N-S(2): 0.081
	LT	0.00	0	0	0.000 *	E-W(1): 0.172 *
Westbound	RT	0.00	0	0	0.000	E-W(2): 0.142
	TH	3.00	751	5,280	0.142	V/C: 0.258 Lost Time: 0.100
	LT	2.00	250	3,168	0.079 *	
Northbound	RT	1.00	277	1,760	0.086 *	
	TH	0.00	0	0	0.000	
	LT	1.00	143	1,760	0.081	
Eastbound	RT	0.00	80	0	0.000	ICU: 0.358
	TH	3.00	409	5,280	0.093 *	LOS: A
	LT	0.00	0	0	0.000	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.291 *
	TH	0.00	0	0	0.000	N-S(2): 0.056
	LT	0.00	0	0	0.000 *	E-W(1): 0.305 *
Westbound	RT	0.00	0	0	0.000	E-W(2): 0.054
	TH	3.00	283	5,280	0.054	V/C: 0.596 Lost Time: 0.100
	LT	2.00	95	3,168	0.030 *	
Northbound	RT	1.00	559	1,760	0.291 *	
	TH	0.00	0	0	0.000	
	LT	1.00	99	1,760	0.056	
Eastbound	RT	0.00	138	0	0.000	ICU: 0.696
	TH	3.00	1,314	5,280	0.275 *	LOS: B
	LT	0.00	0	0	0.000	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 7 North/South Street: ALAMEDA STREET East/West Street: SEPULVEDA BOULEVARD-ALAMEDA RAMP Scenario: Existing Plus Construction						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.275 *
	TH	3.00	766	4,800	0.160	N-S(2): 0.160
	LT	1.00	279	1,600	0.174 *	E-W(1): 0.031 *
Westbound	RT	2.00	290	3,200	0.003	E-W(2): 0.003
	TH	0.00	0	0	0.000	
	LT	1.00	49	1,600	0.031 *	V/C: 0.306
Northbound	RT	0.00	52	0	0.000	Lost Time: 0.100
	TH	3.00	434	4,800	0.101 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.406
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.392 *
	TH	3.00	861	4,800	0.179	N-S(2): 0.179
	LT	1.00	270	1,600	0.169 *	E-W(1): 0.060 *
Westbound	RT	2.00	461	3,200	0.060 *	E-W(2): 0.060 *
	TH	0.00	0	0	0.000	
	LT	1.00	96	1,600	0.060 *	V/C: 0.452
Northbound	RT	0.00	83	0	0.000	Lost Time: 0.100
	TH	3.00	989	4,800	0.223 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.552
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000 *	LOS: A

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study						
Int #: 8						
North/South Street: SEPULVEDA BOULEVARD-ALAMEDA RAMP						
East/West Street: SEPULVEDA BOULEVARD						
Scenario: Existing Plus Construction						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	151	1,600	0.000	N-S(1): 0.070 *
	TH	0.10	9	161	0.056	N-S(2): 0.000
	LT	1.90	170	2,735	0.062 *	E-W(1): 0.233
Westbound	RT	1.00	157	1,600	0.042	E-W(2): 0.282 *
	TH	2.00	602	3,200	0.188 *	V/C: 0.352
	LT	1.00	8	1,600	0.005	Lost Time: 0.100
Northbound	RT	0.00	4	0	0.000	ICU: 0.452
	TH	2.00	19	3,200	0.008 *	
	LT	0.00	2	1,600	0.001	
Eastbound	RT	1.00	6	1,600	0.003	LOS: A
	TH	1.00	365	1,600	0.228	
	LT	1.00	151	1,600	0.094 *	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	179	1,600	0.000	N-S(1): 0.061 *
	TH	0.16	12	251	0.048	N-S(2): 0.000
	LT	1.84	141	2,654	0.053 *	E-W(1): 0.590 *
Westbound	RT	1.00	287	1,600	0.132	E-W(2): 0.320
	TH	2.00	546	3,200	0.171	V/C: 0.651
	LT	1.00	2	1,600	0.001 *	Lost Time: 0.100
Northbound	RT	0.00	9	0	0.000	ICU: 0.751
	TH	2.00	13	3,200	0.008 *	
	LT	0.00	4	1,600	0.003	
Eastbound	RT	1.00	1	1,600	0.000	LOS: C
	TH	1.00	943	1,600	0.589 *	
	LT	1.00	238	1,600	0.149	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study						
Int #: 10						
North/South Street: TERMINAL ISLAND FREEWAY (SR-103)						
East/West Street: WILLOW STREET						
Scenario: Existing Plus Construction						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.035 *
	TH	1.00	0	1,600	0.000	N-S(2): 0.000
	LT	0.00	0	0	0.000 *	E-W(1): 0.184
Westbound	RT	0.00	16	0	0.000	E-W(2): 0.286 *
	TH	2.00	890	3,200	0.283 *	V/C: 0.321
	LT	2.00	236	2,880	0.082	Lost Time: 0.100
Northbound	RT	2.00	99	3,200	0.000	ICU: 0.421
	TH	0.00	0	0	0.000	
	LT	2.00	101	2,880	0.035 *	
Eastbound	RT	1.00	184	1,600	0.083	LOS: A
	TH	2.00	327	3,200	0.102	
	LT	1.00	4	1,600	0.003 *	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.108 *
	TH	1.00	0	1,600	0.000	N-S(2): 0.000
	LT	0.00	0	0	0.000 *	E-W(1): 0.387 *
Westbound	RT	0.00	1	0	0.000	E-W(2): 0.138
	TH	2.00	440	3,200	0.138	V/C: 0.495
	LT	2.00	167	2,880	0.058 *	Lost Time: 0.100
Northbound	RT	2.00	248	3,200	0.051	ICU: 0.595
	TH	0.00	0	0	0.000	
	LT	2.00	312	2,880	0.108 *	
Eastbound	RT	1.00	260	1,600	0.065	LOS: A
	TH	2.00	1,054	3,200	0.329 *	
	LT	1.00	0	1,600	0.000	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study						
Int #: 11						
North/South Street: SANTA FE AVE						
East/West Street: SEPULVEDA BOULEVARD						
Scenario: Existing Plus Construction						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	132	0	0.000	N-S(1): 0.205 *
	TH	2.00	258	3,200	0.122 *	N-S(2): 0.000
	LT	2.00	152	2,880	0.053	E-W(1): 0.202
Westbound	RT	0.00	108	0	0.000	E-W(2): 0.349 *
	TH	2.00	863	3,200	0.303 *	V/C: 0.554
	LT	2.00	159	2,880	0.055	Lost Time: 0.100
Northbound	RT	0.00	80	0	0.000	ICU: 0.654
	TH	2.00	184	3,200	0.083 *	
	LT	1.00	76	1,600	0.048	
Eastbound	RT	0.00	32	0	0.000	LOS: B
	TH	2.00	437	3,200	0.147	
	LT	1.00	73	1,600	0.046 *	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	62	0	0.000	N-S(1): 0.313 *
	TH	2.00	311	3,200	0.117 *	N-S(2): 0.000
	LT	2.00	331	2,880	0.115	E-W(1): 0.385 *
Westbound	RT	0.00	149	0	0.000	E-W(2): 0.290
	TH	2.00	498	3,200	0.202	V/C: 0.698
	LT	2.00	137	2,880	0.048 *	Lost Time: 0.100
Northbound	RT	0.00	200	0	0.000	ICU: 0.798
	TH	2.00	428	3,200	0.196 *	
	LT	1.00	82	1,600	0.051	
Eastbound	RT	0.00	43	0	0.000	LOS: C
	TH	2.00	1,036	3,200	0.337 *	
	LT	1.00	140	1,600	0.088	

* = Critical Movement

I/S #: 31

PROJECT TITLE: ICTF Modification and Expansion Project EIR
North-South Street: 223rd Street (on 223rd) East-West Street:
Scenario: CEQA Baseline
Count Date:

Alameda Street Ramp

Analyst: Iteris, Inc.

Date: 7/22/2014

			AM PEAK HOUR			MD PEAK HOUR			PM PEAK HOUR		
No. of Phases			3			3			3		
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?			2			2			2		
Right Turns: FREE-1, NRTOR-2 or OLA-3?			NB -- 3	SB -- 0		NB -- 3	SB -- 0		NB -- 0	SB -- 0	
ATSAC-1 or ATSAC+ATCS-2?			EB -- 0	WB -- 0		EB -- 0	WB -- 0		EB -- 3	WB -- 0	
Override Capacity			1500			1500			1500		
MOVEMENT			Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left		143	1	143	0	1	60	97	1	97
	Left-Through			0			0			0	
	Through		0	0	0	0	0	0	0	0	0
	Through-Right			0			0			0	
	Right		266	1	143	0	1	403	494	1	443
	Left-Through-Right			0			0			0	
SOUTHBOUND	Left		0	0	0	0	0	0	0	0	0
	Left-Through			0			0			0	
	Through		0	0	0	0	0	0	0	0	0
	Through-Right			0			0			0	
	Right		0	0	0	0	0	0	0	0	0
	Left-Through-Right			0			0			0	
EASTBOUND	Left		0	0	0	0	0	0	0	0	0
	Left-Through			0			0			0	
	Through		398	2	159	0	2	380	1,183	2	440
	Through-Right			1			1			1	
	Right		80	0	80	0	0	45	138	0	138
	Left-Through-Right			0			0			0	
WESTBOUND	Left		223	2	123	0	2	77	92	2	51
	Left-Through			0			0			0	
	Through		747	3	249	0	3	82	283	3	94
	Through-Right			0			0			0	
	Right		0	0	0	0	0	0	0	0	0
	Left-Through-Right			0			0			0	
CRITICAL VOLUMES			North-South: 143			North-South: 403			North-South: 443		
			East-West: 408			East-West: 462			East-West: 534		
			SUM: 551			SUM: 865			SUM: 977		
VOLUME/CAPACITY (V/C) RATIO:			0.387			0.577			0.686		
V/C LESS ATSAC/ATCS ADJUSTMENT:			0.287			0.477			0.586		
LEVEL OF SERVICE (LOS):			A			A			A		

EX + Const AM EX+Const-AM.out Page 1-1
Mon Nov 24, 2014 13:57:52

Tesoro Los Angeles Refinery
Existing Plus Construction Conditions
AM Peak Hour

Scenario Report

Scenario: EX + Const AM
Command: EX+Const-AM
Volume: AM
Geometry: Existing
Impact Fee: Default Impact Fee
Trip Generation: Const-AM
Trip Distribution: Default Trip Distribution
Paths: Default Path
Routes: Default Route
Configuration: EX+Const-AM

Trafix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
EX + Const AM Mon Nov 24, 2014 13:57:53 Page 2-1

Tesoro Los Angeles Refinery
Page 1

EX+Const-AM.out
Existing Plus Construction Conditions
AM Peak Hour

Impact Analysis Report
Level Of Service

Intersection		Base			Future			Change in
		LOS	Del/ Veh	V/ C	LOS	Del/ Veh	V/ C	
# 1	Wilmington Ave / I-405 NB Ramp	C	21.4	0.499	C	21.5	0.500	+ 0.080 D/V
# 2	Wilmington Ave / I-405 SB Ramp	D	44.2	0.355	E	57.9	0.439	+13.706 D/V
# 4	Alameda Ave / I-405 NB Ramps	C	21.2	0.690	C	25.6	0.807	+ 4.446 D/V
# 9	I-405 SB Ramps / 223rd St	C	23.4	0.472	C	24.6	0.502	+ 1.194 D/V

EX+Const-AM.out

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

 Intersection #1 Wilmington Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.500
 Loss Time (sec): 8 (Y+R=4.0 sec) Average Delay (sec/veh): 21.5
 Optimal Cycle: 37 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Permitted					Permitted					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	3	0	0	0	0	0	0	0	2	0	0	0	1

Volume Module:	North Bound					South Bound					East Bound					West Bound				
Base Vol:	0	362	33	21	371	0	0	0	0	693	0	484	0	362	33	21	371	0	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	362	33	21	371	0	0	0	0	693	0	484	0	362	33	21	371	0	0	0
Added Vol:	0	1	13	0	4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	363	46	21	375	0	0	0	0	693	0	484	0	363	46	21	375	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
PHF Volume:	0	405	51	23	419	0	0	0	0	773	0	540	0	405	51	23	419	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	405	51	23	419	0	0	0	0	773	0	540	0	405	51	23	419	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Volume:	0	405	51	23	419	0	0	0	0	773	0	540	0	405	51	23	419	0	0	0

Saturation Flow Module:	North Bound					South Bound					East Bound					West Bound				
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.30	0.91	1.00	1.00	1.00	1.00	0.59	1.00	0.85	0.00	0.00	0.00	2.00	0.00	1.00	0.00	0.85
Lanes:	0.00	2.00	1.00	1.00	3.00	0.00	0.00	0.00	0.00	2.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00
Final Sat.:	0	3610	1615	574	5187	0	0	0	0	2226	0	1615	0	0	0	0	0	0	0	1615

Capacity Analysis Module:	North Bound					South Bound					East Bound					West Bound				
Vol/Sat:	0.00	0.11	0.03	0.04	0.08	0.00	0.00	0.00	0.00	0.35	0.00	0.33	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.33
Crit Moves:	****					****					****					****				
Green/Cycle:	0.00	0.33	0.33	0.14	0.14	0.00	0.00	0.00	0.00	0.59	0.00	0.59	0.00	0.00	0.59	0.00	0.00	0.00	0.00	0.59
Volume/Cap:	0.00	0.34	0.10	0.30	0.59	0.00	0.00	0.00	0.00	0.59	0.00	0.56	0.00	0.00	0.56	0.00	0.00	0.00	0.00	0.56
Delay/Veh:	0.0	25.6	23.4	40.9	41.8	0.0	0.0	0.0	0.0	13.4	0.0	13.3	0.0	0.0	13.3	0.0	0.0	0.0	0.0	13.3
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	25.6	23.4	40.9	41.8	0.0	0.0	0.0	0.0	13.4	0.0	13.3	0.0	0.0	13.3	0.0	0.0	0.0	0.0	13.3
LOS by Move:	A	C	C	D	D	A	A	A	A	B	A	B	A	A	B	B	A	A	A	B
HCM2kAvgQ:	0	5	1	1	5	0	0	0	0	8	0	10	0	0	10	0	0	0	0	10

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX + Const AM Mon Nov 24, 2014 13:57:53 Page 4-1

Tesoro Los Angeles Refinery
 Existing Plus Construction Conditions
 AM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

EX+Const-AM.out

Intersection #2 Wilmington Ave / I-405 SB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.439

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 57.9

Optimal Cycle: 44 Level Of Service: E

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Permitted					Protected					Permitted					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	3	0	0	0	1	0	1	0	0	0	0	0	0

Volume Module:												
Base Vol:	0	304	359	141	906	0	123	0	164	0	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	304	359	141	906	0	123	0	164	0	0	0
Added Vol:	0	13	0	0	4	0	0	0	96	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	317	359	141	910	0	123	0	260	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	0	335	379	149	962	0	130	0	275	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	335	379	149	962	0	130	0	275	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	335	379	149	962	0	130	0	275	0	0	0

Saturation Flow Module:												
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.95	0.91	1.00	0.72	0.95	0.72	1.00	1.00	1.00
Lanes:	0.00	2.00	1.00	1.00	3.00	0.00	1.00	0.00	1.00	0.00	0.00	0.00
Final Sat.:	0	3610	1615	1805	5187	0	1368	0	1368	0	0	0

Capacity Analysis Module:												
Vol/Sat:	0.00	0.09	0.23	0.08	0.19	0.00	0.10	0.00	0.20	0.00	0.00	0.00
Crit Moves:	*****											
Green/Cycle:	0.00	0.17	0.17	0.34	0.51	0.00	0.37	0.00	0.37	0.00	0.00	0.00
Volume/Cap:	0.00	0.54	1.38	0.24	0.36	0.00	0.26	0.00	0.54	0.00	0.00	0.00
Delay/Veh:	0.0	38.9	232.8	23.9	14.8	0.0	22.1	0.0	25.8	0.0	0.0	0.0
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	38.9	232.8	23.9	14.8	0.0	22.1	0.0	25.8	0.0	0.0	0.0
LOS by Move:	A	D	F	C	B	A	C	A	C	A	A	A
HCM2kAvgQ:	0	6	27	3	6	0	3	0	7	0	0	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX + Const AM Mon Nov 24, 2014 13:57:53 Page 5-1

Tesoro Los Angeles Refinery
 Existing Plus Construction Conditions
 AM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #4 Alameda Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.807

Page 4

EX+Const-AM.out

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 25.6
 Optimal Cycle: 79 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Protected					Protected					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	1	1	0	0	0	0	0	0	1	0	0	0	1

Volume Module:

Base Vol:	0	557	47	0	840	50	0	0	0	462	0	312
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	557	47	0	840	50	0	0	0	462	0	312
Added Vol:	0	2	4	0	12	0	0	0	0	135	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	559	51	0	852	50	0	0	0	597	0	312
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
PHF Volume:	0	601	55	0	916	54	0	0	0	642	0	335
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	601	55	0	916	54	0	0	0	642	0	335
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	601	55	0	916	54	0	0	0	642	0	335

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	1.00	0.94	0.94	1.00	1.00	1.00	0.77	1.00	0.85
Lanes:	0.00	2.00	1.00	1.00	1.89	0.11	0.00	0.00	0.00	1.00	0.00	1.00
Final Sat.:	0	3610	1615	1900	3383	199	0	0	0	1461	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.17	0.03	0.00	0.27	0.27	0.00	0.00	0.00	0.44	0.00	0.21
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.34	0.34	0.00	0.34	0.34	0.00	0.00	0.00	0.54	0.00	1.09
Volume/Cap:	0.00	0.50	0.10	0.00	0.81	0.81	0.00	0.00	0.00	0.81	0.00	0.19
Delay/Veh:	0.0	26.8	22.9	0.0	34.4	34.4	0.0	0.0	0.0	24.6	0.0	0.6
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	26.8	22.9	0.0	34.4	34.4	0.0	0.0	0.0	24.6	0.0	0.6
LOS by Move:	A	C	C	A	C	C	A	A	A	C	A	A
HCM2kAvgQ:	0	8	1	0	16	16	0	0	0	18	0	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX + Const AM Mon Nov 24, 2014 13:57:53 Page 6-1

Tesoro Los Angeles Refinery
 Existing Plus Construction Conditions
 AM Peak Hour

Level Of Service Computation Report 2000 HCM Operations Method (Future Volume Alternative)

Intersection #9 I-405 SB Ramps / 223rd St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.502
 Loss Time (sec): 16 (Y+R=4.0 sec) Average Delay (sec/veh): 24.6
 Optimal Cycle: 49 Level Of Service: C

EX+Const-AM.out

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Split Phase					Split Phase					Protected					Protected				
Rights:	Include					Include					Include					Include				
Min. Green:	0		0		0	0		0		0	0		0		0	0		0		0
Lanes:	0	0	1	0	0	1	0	0	1	0	2	0	2	1	0	1	0	2	1	0
Volume Module:																				
Base Vol:	1		1		5	55		0		123	353		302		4	3		837		32
Growth Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
Initial Bse:	1		1		5	55		0		123	353		302		4	3		837		32
Added Vol:	0		0		0	0		0		24	21		1		0	0		8		0
PasserByVol:	0		0		0	0		0		0	0		0		0	0		0		0
Initial Fut:	1		1		5	55		0		147	374		303		4	3		845		32
User Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
PHF Adj:	0.88		0.88		0.88	0.88		0.88		0.88	0.88		0.88		0.88	0.88		0.88		0.88
PHF Volume:	1		1		6	62		0		167	425		344		5	3		959		36
Reduct Vol:	0		0		0	0		0		0	0		0		0	0		0		0
Reduced Vol:	1		1		6	62		0		167	425		344		5	3		959		36
PCE Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
MLF Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
FinalVolume:	1		1		6	62		0		167	425		344		5	3		959		36
Saturation Flow Module:																				
Sat/Lane:	1900		1900		1900	1900		1900		1900	1900		1900		1900	1900		1900		1900
Adjustment:	0.90		0.90		0.90	0.95		1.00		0.85	0.92		0.91		0.91	0.95		0.91		0.91
Lanes:	0.14		0.14		0.72	1.00		0.00		1.00	2.00		2.96		0.04	1.00		2.89		0.11
Final Sat.:	244		244		1218	1805		0		1615	3502		5109		67	1805		4973		188
Capacity Analysis Module:																				
Vol/Sat:	0.00		0.00		0.00	0.03		0.00		0.10	0.12		0.07		0.07	0.00		0.19		0.19
Crit Moves:	****					****					****					****				
Green/Cycle:	0.01		0.01		0.01	0.21		0.00		0.21	0.24		0.61		0.61	0.02		0.38		0.38
Volume/Cap:	0.50		0.50		0.50	0.17		0.00		0.50	0.50		0.11		0.11	0.11		0.50		0.50
Delay/Veh:	72.6		72.6		72.6	32.9		0.0		36.4	33.2		8.3		8.3	50.0		23.7		23.7
User DelAdj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
AdjDel/Veh:	72.6		72.6		72.6	32.9		0.0		36.4	33.2		8.3		8.3	50.0		23.7		23.7
LOS by Move:	E		E		E	C		A		D	C		A		A	D		C		C
HCM2kAvgQ:	1		1		1	2		0		5	6		2		2	0		9		9

Note: Queue reported is the number of cars per lane.																				

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA

EX + Const PM EX+Const-PM.out Page 1-1
Mon Nov 24, 2014 13:58:17

Tesoro Los Angeles Refinery
Existing Plus Construction Conditions
PM Peak Hour

Scenario: Scenario Report
EX + Const PM

Command: EX+Const-PM
Volume: PM
Geometry: Existing
Impact Fee: Default Impact Fee
Trip Generation: Const-PM
Trip Distribution: Default Trip Distribution
Paths: Default Path
Routes: Default Route
Configuration: EX+Const-PM

Trafix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
EX + Const PM Mon Nov 24, 2014 13:58:18 Page 2-1

Tesoro Los Angeles Refinery
Page 1

EX+Const-PM.out
Existing Plus Construction Conditions
PM Peak Hour

Impact Analysis Report
Level Of Service

Intersection		Base			Future			Change in
		LOS	Del/ Veh	V/ C	LOS	Del/ Veh	V/ C	
# 1	Wilmington Ave / I-405 NB Ramp	B	18.5	0.395	B	18.6	0.395	+ 0.176 D/V
# 2	Wilmington Ave / I-405 SB Ramp	B	15.7	0.629	B	16.5	0.641	+ 0.786 D/V
# 4	Alameda Ave / I-405 NB Ramps	C	23.2	0.665	C	23.8	0.683	+ 0.617 D/V
# 9	I-405 SB Ramps / 223rd St	C	24.3	0.327	C	23.7	0.395	-0.516 D/V

EX+Const-PM.out

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

 Intersection #1 Wilmington Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.395
 Loss Time (sec): 8 (Y+R=4.0 sec) Average Delay (sec/veh): 18.6
 Optimal Cycle: 27 Level Of Service: B

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Permitted					Permitted					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	3	0	0	0	0	0	0	0	2	0	0	0	1

Volume Module:	North Bound					South Bound					East Bound					West Bound				
Base Vol:	0	282	151	71	794	0	0	0	0	428	0	302	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	282	151	71	794	0	0	0	0	428	0	302	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Added Vol:	0	4	75	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	286	226	71	795	0	0	0	0	428	0	302	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	0	301	238	75	838	0	0	0	0	451	0	318	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Reduced Vol:	0	301	238	75	838	0	0	0	0	451	0	318	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	301	238	75	838	0	0	0	0	451	0	318	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95

Saturation Flow Module:	North Bound					South Bound					East Bound					West Bound				
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.51	0.91	1.00	1.00	1.00	1.00	0.59	1.00	0.85	1.00	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Lanes:	0.00	2.00	1.00	1.00	3.00	0.00	0.00	0.00	0.00	2.00	0.00	1.00	0.00	0.00	1.00	0.00	0.00	0.00	0.00	1.00
Final Sat.:	0	3610	1615	973	5187	0	0	0	0	2234	0	1615	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95

Capacity Analysis Module:	North Bound					South Bound					East Bound					West Bound				
Vol/Sat:	0.00	0.08	0.15	0.08	0.16	0.00	0.00	0.00	0.00	0.20	0.00	0.20	0.00	0.00	0.20	0.00	0.00	0.00	0.00	0.20
Crit Moves:	****				****					****					****					****
Green/Cycle:	0.00	0.41	0.41	0.41	0.41	0.00	0.00	0.00	0.00	0.51	0.00	0.51	0.00	0.00	0.51	0.00	0.00	0.00	0.00	0.51
Volume/Cap:	0.00	0.20	0.36	0.19	0.39	0.00	0.00	0.00	0.00	0.40	0.00	0.40	0.00	0.00	0.39	0.00	0.00	0.00	0.00	0.39
Delay/Veh:	0.0	19.1	20.8	19.2	21.0	0.0	0.0	0.0	0.0	15.2	0.0	15.2	0.0	0.0	15.2	0.0	0.0	0.0	0.0	15.2
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	19.1	20.8	19.2	21.0	0.0	0.0	0.0	0.0	15.2	0.0	15.2	0.0	0.0	15.2	0.0	0.0	0.0	0.0	15.2
LOS by Move:	A	B	C	B	C	A	A	A	A	B	A	B	A	A	B	B	A	A	A	B
HCM2kAvgQ:	0	3	5	2	7	0	0	0	0	5	0	5	0	0	6	0	0	0	0	6

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX + Const PM Mon Nov 24, 2014 13:58:18 Page 4-1

Tesoro Los Angeles Refinery
 Existing Plus Construction Conditions
 PM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

EX+Const-PM.out

Intersection #2 Wilmington Ave / I-405 SB Ramps

```

*****
Cycle (sec):          100          Critical Vol./Cap.(X):          0.641
Loss Time (sec):      12 (Y+R=4.0 sec) Average Delay (sec/veh):      16.5
Optimal Cycle:        52          Level Of Service:          B
*****

```

```

Approach:      North Bound      South Bound      East Bound      West Bound
Movement:      L - T - R      L - T - R      L - T - R      L - T - R
-----|-----|-----|-----|
Control:        Permitted      Protected      Permitted      Permitted
Rights:         Include        Include        Include        Include
Min. Green:     0 0 0 0 0      0 0 0 0 0      0 0 0 0 0      0 0 0 0 0
Lanes:          0 0 2 0 1      1 0 3 0 0      0 1 0 1 0      0 0 0 0 0
-----|-----|-----|-----|

```

```

Volume Module:
Base Vol:       0 406 479 337 888 0 26 0 82 0 0 0
Growth Adj:     1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse:    0 406 479 337 888 0 26 0 82 0 0 0
Added Vol:      0 79 0 0 1 0 0 0 15 0 0 0
PasserByVol:    0 0 0 0 0 0 0 0 0 0 0 0
Initial Fut:    0 485 479 337 889 0 26 0 97 0 0 0
User Adj:       1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj:        0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98
PHF Volume:     0 496 490 345 909 0 27 0 99 0 0 0
Reduct Vol:     0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol:    0 496 490 345 909 0 27 0 99 0 0 0
PCE Adj:        1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj:        1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume:    0 496 490 345 909 0 27 0 99 0 0 0
-----|-----|-----|-----|

```

```

Saturation Flow Module:
Sat/Lane:       1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment:     1.00 0.95 0.85 0.95 0.91 1.00 0.75 0.95 0.75 1.00 1.00 1.00
Lanes:          0.00 2.00 1.00 1.00 3.00 0.00 1.00 0.00 1.00 0.00 0.00 0.00
Final Sat.:     0 3610 1615 1805 5187 0 1423 0 1423 0 0 0
-----|-----|-----|-----|

```

```

Capacity Analysis Module:
Vol/Sat:        0.00 0.14 0.30 0.19 0.18 0.00 0.02 0.00 0.07 0.00 0.00 0.00
Crit Moves:      ****      ****
Green/Cycle:    0.00 0.47 0.47 0.30 0.77 0.00 0.11 0.00 0.11 0.00 0.00 0.00
Volume/Cap:     0.00 0.29 0.64 0.64 0.23 0.00 0.17 0.00 0.64 0.00 0.00 0.00
Delay/Veh:      0.0 16.2 21.7 33.1 3.2 0.0 40.6 0.0 49.9 0.0 0.0 0.0
User DelAdj:    1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh:     0.0 16.2 21.7 33.1 3.2 0.0 40.6 0.0 49.9 0.0 0.0 0.0
LOS by Move:    A B C C A A D A D A A A
HCM2kAvgQ:      0 5 12 10 3 0 1 0 4 0 0 0
*****

```

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX + Const PM Mon Nov 24, 2014 13:58:18 Page 5-1

Tesoro Los Angeles Refinery
 Existing Plus Construction Conditions
 PM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #4 Alameda Ave / I-405 NB Ramps

```

*****
Cycle (sec):          100          Critical Vol./Cap.(X):          0.683
Page 4

```

EX+Const-PM.out

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 23.8
 Optimal Cycle: 57 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Protected					Protected					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	2	0	0	0	0	0	0	0	1	0	0	0	1

Volume Module:

Base Vol:	0	922	190	80	755	0	0	0	0	384	0	105
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	922	190	80	755	0	0	0	0	384	0	105
Added Vol:	0	13	50	0	2	0	0	0	0	17	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	935	240	80	757	0	0	0	0	401	0	105
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
PHF Volume:	0	973	250	83	788	0	0	0	0	417	0	109
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	973	250	83	788	0	0	0	0	417	0	109
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	973	250	83	788	0	0	0	0	417	0	109

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.95	0.95	1.00	1.00	1.00	1.00	0.77	1.00	0.85
Lanes:	0.00	2.00	1.00	1.00	2.00	0.00	0.00	0.00	0.00	1.00	0.00	1.00
Final Sat.:	0	3610	1615	1805	3610	0	0	0	0	1461	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.27	0.15	0.05	0.22	0.00	0.00	0.00	0.00	0.29	0.00	0.07
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.39	0.39	0.07	0.46	0.00	0.00	0.00	0.00	0.42	0.00	0.84
Volume/Cap:	0.00	0.68	0.39	0.68	0.47	0.00	0.00	0.00	0.00	0.68	0.00	0.08
Delay/Veh:	0.0	26.5	22.1	60.4	18.7	0.0	0.0	0.0	0.0	26.9	0.0	1.5
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	26.5	22.1	60.4	18.7	0.0	0.0	0.0	0.0	26.9	0.0	1.5
LOS by Move:	A	C	C	E	B	A	A	A	A	C	A	A
HCM2kAvgQ:	0	14	6	4	9	0	0	0	0	11	0	1

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 EX + Const PM Mon Nov 24, 2014 13:58:18 Page 6-1

Tesoro Los Angeles Refinery
 Existing Plus Construction Conditions
 PM Peak Hour

Level Of Service Computation Report 2000 HCM Operations Method (Future Volume Alternative)

Intersection #9 I-405 SB Ramps / 223rd St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.395
 Loss Time (sec): 16 (Y+R=4.0 sec) Average Delay (sec/veh): 23.7
 Optimal Cycle: 42 Level Of Service: C

EX+Const-PM.out												
Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	1	0	0	0	1	0	2	1	0	0
Volume Module:												
Base Vol:	3	6	3	125	2	36	353	302	4	4	347	77
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	3	6	3	125	2	36	353	302	4	4	347	77
Added Vol:	0	0	0	0	0	2	187	8	0	0	1	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	3	6	3	125	2	38	540	310	4	4	348	77
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	3	6	3	132	2	40	570	327	4	4	367	81
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	3	6	3	132	2	40	570	327	4	4	367	81
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	3	6	3	132	2	40	570	327	4	4	367	81
Saturation Flow Module:												
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	0.95	0.95	0.95	0.95	0.86	0.86	0.92	0.91	0.91	0.95	0.89	0.89
Lanes:	0.25	0.50	0.25	1.00	0.05	0.95	2.00	2.96	0.04	1.00	2.46	0.54
Final Sat.:	453	907	453	1805	82	1549	3502	5111	66	1805	4133	914
Capacity Analysis Module:												
Vol/Sat:	0.01	0.01	0.01	0.07	0.03	0.03	0.16	0.06	0.06	0.00	0.09	0.09
Crit Moves:	****			****			****			****		
Green/Cycle:	0.02	0.02	0.02	0.19	0.19	0.19	0.41	0.61	0.61	0.02	0.23	0.23
Volume/Cap:	0.39	0.39	0.39	0.39	0.14	0.14	0.39	0.10	0.10	0.10	0.39	0.39
Delay/Veh:	56.4	56.4	56.4	36.6	34.3	34.3	20.8	7.9	7.9	49.0	33.2	33.2
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	56.4	56.4	56.4	36.6	34.3	34.3	20.8	7.9	7.9	49.0	33.2	33.2
LOS by Move:	E	E	E	D	C	C	C	A	A	D	C	C
HCM2kAvgQ:	1	1	1	4	1	1	6	2	2	0	5	5

Note: Queue reported is the number of cars per lane.												

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA

YEAR 2021
WITHOUT PROJECT

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 3 North/South Street: WILMINGTON AVENUE East/West Street: 223RD STREET Scenario: 2021 Base							
Thru Lane: 1600 vph				N-S Split Phase : N			
Left-Turn Lane: 1600 vph				E-W Split Phase : N			
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10			
Peak Period: AM PEAK HOUR							
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	1.00	327	1,600	0.117	N-S(1):	0.163
	TH	2.00	663	3,200	0.207 *	N-S(2):	0.214 *
	LT	1.00	58	1,600	0.036	E-W(1):	0.302
Westbound	RT	1.00	54	1,600	0.000	E-W(2):	0.342 *
	TH	2.00	813	3,200	0.254 *	V/C: 0.556	
	LT	1.00	205	1,600	0.128	Lost Time: 0.100	
Northbound	RT	0.50	82	800	0.000		
	TH	2.50	506	4,000	0.127		
	LT	1.00	11	1,600	0.007 *		
Eastbound	RT	1.00	16	1,600	0.003	ICU:	0.656
	TH	2.00	558	3,200	0.174		
	LT	1.00	140	1,600	0.088 *	LOS:	B
Peak Period: PM PEAK HOUR							
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	1.00	204	1,600	0.000	N-S(1):	0.142
	TH	2.00	742	3,200	0.232 *	N-S(2):	0.237 *
	LT	1.00	56	1,600	0.035	E-W(1):	0.366 *
Westbound	RT	1.00	146	1,600	0.056	E-W(2):	0.264
	TH	2.00	353	3,200	0.110	V/C: 0.603	
	LT	1.00	181	1,600	0.113 *	Lost Time: 0.100	
Northbound	RT	0.50	127	800	0.000		
	TH	2.50	426	4,000	0.107		
	LT	1.00	8	1,600	0.005 *		
Eastbound	RT	1.00	10	1,600	0.001	ICU:	0.703
	TH	2.00	811	3,200	0.253 *		
	LT	1.00	246	1,600	0.154	LOS:	C

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 5 North/South Street: 223rd Street Ramp (on Alameda Street) East/West Street: Alameda Street Scenario: 2021 Base						
Thru Lane: 1600 vph Left-Turn Lane: 1600 vph Dual LT Penalty: 10 %				N-S Split Phase : N E-W Split Phase : N Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.257 *
	TH	3.00	1,149	4,800	0.239	N-S(2): 0.239
	LT	1.00	163	1,600	0.102 *	E-W(1): 0.113 *
Westbound	RT	1.00	122	1,600	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	V/C: 0.370 Lost Time: 0.100
	LT	1.00	180	1,600	0.113 *	
Northbound	RT	0.00	248	1,600	0.155 *	
	TH	3.00	482	3,200	0.151	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	LOS: A
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.410 *
	TH	3.00	1,004	4,800	0.209	N-S(2): 0.209
	LT	1.00	168	1,600	0.105 *	E-W(1): 0.071 *
Westbound	RT	1.00	125	1,600	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	V/C: 0.481 Lost Time: 0.100
	LT	1.00	114	1,600	0.071 *	
Northbound	RT	0.00	472	0	0.000	
	TH	3.00	991	4,800	0.305 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	LOS: A
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 6 North/South Street: 223rd Street East/West Street: Alameda Street Ramp Scenario: 2021 Base						
Thru Lane: 1600 vph Left-Turn Lane: 1600 vph Dual LT Penalty: 10 %				N-S Split Phase : N E-W Split Phase : N Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.090 *
	TH	0.00	0	0	0.000	N-S(2): 0.083
	LT	0.00	0	0	0.000 *	E-W(1): 0.165 *
Westbound	RT	0.00	0	0	0.000	E-W(2): 0.145
	TH	3.00	765	5,280	0.145	V/C: 0.255 Lost Time: 0.100
	LT	2.00	228	3,168	0.072 *	
Northbound	RT	1.00	272	1,760	0.090 *	ICU: 0.355
	TH	0.00	0	0	0.000	
	LT	1.00	146	1,760	0.083	
Eastbound	RT	0.00	82	0	0.000	LOS: A
	TH	3.00	408	5,280	0.093 *	
	LT	0.00	0	0	0.000	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.261 *
	TH	0.00	0	0	0.000	N-S(2): 0.056
	LT	0.00	0	0	0.000 *	E-W(1): 0.286 *
Westbound	RT	0.00	0	0	0.000	E-W(2): 0.055
	TH	3.00	290	5,280	0.055	V/C: 0.547 Lost Time: 0.100
	LT	2.00	94	3,168	0.030 *	
Northbound	RT	1.00	506	1,760	0.261 *	ICU: 0.647
	TH	0.00	0	0	0.000	
	LT	1.00	99	1,760	0.056	
Eastbound	RT	0.00	141	0	0.000	LOS: B
	TH	3.00	1,212	5,280	0.256 *	
	LT	0.00	0	0	0.000	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 7 North/South Street: ALAMEDA STREET East/West Street: SEPULVEDA BOULEVARD-ALAMEDA RAMP Scenario: 2021 Base						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.249 *
	TH	3.00	785	4,800	0.164	N-S(2): 0.164
	LT	1.00	235	1,600	0.147 *	E-W(1): 0.031 *
Westbound	RT	2.00	203	3,200	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	
	LT	1.00	50	1,600	0.031 *	V/C: 0.280
Northbound	RT	0.00	51	0	0.000	Lost Time: 0.100
	TH	3.00	438	4,800	0.102 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.380
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.389 *
	TH	3.00	877	4,800	0.183	N-S(2): 0.183
	LT	1.00	256	1,600	0.160 *	E-W(1): 0.059 *
Westbound	RT	2.00	417	3,200	0.050	E-W(2): 0.050
	TH	0.00	0	0	0.000	
	LT	1.00	95	1,600	0.059 *	V/C: 0.448
Northbound	RT	0.00	85	0	0.000	Lost Time: 0.100
	TH	3.00	1,012	4,800	0.229 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.548
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study						
Int #: 8						
North/South Street: SEPULVEDA BOULEVARD-ALAMEDA RAMP						
East/West Street: SEPULVEDA BOULEVARD						
Scenario: 2021 Base						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	147	1,600	0.016	N-S(1): 0.056 *
	TH	0.13	9	210	0.043	N-S(2): 0.000
	LT	1.87	128	2,691	0.048 *	E-W(1): 0.233
Westbound	RT	1.00	100	1,600	0.020	E-W(2): 0.266 *
	TH	2.00	608	3,200	0.190 *	
	LT	1.00	8	1,600	0.005	V/C: 0.322
Northbound	RT	0.00	4	0	0.000	Lost Time: 0.100
	TH	2.00	19	3,200	0.008 *	
	LT	0.00	2	1,600	0.001	
Eastbound	RT	1.00	6	1,600	0.003	ICU: 0.422
	TH	1.00	364	1,600	0.228	
	LT	1.00	121	1,600	0.076 *	LOS: A
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	176	1,600	0.000	N-S(1): 0.058 *
	TH	0.17	12	269	0.045	N-S(2): 0.000
	LT	1.83	131	2,638	0.050 *	E-W(1): 0.600 *
Westbound	RT	1.00	244	1,600	0.108	E-W(2): 0.318
	TH	2.00	547	3,200	0.171	
	LT	1.00	2	1,600	0.001 *	V/C: 0.658
Northbound	RT	0.00	9	0	0.000	Lost Time: 0.100
	TH	2.00	13	3,200	0.008 *	
	LT	0.00	4	1,600	0.003	
Eastbound	RT	1.00	1	1,600	0.000	ICU: 0.758
	TH	1.00	958	1,600	0.599 *	
	LT	1.00	235	1,600	0.147	LOS: C

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 10 North/South Street: TERMINAL ISLAND FREEWAY (SR-103) East/West Street: WILLOW STREET Scenario: 2021 Base							
Thru Lane: 1600 vph				N-S Split Phase : Y			
Left-Turn Lane: 1600 vph				E-W Split Phase : N			
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10			
Peak Period: AM PEAK HOUR							
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	0.00	0	0	0.000	N-S(1):	0.034 *
	TH	1.00	0	1,600	0.000	N-S(2):	0.000
	LT	0.00	0	0	0.000 *	E-W(1):	0.185
Westbound	RT	0.00	16	0	0.000	E-W(2):	0.262 *
	TH	2.00	813	3,200	0.259 *	V/C:	0.296
	LT	2.00	242	2,880	0.084	Lost Time:	0.100
Northbound	RT	2.00	101	3,200	0.000	ICU: 0.396	
	TH	0.00	0	0	0.000		
	LT	2.00	99	2,880	0.034 *		
Eastbound	RT	1.00	187	1,600	0.086	LOS: A	
	TH	2.00	324	3,200	0.101		
	LT	1.00	4	1,600	0.003 *		
Peak Period: PM PEAK HOUR							
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	0.00	0	0	0.000	N-S(1):	0.111 *
	TH	1.00	0	1,600	0.000	N-S(2):	0.000
	LT	0.00	0	0	0.000 *	E-W(1):	0.379 *
Westbound	RT	0.00	1	0	0.000	E-W(2):	0.136
	TH	2.00	435	3,200	0.136	V/C:	0.490
	LT	2.00	171	2,880	0.059 *	Lost Time:	0.100
Northbound	RT	2.00	254	3,200	0.053	ICU: 0.590	
	TH	0.00	0	0	0.000		
	LT	2.00	319	2,880	0.111 *		
Eastbound	RT	1.00	262	1,600	0.064	LOS: A	
	TH	2.00	1,024	3,200	0.320 *		
	LT	1.00	0	1,600	0.000		

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 11 North/South Street: SANTA FE AVE East/West Street: SEPULVEDA BOULEVARD Scenario: 2021 Base						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	135	0	0.000	N-S(1): 0.209 *
	TH	2.00	264	3,200	0.125 *	N-S(2): 0.000
	LT	2.00	156	2,880	0.054	E-W(1): 0.204
Westbound	RT	0.00	111	0	0.000	E-W(2): 0.327 *
	TH	2.00	786	3,200	0.280 *	V/C: 0.536
	LT	2.00	163	2,880	0.057	Lost Time: 0.100
Northbound	RT	0.00	82	0	0.000	ICU: 0.636
	TH	2.00	188	3,200	0.084 *	
	LT	1.00	78	1,600	0.049	
Eastbound	RT	0.00	33	0	0.000	LOS: B
	TH	2.00	436	3,200	0.147	
	LT	1.00	75	1,600	0.047 *	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	64	0	0.000	N-S(1): 0.321 *
	TH	2.00	319	3,200	0.120 *	N-S(2): 0.000
	LT	2.00	339	2,880	0.118	E-W(1): 0.377 *
Westbound	RT	0.00	153	0	0.000	E-W(2): 0.292
	TH	2.00	495	3,200	0.203	V/C: 0.698
	LT	2.00	140	2,880	0.049 *	Lost Time: 0.100
Northbound	RT	0.00	205	0	0.000	ICU: 0.798
	TH	2.00	438	3,200	0.201 *	
	LT	1.00	84	1,600	0.053	
Eastbound	RT	0.00	44	0	0.000	LOS: C
	TH	2.00	1,006	3,200	0.328 *	
	LT	1.00	143	1,600	0.089	

* = Critical Movement

I/S #:
31

PROJECT TITLE: ICTF Modification and Expansion Project EIR
North-South Street: 223rd Street (on 223rd) East-West Street:
Scenario: CEQA Baseline
Count Date:

Alameda Street Ramp

Analyst: Iteris, Inc.

Date: 7/22/2014

			AM PEAK HOUR			MD PEAK HOUR			PM PEAK HOUR		
No. of Phases			3			3			3		
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?			2			2			2		
Right Turns: FREE-1, NRTOR-2 or OLA-3?			NB -- 3	SB -- 0		NB -- 3	SB -- 0		NB -- 0	SB -- 0	
ATSAC-1 or ATSAC+ATCS-2?			EB -- 0	WB -- 0		EB -- 0	WB -- 0		EB -- 3	WB -- 0	
Override Capacity			1500			1500			1500		
MOVEMENT			Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left		146	1	146	0	1	60	99	1	99
	Left-Through			0			0			0	
	Through		0	0	0	0	0	0	0	0	0
	Through-Right			0			0			0	
	Right		272	1	147	0	1	403	506	1	454
	Left-Through-Right			0			0			0	
SOUTHBOUND	Left		0	0	0	0	0	0	0	0	0
	Left-Through			0			0			0	
	Through		0	0	0	0	0	0	0	0	0
	Through-Right			0			0			0	
	Right		0	0	0	0	0	0	0	0	0
	Left-Through-Right			0			0			0	
EASTBOUND	Left		0	0	0	0	0	0	0	0	0
	Left-Through			0			0			0	
	Through		408	2	163	0	2	380	1,212	2	451
	Through-Right			1			1			1	
	Right		82	0	82	0	0	45	141	0	141
	Left-Through-Right			0			0			0	
WESTBOUND	Left		228	2	125	0	2	77	94	2	52
	Left-Through			0			0			0	
	Through		765	3	255	0	3	82	290	3	97
	Through-Right			0			0			0	
	Right		0	0	0	0	0	0	0	0	0
	Left-Through-Right			0			0			0	
CRITICAL VOLUMES			North-South: 147			North-South: 403			North-South: 454		
			East-West: 418			East-West: 462			East-West: 548		
			SUM: 565			SUM: 865			SUM: 1002		
VOLUME/CAPACITY (V/C) RATIO:			0.396			0.577			0.703		
V/C LESS ATSAC/ATCS ADJUSTMENT:			0.296			0.477			0.603		
LEVEL OF SERVICE (LOS):			A			A			B		

Scenario:	2020 NP AM	Scenario Report
Command:	2020-AM	
Volume:	2020 AM	
Geometry:	2017	
Impact Fee:	Default Impact Fee	
Trip Generation:	Const-AM	
Trip Distribution:	Default Trip Distribution	
Paths:	Default Path	
Routes:	Default Route	
Configuration:	2020-AM	

2020NP-AM.out
 Year 2020 No Project
 AM Peak Hour

Impact Analysis Report
 Level Of Service

Intersection		Base			Future			Change in
		LOS	Del/ Veh	V/ C	LOS	Del/ Veh	V/ C	
# 1	Wilmington Ave / I-405 NB Ramp	C	21.7	0.512	C	21.7	0.512	+ 0.000 D/V
# 2	Wilmington Ave / I-405 SB Ramp	C	21.8	0.364	C	21.8	0.364	+ 0.000 D/V
# 4	Alameda Ave / I-405 NB Ramps	C	23.4	0.687	C	23.4	0.687	+ 0.000 D/V
# 9	I-405 SB Ramps / 223rd St	C	23.5	0.484	C	23.5	0.484	+ 0.000 D/V

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 NP AM Tue Dec 2, 2014 11:59:34 Page 3-1

Tesoro Los Angeles Refinery
 Year 2020 No Project
 AM Peak Hour

2020NP-AM.out

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

Intersection #1 Wilmington Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.512
Loss Time (sec): 8 (Y+R=4.0 sec) Average Delay (sec/veh): 21.7
Optimal Cycle: 39 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Permitted					Permitted					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	0	0	3	0	0	0	0	0	0	0	2	0	0	0	1

Volume Module:	North Bound					South Bound					East Bound					West Bound				
Base Vol:	0	371	34	0	402	0	0	0	0	710	0	496	0	371	34	0	402			
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Initial Bse:	0	371	34	0	402	0	0	0	0	710	0	496	0	371	34	0	402			
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
Initial Fut:	0	371	34	0	402	0	0	0	0	710	0	496	0	371	34	0	402			
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
PHF Adj:	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90			
PHF Volume:	0	414	38	0	449	0	0	0	0	792	0	554	0	414	38	0	449			
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
Reduced Vol:	0	414	38	0	449	0	0	0	0	792	0	554	0	414	38	0	449			
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Final Volume:	0	414	38	0	449	0	0	0	0	792	0	554	0	414	38	0	449			

Saturation Flow Module:	North Bound					South Bound					East Bound					West Bound				
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900			
Adjustment:	1.00	0.95	0.85	1.00	0.91	1.00	1.00	1.00	1.00	0.59	1.00	0.85	1.00	0.95	0.85	1.00	0.91			
Lanes:	0.00	2.00	1.00	0.00	3.00	0.00	0.00	0.00	0.00	2.00	0.00	1.00	0.00	0.00	0.00	2.00	3.00			
Final Sat.:	0	3610	1615	0	5187	0	0	0	0	2226	0	1615	0	0	0	2226	5187			

Capacity Analysis Module:	North Bound					South Bound					East Bound					West Bound				
Vol/Sat:	0.00	0.11	0.02	0.00	0.09	0.00	0.00	0.00	0.00	0.36	0.00	0.34	0.00	0.00	0.00	0.36	0.09			
Crit Moves:	****					****					****					****				
Green/Cycle:	0.00	0.33	0.33	0.00	0.14	0.00	0.00	0.00	0.00	0.59	0.00	0.59	0.00	0.00	0.33	0.59	0.14			
Volume/Cap:	0.00	0.35	0.07	0.00	0.61	0.00	0.00	0.00	0.00	0.60	0.00	0.58	0.00	0.00	0.35	0.58	0.61			
Delay/Veh:	0.0	25.4	22.9	0.0	41.7	0.0	0.0	0.0	0.0	14.0	0.0	13.8	0.0	0.0	25.4	13.8	41.7			
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
AdjDel/Veh:	0.0	25.4	22.9	0.0	41.7	0.0	0.0	0.0	0.0	14.0	0.0	13.8	0.0	0.0	25.4	13.8	41.7			
LOS by Move:	A	C	C	A	D	A	A	A	A	B	A	B	A	A	C	C	D			
HCM2kAvgQ:	0	5	1	0	6	0	0	0	0	9	0	11	0	0	5	1	6			

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
2020 NP AM Tue Dec 2, 2014 11:59:34 Page 4-1

Tesoro Los Angeles Refinery
Year 2020 No Project
AM Peak Hour

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

2020NP-AM.out

Intersection #2 Wilmington Ave / I-405 SB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.364

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 21.8

Optimal Cycle: 40 Level Of Service: C

Approach:	North Bound			South Bound			East Bound			West Bound			
Movement:	L	T	R	L	T	R	L	T	R	L	T	R	
Control:	Permitted			Protected			Permitted			Permitted			
Rights:	Include			Include			Include			Include			
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	
Lanes:	0	0	2	1	1	2	0	3	0	0	0	1	0

Volume Module:	North Bound			South Bound			East Bound			West Bound		
Base Vol:	0	311	368	144	928	0	126	0	168	0	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	311	368	144	928	0	126	0	168	0	0	0
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	311	368	144	928	0	126	0	168	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	0	329	389	152	981	0	133	0	178	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	329	389	152	981	0	133	0	178	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	329	389	152	981	0	133	0	178	0	0	0

Saturation Flow Module:	North Bound			South Bound			East Bound			West Bound		
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.84	0.84	0.92	0.91	1.00	0.71	0.95	0.71	1.00	1.00	1.00
Lanes:	0.00	2.00	2.00	2.00	3.00	0.00	1.00	0.00	1.00	0.00	0.00	0.00
Final Sat.:	0	3178	3178	3502	5187	0	1353	0	1353	0	0	0

Capacity Analysis Module:	North Bound			South Bound			East Bound			West Bound		
Vol/Sat:	0.00	0.10	0.12	0.04	0.19	0.00	0.10	0.00	0.13	0.00	0.00	0.00
Crit Moves:				****						****		
Green/Cycle:	0.00	0.21	0.21	0.39	0.61	0.00	0.27	0.00	0.27	0.00	0.00	0.00
Volume/Cap:	0.00	0.48	0.57	0.11	0.31	0.00	0.36	0.00	0.48	0.00	0.00	0.00
Delay/Veh:	0.0	34.6	35.8	19.3	9.6	0.0	29.6	0.0	31.0	0.0	0.0	0.0
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	34.6	35.8	19.3	9.6	0.0	29.6	0.0	31.0	0.0	0.0	0.0
LOS by Move:	A	C	D	B	A	A	C	A	C	A	A	A
HCM2kAvgQ:	0	5	7	2	5	0	4	0	5	0	0	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 NP AM Tue Dec 2, 2014 11:59:34 Page 5-1

Tesoro Los Angeles Refinery
 Year 2020 No Project
 AM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #4 Alameda Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.687

Page 4

2020NP-AM.out

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 23.4
 Optimal Cycle: 58 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Protected					Protected					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	2	0	0	0	0	0	0	0	1	0	0	0	1

Volume Module:	North Bound					South Bound					East Bound					West Bound				
Base Vol:	0	571	48	51	860	0	0	0	0	473	0	320	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	571	48	51	860	0	0	0	0	473	0	320	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	571	48	51	860	0	0	0	0	473	0	320	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
PHF Volume:	0	614	52	55	925	0	0	0	0	509	0	344	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
Reduced Vol:	0	614	52	55	925	0	0	0	0	509	0	344	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	614	52	55	925	0	0	0	0	509	0	344	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

Saturation Flow Module:	North Bound					South Bound					East Bound					West Bound				
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.95	0.95	1.00	1.00	1.00	1.00	1.00	0.77	1.00	0.85	0.77	1.00	0.85	0.77	0.85	0.77	0.85
Lanes:	0.00	2.00	1.00	1.00	2.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	1.00	1.00	0.00	1.00	0.00	1.00	1.00	0.00
Final Sat.:	0	3610	1615	1805	3610	0	0	0	0	0	1461	0	1615	1461	0	1615	1461	1615	1461	0

Capacity Analysis Module:	North Bound					South Bound					East Bound					West Bound				
Vol/Sat:	0.00	0.17	0.03	0.03	0.26	0.00	0.00	0.00	0.00	0.35	0.00	0.21	0.00	0.00	0.00	0.35	0.00	0.21	0.00	0.00
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****	****	****	****	****	****	****	****	****
Green/Cycle:	0.00	0.32	0.32	0.06	0.37	0.00	0.00	0.00	0.00	0.51	0.00	1.01	0.00	0.00	0.00	0.51	0.00	1.01	0.00	0.00
Volume/Cap:	0.00	0.54	0.10	0.54	0.69	0.00	0.00	0.00	0.00	0.69	0.00	0.21	0.00	0.00	0.00	0.69	0.00	0.21	0.00	0.00
Delay/Veh:	0.0	28.7	24.2	51.5	27.9	0.0	0.0	0.0	0.0	21.4	0.0	0.1	0.0	0.0	0.0	21.4	0.0	0.1	0.0	0.0
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	28.7	24.2	51.5	27.9	0.0	0.0	0.0	0.0	21.4	0.0	0.1	0.0	0.0	0.0	21.4	0.0	0.1	0.0	0.0
LOS by Move:	A	C	C	D	C	A	A	A	A	C	A	A	A	A	A	C	A	A	A	A
HCM2kAvgQ:	0	9	1	2	13	0	0	0	0	13	0	0	0	0	0	13	0	0	0	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 NP AM Tue Dec 2, 2014 11:59:34 Page 6-1

Tesoro Los Angeles Refinery
 Year 2020 No Project
 AM Peak Hour

Level Of Service Computation Report

2000 HCM Operations Method (Future Volume Alternative)

Intersection #9 I-405 SB Ramps / 223rd St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.484
 Loss Time (sec): 16 (Y+R=4.0 sec) Average Delay (sec/veh): 23.5
 Optimal Cycle: 48 Level Of Service: C

2020NP-AM.out

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	1	0	0	0	1	0	2	1	0	0
Volume Module:												
Base Vol:	1	1	5	56	0	126	362	309	4	3	857	33
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	1	1	5	56	0	126	362	309	4	3	857	33
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	1	1	5	56	0	126	362	309	4	3	857	33
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
PHF Volume:	1	1	6	64	0	143	411	351	5	3	973	37
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	1	1	6	64	0	143	411	351	5	3	973	37
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	1	1	6	64	0	143	411	351	5	3	973	37
Saturation Flow Module:												
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	0.90	0.90	0.90	0.95	1.00	0.85	0.92	0.91	0.91	0.95	0.90	0.90
Lanes:	0.14	0.14	0.72	1.00	0.00	1.00	2.00	2.96	0.04	1.00	2.89	0.11
Final Sat.:	244	244	1218	1805	0	1615	3502	5110	66	1805	4965	191
Capacity Analysis Module:												
Vol/Sat:	0.00	0.00	0.00	0.04	0.00	0.09	0.12	0.07	0.07	0.00	0.20	0.20
Crit Moves:	****			****			****			****		
Green/Cycle:	0.01	0.01	0.01	0.18	0.00	0.18	0.24	0.63	0.63	0.02	0.40	0.40
Volume/Cap:	0.48	0.48	0.48	0.19	0.00	0.48	0.48	0.11	0.11	0.11	0.48	0.48
Delay/Veh:	70.0	70.0	70.0	34.9	0.0	37.9	32.9	7.4	7.4	49.9	22.2	22.2
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	70.0	70.0	70.0	34.9	0.0	37.9	32.9	7.4	7.4	49.9	22.2	22.2
LOS by Move:	E	E	E	C	A	D	C	A	A	D	C	C
HCM2kAvgQ:	1	1	1	2	0	4	6	2	2	0	9	9

Note: Queue reported is the number of cars per lane.												

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA

Scenario:	2020 NP PM	Scenario Report
Command:	2020-PM	
Volume:	2020 PM	
Geometry:	2017	
Impact Fee:	Default Impact Fee	
Trip Generation:	Const-PM	
Trip Distribution:	Default Trip Distribution	
Paths:	Default Path	
Routes:	Default Route	
Configuration:	2020-PM	

2020NP-PM.out
 Year 2020 No Project
 PM Peak Hour

Impact Analysis Report
 Level Of Service

Intersection		Base			Future			Change	
		LOS	Del/ Veh	V/ C	LOS	Del/ Veh	V/ C	in	
# 1	Wilmington Ave / I-405 NB Ramp	B	18.4	0.420	B	18.4	0.420	+ 0.000	D/V
# 2	Wilmington Ave / I-405 SB Ramp	B	15.7	0.362	B	15.7	0.362	+ 0.000	D/V
# 4	Alameda Ave / I-405 NB Ramps	C	23.5	0.681	C	23.5	0.681	+ 0.000	D/V
# 9	I-405 SB Ramps / 223rd St	B	19.1	0.514	B	19.1	0.514	+ 0.000	D/V

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 NP PM Tue Dec 2, 2014 12:05:07 Page 3-1

Tesoro Los Angeles Refinery
 Year 2020 No Project
 PM Peak Hour

2020NP-PM.out

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

Intersection #1 Wilmington Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.420
Loss Time (sec): 8 (Y+R=4.0 sec) Average Delay (sec/veh): 18.4
Optimal Cycle: 28 Level Of Service: B

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Permitted					Permitted					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	0	0	3	0	0	0	0	0	0	0	2	0	0	0	1

Volume Module:

Base Vol:	0	289	155	0	886	0	0	0	0	438	0	309
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	289	155	0	886	0	0	0	0	438	0	309
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	289	155	0	886	0	0	0	0	438	0	309
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	0	305	163	0	934	0	0	0	0	462	0	326
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	305	163	0	934	0	0	0	0	462	0	326
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	305	163	0	934	0	0	0	0	462	0	326

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	1.00	0.91	1.00	1.00	1.00	1.00	0.59	1.00	0.85
Lanes:	0.00	2.00	1.00	0.00	3.00	0.00	0.00	0.00	0.00	2.00	0.00	1.00
Final Sat.:	0	3610	1615	0	5187	0	0	0	0	2234	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.08	0.10	0.00	0.18	0.00	0.00	0.00	0.00	0.21	0.00	0.20
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.43	0.43	0.00	0.43	0.00	0.00	0.00	0.00	0.49	0.00	0.49
Volume/Cap:	0.00	0.20	0.24	0.00	0.42	0.00	0.00	0.00	0.00	0.42	0.00	0.41
Delay/Veh:	0.0	17.9	18.4	0.0	20.1	0.0	0.0	0.0	0.0	16.5	0.0	16.5
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	17.9	18.4	0.0	20.1	0.0	0.0	0.0	0.0	16.5	0.0	16.5
LOS by Move:	A	B	B	A	C	A	A	A	A	B	A	B
HCM2kAvgQ:	0	3	3	0	7	0	0	0	0	5	0	6

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
2020 NP PM Tue Dec 2, 2014 12:05:07 Page 4-1

Tesoro Los Angeles Refinery
Year 2020 No Project
PM Peak Hour

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

Page 3

2020NP-PM.out

Intersection #2 Wilmington Ave / I-405 SB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.362

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 15.7

Optimal Cycle: 33 Level Of Service: B

Approach:	North Bound			South Bound			East Bound			West Bound			
Movement:	L	T	R	L	T	R	L	T	R	L	T	R	
Control:	Permitted			Protected			Permitted			Permitted			
Rights:	Include			Include			Include			Include			
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	
Lanes:	0	0	2	1	1	2	0	3	0	0	0	1	0

Volume Module:	North Bound			South Bound			East Bound			West Bound		
Base Vol:	0	416	491	345	910	0	27	0	84	0	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	416	491	345	910	0	27	0	84	0	0	0
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	416	491	345	910	0	27	0	84	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98
PHF Volume:	0	425	502	353	930	0	28	0	86	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	425	502	353	930	0	28	0	86	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	425	502	353	930	0	28	0	86	0	0	0

Saturation Flow Module:	North Bound			South Bound			East Bound			West Bound		
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.84	0.84	0.92	0.91	1.00	0.75	0.95	0.75	1.00	1.00	1.00
Lanes:	0.00	2.00	2.00	2.00	3.00	0.00	1.00	0.00	1.00	0.00	0.00	0.00
Final Sat.:	0	3178	3178	3502	5187	0	1430	0	1430	0	0	0

Capacity Analysis Module:	North Bound			South Bound			East Bound			West Bound		
Vol/Sat:	0.00	0.13	0.16	0.10	0.18	0.00	0.02	0.00	0.06	0.00	0.00	0.00
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.44	0.44	0.28	0.71	0.00	0.17	0.00	0.17	0.00	0.00	0.00
Volume/Cap:	0.00	0.31	0.36	0.36	0.25	0.00	0.12	0.00	0.36	0.00	0.00	0.00
Delay/Veh:	0.0	18.4	19.0	29.2	5.0	0.0	35.5	0.0	37.7	0.0	0.0	0.0
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	18.4	19.0	29.2	5.0	0.0	35.5	0.0	37.7	0.0	0.0	0.0
LOS by Move:	A	B	B	C	A	A	D	A	D	A	A	A
HCM2kAvgQ:	0	5	6	5	4	0	1	0	3	0	0	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 NP PM Tue Dec 2, 2014 12:05:07 Page 5-1

Tesoro Los Angeles Refinery
 Year 2020 No Project
 PM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #4 Alameda Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.681

Page 4

2020NP-PM.out

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 23.5
 Optimal Cycle: 57 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Protected					Protected					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	2	0	0	0	0	0	0	0	1	0	0	0	1

Volume Module:	North Bound					South Bound					East Bound					West Bound				
Base Vol:	0	944	195	82	773	0	0	0	0	0	0	0	0	0	0	393	0	108	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	944	195	82	773	0	0	0	0	0	0	0	0	0	0	393	0	108	0	0
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	944	195	82	773	0	0	0	0	0	0	0	0	0	0	393	0	108	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
PHF Volume:	0	982	203	85	804	0	0	0	0	0	0	0	0	0	0	409	0	112	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	982	203	85	804	0	0	0	0	0	0	0	0	0	0	409	0	112	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	982	203	85	804	0	0	0	0	0	0	0	0	0	0	409	0	112	0	0

Saturation Flow Module:	North Bound					South Bound					East Bound					West Bound				
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.95	0.95	1.00	1.00	1.00	1.00	1.00	0.77	1.00	0.85	0.77	1.00	0.77	1.00	0.85	0.77	1.00
Lanes:	0.00	2.00	1.00	1.00	2.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	1.00	1.00	0.00	1.00	0.00	1.00	1.00	0.00
Final Sat.:	0	3610	1615	1805	3610	0	0	0	0	0	1461	0	1615	1461	0	1461	0	1615	1461	0

Capacity Analysis Module:	North Bound					South Bound					East Bound					West Bound				
Vol/Sat:	0.00	0.27	0.13	0.05	0.22	0.00	0.00	0.00	0.00	0.00	0.28	0.00	0.07	0.28	0.00	0.28	0.00	0.07	0.28	0.00
Crit Moves:	****					****					****					****				
Green/Cycle:	0.00	0.40	0.40	0.07	0.47	0.00	0.00	0.00	0.00	0.00	0.41	0.00	0.82	0.41	0.00	0.41	0.00	0.82	0.41	0.00
Volume/Cap:	0.00	0.68	0.31	0.68	0.48	0.00	0.00	0.00	0.00	0.00	0.68	0.00	0.08	0.68	0.00	0.68	0.00	0.08	0.68	0.00
Delay/Veh:	0.0	26.1	20.9	59.7	18.4	0.0	0.0	0.0	0.0	0.0	27.3	0.0	1.7	27.3	0.0	27.3	0.0	1.7	27.3	0.0
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	26.1	20.9	59.7	18.4	0.0	0.0	0.0	0.0	0.0	27.3	0.0	1.7	27.3	0.0	27.3	0.0	1.7	27.3	0.0
LOS by Move:	A	C	C	E	B	A	A	A	A	A	C	A	A	C	A	C	A	A	C	A
HCM2kAvgQ:	0	14	4	4	9	0	0	0	0	0	11	0	1	11	0	11	0	1	11	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 NP PM Tue Dec 2, 2014 12:05:07 Page 6-1

Tesoro Los Angeles Refinery
 Year 2020 No Project
 PM Peak Hour

Level Of Service Computation Report 2000 HCM Operations Method (Future Volume Alternative)

Intersection #9 I-405 SB Ramps / 223rd St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.514
 Loss Time (sec): 16 (Y+R=4.0 sec) Average Delay (sec/veh): 19.1
 Optimal Cycle: 50 Level Of Service: B

2020NP-PM.out

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	1	0	0	0	1	0	2	1	0	0
Volume Module:												
Base Vol:	3	6	3	128	2	37	860	817	18	4	355	79
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	3	6	3	128	2	37	860	817	18	4	355	79
Added Vol:	0	0	0	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	3	6	3	128	2	37	860	817	18	4	355	79
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	3	6	3	135	2	39	907	862	19	4	374	83
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	3	6	3	135	2	39	907	862	19	4	374	83
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	3	6	3	135	2	39	907	862	19	4	374	83
Saturation Flow Module:												
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	0.95	0.95	0.95	0.95	0.86	0.86	0.92	0.91	0.91	0.95	0.89	0.89
Lanes:	0.25	0.50	0.25	1.00	0.05	0.95	2.00	2.94	0.06	1.00	2.45	0.55
Final Sat.:	453	907	453	1805	84	1547	3502	5060	111	1805	4128	919
Capacity Analysis Module:												
Vol/Sat:	0.01	0.01	0.01	0.07	0.03	0.03	0.26	0.17	0.17	0.00	0.09	0.09
Crit Moves:	****			****			****			****		
Green/Cycle:	0.01	0.01	0.01	0.15	0.15	0.15	0.50	0.67	0.67	0.01	0.18	0.18
Volume/Cap:	0.51	0.51	0.51	0.51	0.17	0.17	0.51	0.25	0.25	0.25	0.51	0.51
Delay/Veh:	66.3	66.3	66.3	41.2	37.8	37.8	16.8	6.5	6.5	57.1	37.8	37.8
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	66.3	66.3	66.3	41.2	37.8	37.8	16.8	6.5	6.5	57.1	37.8	37.8
LOS by Move:	E	E	E	D	D	D	B	A	A	E	D	D
HCM2kAvgQ:	1	1	1	4	1	1	10	4	4	0	5	5

Note: Queue reported is the number of cars per lane.												

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA

YEAR 2021
WITH PROJECT

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 3 North/South Street: WILMINGTON AVENUE East/West Street: 223RD STREET Scenario: 2021 Plus Operations						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	327	1,600	0.117	N-S(1): 0.163
	TH	2.00	664	3,200	0.208 *	N-S(2): 0.215 *
	LT	1.00	58	1,600	0.036	E-W(1): 0.302
Westbound	RT	1.00	54	1,600	0.000	E-W(2): 0.342 *
	TH	2.00	813	3,200	0.254 *	V/C: 0.557
	LT	1.00	205	1,600	0.128	Lost Time: 0.100
Northbound	RT	0.50	82	800	0.000	
	TH	2.50	507	4,000	0.127	
	LT	1.00	11	1,600	0.007 *	
Eastbound	RT	1.00	16	1,600	0.003	ICU: 0.657
	TH	2.00	558	3,200	0.174	
	LT	1.00	140	1,600	0.088 *	LOS: B
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	204	1,600	0.000	N-S(1): 0.142
	TH	2.00	743	3,200	0.232 *	N-S(2): 0.237 *
	LT	1.00	56	1,600	0.035	E-W(1): 0.366 *
Westbound	RT	1.00	146	1,600	0.056	E-W(2): 0.264
	TH	2.00	353	3,200	0.110	V/C: 0.603
	LT	1.00	181	1,600	0.113 *	Lost Time: 0.100
Northbound	RT	0.50	127	800	0.000	
	TH	2.50	427	4,000	0.107	
	LT	1.00	8	1,600	0.005 *	
Eastbound	RT	1.00	10	1,600	0.001	ICU: 0.703
	TH	2.00	811	3,200	0.253 *	
	LT	1.00	246	1,600	0.154	LOS: C

* = Critical Movement

Project:		Tesoro Los Angeles Refinery Traffic Study					
Int #:		5					
North/South Street:		223rd Street Ramp (on Alameda Street)					
East/West Street:		Alameda Street					
Scenario:		2021 Plus Operations					
Thru Lane:		1600 vph			N-S Split Phase :		N
Left-Turn Lane:		1600 vph			E-W Split Phase :		N
Dual LT Penalty:		10 %			Lost Time (% of cycle) :		10
Peak Period:		AM PEAK HOUR					
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	0.00	0	0	0.000	N-S(1):	0.258 *
	TH	3.00	1,150	4,800	0.240	N-S(2):	0.240
	LT	1.00	163	1,600	0.102 *	E-W(1):	0.113 *
Westbound	RT	1.00	122	1,600	0.000	E-W(2):	0.000
	TH	0.00	0	0	0.000	V/C:	0.371
	LT	1.00	180	1,600	0.113 *	Lost Time:	0.100
Northbound	RT	0.00	249	1,600	0.156 *		
	TH	3.00	482	3,200	0.151		
	LT	0.00	0	0	0.000		
Eastbound	RT	0.00	0	0	0.000	ICU:	0.471
	TH	0.00	0	0	0.000 *		
	LT	0.00	0	0	0.000	LOS:	A
Peak Period:		PM PEAK HOUR					
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	0.00	0	0	0.000	N-S(1):	0.410 *
	TH	3.00	1,005	4,800	0.209	N-S(2):	0.209
	LT	1.00	168	1,600	0.105 *	E-W(1):	0.071 *
Westbound	RT	1.00	125	1,600	0.000	E-W(2):	0.000
	TH	0.00	0	0	0.000	V/C:	0.481
	LT	1.00	114	1,600	0.071 *	Lost Time:	0.100
Northbound	RT	0.00	473	0	0.000		
	TH	3.00	991	4,800	0.305 *		
	LT	0.00	0	0	0.000		
Eastbound	RT	0.00	0	0	0.000	ICU:	0.581
	TH	0.00	0	0	0.000 *		
	LT	0.00	0	0	0.000	LOS:	A

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 6 North/South Street: Alameda Street Ramp East/West Street: 223rd Street Scenario: 2021 Plus Operations						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.090 *
	TH	0.00	0	0	0.000	N-S(2): 0.083
	LT	0.00	0	0	0.000 *	E-W(1): 0.165 *
Westbound	RT	0.00	0	0	0.000	E-W(2): 0.145
	TH	3.00	765	5,280	0.145	V/C: 0.255
	LT	2.00	228	3,168	0.072 *	
Northbound	RT	1.00	273	1,760	0.090 *	
	TH	0.00	0	0	0.000	
	LT	1.00	146	1,760	0.083	
Eastbound	RT	0.00	82	0	0.000	ICU: 0.355
	TH	3.00	408	5,280	0.093 *	LOS: A
	LT	0.00	0	0	0.000	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.261 *
	TH	0.00	0	0	0.000	N-S(2): 0.056
	LT	0.00	0	0	0.000 *	E-W(1): 0.286 *
Westbound	RT	0.00	0	0	0.000	E-W(2): 0.055
	TH	3.00	290	5,280	0.055	V/C: 0.547
	LT	2.00	94	3,168	0.030 *	
Northbound	RT	1.00	507	1,760	0.261 *	
	TH	0.00	0	0	0.000	
	LT	1.00	99	1,760	0.056	
Eastbound	RT	0.00	141	0	0.000	ICU: 0.647
	TH	3.00	1,212	5,280	0.256 *	LOS: B
	LT	0.00	0	0	0.000	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 7 North/South Street: ALAMEDA STREET East/West Street: SEPULVEDA BOULEVARD-ALAMEDA RAMP Scenario: 2021 Plus Operations						
Thru Lane: 1600 vph				N-S Split Phase : N		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.250 *
	TH	3.00	785	4,800	0.164	N-S(2): 0.164
	LT	1.00	236	1,600	0.148 *	E-W(1): 0.031 *
Westbound	RT	2.00	204	3,200	0.000	E-W(2): 0.000
	TH	0.00	0	0	0.000	
	LT	1.00	50	1,600	0.031 *	V/C: 0.281
Northbound	RT	0.00	51	0	0.000	Lost Time: 0.100
	TH	3.00	438	4,800	0.102 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.381
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	0	0	0.000	N-S(1): 0.390 *
	TH	3.00	877	4,800	0.183	N-S(2): 0.183
	LT	1.00	257	1,600	0.161 *	E-W(1): 0.059 *
Westbound	RT	2.00	418	3,200	0.050	E-W(2): 0.050
	TH	0.00	0	0	0.000	
	LT	1.00	95	1,600	0.059 *	V/C: 0.449
Northbound	RT	0.00	85	0	0.000	Lost Time: 0.100
	TH	3.00	1,012	4,800	0.229 *	
	LT	0.00	0	0	0.000	
Eastbound	RT	0.00	0	0	0.000	ICU: 0.549
	TH	0.00	0	0	0.000 *	
	LT	0.00	0	0	0.000	LOS: A

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 8 North/South Street: SEPULVEDA BOULEVARD-ALAMEDA RAMP East/West Street: SEPULVEDA BOULEVARD Scenario: 2021 Plus Operations						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	148	1,600	0.016	N-S(1): 0.056 *
	TH	0.13	9	210	0.043	N-S(2): 0.000
	LT	1.87	128	2,691	0.048 *	E-W(1): 0.234
Westbound	RT	1.00	100	1,600	0.020	E-W(2): 0.267 *
	TH	2.00	610	3,200	0.191 *	V/C: 0.323
	LT	1.00	8	1,600	0.005	Lost Time: 0.100
Northbound	RT	0.00	4	0	0.000	ICU: 0.423
	TH	2.00	19	3,200	0.008 *	
	LT	0.00	2	1,600	0.001	
Eastbound	RT	1.00	6	1,600	0.003	LOS: A
	TH	1.00	366	1,600	0.229	
	LT	1.00	122	1,600	0.076 *	
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	1.00	177	1,600	0.000	N-S(1): 0.058 *
	TH	0.17	12	269	0.045	N-S(2): 0.000
	LT	1.83	131	2,638	0.050 *	E-W(1): 0.601 *
Westbound	RT	1.00	244	1,600	0.108	E-W(2): 0.320
	TH	2.00	549	3,200	0.172	V/C: 0.659
	LT	1.00	2	1,600	0.001 *	Lost Time: 0.100
Northbound	RT	0.00	9	0	0.000	ICU: 0.759
	TH	2.00	13	3,200	0.008 *	
	LT	0.00	4	1,600	0.003	
Eastbound	RT	1.00	1	1,600	0.000	LOS: C
	TH	1.00	960	1,600	0.600 *	
	LT	1.00	236	1,600	0.148	

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study Int #: 10 North/South Street: TERMINAL ISLAND FREEWAY (SR-103) East/West Street: WILLOW STREET Scenario: 2021 Plus Operations							
Thru Lane: 1600 vph				N-S Split Phase : Y			
Left-Turn Lane: 1600 vph				E-W Split Phase : N			
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10			
Peak Period: AM PEAK HOUR							
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	0.00	0	0	0.000	N-S(1):	0.034 *
	TH	1.00	0	1,600	0.000	N-S(2):	0.000
	LT	0.00	0	0	0.000 *	E-W(1):	0.186
Westbound	RT	0.00	16	0	0.000	E-W(2):	0.263 *
	TH	2.00	815	3,200	0.260 *	V/C: 0.297 Lost Time: 0.100	
	LT	2.00	242	2,880	0.084		
Northbound	RT	2.00	101	3,200	0.000	ICU: 0.397	
	TH	0.00	0	0	0.000		
	LT	2.00	99	2,880	0.034 *		
Eastbound	RT	1.00	187	1,600	0.086	LOS: A	
	TH	2.00	326	3,200	0.102		
	LT	1.00	4	1,600	0.003 *		
Peak Period: PM PEAK HOUR							
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS	
Southbound	RT	0.00	0	0	0.000	N-S(1):	0.111 *
	TH	1.00	0	1,600	0.000	N-S(2):	0.000
	LT	0.00	0	0	0.000 *	E-W(1):	0.380 *
Westbound	RT	0.00	1	0	0.000	E-W(2):	0.137
	TH	2.00	437	3,200	0.137	V/C: 0.491 Lost Time: 0.100	
	LT	2.00	171	2,880	0.059 *		
Northbound	RT	2.00	254	3,200	0.053	ICU: 0.591	
	TH	0.00	0	0	0.000		
	LT	2.00	319	2,880	0.111 *		
Eastbound	RT	1.00	262	1,600	0.064	LOS: A	
	TH	2.00	1,026	3,200	0.321 *		
	LT	1.00	0	1,600	0.000		

* = Critical Movement

Project: Tesoro Los Angeles Refinery Traffic Study						
Int #: 11						
North/South Street: SANTA FE AVE						
East/West Street: SEPULVEDA BOULEVARD						
Scenario: 2021 Plus Operations						
Thru Lane: 1600 vph				N-S Split Phase : Y		
Left-Turn Lane: 1600 vph				E-W Split Phase : N		
Dual LT Penalty: 10 %				Lost Time (% of cycle) : 10		
Peak Period: AM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	135	0	0.000	N-S(1): 0.209 *
	TH	2.00	264	3,200	0.125 *	N-S(2): 0.000
	LT	2.00	156	2,880	0.054	E-W(1): 0.204
Westbound	RT	0.00	111	0	0.000	E-W(2): 0.328 *
	TH	2.00	788	3,200	0.281 *	
	LT	2.00	163	2,880	0.057	V/C: 0.537
Northbound	RT	0.00	82	0	0.000	Lost Time: 0.100
	TH	2.00	188	3,200	0.084 *	
	LT	1.00	78	1,600	0.049	
Eastbound	RT	0.00	33	0	0.000	ICU: 0.637
	TH	2.00	438	3,200	0.147	
	LT	1.00	75	1,600	0.047 *	LOS: B
Peak Period: PM PEAK HOUR						
Approach	Movement	Lanes	Volume	Capacity	V/C	ICU ANALYSIS
Southbound	RT	0.00	64	0	0.000	N-S(1): 0.321 *
	TH	2.00	319	3,200	0.120 *	N-S(2): 0.000
	LT	2.00	339	2,880	0.118	E-W(1): 0.378 *
Westbound	RT	0.00	153	0	0.000	E-W(2): 0.292
	TH	2.00	497	3,200	0.203	
	LT	2.00	140	2,880	0.049 *	V/C: 0.699
Northbound	RT	0.00	205	0	0.000	Lost Time: 0.100
	TH	2.00	438	3,200	0.201 *	
	LT	1.00	84	1,600	0.053	
Eastbound	RT	0.00	44	0	0.000	ICU: 0.799
	TH	2.00	1,008	3,200	0.329 *	
	LT	1.00	143	1,600	0.089	LOS: C

* = Critical Movement

I/S #:
31

PROJECT TITLE: ICTF Modification and Expansion Project EIR
North-South Street: 223rd Street (on 223rd) East-West Street:
Scenario: CEQA Baseline
Count Date:

Alameda Street Ramp

Analyst: Iteris, Inc.

Date: 7/22/2014

			AM PEAK HOUR			MD PEAK HOUR			PM PEAK HOUR		
No. of Phases			3			3			3		
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?			2			2			2		
Right Turns: FREE-1, NRTOR-2 or OLA-3?			NB -- 3	SB -- 0		NB -- 3	SB -- 0		NB -- 0	SB -- 0	
ATSAC-1 or ATSAC+ATCS-2?			EB -- 0	WB -- 0		EB -- 0	WB -- 0		EB -- 3	WB -- 0	
Override Capacity			1500			1500			1500		
MOVEMENT			Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left		146	1	146	0	1	60	99	1	99
	Left-Through			0			0			0	
	Through		0	0	0	0	0	0	0	0	0
	Through-Right			0			0			0	
	Right		273	1	148	0	1	403	507	1	455
	Left-Through-Right			0			0			0	
SOUTHBOUND	Left		0	0	0	0	0	0	0	0	0
	Left-Through			0			0			0	
	Through		0	0	0	0	0	0	0	0	0
	Through-Right			0			0			0	
	Right		0	0	0	0	0	0	0	0	0
	Left-Through-Right			0			0			0	
EASTBOUND	Left		0	0	0	0	0	0	0	0	0
	Left-Through			0			0			0	
	Through		408	2	163	0	2	380	1,212	2	451
	Through-Right			1			1			1	
	Right		82	0	82	0	0	45	141	0	141
	Left-Through-Right			0			0			0	
WESTBOUND	Left		228	2	125	0	2	77	94	2	52
	Left-Through			0			0			0	
	Through		765	3	255	0	3	82	290	3	97
	Through-Right			0			0			0	
	Right		0	0	0	0	0	0	0	0	0
	Left-Through-Right			0			0			0	
CRITICAL VOLUMES			North-South: 148			North-South: 403			North-South: 455		
			East-West: 418			East-West: 462			East-West: 548		
			SUM: 566			SUM: 865			SUM: 1003		
VOLUME/CAPACITY (V/C) RATIO:			0.397			0.577			0.704		
V/C LESS ATSAC/ATCS ADJUSTMENT:			0.297			0.477			0.604		
LEVEL OF SERVICE (LOS):			A			A			B		

Scenario:	2020 Ops AM	Scenario Report
Command:	2020+Ops-AM	
Volume:	2020 AM	
Geometry:	2017	
Impact Fee:	Default Impact Fee	
Trip Generation:	Const-AM	
Trip Distribution:	Default Trip Distribution	
Paths:	Default Path	
Routes:	Default Route	
Configuration:	2020+Ops-AM	

2020+Ops_AM.out
 Year 2020 With Project Operations
 AM Peak Hour

Impact Analysis Report
 Level Of Service

Intersection		Base			Future			Change in
		LOS	Del/ Veh	V/ C	LOS	Del/ Veh	V/ C	
# 1	Wilmington Ave / I-405 NB Ramp	C	21.7	0.512	C	21.7	0.512	+ 0.001 D/V
# 2	Wilmington Ave / I-405 SB Ramp	C	21.8	0.364	C	21.8	0.365	+ 0.026 D/V
# 4	Alameda Ave / I-405 NB Ramps	C	23.4	0.687	C	23.4	0.687	+ 0.029 D/V
# 9	I-405 SB Ramps / 223rd St	C	23.5	0.484	C	23.5	0.484	+ 0.012 D/V

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 Ops AM Tue Dec 2, 2014 13:55:36 Page 3-1

Tesoro Los Angeles Refinery
 Year 2020 With Project Operations
 AM Peak Hour

2020+Ops_AM.out

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

Intersection #1 Wilmington Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.512
Loss Time (sec): 8 (Y+R=4.0 sec) Average Delay (sec/veh): 21.7
Optimal Cycle: 39 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Permitted					Permitted					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	0	0	3	0	0	0	0	0	0	0	2	0	0	0	1

Volume Module:	North Bound					South Bound					East Bound					West Bound				
Base Vol:	0	371	34	0	402	0	0	0	0	710	0	496	0	371	34	0	402			
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Initial Bse:	0	371	34	0	402	0	0	0	0	710	0	496	0	371	34	0	402			
Added Vol:	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
Initial Fut:	0	371	35	0	402	0	0	0	0	710	0	496	0	371	35	0	402			
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
PHF Adj:	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90			
PHF Volume:	0	414	39	0	449	0	0	0	0	792	0	554	0	414	39	0	449			
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
Reduced Vol:	0	414	39	0	449	0	0	0	0	792	0	554	0	414	39	0	449			
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
Final Volume:	0	414	39	0	449	0	0	0	0	792	0	554	0	414	39	0	449			

Saturation Flow Module:	North Bound					South Bound					East Bound					West Bound				
Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900			
Adjustment:	1.00	0.95	0.85	1.00	0.91	1.00	1.00	1.00	1.00	0.59	1.00	0.85	1.00	0.95	0.85	1.00	0.91			
Lanes:	0.00	2.00	1.00	0.00	3.00	0.00	0.00	0.00	0.00	2.00	0.00	1.00	0.00	0.00	0.00	2.00	3.00			
Final Sat.:	0	3610	1615	0	5187	0	0	0	0	2226	0	1615	0	0	0	3610	5187			

Capacity Analysis Module:	North Bound					South Bound					East Bound					West Bound				
Vol/Sat:	0.00	0.11	0.02	0.00	0.09	0.00	0.00	0.00	0.00	0.36	0.00	0.34	0.00	0.00	0.00	0.36	0.09			
Crit Moves:	****					****					****					****				
Green/Cycle:	0.00	0.33	0.33	0.00	0.14	0.00	0.00	0.00	0.00	0.59	0.00	0.59	0.00	0.00	0.33	0.59	0.14			
Volume/Cap:	0.00	0.35	0.07	0.00	0.61	0.00	0.00	0.00	0.00	0.60	0.00	0.58	0.00	0.00	0.35	0.60	0.61			
Delay/Veh:	0.0	25.4	23.0	0.0	41.7	0.0	0.0	0.0	0.0	14.0	0.0	13.8	0.0	0.0	25.4	14.0	41.7			
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00			
AdjDel/Veh:	0.0	25.4	23.0	0.0	41.7	0.0	0.0	0.0	0.0	14.0	0.0	13.8	0.0	0.0	25.4	14.0	41.7			
LOS by Move:	A	C	C	A	D	A	A	A	A	B	A	B	A	A	C	B	D			
HCM2kAvgQ:	0	5	1	0	6	0	0	0	0	9	0	11	0	0	5	9	6			

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
2020 Ops AM Tue Dec 2, 2014 13:55:36 Page 4-1

Tesoro Los Angeles Refinery
Year 2020 With Project Operations
AM Peak Hour

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

2020+Ops_AM.out

Intersection #2 Wilmington Ave / I-405 SB Ramps

```

*****
Cycle (sec):          100          Critical Vol./Cap.(X):          0.365
Loss Time (sec):      12 (Y+R=4.0 sec) Average Delay (sec/veh):      21.8
Optimal Cycle:        40          Level Of Service:          C
*****

```

```

Approach:      North Bound      South Bound      East Bound      West Bound
Movement:      L - T - R      L - T - R      L - T - R      L - T - R
-----|-----|-----|-----|
Control:      Permitted      Protected      Permitted      Permitted
Rights:      Include      Include      Include      Include
Min. Green:      0 0 0 0      0 0 0 0      0 0 0 0      0 0 0 0
Lanes:      0 0 2 1 1      2 0 3 0 0      0 1 0 1 0      0 0 0 0 0
-----|-----|-----|-----|

```

```

Volume Module:
Base Vol:      0 311 368 144 928 0 126 0 168 0 0 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 311 368 144 928 0 126 0 168 0 0 0
Added Vol: 0 1 0 0 0 0 0 0 1 0 0 0
PasserByVol: 0 0 0 0 0 0 0 0 0 0 0 0
Initial Fut: 0 312 368 144 928 0 126 0 169 0 0 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 0.95 0.95 0.95 0.95 0.95 0.95 0.95 0.95 0.95 0.95 0.95 0.95
PHF Volume: 0 330 389 152 981 0 133 0 179 0 0 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 0 330 389 152 981 0 133 0 179 0 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 0 330 389 152 981 0 133 0 179 0 0 0
-----|-----|-----|-----|

```

```

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 1.00 0.84 0.84 0.92 0.91 1.00 0.71 0.95 0.71 1.00 1.00 1.00
Lanes: 0.00 2.00 2.00 2.00 3.00 0.00 1.00 0.00 1.00 0.00 0.00 0.00
Final Sat.: 0 3178 3178 3502 5187 0 1353 0 1353 0 0 0
-----|-----|-----|-----|

```

```

Capacity Analysis Module:
Vol/Sat: 0.00 0.10 0.12 0.04 0.19 0.00 0.10 0.00 0.13 0.00 0.00 0.00
Crit Moves:
Green/Cycle: 0.00 0.21 0.21 0.39 0.61 0.00 0.27 0.00 0.27 0.00 0.00 0.00
Volume/Cap: 0.00 0.48 0.57 0.11 0.31 0.00 0.36 0.00 0.48 0.00 0.00 0.00
Delay/Veh: 0.0 34.7 35.8 19.4 9.6 0.0 29.5 0.0 30.9 0.0 0.0 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 0.0 34.7 35.8 19.4 9.6 0.0 29.5 0.0 30.9 0.0 0.0 0.0
LOS by Move: A C D B A A C A C A A A
HCM2kAvgQ: 0 5 7 2 5 0 4 0 5 0 0 0
*****

```

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 Ops AM Tue Dec 2, 2014 13:55:36 Page 5-1

Tesoro Los Angeles Refinery
 Year 2020 With Project Operations
 AM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #4 Alameda Ave / I-405 NB Ramps

```

*****
Cycle (sec):          100          Critical Vol./Cap.(X):          0.687
Page 4

```

2020+Ops_AM.out

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 23.4
 Optimal Cycle: 58 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Protected					Protected					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	2	0	0	0	0	0	0	0	1	0	0	0	1

Volume Module:

Base Vol:	0	571	48	51	860	0	0	0	0	473	0	320
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	571	48	51	860	0	0	0	0	473	0	320
Added Vol:	0	0	0	0	0	0	0	0	0	1	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	571	48	51	860	0	0	0	0	474	0	320
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
PHF Volume:	0	614	52	55	925	0	0	0	0	510	0	344
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	614	52	55	925	0	0	0	0	510	0	344
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	614	52	55	925	0	0	0	0	510	0	344

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.95	0.95	1.00	1.00	1.00	1.00	0.77	1.00	0.85
Lanes:	0.00	2.00	1.00	1.00	2.00	0.00	0.00	0.00	0.00	1.00	0.00	1.00
Final Sat.:	0	3610	1615	1805	3610	0	0	0	0	1461	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.17	0.03	0.03	0.26	0.00	0.00	0.00	0.00	0.35	0.00	0.21
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.32	0.32	0.06	0.37	0.00	0.00	0.00	0.00	0.51	0.00	1.01
Volume/Cap:	0.00	0.54	0.10	0.54	0.69	0.00	0.00	0.00	0.00	0.69	0.00	0.21
Delay/Veh:	0.0	28.7	24.2	51.5	28.0	0.0	0.0	0.0	0.0	21.4	0.0	0.1
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	28.7	24.2	51.5	28.0	0.0	0.0	0.0	0.0	21.4	0.0	0.1
LOS by Move:	A	C	C	D	C	A	A	A	A	C	A	A
HCM2kAvgQ:	0	9	1	2	13	0	0	0	0	13	0	0

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 Ops AM Tue Dec 2, 2014 13:55:36 Page 6-1

Tesoro Los Angeles Refinery
 Year 2020 With Project Operations
 AM Peak Hour

Level Of Service Computation Report 2000 HCM Operations Method (Future Volume Alternative)

Intersection #9 I-405 SB Ramps / 223rd St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.484
 Loss Time (sec): 16 (Y+R=4.0 sec) Average Delay (sec/veh): 23.5
 Optimal Cycle: 48 Level Of Service: C

2020+Ops_AM.out

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Split Phase					Split Phase					Protected					Protected				
Rights:	Include					Include					Include					Include				
Min. Green:	0		0		0	0		0		0	0		0		0	0		0		0
Lanes:	0	0	1	0	0	1	0	0	1	0	2	0	2	1	0	1	0	2	1	0
Volume Module:																				
Base Vol:	1		1		5	56		0		126	362		309		4	3		857		33
Growth Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
Initial Bse:	1		1		5	56		0		126	362		309		4	3		857		33
Added Vol:	0		0		0	0		0		0	1		0		0	0		0		0
PasserByVol:	0		0		0	0		0		0	0		0		0	0		0		0
Initial Fut:	1		1		5	56		0		126	363		309		4	3		857		33
User Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
PHF Adj:	0.88		0.88		0.88	0.88		0.88		0.88	0.88		0.88		0.88	0.88		0.88		0.88
PHF Volume:	1		1		6	64		0		143	412		351		5	3		973		37
Reduct Vol:	0		0		0	0		0		0	0		0		0	0		0		0
Reduced Vol:	1		1		6	64		0		143	412		351		5	3		973		37
PCE Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
MLF Adj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
FinalVolume:	1		1		6	64		0		143	412		351		5	3		973		37
Saturation Flow Module:																				
Sat/Lane:	1900		1900		1900	1900		1900		1900	1900		1900		1900	1900		1900		1900
Adjustment:	0.90		0.90		0.90	0.95		1.00		0.85	0.92		0.91		0.91	0.95		0.90		0.90
Lanes:	0.14		0.14		0.72	1.00		0.00		1.00	2.00		2.96		0.04	1.00		2.89		0.11
Final Sat.:	244		244		1218	1805		0		1615	3502		5110		66	1805		4965		191
Capacity Analysis Module:																				
Vol/Sat:	0.00		0.00		0.00	0.04		0.00		0.09	0.12		0.07		0.07	0.00		0.20		0.20
Crit Moves:	****					****					****					****				
Green/Cycle:	0.01		0.01		0.01	0.18		0.00		0.18	0.24		0.63		0.63	0.02		0.40		0.40
Volume/Cap:	0.48		0.48		0.48	0.19		0.00		0.48	0.48		0.11		0.11	0.11		0.48		0.48
Delay/Veh:	70.1		70.1		70.1	34.9		0.0		37.9	32.9		7.4		7.4	49.9		22.2		22.2
User DelAdj:	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00	1.00		1.00		1.00
AdjDel/Veh:	70.1		70.1		70.1	34.9		0.0		37.9	32.9		7.4		7.4	49.9		22.2		22.2
LOS by Move:	E		E		E	C		A		D	C		A		A	D		C		C
HCM2kAvgQ:	1		1		1	2		0		4	6		2		2	0		9		9

Note: Queue reported is the number of cars per lane.																				

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA

Scenario:	2020 Ops PM
Command:	2020+Ops-PM
Volume:	2020 PM
Geometry:	2017
Impact Fee:	Default Impact Fee
Trip Generation:	Const-PM
Trip Distribution:	Default Trip Distribution
Paths:	Default Path
Routes:	Default Route
Configuration:	2020+Ops-PM

2020+Ops_PM.out
 Year 2020 With Project Operations
 PM Peak Hour

Impact Analysis Report
 Level Of Service

Intersection		Base			Future			Change in
		LOS	Del/ Veh	V/ C	LOS	Del/ Veh	V/ C	
# 1	Wilmington Ave / I-405 NB Ramp	B	18.4	0.420	B	18.4	0.420	+ 0.001 D/V
# 2	Wilmington Ave / I-405 SB Ramp	B	15.7	0.362	B	15.8	0.363	+ 0.063 D/V
# 4	Alameda Ave / I-405 NB Ramps	C	23.5	0.681	C	23.6	0.682	+ 0.038 D/V
# 9	I-405 SB Ramps / 223rd St	B	19.1	0.514	B	19.1	0.514	-0.002 D/V

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 Ops PM Tue Dec 2, 2014 13:55:46 Page 3-1

Tesoro Los Angeles Refinery
 Year 2020 With Project Operations
 PM Peak Hour

2020+Ops_PM.out

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

Intersection #1 Wilmington Ave / I-405 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.420

Loss Time (sec): 8 (Y+R=4.0 sec) Average Delay (sec/veh): 18.4

Optimal Cycle: 28 Level Of Service: B

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Permitted			Permitted			Permitted		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1		0	0	3	0	0	
	0	0	0	0	0	0	0	0	0	0	0	1

Volume Module:

Base Vol:	0	289	155	0	886	0	0	0	0	438	0	309
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	289	155	0	886	0	0	0	0	438	0	309
Added Vol:	0	0	1	0	0	0	0	0	0	0	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	289	156	0	886	0	0	0	0	438	0	309
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
PHF Volume:	0	305	164	0	934	0	0	0	0	462	0	326
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	305	164	0	934	0	0	0	0	462	0	326
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	305	164	0	934	0	0	0	0	462	0	326

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	1.00	0.91	1.00	1.00	1.00	1.00	0.59	1.00	0.85
Lanes:	0.00	2.00	1.00	0.00	3.00	0.00	0.00	0.00	0.00	2.00	0.00	1.00
Final Sat.:	0	3610	1615	0	5187	0	0	0	0	2234	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.08	0.10	0.00	0.18	0.00	0.00	0.00	0.00	0.21	0.00	0.20
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.43	0.43	0.00	0.43	0.00	0.00	0.00	0.00	0.49	0.00	0.49
Volume/Cap:	0.00	0.20	0.24	0.00	0.42	0.00	0.00	0.00	0.00	0.42	0.00	0.41
Delay/Veh:	0.0	17.9	18.4	0.0	20.1	0.0	0.0	0.0	0.0	16.5	0.0	16.5
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	17.9	18.4	0.0	20.1	0.0	0.0	0.0	0.0	16.5	0.0	16.5
LOS by Move:	A	B	B	A	C	A	A	A	A	B	A	B
HCM2kAvgQ:	0	3	3	0	7	0	0	0	0	5	0	6

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA

2020 Ops PM Tue Dec 2, 2014 13:55:46

Page 4-1

Tesoro Los Angeles Refinery
Year 2020 With Project Operations
PM Peak Hour

Level Of Service Computation Report
2000 HCM Operations Method (Future Volume Alternative)

2020+Ops_PM.out

Intersection #2 Wilmington Ave / I-405 SB Ramps

```

*****
Cycle (sec):          100          Critical Vol./Cap.(X):          0.363
Loss Time (sec):      12 (Y+R=4.0 sec) Average Delay (sec/veh):      15.8
Optimal Cycle:        34          Level Of Service:          B
*****

```

```

Approach:      North Bound      South Bound      East Bound      West Bound
Movement:      L - T - R      L - T - R      L - T - R      L - T - R
-----|-----|-----|-----|
Control:        Permitted      Protected      Permitted      Permitted
Rights:         Include      Include      Include      Include
Min. Green:     0 0 0 0      0 0 0 0      0 0 0 0      0 0 0 0
Lanes:          0 0 2 1 1      2 0 3 0 0      0 1 0 1 0      0 0 0 0 0
-----|-----|-----|-----|

```

```

Volume Module:
Base Vol:       0 416 491 345 910 0 27 0 84 0 0 0
Growth Adj:     1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse:    0 416 491 345 910 0 27 0 84 0 0 0
Added Vol:      0 1 0 0 0 0 0 0 1 0 0 0
PasserByVol:    0 0 0 0 0 0 0 0 0 0 0 0
Initial Fut:    0 417 491 345 910 0 27 0 85 0 0 0
User Adj:       1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj:        0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98 0.98
PHF Volume:     0 426 502 353 930 0 28 0 87 0 0 0
Reduct Vol:     0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol:    0 426 502 353 930 0 28 0 87 0 0 0
PCE Adj:        1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj:        1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume:    0 426 502 353 930 0 28 0 87 0 0 0
-----|-----|-----|-----|

```

```

Saturation Flow Module:
Sat/Lane:       1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment:     1.00 0.84 0.84 0.92 0.91 1.00 0.75 0.95 0.75 1.00 1.00
Lanes:          0.00 2.00 2.00 2.00 3.00 0.00 1.00 0.00 1.00 0.00 0.00
Final Sat.:     0 3178 3178 3502 5187 0 1431 0 1431 0 0 0
-----|-----|-----|-----|

```

```

Capacity Analysis Module:
Vol/Sat:        0.00 0.13 0.16 0.10 0.18 0.00 0.02 0.00 0.06 0.00 0.00 0.00
Crit Moves:      ****      ****
Green/Cycle:    0.00 0.43 0.43 0.28 0.71 0.00 0.17 0.00 0.17 0.00 0.00 0.00
Volume/Cap:     0.00 0.31 0.36 0.36 0.25 0.00 0.11 0.00 0.36 0.00 0.00 0.00
Delay/Veh:      0.0 18.5 19.1 29.3 5.1 0.0 35.3 0.0 37.5 0.0 0.0 0.0
User DelAdj:    1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh:     0.0 18.5 19.1 29.3 5.1 0.0 35.3 0.0 37.5 0.0 0.0 0.0
LOS by Move:    A B B C A A D A D A A A
HCM2kAvgQ:      0 5 6 5 4 0 1 0 3 0 0 0
*****

```

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 Ops PM Tue Dec 2, 2014 13:55:46 Page 5-1

Tesoro Los Angeles Refinery
 Year 2020 With Project Operations
 PM Peak Hour

Level Of Service Computation Report
 2000 HCM Operations Method (Future Volume Alternative)

Intersection #4 Alameda Ave / I-405 NB Ramps

```

*****
Cycle (sec):          100          Critical Vol./Cap.(X):          0.682
Page 4

```

2020+Ops_PM.out

Loss Time (sec): 12 (Y+R=4.0 sec) Average Delay (sec/veh): 23.6
 Optimal Cycle: 57 Level Of Service: C

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Protected					Protected					Protected					Permitted				
Rights:	Include					Include					Include					Include				
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:	0	0	2	0	1	1	0	2	0	0	0	0	0	0	0	1	0	0	0	1

Volume Module:

Base Vol:	0	944	195	82	773	0	0	0	0	393	0	108
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	944	195	82	773	0	0	0	0	393	0	108
Added Vol:	0	0	0	0	0	0	0	0	0	1	0	0
PasserByVol:	0	0	0	0	0	0	0	0	0	0	0	0
Initial Fut:	0	944	195	82	773	0	0	0	0	394	0	108
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
PHF Volume:	0	982	203	85	804	0	0	0	0	410	0	112
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	982	203	85	804	0	0	0	0	410	0	112
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	982	203	85	804	0	0	0	0	410	0	112

Saturation Flow Module:

Sat/Lane:	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Adjustment:	1.00	0.95	0.85	0.95	0.95	1.00	1.00	1.00	1.00	0.77	1.00	0.85
Lanes:	0.00	2.00	1.00	1.00	2.00	0.00	0.00	0.00	0.00	1.00	0.00	1.00
Final Sat.:	0	3610	1615	1805	3610	0	0	0	0	1461	0	1615

Capacity Analysis Module:

Vol/Sat:	0.00	0.27	0.13	0.05	0.22	0.00	0.00	0.00	0.00	0.28	0.00	0.07
Crit Moves:	****			****			****			****		
Green/Cycle:	0.00	0.40	0.40	0.07	0.47	0.00	0.00	0.00	0.00	0.41	0.00	0.82
Volume/Cap:	0.00	0.68	0.31	0.68	0.48	0.00	0.00	0.00	0.00	0.68	0.00	0.08
Delay/Veh:	0.0	26.2	20.9	59.8	18.4	0.0	0.0	0.0	0.0	27.3	0.0	1.7
User DelAdj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
AdjDel/Veh:	0.0	26.2	20.9	59.8	18.4	0.0	0.0	0.0	0.0	27.3	0.0	1.7
LOS by Move:	A	C	C	E	B	A	A	A	A	C	A	A
HCM2kAvgQ:	0	14	4	4	9	0	0	0	0	11	0	1

Note: Queue reported is the number of cars per lane.

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA
 2020 Ops PM Tue Dec 2, 2014 13:55:46 Page 6-1

Tesoro Los Angeles Refinery
 Year 2020 With Project Operations
 PM Peak Hour

Level Of Service Computation Report 2000 HCM Operations Method (Future Volume Alternative)

Intersection #9 I-405 SB Ramps / 223rd St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.514
 Loss Time (sec): 16 (Y+R=4.0 sec) Average Delay (sec/veh): 19.1
 Optimal Cycle: 50 Level Of Service: B

2020+Ops_PM.out

Approach:	North Bound					South Bound					East Bound					West Bound				
Movement:	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R	L	-	T	-	R
Control:	Split Phase					Split Phase					Protected					Protected				
Rights:	Include					Include					Include					Include				
Min. Green:	0		0		0	0		0		0	0		0		0	0		0		0
Lanes:	0	0	1	0	0	1	0	0	1	0	2	0	2	1	0	1	0	2	1	0
Volume Module:																				
Base Vol:	3		6		3	128		2		37	860		817		18	4		355		79
Growth Adj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
Initial Bse:	3		6		3	128		2		37	860		817		18	4		355		79
Added Vol:	0		0		0	0		0		0	1		0		0	0		0		0
PasserByVol:	0		0		0	0		0		0	0		0		0	0		0		0
Initial Fut:	3		6		3	128		2		37	861		817		18	4		355		79
User Adj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
PHF Adj:	0.95	0.95	0.95			0.95	0.95	0.95			0.95	0.95	0.95			0.95	0.95	0.95		
PHF Volume:	3		6		3	135		2		39	908		862		19	4		374		83
Reduct Vol:	0		0		0	0		0		0	0		0		0	0		0		0
Reduced Vol:	3		6		3	135		2		39	908		862		19	4		374		83
PCE Adj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
MLF Adj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
FinalVolume:	3		6		3	135		2		39	908		862		19	4		374		83
Saturation Flow Module:																				
Sat/Lane:	1900		1900		1900	1900		1900		1900	1900		1900		1900	1900		1900		1900
Adjustment:	0.95	0.95	0.95			0.95	0.86	0.86			0.92	0.91	0.91			0.95	0.89	0.89		
Lanes:	0.25	0.50	0.25			1.00	0.05	0.95			2.00	2.94	0.06			1.00	2.45	0.55		
Final Sat.:	453		907		453	1805		84		1547	3502		5060		111	1805		4128		919
Capacity Analysis Module:																				
Vol/Sat:	0.01	0.01	0.01			0.07	0.03	0.03			0.26	0.17	0.17			0.00	0.09	0.09		
Crit Moves:	****					****					****					****				
Green/Cycle:	0.01	0.01	0.01			0.15	0.15	0.15			0.50	0.67	0.67			0.01	0.18	0.18		
Volume/Cap:	0.51	0.51	0.51			0.51	0.17	0.17			0.51	0.25	0.25			0.25	0.51	0.51		
Delay/Veh:	66.4	66.4	66.4			41.2	37.8	37.8			16.8	6.5	6.5			57.1	37.8	37.8		
User DelAdj:	1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00			1.00	1.00	1.00		
AdjDel/Veh:	66.4	66.4	66.4			41.2	37.8	37.8			16.8	6.5	6.5			57.1	37.8	37.8		
LOS by Move:	E	E	E			D	D	D			B	A	A			E	D	D		
HCM2kAvgQ:	1		1		1	4		1		1	10		4		4	0		5		5

Note: Queue reported is the number of cars per lane.																				

Traffix 7.9.0415 (c) 2007 Dowling Assoc. Licensed to MMA, LONG BEACH, CA