



Particulate Matter (PM) Emission Factors For Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Revised December 2021

This document provides emission factors for estimating **total suspended particulate matter (PM) emissions (not PM₁₀)** for **individual** emission source at aggregate (sand and gravel), brick and tile, hot mix asphalt, cement, concrete batch plants. These factors are also applicable to emission sources other than processes identified in recently adopted Rules 1156 and 1157.

The factors and equations are extracted from the US EPA AP-42 document. Some of the complex equations are simplified with either default settings or assumptions that are applicable to the conditions and operations existing in the South Coast Air Basin as shown in the Reference column of the attached table. Emission factors with an asterisk (*) are not published in the EPA AP-42. These emission factors are determined using the agreed control efficiencies that were established during rule development and also are listed in the Reference column.

Facility is encouraged to apply specific parameters that are applicable to its operations to calculate emissions from the equipment/processes including the results from approved source tests and efficiencies of the add-on control equipment. Supporting documents must be submitted with the annual emission report to show the use of such parameters or source test results in calculating annual emissions.

In the absence of specific parameters and/or source tests, facility can calculate its annual emissions using the factors provided in the attached table and the following equation.

$$E = TP \times EF$$

Where: E = Emission (tons/year)
TP = Annual Throughput
EF = Emission Factor

The unit for TP in this equation must be consistent with the unit of EF. For example, if EF is in pound per ton of material transferred (lbs. /ton), then TP must be tons of transferred material. For unique emission sources, additional data must be used in determining the factor (EF or TP) before it can be used in emission calculation as discussed in the following notes:

Note 1: For mining/quarrying, **emission factor** is expressed in pound per blast (lbs. /blast) for TSP (Total Suspended Particulate) $\leq 30 \mu\text{m}$ and is calculated as:

$$EF = 0.000014 \times A^{1.5}$$

Where: A = Total horizontal blasted area in squared foot (ft²), provided that the blast depth is less than 70 ft. Not for vertical face of a bench.

Reference: EPA, AP-42, Table 11.9-1, July 1998

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

In this case, the throughput (TP) is number of blast per year.

Note 2: For road emissions (E) caused by vehicle traffic, the **throughput** is expressed in annual vehicle miles traveled (VMT) as follows:

$$TP = VMT = \text{Road Length} \times \left(\frac{\# \text{ Truck Trips}}{\text{Day}} \right) \times \left(\frac{\# \text{ Days}}{\text{Year}} \right) \times \left(\frac{1 \text{ Mile}}{5,280 \text{ ft}} \right)$$

Where: Road Length = One-way distance in feet (ft.) of paved or unpaved road within the facility, used by haul trucks and non-haul trucks.

Truck Trips = the number of roundtrips the vehicle made.

Definitions: Haul Road: an unpaved road used by haul trucks to carry materials from the quarry to different locations within the facility.

Non-Haul Road: unpaved and/or paved road used by non-haul trucks to carry materials from one location to another location within the facility, usually between the facility's entrance/exit to loading/unloading/processing areas.

Note 3: In addition to PM emissions, VOC emissions are also expected from asphalt product during loading out and silo filling operations. **Emission factor** (lbs. /ton of product loaded) is expressed in as follows:

ASPHALT LOAD-OUT (Drum Mix or Batch Mix Plant)

$$EF_{PM} = 0.000181 + 0.00141(-V)e^{((0.0251) \times (T+460) - 20.43)}$$

$$EF_{VOC} = 0.0172(-V)e^{((0.0251) \times (T+460) - 20.43)}$$

Reference: EPA, AP-42, Table 11.1-14, March 2004

SILO FILLING

$$EF_{PM} = 0.000332 + 0.00105(-V)e^{((0.0251) \times (T+460) - 20.43)}$$

$$EF_{VOC} = 0.0504(-V)e^{((0.0251) \times (T+460) - 20.43)}$$

Reference: EPA, AP-42, Table 11.1-14, March 2004

Where: V = Asphalt Volatility (in negative %); (Default: -0.5%)

T = Asphalt Product Mix Temperature (degree F); (Default: 325 °F)

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Operation/Emission Sources	Emission Factor		Unit	References And Assumptions
	UNCONTROLLED	<u>CONTROLLED</u>		
<p><u>ROAD EMISSIONS FROM VEHICLE TRAFFIC</u></p> <ul style="list-style-type: none"> PAVED ROAD $E = VMT \times k \times (sL)^a \times (W)^b$ <p>Where:</p> <p>E = PM emissions</p> <p>TP = VMT = annual vehicle mile traveled (see Note 2)</p> $EF = k \times (sL)^a \times (W)^b$ <p>k = particle size multiplier a, b = constants sL = road surface silt loading (g/m²) W = average weight (tons) of the vehicle</p>	<p>Aggregate / Crushed Material Plants</p> <p>EF = 7.56</p> <p><u>EF = 1.51*</u></p> <p>Hot Mix Asphalt Plants</p> <p>EF = 10.49</p> <p><u>EF = 2.10*</u></p> <p>Concrete Batching</p> <p>EF = 2.18</p> <p><u>EF = 0.44*</u></p> <p>Cement/Other Plants</p> <p>EF = 1.81</p> <p><u>EF = 0.36*</u></p>	<p>lb/VMT</p> <p>lb/VMT</p> <p>lb/VMT</p>	<p>AP-42, Jan 2011</p> <p>Chapter 13.2.1.3, Equation 1</p> <p>Assumptions:</p> <p>k = 0.011, a = 0.91, b = 1.02</p> <p>W_{Loaded} = 30 tons</p> <p>W_{Unloaded} = 5 tons</p> <p>W_{Unloaded for concrete Batching} = 12 tons</p> <p>Aggregate / Crushed Material</p> <p>sL = 53 g/m² [Table 13.2.1-3]</p> <p>Hot Mix Asphalt</p> <p>sL = 76 g/m² [Table 13.2.1-3]</p> <p>Cement / Concrete / Others</p> <p>sL = 11 g/m² [Table 13.2.1-3]</p> <p>Control Efficiency for chemical stabilizer = 80%</p>	

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Operation/Emission Sources	Emission Factor		Unit	References And Assumptions
	UNCONTROLLED	<u>CONTROLLED</u>		
<p>• UNPAVED ROAD</p> $E = VMT \times k \times \left(\frac{S}{12}\right)^a \times \left(\frac{W}{3}\right)^b$ <p>Where: E = PM emissions TP = VMT = annual vehicle mile traveled (see Note 2)</p> $EF = k \times \left(\frac{S}{12}\right)^a \times \left(\frac{W}{3}\right)^b$ <p>k = particle size multiplier a, b = constants S = surface material silt content (%) W = average weight (tons) of the vehicle</p>	<p>Aggregate Plants</p> <p>HAUL VEHICLE</p> <p>EF = 16.82</p> <p>NON-HAUL VEHICLE</p> <p>EF = 9.54</p> <p>Other Plant</p> <p>HAUL VEHICLE</p> <p>EF = 15.08</p> <p>NON-HAUL VEHICLE</p> <p>EF = 5.71</p>	<p><u>EF = 3.36*</u></p> <p><u>EF = 1.91*</u></p> <p><u>EF = 3.02*</u></p> <p><u>EF = 1.14*</u></p>	<p>lb/VMT</p> <p>lb/VMT</p> <p>lb/VMT</p> <p>lb/VMT</p>	<p>AP-42, Nov 2006</p> <p>Assumptions: [Table 13.2.2-2] k = 4.9, a = 0.7, b = 0.45</p> <p>HAUL</p> <p>W_{Loaded} = 120 tons W_{Unloaded} = 45 tons</p> <p>S_{Aggregate} = 8.3% [Table 13.2.2-1] S_{Others} = 7.1% [Table 13.2.2-1]</p> <p>NON-HAUL</p> <p>W_{Loaded} = 30 tons W_{Unloaded} = 5 tons</p> <p>S_{Aggregate} = 10% [Table 13.2.2-1] S_{Others} = 4.8 % [Table 13.2.2-1]</p> <p>Control Efficiency for chemical stabilizer = 80%</p>

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Operation/Emission Sources	Emission Factor		Unit	References And Assumptions
	UNCONTROLLED	<u>CONTROLLED</u>		
<p><u>OPEN STORAGE PILE</u> TP = annual tonnage of material stored Emissions include wind erosion, vehicle traffic in vicinity of storage piles, and material handling</p>	Active EF = 0.42	<u>EF = 0.042*</u>	lb/ton	AP-42, Chapter 11.19.1, Sand and Gravel Processing Final Report, Table 4-1, April 1995 Control Efficiency = 90% (page 2-13)
	Inactive EF = 0.11	<u>EF = 0.011*</u>	lb /ton	
	Active/Inactive EF = 0.33	<u>EF = 0.033*</u>	lb/ton	
<p><u>MINING/QUARRYING</u></p> <ul style="list-style-type: none"> DRILLING TP = number of hole drilled BLASTING (see Note 1) TP = number of blast 	EF = 1.3		lb/hole	AP-42, July 1998 Chapter 11.9, Table 11.9-4
	EF = 0.000014 (A) ^{1.5} for TSP ≤ 30 μm		lb /blast	Chapter 11.9, Table 11.9-1

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Operation/Emission Sources	Emission Factor		Unit	References And Assumptions
	UNCONTROLLED	<u>CONTROLLED</u>		
<p><u>LOADING / UNLOADING</u></p> <ul style="list-style-type: none"> • CONVEYOR TRANSFER POINT For a system of multiple transfer points, this EF must be multiplied by the number of transfer points (where materials drop from one point to another). Refer to Rule 1157 definition for more detail. • WEIGHT HOPPER / SURGE BIN • SILOS <ul style="list-style-type: none"> Cement Cement Supplements (Fly Ash) 	<p>Aggregate/Crushed Miscellaneous Base/ Asphalt Plants</p> <p>EF = 0.003</p>	<p><u>EF = 0.00014</u></p>	lb /ton	<p>AP-42, Aug 2004 Chapter 11.19.2, Table 11.19.2-2 (controlled by wet suppression)</p>
	<p>Concrete Batching and Others</p> <p>SAND:</p> <p>EF = 0.0021</p>	<p><u>EF = 0.00011*</u></p>	lb /ton	<p>AP-42, June 2006 Chapter 11.12, Table 11.12-2 Control Efficiency = 95%</p>
	<p>AGGREGATE:</p> <p>EF = 0.0069</p>	<p><u>EF = 0.00035*</u></p>	lb /ton	<p>AP-42, June 2006 Chapter 11.12, Table 11.12-2 Control Efficiency = 95% Chapter 11.12, Table 11.12-2</p>
	<p>EF = 0.0048</p>	<p><u>EF = 0.00024*</u></p>	lb /ton	<p>AP-42, June 2006 Chapter 11.12, Table 11.12-2 Control Efficiency = 95%</p>
	<p>EF = 0.73</p>	<p><u>EF = 0.00099</u></p>	lb/ton	<p>Chapter 11.12, Table 11.12-2</p>
	<p>EF = 3.14</p>	<p><u>EF = 0.0089</u></p>	lb /ton	

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Operation/Emission Sources	Emission Factor		Unit	References And Assumptions
	UNCONTROLLED	<u>CONTROLLED</u>		
<ul style="list-style-type: none"> • CONCRETE LOADING (Truck Mix) 	EF = 1.118	<u>EF = 0.098</u>	lb /ton	Chapter 11.12, Table 11.12-2
<ul style="list-style-type: none"> • CONCRETE LOADING (Central Mix) 	EF = 0.572	<u>EF = 0.0184</u>	lb /ton	Chapter 11.12, Table 11.12-2
<ul style="list-style-type: none"> • ASPHALT PRODUCTS LOAD OUT (see Note 3) 	PM: <u>EF = 0.00052</u> Organic PM (for TAC estimates): EF: <u>0.00034</u> VOC: <u>EF = 0.0042</u>		lb /ton lb /ton lb /ton	Chapter 11.1, Table 11.1-14 V=-0.5, T=325 °F TAC emissions should be estimated using AP-42, 3/2004 Tables 11.1-15 and 11.1-16
<ul style="list-style-type: none"> • ASPHALT SILO FILLING (see Note 3) 	PM: <u>EF = 0.00059</u> Organic PM (for TAC estimates): EF: <u>0.00025</u> VOC: <u>EF = 0.0122</u>		lb /ton lb /ton lb /ton	Chapter 11.1, Table 11.1-14 V=-0.5, T=325 °F TAC emissions should be estimated using AP-42, 3/2004 Tables 11.1-15 and 11.1-16

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Operation/Emission Sources	Emission Factor		Unit	References And Assumptions
	UNCONTROLLED	<u>CONTROLLED</u>		
<u>CRUSHING</u>				
<ul style="list-style-type: none"> • SECONDARY SCREENING and Crushing 	EF = 0.014*	<u>EF = 0.00031</u>	lb/ton	AP-42, Jan 1995 Chapter 11.6, Table 11.6-4 (controlled by fabric filter)
<ul style="list-style-type: none"> • TERTIARY CRUSHER 	EF = 0.0054	<u>EF = 0.0012</u>	lb /ton	AP-42, Aug 2004 Control Efficiency = 97.8% Chapter 11.19.2, Table 11.19.2-2 (controlled by wet suppression)
<ul style="list-style-type: none"> • FINE CRUSHER 	EF = 0.039	<u>EF = 0.003</u>	lb /ton	Chapter 11.19.2, Table 11.19.2-2 (controlled by wet suppression)
<u>SCREENING</u>				
<ul style="list-style-type: none"> • COARSE 	EF = 0.025	<u>EF = 0.0022</u>	lb /ton	AP-42, Aug 2004 Chapter 11.19.2, Table 11.19.2-2 (controlled by wet suppression)
<ul style="list-style-type: none"> • FINE 	EF = 0.30	<u>EF = 0.0036</u>	lb /ton	Chapter 11.19.2, Table 11.19.2-2 (controlled by wet suppression)
<ul style="list-style-type: none"> • SAND 	EF = 0.21*	<u>EF = 0.0083</u>	lb /ton	AP-42, Nov 1995 Chapter 11.19.1, Table 11.19.1-1 (controlled by venturi scrubber) Control Efficiency = 96.1%

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Operation/Emission Sources	Emission Factor		Unit	References And Assumptions
	UNCONTROLLED	<u>CONTROLLED</u>		
<u>GRINDING</u>	EF = 8.5	<u>EF = 0.0062</u>	lb/ton	AP-42, Aug 1997 Chapter 11.3, Table 11.3-2 (controlled by fabric filter)
<u>CEMENT MILLING</u>				
• Raw Mill	EF = 1.2*	<u>EF = 0.012</u>	lb/ton	AP-42, Jan 1995
• Finish Grinding Mill	EF = 0.8*	<u>EF = 0.008</u>	lb/ton	Chapter 11.6, Table 11.6-4 (controlled by fabric filter) Control Efficiency = 99%
<u>OTHER PROCESS/EQUIPMENT</u>				
• DRYER SAND and GRAVEL	EF = 2.0	<u>EF = 0.039</u>	lb /ton	AP-42, Nov 1995 Chapter 11.19.1, Table 11.19.1-1 (controlled by wet scrubber)
BATCH MIX ASPHALT	EF = 32	<u>EF = 0.042</u>	lb /ton	AP-42, Mar 2004 Chapter 11.1, Table 11.1-1 (controlled by fabric filter)
DRUM MIX ASPHALT	EF = 28	<u>EF = 0.033</u>	lb /ton	Chapter 11.1, Table 11.1-3 (controlled by fabric filter)
BRICK MANUFACTURING	EF = 0.187		lb /ton	Chapter 11.3., Table 11.3-1

Particulate Matter (PM) Emission Factors for Processes/Equipment at Asphalt, Cement, Concrete, and Aggregate Product Plants

Operation/Emission Sources	Emission Factor		Unit	References And Assumptions
	UNCONTROLLED	<u>CONTROLLED</u>		
KILNS				
<ul style="list-style-type: none"> • BRICK (natural gas fueled) 	EF = 0.96		lb/ton	AP-42, Aug 1997 Chapter 11.3., Table 11.3-1
<ul style="list-style-type: none"> • CEMENT, DRY PROCESS 	EF = 109*	<u>EF = 1.09</u>	lb/ton	Chapter 11.6, Table 11.6-2 (controlled by fabric filter)
<ul style="list-style-type: none"> • CLINKER COOLER 	EF = 14.7 *	<u>EF = 0.147</u>	lb/ton	Chapter 11.6, Table 11.6-2 (controlled by fabric filter) Control Efficiency = 99%