BOARD MEETING DATE: June 6, 2025 AGENDA NO. 29

PROPOSAL: Determine That Proposed Amended Rule 1171 – Solvent Cleaning

Operations, Is Exempt from CEQA; and Amend Rule 1171

SYNOPSIS: Rule 1171 establishes VOC limits for commercial and industrial

cleaning materials. The California Office of Environmental Health

Hazard Assessment determined that two compounds, para-Chlorobenzotrifluoride (pCBtF) and *tert*-Butyl Acetate (t-BAc), have carcinogenic health effects. Both pCBtF and t-BAc are used in some solvent cleaning materials. Proposed Amended Rule 1171 (PAR 1171) includes a future effective prohibition for cleaning solvents formulated with pCBtF and t-BAc, allows for products in the supply chain to continue to be sold and used for specified periods of time, and includes alternative compliance options for certain cleaning activities. PAR 1171 also addresses the AB 617 South Los Angeles Community Emission Reduction Plan air quality objectives related to solvent cleaning materials used for the cleaning of automotive refinishing coating spray equipment by

phasing out pCBtF and t-BAc.

COMMITTEE: Stationary Source, April 18, 2025, Reviewed

RECOMMENDED ACTIONS:

Adopt the attached Resolution:

- 1. Determining that Proposed Amended Rule 1171 Solvent Cleaning Operations, is exempt from the requirements of the California Environmental Quality Act; and
- 2. Amending Rule 1171 Solvent Cleaning Operations.

Wayne Nastri Executive Officer

Background

Rule 1171 – Solvent Cleaning Operations was adopted on August 2, 1991. It has been amended ten times, with the most recent amendment in 2009. Rule 1171 establishes requirements to reduce VOC emissions, toxic air contaminants, and stratospheric ozone-depleting compounds from the use of solvent cleaning materials that are used as part of a solvent cleaning operation at a business. The rule includes five primary categories of solvent cleaning activities with VOC limits and applies to any person who uses solvent materials in solvent cleaning operations during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas within South Coast AQMD. The rule also applies to all persons who store and dispose of solvent cleaning materials used in solvent cleaning operations, and all solvent suppliers who supply, sell, or offer for sale solvent cleaning materials for use in solvent cleaning operations within the South Coast AQMD.

To reduce the VOC emissions from solvent cleaning materials and activities, many cleaning solvent manufacturers have relied on the use of aqueous or water-based options or using solvents that are exempt from the definition of a VOC due to their low photochemical reactivity and, therefore, do not significantly contribute to the formation of ground-level ozone. In April 2017, the Stationary Source Committee recommended a precautionary approach when considering exempt compounds with a potential toxic endpoint and removing the exempt status for any compound that has an established toxic endpoint. In 2018 and 2020, respectively, the California Office of Environmental Health Hazard Assessment (OEHHA) determined that two exempt compounds, parachlorobenzotrifluoride (pCBtF) and tert-butyl acetate (t-BAc), have carcinogenic toxic endpoints.

Proposed Amended Rule 1171 (PAR 1171) partially implements Control Measure CTS-01 – Further Emission Reductions from Coatings, Solvents, Adhesives, and Lubricants of the 2022 AQMP, which seeks VOC emission reduction where feasible while making the effort to eliminate the toxic impact of pCBtF and t-BAc used in coatings and solvents. Furthermore, during the development of the Assembly Bill 617 (AB 617) Community Emission Reduction Plan (CERP) for South Los Angeles (SLA), community members expressed concern about the impacts from autobody shops, many of which are located close to residents and can be clustered within the community. PAR 1171 addresses the SLA CERP air quality objectives related to solvent cleaning materials used for the cleaning of automotive refinishing coating spray equipment by phasing out pCBtF and t-BAc.

Proposed Amendments

The two primary amendments to PAR 1171 are: 1) phasing-out and prohibiting the use of pCBtF and t-BAc, and 2) addressing stakeholder concerns regarding the availability of certain aerosolized alcohol cleaning solvents needed to clean critical equipment at water and electricity distribution facilities.

Regarding phasing out pCBtF and t-BAc from cleaning solvents, industry stakeholders commented that pCBtF and t-BAc are not used extensively for solvent cleaning and viable alternatives are readily available; therefore, the rule includes a shorter timeline prior to the prohibition taking effect. The effective date for the prohibition will be January 1, 2026; meaning, no solvent cleaning materials containing pCBtF and t-BAc, that are manufactured after January 1, 2026, can be manufactured for use in South Coast AQMD. PAR 1171 allow products in the supply chain to be sold until July 1, 2027, and products at facilities to be used until July 1, 2028.

Stakeholders from the water and electricity distribution industry have expressed concerns about the ability to purchase aerosol isopropyl alcohol and denatured alcohol, the cleaning solvents specified by the equipment manufacturers for cleaning chemically sensitive equipment such as electrical circuit breaker components and UV disinfection equipment. To address these concerns, PAR 1171 will allow for the limited use of liquid alcohol cleaning materials, instead of being restricted to using aerosolized alcohol cleaning materials, for specific equipment used at electricity and water distribution facilities. The industry has relied on the aerosol exemption to clean specific equipment, but the aerosolized alcohol solvents are not always available. PAR 1171 would allow the limited use of liquid alcohols and include Product Weighted – Maximum Incremental Reactivity VOC limits, in grams of ozone produced per grams of VOC emitted (g O₃/g VOC), to ensure the cleaning solvents used do not result in more ozone generation than the aerosolized isopropyl and denatured alcohol cleaners currently used.

PAR 1171 also addresses stakeholders' concerns for cleaning energy-curing lamps and reflectors used in the printing industry. Solvent cleaning materials used to clean energy curable ink application equipment have been subject to a 100 g/L VOC limit since 2010; however, facilities have indicated that use of these cleaning materials resulted in residue being left on the energy curing lamps and reflectors. The equipment manufacturers recommend that energy-curing lamps and reflectors be cleaned with a cloth and an alcohol-based cleaner. To allow this cleaning activity, PAR 1171 includes an 800 g/L VOC limit for the cleaning of energy-curing lamps and reflectors. This cleaning activity is infrequent and uses a small quantity of solvent when compared to the cleaning of other ink application equipment used in the printing industry.

Another printing industry concern that is addressed pertains to the cleaning of energy curable, lithographic, and screen printing equipment, which currently requires solvent cleaning materials to meet a 100 g/L VOC limit. This limit has been in place for over 15 years; however, some facilities requested an equivalent Maximum Incremental Reactivity limit be established to allow for formulation flexibility and address shortcomings of compliant solvent cleaning materials. PAR 1171 includes an alternative Product Weighted – Maximum Incremental Reactivity VOC limit of 0.70 g O₃/g VOC for energy curable, lithographic, and screen printing solvent cleaning activities.

The proposed amendment also includes another alternative Product Weighted – Maximum Incremental Reactivity VOC limit of 0.38 g O₃/g VOC for *any* solvent cleaning activity. That limit is equivalent to the general 25 g/L VOC limit and is proposed to allow for some formulation flexibility.

Other proposed changes include lowering the usage limits for non-compliant aerosol solvent cleaning products, adding new definitions, removing outdated rule provisions, and updating rule provisions for clarity.

Public Process

PAR 1171 was developed through a public process. Staff held three Working Group Meetings on: January 16, 2024, May 29, 2024, and February 26, 2025. The Working Group Meetings included a variety of stakeholders such as solvent manufacturers and affected facilities including public water and electricity utilities and industry associations, public agencies, and environmental and community groups. In addition, staff held a Public Workshop on March 28, 2025. As part of this rule development process, staff also met with individual stakeholders and conducted site visits at facilities subject to this rule.

Emission Reductions

PAR 1171 will phase out the use of two toxic exempt solvents, pCBtF and t-BAc, without increasing VOC emissions. Staff evaluated if any VOC limits for cleaning materials could be lowered, but did not identify any lower-VOC cleaning materials that could replace existing cleaning materials. As a result, all of the VOC limits will remain the same other than the carve out that allows for the use of alcohol to clean energy curing lamps and reflectors used in energy curable printing systems. The usage will be small and is not anticipated to increase VOC emissions. PAR 1171 also allows for the use of liquid alcohol for cleaning at the utilities; however, this change will not result in an increase in emissions as the cleaning is currently performed using the same solvent, but in aerosol form. Lastly, the usage allowance for aerosol solvent cleaning products that exceed the Rule 1171 VOC limits have been reduced for solvent cleaning activities other than automotive throttle body cleaning performed at automotive repair facilities.

Key Issues

Throughout the rule development process, staff worked with stakeholders to address, clarify, and resolve key issues, but two key issues remain. A stakeholder opposes the addition of new requirements for recordkeeping, reporting, and labeling provisions and stakeholders have requested an exemption for liquid alcohol usage limits proposed for cleaning UV light disinfection equipment at water agencies.

Opposition for New Recordkeeping, Reporting, and Labeling Requirements

An industry stakeholder is opposed to recordkeeping, reporting and labeling requirements, and claims that they are too burdensome, unnecessary, and a disincentive to use low-VOC materials. Most of the recordkeeping requirements in PAR 1171 are

not new, the rule was reorganized for clarity and the recordkeeping provisions were compiled into a new recordkeeping subdivision. The recordkeeping requirements rely on compliance with Rule 109 – Recordkeeping for Volatile Organic Compound Emissions requirements which allow for minimal recordkeeping for super-compliant VOC coatings, defined as coatings containing 50 grams or less of VOC per liter (g/L) of material, to encourage the sale and use of low VOC products. Minimal recordkeeping is crucial to demonstrate compliance with permit conditions and rule requirements. Furthermore, U.S. EPA commented in recent rulemakings that the lack of consistent recordkeeping for all sources is a potential SIP deficiency subject to disapproval. In addition, recordkeeping requirements are necessary for all solvent cleaning materials including low-VOC cleaners because proper recordkeeping provides compliance information to ensure operators are using VOC compliant solvent cleaning materials and are operating within usage limits provided in the rule and permit conditions. In response to concerns with any new recordkeeping, some provisions were removed that would not have already been required under Rule 109 or for rule compliance purposes.

PAR 1171 proposes minor additions to recordkeeping requirements, including repair records for remote reservoir cleaning systems and basic recordkeeping requirements for solvent cleaning material suppliers. Rule 1171 currently requires that remote reservoir cleaning systems be repaired within one calendar day if any liquid leaks, visible tears, or cracks are detected. The added recordkeeping requirement ensures that this requirement is enforceable. PAR 1171 does not propose any new reporting requirements. The added labeling requirement in PAR 1171 is only applicable to solvent cleaning material manufacturers that opt to comply with the proposed alternative Product Weighted – Maximum Incremental Reactivity VOC limits.

Exemption to Clean UV Light Disinfection Equipment

Public water agencies requested the proposed usage limits and ability to use liquid alcohol to clean UV light disinfection equipment. Staff collaborated with multiple large public water agencies, including the Los Angeles Department of Water and Power (LADWP) and Metropolitan Water District (MWD), to reach a consensus on feasible usage limits and Product Weighted – Maximum Incremental Reactivity-based VOC limits that allow the use of recommended cleaning solvents. Staff does not support a total exemption, as that could lead to potential backsliding of emissions.

California Environmental Quality Act

Pursuant to CEQA Guidelines Sections 15002(k) and 15061, the proposed project (PAR 1171) is exempt from CEQA pursuant to CEQA Guidelines Sections 15061(b)(3) and 15308. Further, there is no substantial evidence indicating that the exceptions set forth in CEQA Guidelines Section 15300.2 apply to the proposed project. A Notice of Exemption has been prepared pursuant to CEQA Guidelines Section 15062, and if the proposed project is approved, the Notice of Exemption will be filed with the county clerks of Los Angeles, Orange, Riverside, and San Bernardino counties, and with the State Clearinghouse of the Governor's Office of Planning and Research.

Socioeconomic Impact Assessment

The proposed amendments to Rule 1171 to phase out the use of pCBtF and t-BAc will not result in adverse socioeconomic impacts since there are existing cleaning materials that do not include these toxic solvents and will not require reformulations. The proposed amendments will not significantly affect air quality or emission limitations as there are no decreases in VOC limits, and the one small carve out for a higher VOC limit is to clean energy curable lamps and reflectors that do not require frequent cleaning and are in a small area. Therefore, a socioeconomic impact assessment is not required by Health and Safety Code Sections 40440.8 and 40728.5.

AQMP and Legal Mandates

Pursuant to Health and Safety Code Section 40460(a), South Coast AQMD is required to adopt an AQMP demonstrating compliance with all federal regulations and standards. South Coast AQMD is required to adopt rules and regulations that carry out the objectives of the AQMP. PAR 1171 partially implements the 2022 AQMP Control Measure CTS-01 by not increasing VOC emissions while phasing out pCBtF and t-BAc and achieves the objectives set forth by the AB 617 CERP for the SLA community.

Resource Impacts

Existing staff resources are adequate to implement the proposed amended rule. PAR 1171 includes prohibition and phase out timelines for pCBtF and t-BAc without changing current VOC limits; therefore, the rule amendment is not anticipated to impact existing permits.

Attachments

- A. Summary of Proposal
- B. Key Issues and Responses
- C. Rule Development Process
- D. Key Contacts List
- E. Resolution
- F. PAR 1171
- G. Final Staff Report
- H. Notice of Exemption from CEQA
- I. Board Presentation

ATTACHMENT A SUMMARY OF PROPOSAL

Proposed Amended Rule 1171 – Solvent Cleaning Operations

Purpose and Applicability

• Separates "Purpose and "Applicability" into two subdivisions to standardize rule structure.

Phase out of para-chlorobenzotrifluoride (pCBtF) and *tert*-butyl acetate (t-BAc):

Two exempt compounds have been determined to have toxic endpoints. PAR 1171 proposes to phase out those solvents as soon as practicable to reduce toxic exposure.

pCBtF and t-BAc Prohibition Schedule

- t-BAc was not identified in any solvent cleaning material formulations.
- Limited use of pCBtF was identified, commercially available non-pCBtF alternatives readily available.
- PAR 1171 transitions away from both solvents rapidly:
 - o Prohibition effective date: January 1, 2026;
 - o Sell-through end date: July 1, 2027;
 - o Use-through end date: July 1, 2028.

Emission Limits

- VOC Content Limit for Energy Curable Printing Lamps and Reflectors:
 - o Establishes VOC limit consistent with manufacturer cleaning recommendations.
- Alternative Usage Limits for Electricity and Water Equipment:
 - Establishes annual solvent cleaning material usage limits for electricity and water utility facilities based on current operations.
- Alternative Usage Limits for Aerosol Cleaning:
 - o Establishes monthly usage limits for facilities conducting specific solvent cleaning activities using aerosols.
- Alternative Product Weighted Maximum Incremental Reactivity VOC Limits
 - Establishes alternative Product Weighted Maximum Incremental Reactivity VOC limits to maintain ozone forming impact of the cleaning solvent used at electricity and water utility facilities at current levels.

Monitoring, Recordkeeping, and Reporting Requirements

• Establishes requirements for facilities or operators that use remote reservoir cleaners to maintain records of any repair of leaks, visible tears, or cracks of the remote reservoir.

Proposed Amended Rule 1171 – Solvent Cleaning Operations

• Establishes labeling requirements for solvent manufacturers opting to comply with the alternative Product Weighted – Maximum Incremental Reactivity VOC limits VOC limit.

Exemptions

- Clarifies that cleaning with aerosol products that comply with the VOC limits in Table 1 are exempt from the prohibition from atomizing solvent cleaners.
- Exempts specific solvent cleaning activities conducted at water and electricity utility facilities from the prohibition on atomizing solvent cleaners.
- Exempts the use of individually wrapped, saturated towelettes, during cable splicing activity for high voltage electrical cables.

ATTACHMENT B KEY ISSUES AND RESPONSES

Proposed Amended Rule 1171 – Solvent Cleaning Operations

Throughout the rule development process, staff worked with stakeholders to address and resolve key issues.

There are two remaining key issues: 1) A stakeholder opposes the addition of new requirements for recordkeeping, reporting and labeling provisions; 2) stakeholders have requested an exemption for liquid alcohol usage limits proposed for cleaning UV light disinfection equipment at water agencies.

PAR 1171 recordkeeping requirements rely on compliance with Rule 109 — Recordkeeping for Volatile Organic Compound Emissions requirements which allow for minimal recordkeeping for super-compliant VOC coatings, defined as coatings containing 50 grams or less of VOC per liter (g/L) of material, to encourage the sale and use of low VOC products. Minimal recordkeeping is needed to demonstrate compliance with permit conditions and rule requirements. Furthermore, U.S. EPA commented in recent rulemakings that the lack of consistent recordkeeping for all sources is a potential SIP deficiency subject to disapproval. In addition, recordkeeping requirements are necessary for all solvent cleaning materials including low-VOC cleaners because proper recordkeeping provides compliance information to ensure operators are using VOC compliant solvent cleaning materials and are operating within usage limits provided in the rule and permit conditions. In response to concerns with any new recordkeeping, some provisions were removed that would not have already been required under Rule 109 or for rule compliance purposes.

PAR 1171 proposes minor additions to recordkeeping requirements, including repair records for remote reservoir cleaning systems and basic recordkeeping requirements for solvent cleaning material suppliers. Rule 1171 currently requires that remote reservoir cleaning systems be repaired within one calendar day if any liquid leaks, visible tears or cracks are detected. The added recordkeeping requirement ensures that this requirement is enforceable. PAR 1171 does not propose any new reporting requirements. The added labeling requirement in PAR 1171 is only applicable to solvent cleaning material manufacturers that opt to comply with the proposed alternative Product Weighted – Maximum Incremental Reactivity VOC limits.

Public water agencies requested the proposed usage limits and ability to use liquid alcohol to clean UV light disinfection equipment. Staff collaborated with multiple large public water agencies, including the Los Angeles Department of Water and Power (LADWP) and Metropolitan Water District (MWD), to reach a consensus on feasible usage limits and Product Weighted – Maximum Incremental Reactivity-based VOC limits that allow the use of recommended cleaning solvents. Staff does not support a total exemption, as that could lead to potential backsliding of emissions.

ATTACHMENT C RULE DEVELOPMENT PROCESS

Proposed Amended Rule 1171 – Solvent Cleaning Operations

Initiated Rule Development December 2023 **Working Group Meetings (3)** January 16, 2024 May 29, 2024 February 26, 2025 75-Day Notice of Public Workshop March 13, 2025 **Public Workshop** March 28, 2025 **Stationary Source Committee Meeting** April 18, 2025 **Set Hearing** May 2, 2025 **30-Day Notice of Public Hearing** April 30, 2025 **Public Hearing**

Eighteen (18) months spent in rule development One (1) Public Workshop One (1) Stationary Source Committee Meeting Three (3) Working Group Meetings Ten (10) Stakeholder Meetings Three (3) Site Visits

June 6, 2025

ATTACHMENT D

KEY CONTACTS LIST

Proposed Amended Rule 1171 – Solvent Cleaning Operations

The	e Bo	eing	Com	banv
		01115	00111	Pari

California Council for Environmental and Economic Balance (CCEEB)

Clean Water SoCal

Communities for a Better Environment (CBE)

Construction Industry Air Quality Coalition (CIAQC)

Eastern Municipal Water District (EMWD)

Katy Wolf, Institute for Research and Technical Assistance

Household & Commercial Products Association (HCPA)

Independent Lubricant Manufacturers Association (ILMA)

International Ultraviolet Association (IUVA)

Los Angeles Department of Water and Power (LADWP)

Los Angeles Sanitation District (LASD)

Metropolitan Water District (MWD)

Printing United Alliance

RadTech International

Raymond Regulatory Resources (3R), LLC

Safety-Kleen

Southern California Edison (SCE)

W.M. Barr

ATTACHMENT E

RESOLUTION NO. 25-

A Resolution of the Governing Board of the South Coast Air Quality Management District (South Coast AQMD) determining that Proposed Amended Rule 1171 – Solvent Cleaning Operations, is exempt from the requirements of the California Environmental Quality Act (CEQA).

A Resolution of the South Coast AQMD Governing Board amending Rule 1171 – Solvent Cleaning Operations.

WHEREAS, the South Coast AQMD Governing Board finds and determines that Proposed Amended Rule 1171 is considered a "project" as defined by CEOA; and

WHEREAS, the South Coast AQMD has had its regulatory program certified pursuant to Public Resources Code Section 21080.5 and CEQA Guidelines Section 15251(l), and has conducted a CEQA review and analysis of the proposed project pursuant to such program (South Coast AQMD Rule 110); and

WHEREAS, the South Coast AQMD Governing Board finds and determines that after conducting a review of the proposed project in accordance with CEQA Guidelines Section 15002(k) – General Concepts, the three-step process for deciding which document to prepare for a project subject to CEQA, and CEQA Guidelines Section 15061 – Review for Exemption, procedures for determining if a project is exempt from CEQA, that Proposed Amended Rule 1171 is exempt from CEQA; and

WHEREAS, the South Coast AQMD Governing Board finds and determines that, Proposed Amended Rule 1171 is not expected to result in a change in VOC emissions relative to baseline conditions, and there are commercially available alternative compliant formulations that do not contain para-chlorobenzotrifluoride (pCBtF) and *tert*-butyl acetate (t-BAc) such that the sell-through and use-through provisions provide sufficient time to find suitable replacements which will prevent stranded assets and the generation of waste; therefore, it can be seen with certainty that the proposed project would not cause a significant adverse effect on the environment and as such, is exempt from CEQA pursuant to CEQA Guidelines Section 15061(b)(3) – Common Sense Exemption; and

WHEREAS, the South Coast AQMD Governing Board finds and determines that the proposed project is also categorically exempt from CEQA pursuant to CEQA Guidelines Section 15308 – Actions by Regulatory Agencies for Protection of the Environment, because Proposed Amended Rule 1171 is designed to further protect or enhance the environment by reducing the potential exposure to toxic chemicals; and

WHEREAS, the South Coast AQMD Governing Board has determined that there is no substantial evidence indicating that any of the exceptions set forth in CEQA Guidelines Section 15300.2 – Exceptions, apply to the proposed project; and

WHEREAS, the South Coast AQMD staff has prepared a Notice of Exemption for the proposed project, that is completed in compliance with CEQA Guidelines Section 15062 – Notice of Exemption; and

WHEREAS, Proposed Amended Rule 1171 and supporting documentation, including but not limited to, the Notice of Exemption and Final Staff Report, were presented to the South Coast AQMD Governing Board and the South Coast AQMD Governing Board has reviewed and considered this information, as well as has taken and considered staff testimony and public comment prior to approving the project; and

WHEREAS, the South Coast AQMD Governing Board finds and determines, taking into consideration the factors in Section (d)(4)(D) of the Governing Board Procedures (codified as Section 30.5(4)(D)(i) of the Administrative Code), that the modifications to Proposed Amended Rule 1171 since the Notice of Public Hearing was published are clarifications that meet the same air quality objective and are not so substantial as to significantly affect the meaning of Proposed Amended Rule 1171 within the meaning of Health and Safety Code Section 40726 because: 1) the removal of subparagraph (g)(2)(B) "Names and address of the supplier for each Solvent Cleaner used" is not necessary since the information can be determined based on the other records that the facility is required to keep; 2) the amended sell through and use through dates in paragraph (f)(4) from "January 1, 2027" to "July 1, 2027" and "January 1, 2028" to "July 1, 2028", respectively, will provide some additional time for solvent cleaner suppliers to sell and facilities to use any remaining solvent cleaning materials containing pCBtF and t-BAc; 3) the restructuring of paragraph (e)(5) was made for clarification; 5) the addition of energy curable in subparagraph (e)(5)(A) was to provide compliance flexibility for printing operations and will not increase VOC emissions; 6) the addition of subparagraph (h)(1)(D) "ASTM Standard Test Method E 1868 – Standard Test Method for Loss-On-Drying by Thermogravimetry" is to provide additional flexibility and accuracy when determining the VOC content of certain solvent cleaning materials; 7) the change from "letter press" to "letterpress" throughout the rule was made for consistency; 8) the change from "person" to "Person" throughout the rule was to correct a typo; 9) the deletion of "and" from "Cleaning of Ink Application Equipment" Category in Table 1 of paragraph (d)(1) was to correct a typo; 10) the change from "facility" to "Facility" throughout the rule was to correct a typo; and 11) the addition of "(e)(5)" to subparagraph (g)(2)(D) was to correct a reference; and: (a) the changes do not impact emission reductions, (b) the changes do not affect the number or type of sources regulated by the rule, (c) the changes are consistent with the information contained in the Notice of Public Hearing, and (d) the consideration of the range of CEQA alternatives is not applicable because the proposed project is exempt from CEQA; and

WHEREAS, Proposed Amended Rule 1171 will be submitted for inclusion into the State Implementation Plan; and

WHEREAS, Health and Safety Code Section 40727 requires that prior to adopting, amending, or repealing a rule or regulation, the South Coast AQMD Governing Board shall make findings of necessity, authority, clarity, consistency, non-duplication, and reference based on relevant information presented at the public hearing, in the rulemaking record, and in the Final Staff Report; and

WHEREAS, the South Coast AQMD Governing Board has determined that a need exists to amend Rule 1171 to prohibit the use of two solvents from solvent cleaning materials, pCBtF and t-BAc, that have been determined to have toxic endpoints, including potential carcinogenicity, by the Office of Environmental Health Hazard Assessment (OEHHA) and to partially implement the 2022 AQMP Control Measure CTS-01; and

WHEREAS, the South Coast AQMD Governing Board obtains its authority to adopt, amend or repeal rules and regulations from Health and Safety Code Sections 39002, 40000, 40001, 40440, 40441, 40702, 40725 through 40728.5, 40920.6, and 41508 as well as the federal Clean Air Act; and

WHEREAS, the South Coast AQMD Governing Board has determined that Proposed Amended Rule 1171 is written or displayed so that its meaning can be easily understood by the persons directly affected by it; and

WHEREAS, the South Coast AQMD Governing Board has determined that Proposed Amended Rule 1171 is in harmony with, and not in conflict with or contradictory to, existing statutes, court decisions, or state or federal regulations; and

WHEREAS, the South Coast AQMD Governing Board has determined that Proposed Amended Rule 1171 does not impose the same requirements as any existing state or federal regulations, and the proposed amended rule is necessary and proper to execute the powers and duties granted to, and imposed upon, the South Coast AQMD; and

WHEREAS, the South Coast AQMD Governing Board, in amending Rule 1171, references the following statutes which the South Coast AQMD hereby implements, interprets or makes specific: Health and Safety Code Sections 39002, 40000, 40001, 40406, 40702, 40440(a), 40725 through 40728.5, 40920.6, 41508 and federal Clean Air Act Sections 110, 172, and 182(e); and

WHEREAS, the South Coast AQMD Governing Board determines that Proposed Amended Rule 1171 does not significantly affect air quality or emission limitations; therefore, a socioeconomic impact assessment pursuant to Health and Safety Code Sections 40440.8 and 40728.5 is not required; and

WHEREAS, Health and Safety Code Section 40727.2 requires the South Coast AQMD to prepare a written analysis of existing federal air pollution control requirements applicable to the same source type being regulated whenever it adopts, or amends a rule, and that the South Coast AQMD's comparative analysis of Proposed Amended Rule 1171 is included in the Final Staff Report; and

WHEREAS, the South Coast AQMD staff conducted a Public Workshop regarding Proposed Amended Rule 1171 on March 28, 2025; and

WHEREAS, the Public Hearing has been properly noticed in accordance with the provisions of Health and Safety Code Sections 40725 and 40440.5; and

WHEREAS, the South Coast AQMD Governing Board has held a Public Hearing in accordance with all provisions of state and federal law; and

WHEREAS, the South Coast AQMD Governing Board specifies the Planning, Rule Development and Implementation Manager overseeing the development of Proposed Amended Rule 1171 as the custodian of the documents or other materials which constitute the record of proceedings upon which the adoption of this proposed project is based, which are located at the South Coast Air Quality Management District, 21865 Copley Drive, Diamond Bar, California; and

NOW, THEREFORE, BE IT RESOLVED, that the South Coast AQMD Governing Board does hereby determine, pursuant to the authority granted by law, that the proposed project is exempt from CEQA pursuant to CEQA Guidelines Section 15061(b)(3) – Common Sense Exemption. The South Coast AQMD Governing Board does also hereby determine, pursuant to the authority granted by law, that the proposed project is categorically exempt from CEQA pursuant to CEQA Guidelines Section 15308 – Actions by Regulatory Agencies for Protection of the Environment. No exceptions to the application of the categorical exemption as set forth in CEQA Guidelines Section 15300.2 – Exceptions, apply to the proposed project. This information was presented to the South Coast AQMD Governing Board, whose members exercised their independent judgement and reviewed, considered, and approved the information therein prior to acting on the proposed project; and

BE IT FURTHER RESOLVED, that the South Coast AQMD Governing Board does hereby adopt, pursuant to the authority granted by law, Proposed Amended Rule 1171 as set forth in the attached, and incorporated herein by reference; and

BE IT FURTHER RESOLVED, that the South Coast AQMD Governing Board requests that Proposed Amended Rule 1171 be submitted for inclusion in the State Implementation Plan; and

BE IT FURTHER RESOLVED, that the Executive Officer is hereby directed to forward a copy of this Resolution and Proposed Amended Rule 1171 to the

California Air Resources Board for approval a Environmental Protection Agency for inclusion	•
DATE:	CLERK OF THE BOARDS

ATTACHMENT F

(Adopted August 2, 1991)(Amended May 12, 1995)(Amended September 13, 1996) (Amended June 13, 1997)(Amended October 8, 1999)(Amended August 2, 2002) (Amended November 7, 2003)(Amended May 6, 2005)(Amended July 14, 2006) (Amended February 1, 2008)(Amended May 1, 2009)(Amended [Date of Rule Adoption])

[RULE INDEX TO BE ADDED AFTER RULE ADOPTION]

PROPOSED AMENDED RULE 1171. SOLVENT CLEANING OPERATIONS

(a) Purpose and Applicability

The purpose of this rule is to reduce emissions of volatile organic compounds (VOCs), toxic air contaminants, and stratospheric ozone-depleting compounds, or and global-warming compounds from the use, storage and disposal of solvent cleaning materials Solvent Cleaning Materials in solvent cleaning operations and activities Solvent Cleaning Operations or Solvent Cleaning Activities. A solvent cleaning operation is solvent cleaning conducted as part of a business. This rule applies to: all persons who use these solvent materials in solvent cleaning operations during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas; all persons who store and dispose of these materials used in solvent cleaning operations; and all solvent suppliers who supply, sell, or offer for sale solvent cleaning materials for use in solvent cleaning operations.

(b) Applicability

This rule is applicable to any Person who uses Solvent Cleaning Materials in Solvent Cleaning Operations or Solvent Cleaning Activities during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas as part of a business or public service within the South Coast AQMD. The rule shall also apply to all Persons who store and dispose of Solvent Cleaning Materials used in Solvent Cleaning Activities; and all Solvent Cleaner Suppliers who supply, sell, or offer for sale Solvent Cleaning Materials for use in Solvent Cleaning Operations or Solvent Cleaning Activities within the South Coast AQMD.

(b)(c) Definitions

For the purpose of this rule, the following definitions shall apply:

(1) AEROSOL PRODUCT <u>ismeans</u> a hand-held, non-refillable container <u>whichthat</u> expels pressurized product by means of a propellant-induced force. Aerosol Product does not include pump spray devices, which are

- packaging systems in which the product ingredients, or Solvent Cleaning Materials, are expelled only while a pumping action is applied to a button, trigger, or other actuator. Ingredients in a pump spray device are not under pressure.
- (2) APPLICATION EQUIPMENT is a means any device used to apply adhesive, coating, ink, or polyester resin materials.
- (3) APPLICATION LINE <u>ismeans</u> that portion of a motor vehicle assembly production line <u>whichthat</u> applies surface and other coatings to motor vehicle bodies, hoods, fenders, cargo boxes, doors, and grill opening panels.
- (4) ARCHITECTURAL COATING is any coating applied to stationary structures and their appurtenances, to mobile homes, to pavements, or to eurbs.
- (4) AUTOMOTIVE PART means any individual mechanical component that that is part of a vehicle that allows the vehicle to operate, including but not limited to, engine components, transmission components, suspension components, brake components, and intake system components.
- (5) BATTERY TERMINAL means the electrical contact or component of a battery that connects the battery to a charger, device, other battery, or external electrical circuit and transfers energy.
- (56) BLANKET ismeans a synthetic rubber mat used in offset-lithography to transfer or "offset" an image from a planographic printing plate to the paper or other substrate.
- (67) BLANKET WASH <u>ismeans</u> a <u>solventSolvent Cleaning Material</u> used to remove ink from the <u>blanket Blanket</u> of a <u>pressPress</u>.
- (8) CHLORINATION SYSTEM means a chlorine feed system used for the oxidation of microbiological material, organic compounds or inorganic compounds during the water or wastewater treatment process. Chlorine can be in the form of gaseous chlorine, sodium hypochlorite, or calcium hypochlorite.
- (7) CLEAN AIR SOLVENT is as defined in Rule 102.
- (8) CLEAN AIR SOLVENT CERTIFICATE is a certificate issued by the District to a manufacturer, distributor, or person for a specific product or class of products that meets the criteria for a Clean Air Solvent.
- (9) CURED COATING, CURED INK, OR CURED ADHESIVE is means a coating, ink, or adhesive, which that is dry to the touch, and that has

- undergone a chemical or physical process to achieve its final state and does not release volatile components under normal use conditions.
- (10) ELECTRICAL APPARATUS COMPONENTS is means an internal component such as wires, windings, stators, rotors, magnets, contacts, relays, energizers, and connections in an apparatus that generates or transmits electrical energy including, but not limited to: alternators, generators, transformers, electric motors, cables, and circuit breakers, except for the actual cabinet in which the components are housed. Electrical Apparatus Components also include Electrical electrical components of graphic arts application equipment and Hot-line Toolshot line tools are also included in this category.
- organizations that control energy transmission and distribution in California, including, but are not limited to, the Pacific Gas and Electric Company, the San Diego Gas and Electric Company, Southern California Edison, Los Angeles Department of Water and Power, the Imperial Irrigation District, and the Sacramento Municipal Utility District.
- (12) ELECTRICITY GENERATING FACILITY means
 - (A) A facility-Facility that is owned or operated by an investor-owned electric utility or a public-owned electric utility and has one or more electric generating units; or
 - (B) A facility Facility that has electric generating units for onsite use and or distribution in the state or local electrical grid system.
 - Electricity Generating Facility does not include facilities Facilities subject to Rule 1109.1 Emissions of Oxides of Nitrogen from Petroleum Refineries and Related Operations.
- (11) ELECTRON BEAM INK is an ink that dries by chemical reaction caused by high energy electrons.
- (1213) ELECTRONIC COMPONENT is means that portion an individual part of an assembly, including circuit card assemblies, printed wire assemblies, printed circuit boards, soldered joints, ground wires, bus bars, and other electrical fixtures, except for the actual cabinet in which the components are housed, that collectively perform functions essential for the operation of an electronic device.

<u>PAR</u> Rule 1171 (Cont.) Adoption])

- (14) EMISSION CONTROL SYSTEM means any combination of capture systems and control devices used to reduce VOC emissions.
- (15) ENERGY CURABLE INK means an ink that dries upon exposure to visible-light, ultra-violet light, or an electron beam.
- (1316) EXEMPT COMPOUND is as defined in Rule 102 Definition of Terms (Rule 102).
- (1417) FACILITY means a business, or businesses, or public service engaged in solvent cleaning operations Solvent Cleaning Operations and Solvent Cleaning Activities which that are owned or operated by the same person Person or persons and are located on the same or contiguous parcels.
- (1518) FLEXOGRAPHIC PRINTING <u>ismeans</u> the <u>printing</u> method in which the image area is raised relative to the non-image area and utilizes flexible rubber or other elastomeric plates and rapid drying liquid inks.
- (1619) FULL SERVICE SOLVENT PROVIDER is any person that provides both solvents and services to a solvent cleaning operation. Such services may include, but are not limited to, one or more of the following: filling or refilling solvent cleaning equipment with solvent, collection or pick up of customer's solvent-related waste stream, or cleaning equipment sales or rental.
- (1720) GENERAL WORK SURFACE ismeans an area of a medical device or pharmaceutical *facility* Facility where solvent cleaning is performed on work surfaces including, but not limited to, tables, countertops, and laboratory benches. General work surface Work Surface shall not include items defined under janitorial cleaning Janitorial Cleaning.
- (1821) GRAMS OF VOC PER LITER OF MATERIAL (ACTUAL VOC); ismeans the weight of VOC per volume of material and can be calculated by the following equation:

Grams of VOC per liter of material =

$$\frac{W_{sv} - W_w - W_{esex}}{V_m}$$

Where: $W_s W_v = W_s W_v$ = Weight of volatile compounds in gram-s (includes water, Exempt Compounds, and VOCs)

PAR Rule 1171 (Cont.) Adoption])

 $W_w = Weight of water in grams$

 $W_{es}W_{ex}$ = Weight of exempt compounds Exempt

Compounds in grams

 V_m = Volume of material in liters

(1922) GRAPHIC ARTS <u>aremeans</u> all gravure, letterpress, flexographic, and lithographic printing processes.

- (2023) GRAVURE PRINTING ismeans an intaglio process, which is a technique that involves etching or engraving wells into a roll or cylinder to create an image, in which the and then ink is carried in minutethe etched or engraved wells on a roll or cylinder and transferred to the printing substrate. The excess ink is removed from the surface by a doctor blade.
- (2124) HIGH PRECISION OPTIC <u>ismeans</u> an optical element used in an electrooptical device and is designed to sense, detect, or transmit light energy, including specific wavelengths of light energy and changes in light energy levels.
- (2225) HOT-LINE TOOL ismeans a specialized tool used primarily on the transmission systems, sub-transmission systems, and distribution systems for replacing and repairing circuit components or for other types of work with electrically energized circuits.
- (26) INK APPLICATION EQUIPMENT means any tool, machine, system, or component of any tool, machine, or system used to apply ink to a substrate.
- (2327) INKJET PRINTING ismeans a printing process in which images are formed by the precise placement of small (picoliter-sized) droplets of ink firedejected at high speedsvelocity from the nozzle(s) of computer-controlled printheads.
- (2428) JANITORIAL CLEANING ismeans the cleaning of building or *facility*Facility components including, but not limited to, floors, ceilings, walls, windows, doors, stairs, bathrooms, furnishings, and exterior surfaces of office equipment, and excludes the cleaning of work areas where manufacturing or repair activity is performed.
- (2529) LETTERPRESS PRINTING <u>ismeans</u> the <u>printing</u> method in which the image area is raised relative to the non-image area and the ink is transferred to the paper directly from the image surface.
- (2630) LIQUID LEAK is the means a visible liquid solvent leak from the a container at a rate of more than three (3) drops per minute or a visible liquid mist.

- (2731) LIQUID-TIGHT FOOD CONTAINER ismeans a paperboard container that can hold liquid food and food products without leaking even when it is held upside-down.
- (2832) LITHOGRAPHIC PRINTING <u>ismeans</u> a plane-o-graphic <u>printmaking</u> method in which the image and non-image areas are on the same plane.
- (2933) MAINTENANCE CLEANING ismeans a solvent cleaning operation or activitySolvent Cleaning Activity carried out to keep clean general work areas where manufacturing or repair activity is performed, and to clean tools, machinery, molds, forms, jigs, and equipment. -This definition does not include the cleaning of coatings, adhesives, or ink application equipment.
- (3034) MANUFACTURING PROCESS is means the process of making goods or articles by hand or by machinery.
- of the photochemical reactivity of a VOC, which estimates the weight of ozone produced from a weight of VOC expressed as gram of ozone per gram of VOC (g O3/g VOC). MIR values for individual VOCs are specified in Sections 94700 and 94701, Title17, California Code of Regulations.
- (3136) MEDICAL DEVICE <u>ismeans</u> an instrument, apparatus, implement, machine, contrivance, implant, in vitro reagent, or other similar article, including any component or accessory, that meets one of the following conditions:
 - (A) <u>it is intended Intended</u> for use in the diagnosis of disease or other conditions, or in the cure, mitigation, treatment, or prevention of disease; or
 - (B) it is intended Intended to affect the structure or any function of the body; or
 - (C) <u>it is defined Defined</u> in the National Formulary or the United States Pharmacopeia, or any supplement to them.
- (3237) NON-ABSORBENT CONTAINER <u>ismeans</u> a container made of nonporous material, which does not allow the migration of the liquid solvent through it.
- (3338) NON-ATOMIZED SOLVENT FLOW ismeans the use of a solventSolvent Cleaning Material in the form of a liquid stream without atomization to remove uncured adhesives, uncured inks, uncured coatings, and contaminants from an article.

- (3439) NON-LEAKING CONTAINER is means a container that can hold liquids without leaking without liquid leak and is designed to prevent liquids, vapors, or any other contents from escaping through its seams, closures, or any other openings, ensuring secure storage or transport.
- (3540) ON-PRESS COMPONENT is means a part, component, or accessory of a pressPress that is cleaned while still being physically attached to the pressPress.
- (3641) ON-PRESS SCREEN CLEANING is means a solvent cleaning activity Solvent Cleaning Activity carried out during press runs in screen printing operation to remove excess inks and contaminants from a screen that is still attached to the press Press.
- (42) OZONE GENERATOR means a mechanical system that produces ozone used for water or wastewater treatment. Ozone is produced by applying an electric potential or ultraviolet light to oxygen that can be either in the form of dry air or pure oxygen. Ozone Generator includes the associated oxygen supply equipment that is used to produce ozone.
- (3743) PACKAGING PRINTING ismeans any lithographic, flexographic, gravure, or letterpress printing that results in identifying or beautifying paper, paperboard, or cardboard products to be used as containers, enclosures, wrappings, or boxes.
- (3844) PERSON is any firm, business establishment, association, partnership, corporation or individual, whether acting as principal, agent, employee, or other capacity including any governmental entity or charitable organization as defined in Rule 102.
- (3945) PHARMACEUTICAL PRODUCT is means a preparation or compound of medicinal drugs including, but not limited to, a prescription drug, analgesic, decongestant, antihistamine, cough suppressant, vitamin, mineral and herb, and is used by humans for consumption to enhance personal health.
- (4046) PHOTOCURABLE RESIN is means a chemical material that solidifies upon exposure to light.
- (47) PRESS means a mechanical device used to apply pressure to an inked surface resting on a substrate to transfer color, design, alphabetical text, or numerals to the substrate.
- (41<u>48</u>) PRINTING, in the graphic arts, is means any operation that imparts color, design, alphabet, or numerals on a substrate in Graphic Arts.

<u>PAR</u> Rule 1171 (Cont.) <u>Adoption</u>])

- (49) PUBLIC WATER SYSTEM means a system that provides water for human consumption through pipes or other constructed conveyances that has fifteen or more connections or regularly serves at least twenty-five individuals daily at least sixty days out of the year.
- (50) PRODUCT-WEIGHTED MIR (PW-MIR) means the sum of all weighted-MIR for all ingredients in a Regulated Product. The PW-MIR is the total product reactivity expressed to hundredths of a gram of ozone formed per gram of product (excluding container and packaging) and calculated according to the following equations:

<u>Weighted MIR (Wtd-MIR) ingredient = MIR x Weight fraction</u> ingredient,

and,

 $\underline{PW-MIR} = (\underline{Wtd-MIR})_1 + (\underline{Wtd-MIR})_2 + ... + (\underline{WtdMIR})_n$

where,

MIR = ingredient MIR; and

1,2,3,...,n = each ingredient in the product up to the total n ingredients in the product.

- (4251) RADIATION-EFFECT COATING ismeans a material that prevents radar detection.
- (4352) REMOTE RESERVOIR CLEANER ismeans a cleaning device in which liquid solvent is pumped from a solvent container to a sink-like work area and the solvent from the sink-like area drains into an enclosed solvent container while parts are being cleaned.
- (44<u>53</u>) REMOVABLE PRESS COMPONENT <u>ismeans</u> a part, component, or accessory of a <u>pressPress</u> that is physically attached to the <u>pressPress</u> but is disassembled and removed from the <u>pressPress</u> prior to being cleaned. <u>Removable Press Components do not include Rollersrollers</u>, <u>blanketsBlankets</u>, metering rollers, dampening rollers, ink trays, printing plates, fountains, impression cylinders and plates <u>shall not be considered as removable press components</u>.
- (4554) REPAIR CLEANING ismeans a solvent cleaning operation or activity Solvent Cleaning Activity carried out during a repair process.
- (4655) REPAIR PROCESS <u>ismeans</u> the process of returning a damaged object or an object not operating properly to good condition.

- (47<u>56</u>) ROLLER WASH <u>ismeans</u> a <u>solventSolvent Cleaner</u> used to remove ink from the rollers of a <u>pressPress</u>.
- (48<u>57</u>) SCIENTIFIC INSTRUMENT <u>ismeans</u> an instrument (including the components, assemblies, and subassemblies used in their manufacture) and associated accessories and reagents that is used for the detection, measurement, analysis, separation, synthesis, or sequencing of various compounds.
- (4958) SCREEN PRINTING <u>ismeans</u> a process in which the printing ink passes through a web or a fabric to which a refined form of stencil has been applied. The stencil openings determine the form and dimensions of the imprint.
- (5059) SCREEN RECLAMATION is means a solvent cleaning activity Solvent Cleaning Activity carried out in screen printing Screen Printing operation where the screen is completely cleaned for recycling or reuse of the screen for other production runs.
- (5160) SOLVENT <u>CLEANER OR SOLVENT CLEANING MATERIAL</u> is means a VOC-containing liquid <u>substance</u> used to perform solvent cleaning <u>Solvent Cleaning</u>.
- (61) SOLVENT CLEANER SUPPLIER means any person Person who sells, and delivers or arranges to deliver Solvent Cleaning Materials to a facility Facility subject to this rule.
- (5262) SOLVENT CLEANING ismeans the use of a Solvent Cleaner or Solvent Cleaning Material for the removal of loosely held uncured adhesives, uncured inks, uncured coatings, and contaminants whichthat include, but are not limited to, dirt, soil, and grease from parts, products, tools, machinery, equipment, and general work areas. Each distinct method of Solvent Cleaning eleaning in a cleaning process, which consists of a series of cleaning methods, shall constitute a separate solvent cleaningSolvent Cleaning operationActivity.
- (63) SOLVENT CLEANING ACTIVITY means a distinct method of cleaning, or a series of distinct cleaning methods, in a Solvent Cleaning process or single event.
- (64) SOLVENT CLEANING OPERATION means a Solvent Cleaning Activity or Solvent Cleaning Activities conducted as part of a business or a public service.
- (5365) SOLVENT FLUSHING is the use of a solvent to remove uncured adhesives, uncured inks, uncured coatings, or contaminants from the

- internal surfaces and passages of the equipment by flushing solvent through the equipment.
- (54) SOLVENT SUPPLIER is any person who sells and delivers or arranges to deliver solvent cleaning materials to a solvent cleaning operation subject to this regulation.
- (55) STEREOLITHOGRAPHY is a type of printing process that employs a system using a light to solidify photocurable resins in a desired configuration in order to produce a 3-dimensional object.
- (66) SOUTH COAST AQMD TEST METHOD means a test method included in the manual of "Laboratory Methods of Analysis for Enforcement Samples," which can be found on the South Coast AQMD website and are referenced in subdivision (h).
- (5667) SPECIALTY FLEXOGRAPHIC PRINTING ismeans flexographic printing Flexographic Printing on polyethylene or polypropylene food packaging, fertilizer bags, or liquid-tight food containers.
- (68) STEREOLITHOGRAPHY means a type of printing process that employs a system using a light to solidify photocurable resins in a desired configuration to produce a three-dimensional object
- (5769) STERILIZATION INDICATING INK is means an ink that changes color to indicate that sterilization has occurred, which—Such ink is used to monitor the sterilization of medical instruments, autoclave efficiency, and the thermal processing of foods for prevention of spoilage.
- (5870) STRIPPING ismeans the removal of eured coatings, cured inks, or cured adhesivesCured Coatings, Cured Inks, or Cured Adhesives.
- (5971) SURFACE PREPARATION <u>ismeans</u> the removal of contaminants such as dust, soil, oil, grease, etc., prior to coating, adhesive, or ink applications.
- (72) THROTTLE BODY means a component of a vehicle air intake system, and is located between the air intake filter and intake manifold of the vehicle air intake system, and controls the amount of air that flows into the vehicle engine.
- (60) ULTRAVIOLET INK is an ink that dries by polymerization reaction induced by ultraviolet energy.
- (73) ULTRAVIOLET LIGHT TREATMENT means the process of using ultraviolet light to inactivate microorganisms (i.e., disinfection) or using ultraviolet light either with or without the addition of peroxide to oxidize contaminants (i.e., oxidation). Ultraviolet light treatment is used for both

- potable water and wastewater, including indirect and direct potable water reuse projects.
- (6174) VOLATILE ORGANIC COMPOUND (VOC) is as defined in Rule 102.
- (62) WIPE CLEANING is the method of cleaning a surface by physically rubbing it with a material such as a rag, paper, sponge or a cotton swab moistened with a solvent.
- (75) WATER TREATMENT FACILITY means a public entity that is responsible for water delivery operations, sewage pumping plants, sewage treatment, or water reclamation.

(e)(d) Requirements

(1) Solvent Requirements A Person shall not use a Solvent Cleaner to perform

Solvent Cleaning Activities as part of a Solvent Cleaning Operation unless
the Solvent Cleaner complies with the applicable requirements set forth
below:

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

Delow:		
SOLVENT CLEANING ACTIVITY	CURRENT LIMITS* VOC g/I (lb/gal)	EFFECTIVE 1/1/2010 VOC g/1 (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	

PAR Rule 1171 (Cont.) Adoption])

·		
	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	VOC	VOC
(cont.)	g/1	g/1
	(lb/gal)	(lb/gal)
(C) Cleaning of Coatings or Adhesives	25	
Application Equipment	(0.21)	
Аррисанов Еquiршені	(0.21)	
(D) Cleaning of Ink Application Equipment		
(1)	25	
(i) General	(0.21)	
40. 7	25	
(ii) Flexographic Printing	(0.21)	
(iii) Gravure Printing		
(A) Publication	100	
()	(0.83)	
(B) Packaging	25	
(=)88	(0.21)	
(iv) Lithographic (Offset) or Letter Press	(**==)	
Printing		
(A) Roller Wash, Blanket Wash,	100	
& On Press Components	(0.83)	
-	25	
(B) Removable Press Components	(0.21)	
() G P: ::	100	
(v) Screen Printing	(0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink	` '	
Application Equipment (except screen	100	
printing)	(0.83)	
<u> </u>	100	
(vii) Specialty Flexographic Printing	(0.83)	
(E) Charles (D.1 artes Davis Applicati	25	
(E) Cleaning of Polyester Resin Application	25 (0.21)	
Equipment Equipment	(0.21)	1

^{*} The specified limits remain in effect unless revised limits are listed in subsequent columns.

Table 1 – Table of Standards VOC Content Limits

SOLVENT CLEANING ACTIVITY		VOC Limits	
		lbs/gal	
(A) Product Cleaning During Manufacturing Process, or Surface Prepara	tion for		
Coating, Adhesive, or Ink Application			
(i) General	<u>25</u>	<u>0.21</u>	
(ii) Electrical Apparatus Components & Electronic Components	<u>100</u>	<u>0.83</u>	
(A) Printed Circuit Boards	<u>800</u>	<u>6.7</u>	
(iii) Medical Devices & Pharmaceuticals	<u>800</u>	<u>6.7</u>	
(B) Repair and Maintenance Cleaning			
(i) General	<u>25</u>	<u>0.21</u>	
(ii) Electrical Apparatus Components & Electronic Components	<u>100</u>	<u>0.83</u>	
(A) Electronic or Electrical Cables	<u>400</u>	<u>3.4</u>	
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	<u>800</u>	<u>6.7</u>	
(B) General Work Surfaces	<u>600</u>	<u>5.0</u>	
(C) Cleaning of Coatings or Adhesives Application Equipment			
(i) General	<u>25</u>	<u>0.21</u>	
(ii) Thin or Sheet Metal Laminating Equipment	<u>950</u>	<u>8.0</u>	
(D) Cleaning of Ink Application Equipment and			
(i) General	<u>25</u>	0.21	
(ii) Flexographic Printing	<u>25</u>	<u>0.21</u>	
(iii) Gravure Printing			
(A) Publication	<u>100</u>	0.83	
(B) Packaging	<u>25</u>	<u>0.21</u>	
(iv) Lithographic (Offset) or Letter Press Letterpress Printing	100	0.02	
(A) Roller Wash, Blanket Wash, & On-Press Components	<u>100</u>	0.83	
(B) Removable Press Components	<u>25</u>	0.21	
(v) Screen Printing	<u>100</u>	0.83	
(vi) Energy Curable Printing (A) July Application Fractions of Consent Sensor Printing	100	0.02	
(A) Ink Application Equipment (except Screen Printing)	<u>100</u>	0.83	
(B) Lamps and Reflectors	800	6.7	
(vii) Specialty Flexographic Printing	<u>100</u>	0.83	
(E) Cleaning of Polyester Resin Application Equipment	<u>25</u>	0.21	

- (2) Cleaning Devices and Methods Requirements
 - A <u>person</u> Person shall not perform solvent cleaningSolvent Cleaning Activities listed in paragraph (d)(1) unless one of the following cleaning devices or methods is used:
 - (A) Wipe cleaning, which is a Solvent Cleaning Activity conducted by physically rubbing it with a material such as a rag, paper, sponge or a cotton swab moistened with a solvent;
 - (B) Closed containers or hand—held spray bottles from which solvents Solvent Cleaners are applied without a propellant-induced force;
 - (C) Cleaning equipment whichthat has a solventSolvent Cleaner container that can be closed, and is closed during cleaning operationsSolvent Cleaning Activities, except when depositing and removing objects to be cleaned, and is closed during non-operation with the exception of maintenance and repair to the cleaning equipment itself;
 - (D) Cleaning device which is listed in the Office of Operations' manual
 "Alternative Devices for Rule 1171 Compliance" dated . The
 Executive Officer shall periodically update the manual to identify
 any additional cleaning devices determined by the Executive Officer
 to result in equivalent or lower emissions; the manual to identify any
 additional cleaning devices determined by the Executive Officer to
 result in equivalent or lower emissions;
 - (E)(D) Remote reservoir Reservoir eleaner Used pursuant to the provisions of paragraph (e)(d)(3);
 - (F)(E) Non-atomized solventSolvent flowFlow method where the eleaning solventSolvent Cleaner is collected in a container or a collection system whichthat is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or
 - (G)(F) Solvent flushing Flushing method where the eleaning solvent Solvent Cleaner is discharged into a container which that is closed except for solvent Cleaner collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent Cleaning Material from the equipment must be collected into containers without atomizing into

- the open air. The solvent Solvent Cleaning Material may be flushed through the system by air or hydraulic pressure, or by pumping: or
- (G) Hand-held spray devices, where solvent cleaning material is applied using a hand-held device with a pressurized container used to disperse Solvent Cleaning Material through a nozzle, when performing Solvent Cleaning Activities at Electricity Distribution Utilities, Electricity Generating Facilities, Water Treatment Facilities, or Public Water Systems, provided that Solvent Cleaning Activities are performed pursuant to the alternative compliance options in paragraph (e)(2).

(3) Remote Reservoir Cleaners

Any <u>person Person</u> owning or operating a <u>remote reservoir cleaner Remote Reservoir Cleaner</u> shall comply with all of the following requirements in addition to the applicable VOC limits specified in paragraph $\frac{(e)(d)}{(1)}$:

- (A) Prevent solventSolvent Cleaner vapors from escaping from the solventSolvent Cleaner container by using such devices as a cover or a valve when the remote reservoir is not being used, cleaned, or repaired;
- (B) Direct solventSolvent Cleaner flow in a manner that will prevent liquid solventSolvent Cleaning Material from splashing outside of the remote reservoir cleanerRemote Reservoir Cleaner;
- (C) Do not Not clean porous or absorbent materials, such as cloth, leather, wood, or rope; and
- (D) Use only—solvent containers free of all liquid leaks. —Auxiliary equipment, such as pumps, pipelines, or flanges, shall not have any liquid leaks, visible tears, or cracks. -Any liquid leak, visible tear, or crack detected shall be repaired within one (1) calendar day, or the leaking section of the remote reservoir cold cleaner shall be drained of all solventSolvent Cleaning Materials and shut down until it is replaced or repaired.

(4) Storage and Disposal

All VOC-containing solvents Solvent Cleaning Materials used in solvent cleaning operations Solvent Cleaning Activities listed in paragraph (d)(1) shall be stored in non-absorbent Non-Absorbent, non-leaking Non-Leaking containers, which shall be kept closed at all times except when filling or emptying. It is recommended that cloth Cloth and paper moistened with

PAR Rule 1171 (Cont.) Adoption])

VOC-containing solvents Solvent Cleaning Materials must be stored in closed, non-absorbent Non-Absorbent, non-leaking Non-Leaking containers.

(5) Labeling

Any person Person who sells or offers for sale Solvent Cleaning Materials for use in the South Coast AQMD shall:

- (A) For Solvent Cleaning Materials complying with paragraph (d)(1), comply with the labeling provisions of Rule 443.1 Labeling of Materials Containing Organic Solvents; and
- (B) For Solvent Cleaning Materials complying with the alternative PW-MIR VOC limits pursuant to paragraphs (e)(2), (e)(4), or (e)(5), include the PW-MIR VOC content on the container.
- (e) (5) Alternative Compliance Options Control Equipment
 - In lieu of complying with the requirements in paragraphs (e)(d)(1) orand (e)(d)(2), a person Person may comply by using a VOC emission collection and control system Emission Control System in association with the solvent eleaning operation Solvent Cleaning Activities provided the Emission Control System:
 - (A) the emission control system shall collect Collects at least 90 percent, by weight, of the emissions generated by the solvent cleaning operation Solvent Cleaning Activities; and
 - (i) have <u>Has</u> a destruction efficiency of at least 95 percent, by weight, or
 - (ii) have <u>Has</u> an output of less than 50 parts per million (PPM) calculated as carbon with no dilution; or
 - (B) the emission control system meets Meets the requirements of the applicable source specific rule of the District's South Coast AQMD Regulation XI; or
 - (C) The collection system for For cleaning in graphic arts Graphic Arts and screen printing Screen Printing and cleaning of application equipment used for graphic arts Graphic Arts materials and screen printing Screen Printing materials:
 - (i) , shall collect Collects at least 70 percent, by weight, of the emissions generated.; and

- (ii) This control system shall reduce emissions from the emission collection system by Has a destruction efficiency of at least 95 percent, by weight.
- (D) For internal cleaning of enclosed mobile containers, including but not limited to rail tank cars and tanker truck containers, used to transport materials:
 - (i) Shall be air-tight and leak free during the Solvent Cleaning Activities; and
 - (ii) For all fugitive components, vapor leaks shall not exceed 50 parts per million measured on a South Coast AQMD organic vapor analyzer calculated as carbon, with no dilution.
- (2) Alternative Limits for Electricity and Water Equipment

 Facilities conducting Solvent Cleaning Activities for the following
 equipment listed in Table 2 that are operated at Electricity Generating
 Facilities, Electricity Distributing Utilities, Water Treatment Facilities or
 Public Water Systems may use Solvent Cleaning Materials that exceed the
 VOC limits in paragraph (d)(1) provided:
 - (A) The Facility uses no more than the annual volumes listed in Table 2;
 - (B) The Solvent Cleaning Materials have a PW-MIR no more than those listed in Table 2;
 - (C) The Facility maintains monthly purchase and usage records pursuant to paragraph (g)(2) for a minimum of five years; and
 - (D) The Solvent Cleaning Materials comply with the labeling provisions in subparagraph (d)(5)(B).

Table 2 – Alternative Usage and MIR Limits

Solvent Cleaning Activity	Usage Limits (gallons per year)	PW-MIR
(A) Electricity Generating or Distribution Equipment	<u>70</u>	<u>1.7</u>
(B) Water Distribution Equipment and Water Treatment Equipment		
(i) Chlorination Systems	<u>5</u>	<u>1.7</u>
(ii) Ozone Generators	<u>40</u>	<u>1.7</u>
(iii) Ultraviolet Light Treatment Systems	<u>30</u>	<u>1.7</u>

(3) Alternative Limits for Aerosol Cleaning

Facilities conducting Solvent Cleaning Activities listed in Table 3 may use Aerosol Solvent Cleaners that exceed the VOC limits in paragraph (d)(1) provided:

- (A) The Facility complies with the applicable usage limit(s) listed in Table 3;
- (B) On and after [90 Days after Date of Rule Adoption], the Facility maintains monthly purchase and usage records pursuant to paragraph (g)(2) for a minimum of five years; and
- (C) Such products are compliant with California Air Resources Board (CARB) Consumer Product Regulations, including, but not limited to, meeting the VOC content limit requirements of Article 2 or as allowed by Article 4.

<u>Table 3 – Aerosol Solvent Cleaner Usage Limits</u>

Solvent Cleaning Activity	<u>Usage Limits</u>	
(A) Cleaning of Automotive Parts		
(i) Throttle Body and Intake Systems	4,800 ounces per month	
(ii) All Other Automotive Part Cleaning	32 ounces per month	
(B) Battery Terminal Cleaning at Battery Manufacturing Facilities	2,400 ounces per month	
(C) All Others Solvent Cleaning Activities	1,750 ounces per month	

PAR Rule 1171 (Cont.) Adoption])

(4) Alternative MIR Limit

In lieu of complying with the VOC limits in paragraph (d)(1), a Person may elect to supply for use within South Coast AQMD or use Solvent Cleaning Materials that comply with a PW-MIR limit of 0.38 g O₃/g VOC for any Solvent Cleaning Activity provided the Solvent Cleaning Materials comply with the labeling provision in subparagraph (d)(5)(B).

(5) Alternative MIR Limit for Ink Application Equipment

In lieu of complying with the VOC limits for the following Table 1 Solvent Cleaning Activities for Cleaning of Ink Application Equipment, (D)(iv)(A), lithographic or letter press printing for roller wash, blanket wash, and on press components ink application equipment cleaning, and Table 1 (D)(v) screen printing ink application equipment cleaning, a Person may elect to supply for use within South Coast AQMD or use Solvent Cleaning Materials that comply with a PW-MIR limit of 0.70 g O₃/g VOC provided the Solvent Cleaning Materials comply with the labeling provision in subparagraph (d)(5)(B):

- (A) Table 1 (D)(vi) Energy Curable Printing;
- (B) Table 1 (D)(iv)(A) Lithographic (Offset) or Letterpress Printing for Roller Wash, Blanket Wash, & On-Press Components; and
- (C) Table 1 (D)(v) Screen Printing.

(6) Recordkeeping Requirements

Records shall be maintained pursuant to Rule 109 for all applications subject to this rule, including those exempted under paragraphs (g)(3) through (g)(11), except facilities required to keep records of VOC used pursuant to any other Regulation XI rules.

- (7) Any solvent supplier supplying solvent cleaning material for use by a solvent cleaning operation in the District, shall upon request by the Executive Officer, provide in a District-approved electronic format, the following information: product name of the supplied solvent cleaning material; the name and address of the solvent cleaning operation that the product was supplied to; dates and quantities in which the product was supplied during the time period specified by the Executive Officer; and the VOC content of the product as supplied. The solvent supplier shall maintain records necessary to provide this required information for three (3) years.
- (8) The operator shall maintain at all times, and make available to the Executive officer upon request, the correct written dilution instructions for each

solvent cleaning material if dilution is necessary to meet the applicable VOC limits in this rule. A solvent supplier providing solvent cleaning material for use by a solvent cleaning operation in the District shall supply to the operator, upon the operator's request, the correct written dilution instructions for each supplied solvent cleaning material.

(9) Any person who sells or offers for sale solvent cleaning materials for use in the District shall comply with the provisions of Rule 443.1 Labeling of Materials Containing Organic Solvents.

(d)(f) General Prohibitions

- (1) A <u>person Person</u> shall not atomize any <u>solventSolvent Cleaner</u> unless it is vented to <u>an air pollution control equipmentEmission Control System</u>, <u>whichthat</u> meets the requirements of paragraph (e)(5)(e)(1).
- (2) A <u>person_Person_shall</u> not specify or require any <u>person_Person_solvent_</u>
- (3) <u>Carcinogenic Materials and Exempt Compounds</u>
 - A <u>person_Person_</u> shall not perform <u>solvent_cleaning_activitiesSolvent_Cleaning_Activities_or_operations_subject</u> to the provisions of this rule with any <u>material_Solvent_Cleaning_Material_whichthat_contains_any_of_the_following_chemicals_in_concentrations_greater_than_the_limits_indicated:</u>
 - (A) 0.01 percent by weight of Group II exempt compounds listed in Rule

 102 Exempt Compound except cyclic, branched, or linear,
 completely methylated siloxanes (VMS); or
 - (B) 0.01 percent by weight of para-Chlorobenzotrifluoride (pCBtF),

 CAS 98-56-6 and *tert*-Butyl Acetate (t-BAc), CAS 540-88-5 for

 Solvent Cleaning Materials manufactured after January 1, 2026.
- (4) Sell Through Provision for pCBtF and t-BAc

 Any Solvent Cleaning Material that is manufactured prior to January 1,

 2026, that contains more than 0.01 percent of pCBtF and t-BAc may be sold, supplied, or offered for sale until January July 1, 2027, and used until January July 1, 2028.
- (4<u>5</u>) Any <u>person_Person_</u> subject to the Airborne Toxic Control Measure for Emissions of Chlorinated Toxic Air Contaminants from Automotive Maintenance and Repair Activities Title 17, California Code of Regulations, section 93111, shall comply with its provisions.

PAR Rule 1171 (Cont.) Adoption])

- (56) No <u>full service solventSolvent Cleaner providerSupplier</u> shall aid, abet or assist a <u>facility-Facility or solvent cleaning operation any person Person</u> to use a supplied <u>solventSolvent Cleaner</u> in a <u>non-compliant-manner that does</u> not meet the requirements of this rule.
- (7) No Solvent Cleaner shall be used when documentation cannot be provided pursuant to paragraph (g)(2) for that Solvent Cleaner.
- (8) Prohibition of Possession

Solvent Cleaning Materials that do not meet the requirements of this rule and are used, intended for use, or labeled for use, for Solvent Cleaning Activities within South Coast AQMD shall not be kept on-site, unless the Facility is complying with any of the alternative compliance options pursuant to subdivision (e).

(g) Recordkeeping Requirements

- (1) Any Person who performs Solvent Cleaning Activities shall maintain records pursuant to Rule 109 Recordkeeping for Volatile Organic Compound Emissions for all applications subject to this rule, including those exempted under paragraphs (j)(3) through (j)(6), except facilities Facilities required to keep records of Solvent Cleaning Materials used and Solvent Flushing pursuant to an applicable Regulation XI source specific rule.
- (2) Any person Person who performs Solvent Cleaning Activities shall maintain records for five years for all Solvent Cleaning Materials used, and make available to the Executive Officer upon request, that includes the following for each solvent cleaning activity performed:
 - (A) Product name of each Solvent Cleaner used;
 - (B) Name and address of the supplier for each Solvent Cleaner used;
 - (C)(B) Dates and quantities in which each Solvent Cleaner was used during the time period specified by the Executive Officer;
 - (D)(C) VOC content of each Solvent Cleaner as used; and
 - (E)(D) PW-MIR VOC content if the manufacturer elects to comply with the alternative PW-MIR VOC limits in paragraph (e)(2), or (e)(4), and (e)(5).
- (3) Any Solvent Cleaner Supplier supplying Solvent Cleaning Materials for use in the South Coast AQMD shall maintain the following records for five years and make the data available upon request by the Executive Officer:

- (A) Product name of each supplied Solvent Cleaner;
- (B) Name and address of the facility Facility that the Solvent Cleaner was supplied to;
- (C) Dates and quantities in which the Solvent Cleaner was supplied during the time period specified by the Executive Officer; and
- (D) VOC content of the Solvent Cleaner as supplied.

(4) Dilution Instructions

If a Solvent Cleaner is required to be diluted prior to being used in a Solvent Cleaning Activity to meet the applicable VOC limits:

- (A) Any person Person who uses Solvent Cleaning Materials requiring such dilution shall maintain at all times, and make available to the Executive Officer upon request, the correct written dilution instructions for each of these Solvent Cleaner; and
- (B) The Solvent Cleaner Supplier providing Solvent Cleaning Material for use in the South Coast AQMD shall supply to the operator, upon the operator's request, the correct written dilution instructions for each supplied Solvent Cleaner.

(5) Remote Reservoir Cleaners

Records of any repair of leaks, visible tears, or cracks of remote reservoir cleaner auxiliary equipment shall be maintained and made readily available for a period of five years following the date of repair.

(e)(h) Test Methods

For the purpose of this rule, the following test methods shall be used. Other test methods determined to be equivalent after review by the staffs of the District, the Air Resources Board, and the United States Environmental Protection Agency, and approved in writing by the District Executive Officer may also be used.

- (1) Determination of VOC Content The VOC content of materials subject to the provisions of this rule shall be determined by the following methods:
 - (A) United States Environmental Protection Agency (U.S._EPA)
 Reference Test Method 24 Determination of Volatile Matter
 Content, Water Content, Volume Solids and Weight Solids of
 Surface Coatings, (Code of Federal Regulations, Title 40, Part-60,
 Appendix A with the Exempt Compounds' content determined by
 South Coast AQMD Test Method 303 Determination of Exempt

- <u>Compounds</u>;). The exempt compounds' content shall be determined by the South Coast Air Quality Management District's (SCAQMD) Method 303 (Determination of Exempt Compounds) contained in the SCAQMD "Laboratory Methods of Analysis for Enforcement Samples" manual; or,
- (B) SCAQMD South Coast AQMD Test Method 304 {Determination of Volatile Organic Compounds (VOC) in Various Materials} contained in the SCAQMD—"Laboratory Methods of Analysis for Enforcement Samples" manual.; or
- (C) South Coast AQMD Test Method 313 Determination of Volatile

 Organic Compounds (VOC) by Gas Chromatography-Mass

 Spectrometry/Mass Spectrometry/Flame Ionization Detection

 (GC/MS/FID); or
- (D) ASTM Standard Test Method E 1868 Standard Test Method for Loss-On-Drying by Thermogravimetry with quality assurance and quality control procedures using South Coast AQMD Additional Requirements to ASTM Standard Test Method E 1868-10 for Metalworking Fluids and Direct-Contact Lubricants.

(C)(2) Exempt Perfluorocarbon Compounds

The following classes of compounds shall be analyzed as Exempt Compounds for compliance with subdivision (d), only at such time as manufacturers specify which individual compounds are used in the solvent formulation and identify the test methods, which have been approved by the U.S. EPA, CARB and the South Coast AQMD prior to such analysis, that can be used to quantify the amounts of each exempt compound:

- (A) <u>eyelieCyclic</u>, branched, or linear, completely fluorinated alkanes;
- (B) eyelieCyclic, branched, or linear, completely fluorinated ethers with no unsaturations;
- (C) <u>eyelieCyclic</u>, branched, or linear, completely fluorinated tertiary amines with no unsaturations; and
- (D) <u>sulfurSulfur</u>-containing perfluorocarbons with no unsaturations and with sulfur bonds only to carbon and fluorine.;

 will be analyzed as exempt compounds for compliance with subdivision (c), only when manufacturers specify which individual compounds are used in the solvent formulation and identify the United States Environmental Protection Agency, California Air

Resources Board, and the District approved test methods used to quantify the amount of each exempt compound.

- (2) Determination of Presence of VOC in Cleaning Materials
 - The presence of VOC in the headspace over the cleaning material shall be determined by SCAQMD Test Method 313 [Determination of Presence of Volatile Organic Compounds (VOC) in a Headspace] contained in the SCAQMD "Laboratory Methods of Analysis for Enforcement Samples" manual.
 - The presence of VOC in liquid cleaning materials shall be determined by SCAQMD Method 308 (Quantitation of Compounds by Gas Chromatography) contained in the SCAQMD "Laboratory Methods of Analysis for Enforcement Samples" manual.
- (3) Determination of Efficiency of Emission Control Systems
- (A) The A person Person that elects to comply with the provisions of paragraph (d)(1) using an Emission Control System specified in subparagraph (e)(1)(A) shall:
 - (A) Determine the capture efficiency of an emission control system of the collection device in the Emission Control System by using as specified in subparagraph (c)(5)(A) shall be determined by verifying the use of a Permanent Total Enclosure (PTE) and 100% capture efficiency as defined by:
 - (i) South Coast AQMD's "Protocol for Determination of Volatile Organic Compounds (VOC) Capture

 Efficiency," USEPA Method 204, "Criteria for and Verification of a Permanent or Temporary Total Enclosure."; or
 - (ii) Any other method approved by the U.S. EPA, CARB, and the South Coast AQMD Executive Officer.—Alternatively, iIf a USEPA Method 204 defined PTE is not employed, capture efficiency shall be determined using a minimum of three sampling runs subject to data quality criteria presented in the USEPA technical guidance document "Guidelines for Determining—Capture—Efficiency, January—9, 1995." Individual capture efficiency test runs subject to the USEPA technical guidelines shall be determined by:

- (i) The Temporary Total Enclosure (TTE) approach of USEPA Methods 204 through 204F, June 4, 1997; or
- (ii) The District "Protocol for Determination of Volatile Organic Compounds (VOC) Capture Efficiency," May 1995.
- (B) Determine the efficiency and the VOC content in the Emission

 Control System exhaust gases, measured and calculated as carbon

 by:
 - (i) U. S. EPA Test Method 25 Determination of Total Gaseous Nonmethane Organic Emissions as Carbon;
 - (ii) U. S. EPA Test Method 25A Determination of Total

 Gaseous Organic Concentration Using a Flame Ionization

 Analyzer;
 - (iii) South Coast AQMD Test Method 25.1 Determination of Total Gaseous Non-Methane Organic Emissions as Carbon; or
 - (iv) South Coast AQMD Test Method 25.3 Determination of Low Concentration Non-Methane Non-Ethane Organic Compound Emissions from Clean Fueled Combustion Sources.
- (C) Determine emissions of Exempt Compounds by:
 - (i) U.S. EPA Test Method 18 Volatile Organic Compounds by Gas Chromatography; or
 - (ii) CARB Method 422 Determination of Volatile Organic Compounds in Emissions from Stationary Sources.
- (B) The control equipment efficiency of an emission control system as specified in subparagraph (c)(5)(A), on a mass emissions basis, and the VOC concentrations in the exhaust gases, measured and calculated as carbon, shall be determined by USEPA Test Methods 25, 25A, SCAQMD Method 25.1 (Determination of Total Gaseous Non-Methane Organic Emissions as Carbon), or SCAQMD Method 25.3 (Determination of Low Concentration Non-Methane Non-Ethane Organic Compound Emissions from Clean Fueled Combustion Sources), as applicable. USEPA Test Method 18, or ARB Method 422 shall be used to determine emissions of exempt compounds.

PAR Rule 1171 (Cont.) Adoption])

(4) Equivalent Test Methods

Other test methods determined to be equivalent by the Executive Officer, CARB, and the U.S. EPA, and approved in writing by the Executive Officer may also be used.

(4)(5) Multiple Test Methods

When more than one test method or set of test methods is specified for any testing, a violation of any requirement of this rule established by any one of the specified test methods or set of test methods shall constitute a violation of this rule.

(5)(6) All test methods referenced in this section shall be the most recently approved version.

(f)(i) Rule 442 Applicability

Any solvent Cleaner, Solvent Cleaning Material, solvent cleaning activity Solvent Cleaning Activity, solvent cleaning unit operation Solvent Cleaning Operation, or <u>person</u> Person, which that is exempt from all or a portion of this rule except paragraph (e)(6)(g)(1), shall be subject to the applicable requirements of the applicable Regulation XI source specific rule or Rule 442 - Usage of Solvent.

(g)(j) Exemptions

- The provisions of this rule recordkeeping provisions in subdivision (g), except (c)(1), Solvent Requirements—shall not apply to cleaning operations Solvent Cleaning Activities using a solvent Solvent Cleaning Materials containing no more than 25 grams of VOC per liter of material, provided that, if the Executive Officer determines that a person Person has violated any of the VOC limits in provision of paragraph (c)(1)(d)(1) for any Solvent Cleaning Activities occurring, Solvent Requirements, then for a period of three—five years following the date of such violation, the recordkeeping requirements in paragraph (c)(6) subdivision (g) Recordkeeping Requirements, shall apply to the facility Facility at which the violation occurred.
- (2) The following solvent cleaning operations or activities Solvent Cleaning Activities are not subject to any provision of this rule:
 - (A) Cleaning carried out in batch loaded cold cleaners, vapor degreasers, conveyorized degreasers, or motion picture film cleaning equipment.operations subject to Rule 1122 Solvent Degreasers, or Rule 1425 Film Cleaning and Printing Operations;

- (B) Cleaning operations subject to Rule 1102 Petroleum Solvent Dry Cleaners, andor Rule 1421 Control of Perchloroethylene Emissions from Dry Cleaning Operations;
- (C) Cleaning operations subject to Rule 1164 Semiconductor Manufacturing-;
- (D) Cleaning operations subject to Rule 1124 Aerospace Assembly and Component Manufacturing Operations, except coating application equipment cleaning, and storage and disposal of VOCcontaining materials used in solvent cleaningSolvent Cleaning operationsActivities;
- (E) Cleaning operations subject to Rule 1141 Control of Volatile
 Organic Compound Emissions from Resin Manufacturing, and Rule
 1141.1 Coatings and Ink Manufacturing:
- (F) Janitorial cleaning, including graffiti removal-:
- (G) Stripping of cured coatings, cured ink, or cured adhesives:
- (H) Cleaning operations in Printing pre-press or Graphic Arts pre-press areas, including the cleaning of film processors, color scanners, plate processors, film cleaning, and plate cleaning; and
- (I) Cleaning operations using individually wrapped, saturated towelettes, during cable splicing activity for high voltage electrical cable where the VOC content shall not exceed 790 g/L.
- (3) The VOC limits in Provisions of paragraph (e)(d)(1) shall not apply to the following applications:
 - (A) Cleaning of solar cells, laser hardware, scientific instruments, and high-precision optics:
 - (B) Cleaning conducted with: performance laboratory tests on coatings, adhesives, or inks; research and development programs; and laboratory tests in quality assurance laboratories:;
 - (C) Cleaning of motor vehicles on application lines subject to Rule 1115- Motor Vehicle Assembly Line Coating Operations-;
 - (D) Cleaning of paper-based gaskets, and clutch assemblies where rubber is bonded to metal by means of an adhesive;
 - (E) Cleaning of cotton swabs to remove cottonseed oil before cleaning of high-precision optics:
 - (F) Medical device and pharmaceutical *facilities* <u>Facilities</u> using up to 1.5 gallons per day of solvents-:

- (G) The cleaning of photocurable resins from stereolithography equipment and models-;
- (H) Cleaning of adhesive application equipment used for thin metal laminating operations provided the clean up solvent used contains no more than 950 grams of VOC per liter.
- (I) Cleaning of electronic or electrical cables provided the clean-up solvent used contains no more than 400 grams of VOC per liter.
- (J) Touch up cleaning performed on printed circuit boards where surface mounted devices have already been attached provided that the solvent used contains no more than 800 grams of VOC per liter.
- (4) The provisions of paragraph (f)(1) shall not apply to:
 - (A) Cleaning with aerosol products that do not contain VOC in excess of applicable Table 1 VOC limits in paragraph (d)(1); shall not be subject to the provisions of paragraph (e)(1) and paragraph (d)(1) if 160 fluid ounces or less of non-compliant aerosol products are used per day, per facility. The use of such product shall comply with CARB regulations.
 - (B) Solvent Cleaning Activities performed pursuant to subparagraph (d)(2)(G), paragraph (e)(2), and paragraph (e)(3).
- (5) The <u>provisions of VOC limit in</u> subparagraph (e)(d)(1)(C) shall not apply to the following applications:
 - (A) Cleaning of coating and adhesive application processes utilized to manufacture transdermal drug delivery product using less than 3 three gallons per day of ethyl acetate averaged over a 30-calendar day period-;
 - (B) Cleaning of application equipment Application Equipment used to apply coatings on satellites and radiation effect coatings Radiation Effect Coatings; and
 - (C) The cleaning Cleaning of solvent-based fluoropolymer coating application equipment Application Equipment, used to apply solvent-based fluoropolymer coatings provided the clean-up solvent used for such cleaning contains no more than 900 grams of VOC per liter provided less than one gallon per day of Solvent Cleaning Materials is used.
- (6) The provisions of VOC limit in subparagraph (e)(d)(1)(D) shall not apply to persons or facilities Facilities using less than 1.5 gallons per day

- of solvents Solvent Cleaning Materials to clean sterilization indicating ink application equipment Application Equipment.
- (7) Until January 1, 2010, the provisions of (c)(1)(D)(v) shall not apply to onpress cleaning of screens provided the clean up solvent used for such cleaning activity contains no more than 300 grams of VOC per liter.
- (8) Until January 1, 2010, the provisions of (c)(1)(D)(vi) shall not apply to the cleaning of ultraviolet or electron beam lamps and reflectors used for the curing of ultraviolet or electron beam (UV/EB) ink or coatings, and cleaning of metering rollers, dampening rollers and printing plates in UV/EB ink application equipment, provided the clean-up solvent used for such cleaning contains no more than 800 grams of VOC per liter.
- (9)(7) The Provisions provisions of paragraph (d)(f)(1) shall not apply to the following:
 - (A) Cleaning of the nozzle tips of automated spray equipment systems, except for robotic systems.
 - (B) Cleaning with spray bottles or containers described in subparagraph $\frac{(e)(d)}{(2)}(B)$.
 - (C) Printing operations where the roller Roller Wash or blanket washBlanket Wash is applied automatically.
- (10) The provisions of this rule shall not apply to cleaning operations in printing pre-press or graphic arts pre-press areas, including the cleaning of film processors, color scanners, plate processors, film cleaning, and plate cleaning.

ATTACHMENT G

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Final Staff Report

Proposed Amended Rule 1171 – Solvent Cleaning Operations

June 2025

Deputy Executive Officer

Planning, Rule Development, and Implementation Sarah L. Rees, Ph.D.

Assistant Deputy Executive Officer

Planning, Rule Development, and Implementation Michael Krause

Planning and Rules Manager

Planning, Rule Development, and Implementation Heather Farr

Authors: Christopher Bradley – Air Quality Specialist

Contributors: Sarady Ka – Program Supervisor

Melissa Gamoning – Program Supervisor

Mojtaba Moghani, Ph.D. – Air Quality Specialist Mitch Haimov – Senior Engineering Manager Shannon Lee – Senior Engineering Manager Bradley McClung – Program Supervisor Andrew Burris – Senior Air Quality Chemist

Xian-Liang (Tony) Tian, Ph.D. – Program Supervisor

Chris Yu – Assistant Air Quality Specialist Christopher Gill – Senior Air Quality Engineer Sina Taghvaee, Ph.D. – Air Quality Specialist

Reviewed By: Heather Farr – Planning and Rules Manager

Michael Morris – Planning and Rules Manager

Barbara Baird - Chief Deputy Counsel

Karin Manwaring – Senior Deputy District Counsel Barbara Radlein – Planning and Rules Manager

Kevin Ni – Program Supervisor

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT GOVERNING BOARD

Chair: VANESSA DELGADO

Senator (Ret.)

Senate Rules Committee Appointee

Vice Chair: MICHAEL A. CACCIOTTI

Councilmember, South Pasadena

Cities of Los Angeles County/Eastern Region

MEMBERS:

CURT HAGMAN

Supervisor, Fourth District County of San Bernardino

PATRICIA LOCK DAWSON

Mayor, Riverside

Cities of Riverside County Representative

LARRY MCCALLON

Mayor Pro Tem, Highland

Cities of San Bernardino County

HOLLY J. MITCHELL

Supervisor, Second District

County of Los Angeles

JANET NGUYEN

Supervisor, First District

County of Orange

BRENDA OLMOS

Vice Mayor, City of Paramount

Cities of Los Angeles County/Western Region

VERONICA PADILLA-CAMPOS

Speaker of the Assembly Appointee

V. MANUEL PEREZ

Supervisor, Fourth District

County of Riverside

NITHYA RAMAN

Councilmember, Fourth District

City of Los Angeles Representative

CARLOS RODRIGUEZ

Mayor Pro Tem, Yorba Linda

Cities of Orange County

VACANT

Governor's Appointee

EXECUTIVE OFFICER:

WAYNE NASTRI

TABLE OF CONTENTS

Executive Summary	Ex-1
CHAPTER 1 : BACKGROUND	1-0
Introduction	1-1
Regulatory History	1-1
2022 Air Quality Management Plan	1-2
Assembly Bill 617	1-2
Affected Industries	1-3
Process Description	1-3
Public Process	1-3
CHAPTER 2 : SOLVENT CLEANING ASSESSMENT	2-0
Solvent Cleaners and VOC Control	2-1
Aerosol Usage Exemption	2-5
Product-Weighted Maximum Incremental Reactivity	2-8
Enclosed Mobile Containers Used to Transport Material	2-12
CHAPTER 3: SUMMARY OF PROPOSALS	3-0
Introduction	3-1
Proposed Amended Rule Structure	3-1
Proposed Amended Rule 1171	3-1
CHAPTER 4: IMPACT ASSESSMENT	4-0
Emission Inventory	4-1
Control Technology	4-1
Emission Reductions	4-1
Cost-Effectiveness and Incremental Cost-Effectiveness	4-1
Socioeconomic Impact Assessment	4-2
California Environmental Quality Act	4-2
Draft Findings Under the Health and Safety Code	4-2
Comparative Analysis	4-2
APPENDIX A: RESPONSES TO COMMENTS	A-0
Public Workshop Comments	A-1
Comment Letter #1	A-5
Comment Letter #2	A-9
Comment Letter #3	A-12
Comment Letter #4	A-14

Comment Letter #5
Comment Letter #6
Comment Letter #7
Comment Letter #8
Comment Letters Received After Close of Comment Period
LIST OF TABLES
Table 1-1: Summary of Public Meetings1-4
Table 2-1: Rule 1171 VOC Limits
Table 2-2 Cancer Potency Factor Comparison2-3
Tuoie 2 2 Cancer I ottoney I actor Comparison
Table 2-3 Acute REL Comparison
Table 2-3 Acute REL Comparison2-3Table 2-4 Proposed Prohibition, sell-through, use-through2-5Table 2-5 Proposed Alternative Usage and PW-MIR VOC Limits2-7
Table 2-3 Acute REL Comparison2-3Table 2-4 Proposed Prohibition, sell-through, use-through2-5Table 2-5 Proposed Alternative Usage and PW-MIR VOC Limits2-7
Table 2-3 Acute REL Comparison2-3Table 2-4 Proposed Prohibition, sell-through, use-through2-5
Table 2-3 Acute REL Comparison2-3Table 2-4 Proposed Prohibition, sell-through, use-through2-5Table 2-5 Proposed Alternative Usage and PW-MIR VOC Limits2-7Table 2-6 Proposed Usage Limits for Aerosol Solvent Cleaners2-8
Table 2-3 Acute REL Comparison2-3Table 2-4 Proposed Prohibition, sell-through, use-through2-5Table 2-5 Proposed Alternative Usage and PW-MIR VOC Limits2-7Table 2-6 Proposed Usage Limits for Aerosol Solvent Cleaners2-8Table 2-7 PW-MIR Values for Adhesion Promoters in Rule 11512-10
Table 2-3 Acute REL Comparison2-3Table 2-4 Proposed Prohibition, sell-through, use-through2-5Table 2-5 Proposed Alternative Usage and PW-MIR VOC Limits2-7Table 2-6 Proposed Usage Limits for Aerosol Solvent Cleaners2-8Table 2-7 PW-MIR Values for Adhesion Promoters in Rule 11512-10Table 2-8 Values of Solvents used in Spray Gun Cleaner2-11

EXECUTIVE SUMMARY

Rule 1171 – Solvent Cleaning Operations (Rule 1171) was adopted in August 1991 to limit Volatile Organic Compound (VOC) emissions, toxic air contaminants, stratospheric ozone-depleting compounds, and global-warming compound emissions from solvent cleaning materials used in cleaning operations during the production, repair, maintenance, or servicing of products, tools, machinery, and general work areas. Subsequent rule amendments expanded the scope of the rule to apply to all solvent cleaning activities at all facilities.

Rule 1171 includes five primary categories of solvent cleaning activities with VOC limits and applies to any person who uses solvent cleaning materials in solvent cleaning operations during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas within South Coast Air Quality Management District (South Coast AQMD). The rule also applies to all persons who store and dispose of solvent cleaning materials used in solvent cleaning operations, and all solvent suppliers who supply, sell, or offer for sale solvent cleaning materials for use in solvent cleaning operations within the South Coast AQMD.

The current proposed rule amendments partially implement the 2022 Air Quality Management Plan (AQMP) control measure CTS-01 to address two exempt compounds that were determined to have toxic end points, including potential carcinogenicity, by the Office of Environmental Health Hazard Assessment (OEHHA): *tert*-Butyl Acetate (t-BAc), which is exempt from the definition of a VOC for certain categories of products in a few source specific rules, and parachlorobenzotrifluoride (pCBtF), which is considered exempt from the definition of a VOC for all uses within the South Coast AQMD. These exempt compounds can be utilized by manufacturers of solvent cleaning materials to formulate cleaning solvents that comply with Rule 1171 VOC content limits. The Stationary Source Committee directive on April 21, 2017, was to prioritize lowering the toxicity of coatings and solvents, even if it means increasing VOC levels. Additionally, in 2017, Assembly Bill 617 (AB 617) was signed into state law and required development of strategies to reduce toxic air contaminants and criteria pollutants in overburdened communities.

Staff's proposed changes have two primary goals: 1) a prohibition and a phase-out timeline for pCBtF and t-BAc, and 2) to address specific industry concerns regarding ability to comply with specific rule requirements. The proposed amendments to the rule include:

- Prohibiting the <u>manufacture</u> <u>use</u> of pCBtF and t-BAc <u>containing</u> solvent cleaning materials effective:
 - o January 1, 2026
 - o Sell-through allowed until January July 1, 2027
 - O Use-through allowed until January July 1, 2028
- Prohibiting the possession of non-compliant solvent cleaning materials
- Alternative usage and <u>Product Weighted-Maximum Incremental Reactivity (PW-MIR)</u> <u>VOC</u> limits for electricity and water distribution facilities
- Alternative Revised usage limits for non-compliant aerosol solvent cleaning activities and electric and water utilities products that contain VOC in excess of Table 1 VOC limits
- Alternative PW-MIR limits of 0.38 g O₃/g VOC for any solvent cleaning activity
- Alternative <u>PW-MIR</u> limits of 0.70 g O₃/g VOC for lithographic and screen printing solvent cleaning activities

•	Updating rule structure, adding new definitions, and removing outdated rule provisions
Staff do	es not anticipate any VOC emission increases or costs due to the phase out of pCBtF and
t-BAc as	s most solvent cleaning materials and not formulated with pCBtF or t-BAc.

CHAPTER 1: BACKGROUND

INTRODUCTION

REGULATORY HISTORY

2022 AIR QUALITY MANAGEMENT PLAN

ASSEMBLY BILL 617

AFFECTED INDUSTRIES

PROCESS DESCRIPTION

PUBLIC PROCESS

Introduction

Rule 1171 – Solvent Cleaning Operations is a source-specific rule adopted on August 2, 1991, to reduce Volatile Organic Compound (VOC) emissions, toxic air contaminants, stratospheric ozone-depleting compounds, and global-warming compound emissions from the use of solvents for the removal of loosely held uncured adhesives, uncured inks, uncured coatings, and contaminants from parts, products, tools, machinery, equipment and general work areas. Later rule amendments expanded the scope of the rule to apply to all solvent cleaning activities at all facilities. Rule 1171 includes five categories of solvent cleaning activities with VOC limits and applies to any person who uses solvent materials in solvent cleaning operations during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas within South Coast AQMD. The rule also applies to all persons who store and dispose of solvent cleaning materials used in solvent cleaning operations, and all solvent suppliers who supply, sell, or offer for sale solvent cleaning materials for use in solvent cleaning operations within the South Coast AOMD.

To reduce the VOC emissions from solvent cleaning materials and activities, many cleaning solvent manufacturers have relied on the use of aqueous or water-based options or through the use of solvents that are exempt from the definition of a VOC due to their low photochemical reactivity. In April 2017, the South Coast AQMD Stationary Source Committee recommended a precautionary approach when considering exempt compounds with a potential toxic endpoint and removing the exempt status for any compound that has an established toxic endpoint. The California Office of Environmental Health Hazard Assessment (OEHHA) has determined that two exempt compounds para-chlorobenzotrifluoride (pCBtF) and tert-butyl acetate (t-BAc), have toxic endpoints. Therefore, the current rule development has two primary goals: 1) to propose a phase-out of pCBtF and t-BAc, and 2) to address various industry-specific concerns regarding their ability to continue operations and comply with the rule.

Regulatory History

Rule 1171 was adopted on August 2, 1991, and has since been amended ten times. The most recent amendment was on May 1, 2009, which sought to further extend the compliance date for the 100 grams per liter VOC content limit for solvents used for the cleaning of ultraviolet/electron beam (UV/EB) inks in lithographic printing, and on-press screens and automatic screen reclamation in screen printing operations from January 1, 2009, to January 1, 2010. The amendment also sought to make administrative changes to the rule to enhance the understanding of current applicable rule requirements by removing obsolete rule language and making minor revisions and editorial corrections.

Prior to the 2009 amendment, Rule 1171 was amended in February 2008 to extend the compliance date to January 1, 2009, for the 100 grams per liter VOC content limit for solvents used for the cleaning of ultraviolet/electron beam (UV/EB) inks in lithographic printing, and on-press screens and automatic screen reclamation in screen printing operations. The delay was necessary to allow additional time for the printing industry to test new formulations and transition to the new cleaning materials. Facilities that engage in lithographic and screen printing were directly impacted by the lower VOC limit of 100 grams per liter requirement; the 2006 rule amendment delayed the implementation of the 100 grams per liter due to infeasibility for 18 months; low VOC solvent cleaning material were not available at the time and the technology assessment encountered unforeseen delays. In May 2006, the technology assessment to support the target VOC limit of 100

grams per liter for lithographic ink application was completed and the results indicated that low VOC alternative material such as water-based cleaners, blends of VOC exempt solvents, and methyl esters can be used to clean press rollers and blankets. Additional time that was provided allowed the printing industry and solvent formulators to evaluate the results of the technology assessment, develop and test new formulations, and transition to the new cleaning materials. The printing industry tested compliant products in actual production environments at various printing facilities. The test results indicated significant success in the performance of low VOC cleaning materials for removing conventional inks from rollers and blankets in lithographic in application equipment; the success was achieved for both hand wipe (manual) and automatic cleaning of rollers and blanket.

Background on t-BAc and pCBtF

In 1994, the U.S. EPA exempted pCBtF from the definition of a VOC, and in 2004, South Coast AQMD added pCBtF as an exempt VOC compound in Rule 102. A Rule 102 VOC exemption means pCBtF is not considered a VOC for any application in the South Coast AQMD.

In 2004, the U.S. EPA exempted t-BAc from the definition of a VOC, but due to toxicity concerns, the South Coast AQMD did not allow for an unlimited Rule 102 exemption but did allow for several limited exemptions in source specific rules, e.g., Rules 1113 and 1151. In 2013, the Rule 1113 amendment included a resolution that directed staff to review the exemption for t-BAc due to renewed toxicity concerns. OEHHA finalized their t-BAc assessment in 2017, concluding that it had a higher cancer potency than previously estimated. In 2018, staff presented the preliminary t-BAc assessment and expressed concerns regarding pCBtF because OEHHA had not assessed its toxicity. Based on staff recommendations, the Stationary Source Committee directed staff to: remove existing t-BAc exemption in Rules 1113 and 1151 when rules are amended and request OEHHA to review the potential toxicity of pCBtF and remove the exemption, as resources allow, if pCBtF is deemed a potential carcinogen. In 2020, the pCBtF Hot Spots cancer inhalation unit risk factor document was adopted by OEHHA, which indicated pCBtF is a potential carcinogen.

The Stationary Source Committee recommended a precautionary approach to prioritize reducing the use of compounds with a known or suspected toxic endpoint over reducing VOC emissions. Based on that recommendation, staff is working to amend each VOC rule, considering category by category, the best approach to reduce the toxicity of coatings and solvents used within the South Coast AQMD.

2022 Air Quality Management Plan

The 2022 AQMP adopted on December 2, 2022, set forth a path for improving air quality and meeting federal air pollution standards by striving for zero-NOx emission technologies across all sectors and lower VOC emissions where feasible. The 2022 AQMP includes Control Measure CTS-01 Further Emission Reductions From Coatings, Solvents, Adhesives, and Lubricants, which seeks to reduce the toxic impact of pCBtF and t-BAc emissions. PAR 1171 partially implements the 2022 AQMP Control Measure CTS-01 by prohibiting the use of solvent cleaning materials that contain pCBtF and t-BAc.

Assembly Bill 617

AB 617 was signed into state law in 2017 and requires development of strategies to reduce toxic air contaminants and criteria pollutants in overburdened communities. During the development of

the AB 617 CERP for the South Los Angeles (SLA) community, community members expressed concern about the impacts from autobody shops, many of which are located close to residents and can be clustered within the community. During the rule development for Rule 1151, staff confirmed that automotive coatings used at autobody shops contain large amounts of pCBtF or t-BAc. Autobody shops also conduct solvent cleaning activities that are subject to PAR 1171. PAR 1171 addresses the air quality commitment objectives related to the solvent cleaning operation of autobody refinishing coating application equipment by reducing toxic air emissions with the phase out of pCBtF and t-BAc.

Affected Industries

Rule 1171 is applicable to any person who uses solvent materials in solvent cleaning operations during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas as part of a business or public service; any person who stores and disposes of solvents used in solvent cleaning operations as part of a business or public service; and all solvent suppliers who supply, sell, or offer for sale solvent cleaning materials for use in solvent cleaning operations within the South Coast AQMD.

Many industries are affected by Rule 1171 and includes but are not limited to automotive refinishing, automotive repair, various types of printing, medical, pharmaceutical, electricity generation and distribution, water distribution, electronics and miscellaneous manufacturing industries.

Process Description

Solvent cleaning materials are used for many purposes including but not limited to product cleaning during manufacturing processes, surface preparation for coating, adhesive or ink application, repair and maintenance cleaning, cleaning of coatings, adhesives, resin or ink application equipment, cleaning of medical tools or devices, and general cleaning of tools, equipment or machinery. Solvent cleaning activities subject to Rule 1171 are those performed during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas as part of a business or public service within the South Coast AQMD.

Public Process

The current rule amendment process began in December 2023. Staff conducted three working group meetings and multiple individual meetings with industry stakeholders and representatives. Table 1-1 summarizes the key topics discussed at each of the Working Group Meetings, which ranged from one to three hours and included presentations that are posted on the South Coast AQMD's website.¹

¹ https://www.aqmd.gov/home/rules-compliance/rules/scaqmd-rule-book/proposed-rules/rule-1171

Table 1-1: Summary of Public Meetings

Meeting title	Date	Highlights
Working Group Meeting #1	January 16, 2024	 Rule background Key amendment objectives Exempt solvent background Preliminary technology assessments
Working Group Meeting #2	May 29, 2024	 Summary of WGM #1 Amendment progress update Industry uses of t-BAc and pCBtF Industry compliance concerns Initial rule concepts
Working Group Meeting #3	February 26, 2025	 Rule amendment resumption update Rule background refresher Key amendment objectives refresher WGM #2 summary t-BAc and pCBtF Regulatory Background Initial rule concepts
Public Workshop	March 28, 2025	 Rule background Proposed Rule Amendments Rule Language Emissions Impact Socioeconomic Assessment CEQA

CHAPTER 2: SOLVENT CLEANING ASSESSMENT

SOLVENT <u>CLEANERS AND VOC CONTROLCLEANING AND EXEMPT COMPOUNDS</u>

pCBtF and t-BAc <u>USE IN SOLVENT CLEANINGBACKGROUND AND TOXICITY</u>

SOLVENT CLEANING MATERIAL ASSESSMENT

AEROSOL USAGE EXEMPTIONAND LIQUID ALCOHOLS

PRODUCT WEIGHTED MAXIMUM INCREMENTAL REACTIVITY

Solvent Cleaners and VOC Control

Solvent cleaning materials are used in a variety of solvent cleaning activities by a wide range of industries and their associated equipment and workspaces. Solvent cleaning materials consist of a variety of different products with varying VOC contents, and can be used at industrial, commercial, and residential facilities. However, solvent cleaning activities that occur at residences are not regulated by PAR 1171 because the solvent cleaning materials used at residence are considered consumer products and regulated by the California Air Resources Board (CARB). Solvent cleaning materials subject to PAR 1171 are used during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas as part of a business or public service within the South Coast AQMD.

VOC emissions resulting from the use of solvent cleaning materials are controlled primarily by two methods. The first approach can be taken at the end-user level through improvement of work practices, including but not limited to keeping solvent containers tightly sealed or properly disposing of used solvents. The second approach includes modifying the chemistry of the solvent cleaning materials to reduce the VOC content. This approach is generally taken at the manufacturer or supplier level. Reducing the VOC content of solvent cleaning materials via reformulation can be achieved by transitioning to a water-based formulation, manufacturing with low-VOC solvent mixtures, or utilizing exempt solvents. The most widely used method for controlling VOC emissions from solvent cleaning materials is to transition to water-based systems since water has excellent cleaning properties and can be enhanced with surfactants, rust inhibitors, and rinsing agents. In these cases, the VOC limit can readily comply with the applicable 25 grams per liter VOC limit. However, for other specific solvent cleaning activities or applications it may be challenging to find suitable effective low-VOC cleaning solvents, these applications are afforded a higher limit in Rule 1171. Another option that manufacturers of solvent cleaning materials can utilize to reduce VOC content is to formulate with exempt compounds or solvents, such as acetone or para-chlorobenzotrifluoride since they do not count towards the VOC content the solvent cleaning material.

Staff is not proposing to change any of the VOC limits. The following table shows the categories and VOC limits in Rule 1171.

Table 2-1: Rule 1171 VOC Limits

Solvent Cleaning Activity	VOC Content Limit (g/L)				
(A) Product Cleaning During Manufacturing Process or Surface Preparation For Coating, Adhesives, or Ink Applications					
(i) General 25					
(ii) Electrical Apparatus Components & Electrical Components	100				
(iii) Medical Devices & Pharmaceuticals	800				
(B) Repair and Maintenance Cleaning					
(i) General	25				
(ii) Electrical Apparatus Components & Electrical Components	100				
(iii) Medical Devices & Pharmaceuticals					
(A) Tool, Equipment, & Machinery	800				
(B) General Work Surfaces	600				
(C) Cleaning of Coatings or Adhesives Application Equipment	25				
(D) Cleaning of Ink Application Equipment					
(i) General	25				
(ii) Flexographic Printing	25				
(iii) Gravure					
(A) Publications	100				
(B) Packaging	25				
(iv) Lithographic (offset) or Letterpress Printing					
(A) Roller Wash, Blanket Wash, & On-Press	100				
(B) Removable Press Components	25				
(v) Screen Printing	100				
(vi) Ultraviolet Ink/Electron Beam Ink Application Equipment (except screen printing)	100				
(vii) Specialty Flexographic Printing	100				
(E) Cleaning of Polyester Resin Application Equipment	25				

Comparing pCBtF and t-BAc toxicity to Other Compounds

Staff considered several approaches to address the toxicity concerns for pCBtF and t-BAc from removing the exempt status to a complete prohibition of use. To inform that decision, staff considered how other compounds with potential toxic endpoints have historically been addressed. Rule 102 defines exempt compounds as being Group I or Group II compounds; Group II compounds are prohibited from use in some rules. Cancer Potency Factor is a measure used to estimate the risk of cancer associated with exposure to a carcinogenic substance and represents the increased cancer risk per unit of exposure over a lifetime. Reference Exposure Level (REL) is the

maximum concentration level of a substance in the air that is not expected to have adverse health effects in humans over a specified exposure duration; RELs can be acute (short-term), 8-hour, or chronic (long-term). Four compounds and their Cancer Potency Factors and RELs are listed in Table 2-2 and 2-3 for comparison.

Compound
Cancer
Potency
Factor (Slope
Factor)

perchloroethylene (perc)

Dimethyl Carbonate
(DMC)Methylene Chloride

t-BAc

pCBtF

0.003

<u>Table 2-2 Cancer Potency Factor Comparison</u>

For the four compounds shown in the Table 2-2, pCBtF has the highest Cancer Potency Factor. The Cancer Potency Factor of pCBtF is almost 50 percent higher than perchloroethylene's, a prohibited Group II Exempt Compound.

Table 2-3 shows the available Acute RELs for the same four compounds. t-BAc has the lowest REL, meaning the highest risk among the compounds. While the Cancer Potency Factor for pCBtF is much higher than t-BAc, perc, and DMCmethylene chloride, but it has no established Acute REL.

	=
Compound	Acute REL
perc	20,000
DMCMethylene Chloride	14,000
t-BAc	10,000
pCBtF	N/A

Table 2-3 Acute REL Comparison

Staff Recommendations on pCBtF and t-BAc

The preceding comparison of pCBtF and t-BAc to other toxic compounds that are prohibited from use in VOC rules, including Rule 1171, supports a prohibition of pCBtF and t-BAc. OEHHA's assessment of pCBtF and t-BAc shows these compounds to be as toxic as many chemicals currently prohibited; therefore, staff recommends prohibiting the use of pCBtF and t-BAc.

pCBtF and t-BAc Use in Solvent Cleaning

The main objective of PAR 1171 is to prohibit the use of the two exempt compounds or partially exempt compounds that have been determined to have toxic endpoints: pCBtF and t-BAc. PAR 1171 regulates five main categories of solvent cleaning activities in which each of the main category can further be subcategorized into general and more specific solvent cleaning activities. Staff assessed solvent cleaning materials used in each of the main solvent cleaning activity categories and concluded that majority of the solvent cleaning materials used do not contain pCBtF or t-BAc, therefore a prohibition can take effect relatively quickly.

Automotive Coating Manufacturer pCBtF and t-BAc Survey

During the rulemaking for Rule 1151, staff conducted a survey of automotive coating manufacturers to further understand the extent to which pCBtF and t-BAc is used to comply with the VOC limits in Rule 1151 and for solvent cleaning activities. The survey was conducted in December 2023, of manufacturers who sell automotive coatings and products subject to Rule 1151. The main exempt compounds of interest of the survey were pCBtF and t-BAc. As part of the survey, staff requested additional information regarding solvent cleaning products used for the cleaning of automotive coating spray guns and body panels. Based on the survey data that was submitted by the manufacturers, the use of pCBtF or t-BAc was only identified in solvent cleaning materials used for automotive coating spray gun cleaning activities. However, the primary solvent used for solvent cleaning of associated spray gun equipment is acetone.

Solvent Cleaning Material Assessment and pCBtF Usage

The use of t-BAc is not common since it is not a fully exempted solvent in many South Coast AQMD regulations; it is only partially exempt in a few regulations. Since t-BAc is not considered exempted in Rule 1171, its use is still counted towards the overall VOC content. As a result, most solvent cleaning materials subject to Rule 1171 are not formulated with t-BAc. However, pCBtF is a fully exempted solvent and is used in many industries to comply with low VOC limits in many South Coast AQMD regulations. The use of pCBtF in solvent cleaning material subject to Rule 1171 is limited, staff identified three solvent cleaning operations that use solvent cleaning materials that contain pCBtF in its formulation. The three operations are automotive repair and maintenance (parts washing), offset printing (blanket and roller), and autobody repair (spray gun cleaning). Due to its exempt status, pCBtF is not considered a VOC when used in solvent cleaning material; however, it does have potential health impacts due to its toxic end point.

Rule 1171 establishes VOC limits for all solvent cleaning activities identified in the rule. As previously mentioned, achievement of the target VOC limits is expected through greater use of aqueous or water-based cleaning technologies and VOC exempt solvents, through development of new cleaning materials. All of the VOC limits established in the 1999 amendment for Rule 1171 have now been implemented, including ink application equipment which initially encountered challenges in meeting the lower limit. The printing industry has been largely successful in its efforts for finding suitable low VOC solvent cleaning materials and is a prime example of what research and development can achieve. Most recently members of the printing industry have requested an alternative reactivity-based limit to provide additional compliance flexibility in developing solvent cleaning material formulations; giving the industry ability to provide and use more effective solvent cleaning material and provide additional options.

As mentioned previously, the printing industry was given additional time to test many compliant products in actual production environments which showed that water-based cleaners, blend of other exempt solvents, and methyl esters can be successfully used to clean press rollers and blankets. Staff also conducted several visits to autobody facilities which showed the most common lower cost and pCBtF free options used to clean spray guns is acetone; this was also confirmed in the survey that was conducted for Rule 1151 in December 2023. Automotive repair and maintenance facilities use a pCBtF containing solvent to washing parts or components during transmission or engine repairs; the solvent cleaning material contains 95 percent pCBtF by volume and the intended use of the product is for cleaning and degreasing metal parts for the removal of adhesives, carbon deposits, greases, mold release, oils, and waxes. The manufacturer indicated they primarily rely on pCBtF to comply with the current Rule 1171 VOC limits of 25 grams per liter and that the customer base for the pCBtF containing cleaning material is relatively small and limited to parts washing for transmission and engine repair. The manufacturer indicated that existing customers using the pCBtF containing solvent can be transitioned to a replacement solvent cleaner that is free of pCBtF but would require time to completely transition and replace the existing product.

Staff will be proposing a prohibition of pCBtF and t-BAc that includes sell-through and use-through periods for solvent cleaning materials already in the supply chain in order to prevent stranded assets associated with existing inventory. The sell-through and use-through is for any solvent cleaning material that is manufactured prior to the proposed prohibition date of January 1, 2026. The following table provides a summary of the proposal.

Catagomy	Prohibition	Sell-through	Use-through
Category	Effective Date	End Date	End Date
All Solvent		TananamaTalas 1	T T. 1
Cleaning Activities	January 1, 2026	January July 1,	January July 1,
listed in Table 1		2027	2028

Table 2-4 Proposed Prohibition, sell-through, use-through

Aerosol Usage Exemption

Rule 1171 provides an exemption for the use of 160 ounces or less per day of aerosol solvent cleaning products that contain VOC in excess of the limits listed in Table 1 – Table of Standards in the Rule. Aerosol solvent cleaning materials are regulated by the California Air Resources Board and are not required to comply with the VOC limits of Rule 1171; however, Rule 1171 can limit the amount of aerosol solvent that can be used at permitted facilities. Several industries and businesses have indicated that they are currently using and rely on the aerosol exemption for cleaning of specific equipment, while others have indicated that the exemption does not reflect the current operation of their business. Electricity generating and distribution, water distribution, water treatment facilities, battery manufacturing facilities, and automotive repair industry have expressed concerns regarding the current exemption. Staff is proposing to reduce the amount of non-compliant aerosol solvent cleaning products from 160 ounces a day to 1,750 ounces a month.

Aerospace Facilities, Electricity Generating and Distribution, Water Treatment, and Water Distribution

Electricity generating and distribution, water distribution, and water treatment facilities that operate similar equipment currently rely on the aerosol exemption and use aerosolized, alcoholbased solvent cleaning products to clean specific equipment. Many electricity distribution facilities use aerosolized denatured alcohols to clean circuit breaker components such as driving mechanisms and interrupters, as specified by equipment manufacturers. Staff has identified other solvent cleaning materials that can potentially be used to clean the equipment such as dry ice or acetone; however, the equipment manufacturer will not approve the use cleaners that have not been tested; use of untested cleaners can potentially cause safety issues. Furthermore, industry stakeholders expressed concern regarding the availability of denatured alcohol in aerosol spray form since there have been times when it was unavailable. Due to the uncertainty of availability, stakeholders requested the ability to use liquid denatured alcohol or liquid isopropyl alcohol instead of aerosol denatured alcohol. The rule currently allows approximately 456 gallons of denatured alcohol per year in aerosol form, but based on feedback from industry stakeholders, the estimated use of denatured alcohol in liquid form is approximately 70 gallons per year for all large utilities under common ownership. Staff is recommending to allow up to 70 gallons of liquid alcohol use for cleaning and including a maximum incremental reactivity (PW-MIR) VOC limit to reduce the ozone forming potential of the cleaning solvent to the alcohols currently being used. A discission of PW-MIR based-VOC limits is included later in this chapter. Table 2-5 shows the proposed volume and product weighted-MIR limits (PW-MIR).

Similarly, water distribution and water treatment facilities also requested the use of non-compliant liquid denatured alcohols to clean specific equipment such as ozone generators, UV sterilization systems, chlorine systems, and electrical components. Based on the information provided to staff by the facilities, the equipment manufacturers specify using only denatured alcohol for cleaning the specific equipment. Manufacturers of this equipment have indicated that they have not identified suitable, compliant, non-aerosol solvent cleaning alternatives due to insufficient cleaning ability and/or remaining residue that may impact equipment operation and/or safety. Based on facility feedback, the estimated alcohol usage amounts at each facility are:

- Ozone generators at approximately 15 gallons per generator every 10 years and the facilities have several ozone generators
- UV sterilization at approximately five ounces per reactor with a total of 29 reactors every month
- Chlorine system at approximately five gallons per facility per year and can be up to 6 facilities
- Electrical components at approximately five gallons per year per facility

Staff is recommending allowing up to 70 gallons of liquid alcohol use for cleaning of specific equipment located at electricity and water distribution utility operations. Staff will also include a separate usage limit for chlorination systems, ozone generators, ultraviolet light treatment systems, and chlorination systems. Ozone generators and ultraviolet treatment systems will be allowed a usage limit of 40 gallons and 30 gallons, respectively. Chlorination systems will be provided a usage limit of five gallons per year and all solvent cleaning activities will also include a PW-MIR limit to reduce the ozone forming potential of the cleaning solvent to the alcohols currently being used; the two types of alcohol that are currently being used are isopropyl alcohol and denatured

alcohol. Isopropyl alcohol has a MIR value of 0.61 whereas the MIR value of denatured alcohol can vary based on composition. The composition of denatured alcohol can vary by manufacturer, so staff evaluated the composition of several commercial denatured alcohol products to estimate a range of potential PW-MIR values; the PW-MIR values ranged from 0.94 to 1.7. As a result, staff is proposing a PW-MIR limit at the upper limit of 1.7 which will provide flexibility to the facility. Using the upper limit will allow the facility to use denatured alcohol from several manufacturers. Staff acknowledges that as technology matures, and as treatment capacity and water demand grows, facilities may need to increase the amount of solvent cleaning materials used to maintain equipment in acceptable operating condition. Staff recommends addressing this matter in the future should the need arise. Table 2-5 shows the proposed usage volume and PW-MIR limits.

Table 2-5 Proposed Alternative Usage and PW-MIR VOC Limits

Solvent Cleaning Activity	Usage Limits (gallons per year)	PW-MIR VOC Limit
(A) Electricity Generating or Distribution Equipment	70	1.7
(B) Water Distribution Equipment		
(i) Chlorination Systems	5	1.7
(ii) Ozone Generators	40	1.7
(iii) Ultraviolet Light Treatment Systems	30	1.7

Metric used to qualify for aerosol exemption (fluid ounces versus ounces)

In regard to the aerosol exemption, staff is also proposing to change the metric used to qualify for the exemption from fluid ounces to ounces. Fluid ounces are not a unit of weight and is used to measure volume of a liquid and does not align with the California Air Resources Board (CARB) definition for VOC content of an aerosol product. CARB defines the VOC content of an aerosol product as the total weight of VOC in a product expressed as a percentage of the product weight. Since aerosol products sold for use must comply with CARB's consumer product regulation, most aerosol cans sold in California will have labels that display weight in ounces and/or grams.

Automotive Repair Facilities and Battery Manufacturing Facilities

Most of the solvents used for automotive parts washing are aqueous products or are compliant with the 25 grams per liter VOC limit; however, automotive repair facilities also rely on the exempted use of aerosol solvent cleaning products that contain VOC in excess of VOC limits for small solvent cleaning activities, such as adhesive removal, and for the cleaning of intake throttle body automotive components. Battery manufacturers also rely on this exemption to clean grease or other contaminants from battery terminals. Industry stakeholders indicated that they have tested

compliant alternative cleaning products but have not found a suitable replacement that meets the operational and performance requirements. The aerosol solvent cleaning products used for these cleaning operations have a VOC content greater than 25 grams per liter limit of the rule and usage will vary depending on the volume of cars serviced or the amount of batteries manufactured. A high-volume car service dealership typically needs approximately 4,500 ounces per month of noncomplaint aerosol for intake/throttle body cleaning whereas aerosol cleaning solvents used for adhesive removal require a much smaller amount of approximately 75 ounces per year. Battery manufacturers use approximately 2,400 ounces per month to clean the terminals during the battery manufacturing process. The rule currently provides a daily aerosol limit that equates to a 4,800 ounces per month allowance; however, stakeholders expressed concern that the daily allowance does not reflect current operational needs. Stakeholders requested that the allowance for noncomplaint aerosols be changed to a monthly limit rather than a daily limit to provide additional flexibility to the facilities. Aerospace facilities also expressed concerns for cleaning similar equipment as the electricity and water distribution utilities. They indicated that they do not intend to use liquid cleaners but will continue to rely on use the aerosol exemption for their cleaning needs, instead of transitioning to liquid cleaners, but need at least 160 ounces per month of aerosols to clean their electrical equipment. This change would not increase or change the overall usage volume and merely provide flexibility to the facility. Staff's assessment did not identify any low VOC alternatives for these specific cleaning operations. As a result, staff is proposing to revise the current aerosol allowances to reflect the operational needs for auto repair facilities and battery manufacturers, as shown in Table 2-6.

Table 2-6 Proposed Usage Limits for Aerosol Solvent Cleaners

Solvent Cleaning Activity	Usage Limits	
(A) Cleaning of Automotive Parts		
(i) Throttle Body and Intake Systems	4,800 ounces per month	
(ii) All Other Automotive Part Cleaning	32 ounces per month	
(B) Battery Terminal Cleaning at Battery Manufacturing Facilities	2,400 ounces per month	
(C) All Others Solvent Cleaning Activities	1,750 ounces per month	

Product-Weighted Maximum Incremental Reactivity

Many stakeholders have requested that PAR 1171 also includes a general alternative PW-MIR VOC limit of 0.38 g O₃/g VOC for all solvent cleaning activities and an alternative PW-MIR for cleaning of ink application equipment for lithographic and screen printing operations. Staff is proposing an alternative PW-MIR limit of 0.70 g O₃/g VOC for cleaning activities subject to Table 1 (D)(iv)(A), lithographic or letter<u>press</u> press-printing for roller wash, blanket wash, and on-press components ink application equipment cleaning, and Table 1 (D)(v) screen printing ink application equipment cleaning. Alternative PW-MIR limits were introduced in Rule 1151- Motor Vehicle and Mobile Equipment Non-Assembly Line Coating Operations for a few categories to provide

manufacturers additional flexibility to develop alternative compliant formulations with less impact on ozone formation. Traditional mass-based VOC limits treat all VOCs equal, other than water and exempt compounds which are excluded. However, research² has shown that different solvents have varying potentials to form ground-level ozone. The MIR scale measures the relative ozone-forming potential of VOCs, offering a more nuanced approach than traditional mass-based limits. By using a PW-MIR VOC limit, one can account for the differences in reactivity, ensuring that products with more reactive VOCs are more strictly regulated, while less reactive VOCs are afforded some flexibility. The California Air Resources Board (CARB) published MIR values for various VOCs, which have been instrumental in developing these limits³.

As an example, a PW-MIR analysis was conducted in Rule 1151 for the adhesion promoter coating category. Adhesion promoters are typically used to facilitate bonding of paint to plastic automotive parts; adhesion promoters usually consist of a low-solids formulation composed primarily of solvents. One of the primary solvents used is t-BAc but with the prohibition of pCBtF and t-BAc, manufacturers were limited in solvent options to comply with the traditional mass-based limits. For the analysis, staff utilized survey data and online searches to identify adhesion promoters sold within the South Coast AQMD, identifying 15 such products. To gather detailed VOC information for each product, staff reviewed the Safety Data Sheets for all 15 adhesion promoters. Using the CARB MIR values, staff calculated the PW-MIR for each product. In cases where VOC compounds were reported as a range, staff calculated an average PW-MIR based on the mid-point of the reported range, as well as a maximum PW-MIR using the highest reported value for each VOC compound. After calculating the average and maximum PW-MIR values for all the products, staff performed a statistical analysis to propose an appropriate PW-MIR limit for adhesion promoters. Table 2-7 lists the products staff considered; included are the weight percentages (wt%) for pCBtF and t-BAc in those products, as those solvents have very low MIR values. Staff put more emphasis on adhesion promoters without pCBtF and t-BAc to more accurately reflect the potential PW-MIR of these products once those exempt solvents are prohibited.

.

² Carter, William P.L., College of Engineering, Center for Environmental Research and Technology, The SAPRC-99 Chemical Mechanism and Updated VOC Reactivity Scales, February 2023

³ California Air Resources Board (CARB), "Tables of Maximum Incremental Reactivity (MIR) Values", available at https://ww2.arb.ca.gov/sites/default/files/2020-12/cp_reg_mir-tables.pdf

Table 2-7 PW-MIR Values for Adhesion Promoters in Rule 1151

PRODUCT	Regulatory VOC As Applied (g/L)	pCBtF (wt %)	t-BAc (wt %)	PW-MIR with Average VOC Content (g O ₃ /g VOC)	PW-MIR with Max VOC Content (g O ₃ /g VOC)
Product 1	540	87.8	0	0.26	0.36
Product 2	526	0	58.1	1.22	1.75
Product 3	540	0	0	1.35	1.68
Product 4	537	3.1	22	2.72	3.21
Product 5	508	86.9	0	0.35	0.51
Product 6	540	82.8	0	0.4	0.56
Product 7	537	55.8	0	0.49	0.62
Product 8	520	54.8	0	1.42	1.81
Product 9	516	49.4	0	0.16	0.2
Product 10	517	49.3	0	0.37	0.56
Product 11	511	33.9	0	0.47	0.74
Product 12	533	3.5	20.2	2.69	3.17
Product 13	526	0	58.1	1.22	1.75
Product 14	529	0	20	2.68	3.16
Product 15	540	0	0	1.35	1.68

In addition to this assessment, a manufacturer of an adhesion promoter provided data on their potential future non-pCBtF/t-BAc formulation and indicated it could achieve a PW-MIR of between $2.0-2.5~{\rm g}$ O₃/g VOC, which supports staff's assessment and proposed limit for adhesion promoters in Rule 1151.

The proposed PW-MIR limits for alcohol related solvent cleaning activity in PAR 1171 are in Table 2-5. The PW-MIR limits are designed to achieve equal or greater reductions in ground-level ozone compared to traditional mass-based VOC limits because VOCs with the greatest ozone forming potential will be limited rather than treating each VOC equally; this offers more flexibility in product reformulation. The use of PW-MIR is presented as an option rather than a requirement; the PW-MIR approach provides manufacturers with greater flexibility in reformulating their products. It is also important to note that a product complying with the proposed PW-MIR limit can potentially have a higher mass-based VOC content (g/L) than the limits in the Table of Standards in the rule.

As the South Coast AQMD phases out of exempt solvents such as pCBtF and t-BAc, a mechanism to reduce the air quality impact of solvent cleaning operations is to develop PW-MIR limits. The solvent cleaning materials will continue to have a mass-based VOC limit; however, the new PW-MIR limit may potentially result in less ground-level ozone formation. In essence, reactivity-based limits would require manufacturers to choose solvents with lower MIR value. One of the solvent cleaning materials evaluated by staff was an automotive spray gun cleaner used at autobody repair facilities; a facility can either choose to use a specialty spray gun cleaner that is comprised of a mixture of solvents or acetone. Acetone has a MIR value of 0.36 and a lower potential for ozone formation whereas the specialty spray gun cleaner is only slightly higher. To gather detailed VOC information for the product, staff conducted online searches and also reviewed the technical and safety data sheets for the specialty spray gun cleaner. Using the CARB MIR values, staff calculated the PW-MIR for the product. In cases where VOC compounds were reported as a range, staff determined the PW-MIR based on the upper end of the reported range. Table 2-8 shows staff's assessment of the PW-MIR of a spray gun cleaner that would not meet the mass-based limit of 25 g/L but will comply with the proposed PW-MIR limit of 0.38. The spray gun cleaner is a mixture of acetone and alkanes and has a VOC content of 36 g/L which is higher than the VOC limit of 25 g/L allowed in the rule. The evaluation showed that despite having a higher VOC content limit allowed in the rule, the PW-MIR limit of the cleaner is 0.38 which is similar to the MIR value of acetone. Providing a slightly higher alternative PW-MIR limit at 0.38 will give the manufacturer formulation flexibility to meet the performance requirements of the specific solvent cleaning activity.

Weight **Solvent MIR PW-MIR Percent** 0.52 0.03 **Alkanes** 3% 97% 0.36 0.35 Acetone **Total** 100% 0.38

Table 2-8 Values of Solvents used in Spray Gun Cleaner

Potential Ozone Reduction Benefit

By adopting a PW-MIR approach instead of relying solely on mass-based VOC limits measured in grams per liter, the regulatory framework can be better aligned with air quality goals while providing manufacturers with increased flexibility. The PW-MIR approach offers flexibility, allowing manufacturers to explore various formulations without being restricted by a single mass-based VOC limit. This encourages innovation and the development of products that meet regulatory requirements while enhancing performance and reducing environmental impact. Stakeholders that are developing solvent cleaning material also requested that an alternative PW-MIR limit be incorporated since some formulations may not comply with the mass-based limit but would comply with a PW-MIR limit. For the general alternative PW-MIR limits, the stakeholder

indicated that their formulation is comprised primarily acetone with a small mixture of other solvents with an approximate PW-MIR of 0.38. Since acetone is an exempt compound and has a MIR value of approximately 0.4, staff is proposing an alternative PW-MIR limit of 0.38 g O₃/g VOC for all solvent cleaning activities to provide formulation flexibility. For the alternative PW-MIR limit for cleaning lithographic and screen printing ink application equipment, staff consulted with several solvent cleaning manufacturers to determine the PW-MIR limits that would have equivalent or less ozone formation potential than the current 100 g/L VOC limit. Existing solvent cleaning materials were not formulated with the goal of reducing reactivity, so some existing cleaning materials have a very high PW-MIR; however, some solvent cleaners have been formulated to reduce reactivity. Looking at the range of solvents used for cleaning printing equipment and considering what the manufacturers think can be formulated to efficiently clean the equipment, staff is proposing a 0.70 g O₃/g VOC limit. The proposed limit is an alternative limit so facilities can continue to use the 100 g/L mass-based VOC limit that has been in place for 15 years. The alternative is meant to provide flexibility without increasing the ozone formation potential of the cleaning solvents.

Enclosed Mobile Containers Used to Transport Material

Some solvent cleaning operations utilize biodiesel as a solvent cleaning material to clean large enclosed mobile containers used to transport materials. These containers include, but are not limited to, rail tank cars and tanker truck containers. Biodiesel is used as the cleaning agent to remove any residual commodity (known as "heel") remaining in an empty container. This cleaning system works for various commodities requiring cleaning from enclosed containers, such as asphalt, crude oil, and fertilizers.

These solvent cleaning systems are generally closed loop systems, where a nozzle is attached to the top hatch of an enclosed container, forming a sealed high-pressure wash and rinse system that dissolves and dislodges the heel, then removes the residual wash solution through successive high-pressure rinses. The solvent cleaning wash solutions sprayed inside the railcar are pumped from the enclosed container to a holding tank in a closed loop recirculating system. Spent wash solutions are typically pumped from the storage tank into a tank truck for transport to a commercial waste management facility.

Because there is no established VOC content for biodiesel and because the VOC content of biodiesel can vary, staff is proposing an alternate compliance option for solvent cleaning activities that utilize biodiesel as a solvent cleaning material and that are performed on enclosed mobile containers used to transport material. The proposed alternate compliance option includes requiring the container to be completely airtight and leak free during the solvent cleaning activity and ensuring that all vapor leaks from fugitive components do not exceed a concentration of 50 parts per million calculated as carbon and testing requirements to ensure compliance.

CHAPTER 3: SUMMARY OF PROPOSALS

INTRODUCTION
PROPOSED AMENDED RULE STRUCTURE
PROPOSED AMENDED RULE 1171

Introduction

The main objective of the proposed amendments to Rule 1171 is to phase out the use of pCBtF and t-BAc as solvents in solvent cleaning materials, as directed by the South Coast AQMD's Stationary Source Committee, due to toxicity concerns.

Staff is proposing the following amendments to Rule 1171. The proposed amendments primarily pertain to the prohibition of pCBtF and t-BAc use in the regulated products and the introduction of various types of alternative compliance options, including reactivity-based limits and volumetric usage limits. Some other amendments are for the purpose of rule clarification or streamlining. The proposed revised rule structure and key provisions are discussed in the following sections.

Proposed Amended Rule Structure

- (a) Purpose
- (b) Applicability
- (c) Definitions
- (d) Requirements
- (e) Alternative Compliance Options
- (f) General Prohibitions
- (g) Recordkeeping Requirements
- (h) Test Methods
- (i) Rule 442 Applicability
- (j) Exemptions

Proposed Amended Rule 1171

Purpose [Subdivision (a)]

The purpose of this rule is to reduce emissions of VOCs, toxic air contaminants, stratospheric ozone-depleting compounds, and global-warming compounds from the use, storage and disposal of solvent cleaning materials used in solvent cleaning activities performed in South Coast AQMD.

No significant revisions were made to this subdivision. The subdivision previously combined with the following Applicability subdivision; however, staff separated the two into separate subdivisions to be consistent with the structure of similar rules. Staff capitalized defined terms to indicate that definitions for the associated terms can be found in the Definitions subdivision.

Applicability [Subdivision (b)]

PAR 1171 applies to any person who uses solvent cleaning materials in solvent cleaning operations during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas within South Coast AQMD at public service facilities or facilities that are a part of a business or businesses. The rule also applies to all persons who store and dispose of solvent cleaning materials used in solvent cleaning operations, and all solvent suppliers who supply, sell, or offer for sale solvent cleaning materials for use in solvent cleaning operations within the South Coast AQMD.

No significant revisions were made to this subdivision. Staff capitalized defined terms to indicate that definitions for the associated terms can be found in the definition's subdivision.

Definitions [Subdivision (c)]

To provide clarity, definitions are used in the proposed amended rule as a proper noun to better distinguish defined terms from common terms. Refer to PAR 1171 for a complete list of definitions.

The following are new and modified definitions for PAR 1171, including some that distinguish the new solvent cleaning activities and associated equipment and facility types. For all definitions, refer to the preliminary draft of PAR 1171 released with the Staff Report. Accordingly, the following definitions will be added:

AEROSOL PRODUCT in paragraph (c)(1), which means:

"a hand-held, non-refillable container that expels pressurized product by means of a propellant-inducted force. Aerosol Product does not include pump spray devices, which are packaging systems in which the product ingredients, or Solvent Cleaning Materials, are expelled only while a pumping action is applied to a button, trigger, or other actuator. Ingredients in a pump spray device are not under pressure.

AUTOMOTIVE PART in paragraph (c)(4), which means:

"any individual mechanical component that that is part of a vehicle that allows the vehicle to operate, including but not limited to, engine components, transmission components, suspension components, brake components, and intake system components."

BATTERY TERMINAL in paragraph (c)(5), which means:

"the electrical contact or component of a battery that connects the battery to a charger, device, other battery, or external electrical circuit and transfers energy."

CHLORINATION SYSTEM in paragraph (c)(8), which means:

"a chlorine feed system used for the oxidation of microbiological material, organic compounds or inorganic compounds during the water or wastewater treatment process. Chlorine can be in the form of gaseous chlorine, sodium hypochlorite, or calcium hypochlorite."

CURED COATING, CURED INK, OR CURED ADHESIVE in paragraph (c)(9), which means:

"a coating, ink, or adhesive, that is dry to the touch, and that has undergone a chemical or physical process to achieve its final state and does not release volatile components under normal use conditions."

ELECTRICITY DISTRIBUTION UTILITY in paragraph (c)(11), which means:

"one of several organizations that control energy transmission and distribution in California, including, but not limited to, the Pacific Gas and Electric Company, the San Diego Gas and Electric Company, Southern California Edison, Los Angeles Department of Water and Power, the Imperial Irrigation District, and the Sacramento Municipal Utility District."

ELECTRICITY GENERATING FACILITY in paragraph (c)(12), which means:

- "(A) A facility that is owned or operated by an investor-owned electric utility or a publicowned electric utility and has one or more electric generating units; or
- (B) A facility that has electric generating units for onsite use or distribution in the state or local electrical grid system.

Electricity Generating Facility does not include facilities subject to Rule 1109.1 – Emissions of Oxides of Nitrogen from Petroleum Refineries and Related Operations."

EMISSION CONTROL SYSTEM in paragraph (c)(14), which means:

"any combination of capture systems and control devices used to reduce VOC emissions."

ENERGY CURABLE INK in paragraph (c)(15), which means:

"an ink that dries upon exposure to visible-light, ultra-violet light, or an electron beam."

INK APPLICATION EQUIPMENT in paragraph (c)(26), which means:

"any tool, machine, system, or component of any tool, machine, or system used to apply ink to a substrate."

MAXIMUM INCREMENTAL REACTIVITY (MIR) in paragraph (c)(35), which means:

"the measure of the photochemical reactivity of a VOC, which estimates the weight of ozone produced from a weight of VOC expressed as gram of ozone per gram of VOC (g O_3/g VOC). MIR values for individual VOCs are specified in sections 94700 and 94701, Title 17, California Code of Regulations."

NON-LEAKING CONTAINER in paragraph (c)(39), which means:

"a container that can hold liquids without leaking and is designed to prevent liquids, vapors, or any other contents from escaping through its seams, closures, or any other openings, ensuring secure storage or transport."

OZONE GENERATOR in paragraph (c)(42), which means:

"a mechanical system that produces ozone used for water or wastewater treatment. Ozone is produced by applying an electric potential or ultraviolet light to oxygen that can be either in the form of dry air or pure oxygen. "Ozone Generator" includes the associated oxygen supply equipment that is used to produce ozone."

PERSON in paragraph (c)(44), which means:

"as defined in Rule 102."

PRESS in paragraph (c)(47), which means:

"a mechanical device used to apply pressure to an inked surface resting on a substrate to transfer color, design, alphabetical text, or numerals to the substrate."

PUBLIC WATER SYSTEM in paragraph (c)(49), which means:

"a system that provides water for human consumption through pipes or other constructed conveyances that has fifteen or more connections or regularly serves at least twenty-five individuals daily at least sixty days out of the year."

PRODUCT-WEIGHTED MIR (PW-MIR) in paragraph (c)(50), which means:

"the sum of all weighted-MIR for all ingredients in a Regulated Product. The PW-MIR is the total product reactivity expressed to hundredths of a gram of ozone formed per gram of product (excluding container and packaging) and calculated according to the following equations:

Weighted MIR (Wtd-MIR) ingredient = MIR x Weight fraction ingredient,)

and,

 $PW\text{-}MIR = (Wtd\text{-}MIR)_1 + (Wtd\text{-}MIR)_2 + ... + (WtdMIR)_n$

where,

MIR = ingredient MIR; and

1,2,3,...,n = each ingredient in the product up to the total n

ingredients in the product."

SOLVENT CLEANER OR SOLVENT CLEANING MATERIAL in paragraph (c)(60), which means:

"a liquid substance used to perform Solvent Cleaning."

SOLVENT CLEANER SUPPLIER in paragraph (c)(61), which means:

"any person who sells and delivers or arranges to deliver Solvent Cleaning Materials to a facility subject to this rule."

SOLVENT CLEANING in paragraph (c)(62), which means:

"the use of a Solvent Cleaner or Solvent Cleaning Material for the removal of loosely held uncured adhesives, uncured inks, uncured coatings, and contaminants that include, but are not limited to, dirt, soil, and grease from parts, products, tools, machinery, equipment, and general work areas. Each distinct method of Solvent Cleaning shall constitute a Solvent Cleaning Activity."

SOLVENT CLEANING ACTIVITY in paragraph (c)(63), which means:

"a distinct method of cleaning in a Solvent Cleaning process or single event."

SOLVENT CLEANING OPERATION in paragraph (c)(64), which means:

"a Solvent Cleaning Activity or Solvent Cleaning Activities conducted as part of a business or a public service."

SOUTH COAST AQMD TEST METHOD in paragraph (c)(66), which means:

"a test method included in the manual of "Laboratory Methods of Analysis for Enforcement Samples," which can be found on the South Coast AQMD website and are referenced in subdivision (h)."

THROTTLE BODY in paragraph (c)(72), which means:

"a component of a vehicle air intake system, and is located between the air intake filter and intake manifold of the vehicle air intake system, and controls the amount of air that flows into the vehicle engine."

ULTRAVIOLET LIGHT TREATMENT in paragraph (c)(73), which means:

"the process of using ultraviolet light to inactivate microorganisms (i.e., disinfection) or using ultraviolet light either with or without the addition of peroxide to oxidize contaminants (i.e., oxidation). Ultraviolet light treatment is used for both potable water and wastewater, including indirect and direct potable water reuse projects."

WATER TREATMENT FACILITY in paragraph (c)(75), which means:

"a public entity that is responsible for water delivery operations, sewage pumping plants, sewage treatment, or water reclamation."

Requirements [Subdivision (d)]

This subdivision contains the provisions for any person who uses solvent cleaning materials in solvent cleaning operations or solvent cleaning activities, and for any person who supplies solvent cleaning materials.

Paragraph (d)(1) - PAR 1171 VOC Content Limits

PAR 1171 establishes VOC content limits and for solvent cleaning activities by category, as summarized in PAR 1171 Table 1 – Table of Standards. The following table provides a summary of the current VOC content limits, staff is not proposing to change any of the current limits. The inclusion of a VOC limit for the cleaning of energy curable lamps and reflectors under ink application equipment is based on manufacturer recommended cleaning and is considered negligible based on the small amount of solvent used and infrequency of equipment cleaning.

Based on the future effective phase out dates, solvent cleaning materials complying with VOC limits will be prohibited from containing pCBtF or t-BAc.

Table 3-1: Summary of the VOC Content Limits

SOLVENT CLEANING ACTIVITY		VOC Limits	
SOLVENT CLEANING ACTIVITY	g/L	lbs/gal	
(A) Product Cleaning During Manufacturing Process, or Surface Prepara Adhesive, or Ink Application	tion for	Coating,	
(i) General	25	0.21	
(ii) Electrical Apparatus Components & Electronic Components	100	0.83	
(A) Printed Circuit Boards	800	6.7	
(iii) Medical Devices & Pharmaceuticals	800	6.7	
(B) Repair and Maintenance Cleaning			
(i) General	25	0.21	
(ii) Electrical Apparatus Components & Electronic Components	100	0.83	
(A) Electronic or Electrical Cables	400	3.4	
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800	6.7	
(B) General Work Surfaces	600	5.0	
(C) Cleaning of Coatings or Adhesives Application Equipment			
(i) General	25	0.21	
(ii) Thin or Sheet Metal Laminating Equipment	950	8.0	
(D) Cleaning of Ink Application Equipment			
(i) General	25	0.21	
(ii) Flexographic Printing	25	0.21	
(iii) Gravure Printing			
(A) Publication	100	0.83	
(B) Packaging	25	0.21	
(iv) Lithographic (Offset) or Letter <u>press</u> Printing	I	1	
(A) Roller Wash, Blanket Wash, & On-Press Components	100	0.83	
(B) Removable Press Components	25	0.21	
(v) Screen Printing	100	0.83	
(vi) Energy Curable			
(A) Ink Application Equipment (except Screen Printing)	100	0.83	
(B) Lamps and Reflectors	800	6.7	
(vii) Specialty Flexographic Printing	100	0.83	
(E) Cleaning of Polyester Resin Application Equipment	25	0.21	

<u>Paragraph (d)(2) – Cleaning Devices and Methods Requirements</u>

Staff removed language referencing an Office of Operations' manual listing approved devices for solvent cleaning activities that was to be periodically updated by the Executive Officer previously in subparagraph (d)(2)(D). Staff confirmed that this manual no longer exists. Staff added language to clarify acceptable wipe cleaning solvent cleaning methods.

<u>Subparagraph (d)(2)(G) – Hand-held Spray Devices</u>

Subparagraph (d)(2)(G) outlines the conditions under which the use of pressurized hand-held spray devices to perform solvent cleaning activities are an approved solvent cleaning method. These conditions include that these devices shall only be used at either electricity distribution utilities, electricity generating facilities, water treatment facilities, or water distribution equipment supporting a public water system. The amount of solvent cleaning materials used in these devices must comply with the volumetric usage limits and the solvent cleaning materials must also comply PW-MIR VOC limits pursuant to paragraph (e)(2).

<u>Paragraph (d)(5) – Solvent Cleaning Material Labeling Requirements</u>

In paragraph (d)(5), staff moved solvent cleaning material labeling requirements from the General Prohibitions subdivision to the Requirements subdivision and added a subparagraph requiring solvent cleaning materials that comply with an alternative PW-MIR VOC limit to have a label on the solvent cleaning material container that includes the PW-MIR of the solvent cleaning material.

Alternative Compliance Options [Subdivision (e)]

This subdivision contains the provisions for any person that chooses to comply with the provisions of paragraph (d)(1) by using an approved emission control system or complying with the applicable proposed volumetric usage limits or alternative PW-MIR limit.

Subdivision (e) was previously a paragraph in the preceding subdivision and is now its own standalone subdivision. Staff moved this language for better readability and consistency.

Subparagraph (e)(1)(D) – Cleaning of Enclosed Mobile Containers

Subparagraph (e)(1)(D) outlines the requirements for an alternative compliance option for the cleaning of the internal surfaces of enclosed mobile containers used to transport materials. These enclosed containers include but are not limited to rail tank cars and tanker truck containers.

In lieu of complying with the requirements in paragraph (d)(1), subparagraph (e)(1)(D) allows a person to comply with a measuring requirement and output limit of no more than 50 parts per million of VOC calculated as carbon on a South Coast AQMD organic vapor analyzer at all fugitive components, provided that the enclosed container and system is air-tight and leak-free during solvent cleaning activities. For the purpose of this cleaning activity, the air-tight and leak-free enclosed container shall be considered emission control equipment.

Paragraph (e)(2) – Alternative Limits for Electricity and Water Utilities

Paragraph (e)(2) outlines alternative options for the cleaning of specific equipment associated with electricity generation and distribution, water treatment and water distribution utilities. These

options include volumetric usage limits for solvent cleaning materials that exceed VOC limits in paragraph (d)(1) in addition to a PW-MIR incremental reactivity limit.

The proposed PW-MIR limits are based on industry feedback and the solvent cleaning materials reportedly used. This alternative compliance option will require monthly recordkeeping requirements for a minimum of five years and PW-MIR labeling on solvent cleaning material containers.

Table 3-2 Proposed Alternative Usage and PW-MIR VOC Limits

Solvent Cleaning Activity	Usage Limits (gallons per year)	PW-MIR VOC Limit
(A) Electricity Generating or Distribution Equipment	70	1.7
(B) Water Distribution Equipment		
(i) Chlorination Systems	5	1.7
(ii) Ozone Generators	40	1.7
(iii) Ultraviolet Light Treatment Systems	30	1.7

Paragraph (e)(3) – Alternative Limits for Aerosol Solvent Cleaning Materials

Paragraph (e)(3) outlines alternative options for the cleaning of automotive parts, battery terminals, and all other solvent cleaning activities. These options include usage limits for aerosol solvent cleaning products that exceed VOC limits in paragraph (d)(1).

Solvent Cleaning Activity	Usage Limits
(A) Cleaning of Automotive Parts	
(i) Throttle Body and Intake Systems	4,800 ounces per month
(ii) All Other Automotive Part Cleaning	32 ounces per month
(B) Battery Terminal Cleaning at Battery Manufacturing Facilities	2,400 ounces per month
(C) All Others Solvent Cleaning Activities	1,750 ounces per month

Table 3-3 Aerosol Solvent Cleaner Usage Limits

The proposed usage limits are based on industry feedback and reported usage. This alternative compliance option will require monthly recordkeeping requirements for a minimum of five years [90 Days after Date of Rule Adoption] and will require that all aerosol solvent cleaning products comply with applicable CARB regulations.

<u>Paragraph (e)(4) – Alternative PW-MIR VOC Limit</u>

Paragraph (e)(4) clarifies that a person can supply for use within South Coast AQMD or use any solvent cleaning materials that comply with an alternative PW-MIR limit of 0.38 g O₃/g VOC for any solvent cleaning activity in lieu of complying with the applicable VOC limit in paragraph (d)(1).

Paragraph (e)(5) – Alternative PW-MIR VOC Limit for Ink Application Equipment

Paragraph (e)(5) clarifies that a person can supply for use within South Coast AQMD or use any solvent cleaning materials that comply with an alternative PW-MIR limit of 0.70 g O₃/g VOC in lieu of complying with the VOC limits in Table 1 (D)(iv)(A), lithographic or letter<u>press</u> press printing for roller wash, blanket wash, and on-press components, and ink application equipment cleaning, and Table 1 (D)(v) screen printing ink application equipment cleaning, and Table 1 (D)(vi) energy curable printing equipment cleaning.

General Prohibitions [Subdivision (f)]

This subdivision contains the provisions for any person that supplies for use within or uses solvent cleaning materials to perform solvent cleaning activities within the South Coast AQMD.

<u>Paragraph (f)(3) – Carcinogenic Materials and Exempt Compounds</u>

Paragraph (f)(3) was restructured to streamline the rule and group all provisions that include prohibitions together in the same subdivision.

Currently, the rule prohibits the use of any solvent cleaning materials that contain any Group II exempt compounds other than cyclic, branded, or linear, completely methylated siloxanes (VMS).

In addition, PAR 1171 proposes to prohibit the use of solvent cleaning materials that contain pCBtF or t-BAc, with an upper concentration limit of 0.01 weight percent effective January 1, 2026.

Paragraph(f)(4) - Sell-Through and Use-Through Provision

Paragraph (f)(4) clarifies the periods in which solvent cleaning materials that contain pCBtF or t-BAc, and that were manufactured prior to January 1, 2026, can continue to be sold and used.

The sell-through and use-through periods are intended to prevent stranded assets for solvent cleaning materials that are already in the supply chain on the prohibition effective date.

Paragraph (f)(7) - Solvent Cleaning Material Documentation

Paragraph (f)(7) prohibits the use of solvent cleaning materials when documentation confirming the VOC content of the solvent cleaning materials cannot be provided.

This Documentation is required to confirm compliance with applicable VOC limits.

Paragraph (f)(8) – *Prohibition of Possession of Non-Compliant Solvent Cleaning Materials*

Paragraph (f)(8) prohibits the possession of solvent cleaning materials that do not comply with the requirements of PAR 1171 that are used, intended for use, or labeled for use, for solvent cleaning activities within South Coast AQMD, unless the facility is complying with any of the alternative compliance options pursuant to subdivision (e).

Similar South Coast AQMD rules include a prohibition of the possession applicable non-compliant regulated products in addition to the prohibition of sale and use of applicable non-compliant regulated products.

Recordkeeping Requirements [Subdivision (g)]

Subdivision (g) outlines the recordkeeping requirements including maintaining records for VOC emissions pursuant to Rule 109 – Recordkeeping for Volatile Organic Compound Emissions, emission control systems, and for any person who supplies for use or uses solvent cleaning materials within South Coast AQMD.

This subdivision was previously included in the requirements subdivision; however, staff moved recordkeeping requirements to its own separate subdivision and restructured to streamline and better organize the rule provisions in a manner consistent with the structure of similar rules. Most of the changes are minor, defined terms were capitalized.

Staff revised the lengths of time that records are required to be maintained for uniformity and consistency.

Paragraph(g)(2) - Documentation Requirements

Paragraph (g)(2) specifies the timeframe, information, and documentation to be maintained for each solvent cleaning materials used. The documents must be made available upon request and maintained for five years with the following information: Product name, name and address of suppliers, and dates and quantities used during time period requested by South Coast AQMD, VOC content, PW-MIR value if complying with paragraph (e)(2), (e)(4), or (e)(5).

Subparagraph (g)(2)(C) – Dates and Quantities for Each Solvent Material Used

Subparagraph (g)(2)(C) requires each facility to keep records of the dates and quantities for each solvent cleaning material used. For example, large operations such as electrical utilities and water distribution facilities may have multiple storage and distribution warehouses throughout an area in which they serve; the warehouse issues the solvent cleaning material to the end-user (field or maintenance staff) as needed for each job. Usage and documentation out in the field may be challenging for operations that service a large area, so in order to comply with the recordkeeping requirement, the warehousing issuing the solvent cleaning material will must document the date and quantity of solvent cleaning material issued to end-user. Also added to this requirement, South Coast AQMD can request documentation or records for any specified time period deemed necessary to determine compliance from the facility. For example, South Coast AQMD can request the dates and quantities ranging from one month, three months, six months, twelve months, or any other time period necessary to determine compliance.

Paragraph (g)(2) specifies the timeframe, information, and documentation to be maintained for each solvent cleaning materials used. The documents must be maintained for five years with the following information: Product name, name and address of suppliers, and dates and quantities used during time period requested by South Coast AQMD, VOC content, PW-MIR value if complying with paragraph (e)(2) or (e)(4).

<u>Subparagraph (g)(2)(E) - PW-MIR Record</u>keeping</u>

Staff added a subparagraph requiring documentation to be maintained confirming the PW-MIR value of materials used that comply with an alternative PW-MIR limit in lieu of applicable Table 1 VOC limits.

Paragraph(g)(3) - Solvent Cleaning Material Suppliers

Staff added recordkeeping requirements for any solvent cleaner supplier supplying solvent cleaning materials for use in the South Coast AQMD.

Paragraph(g)(5) - Remote Reservoir Cleaners

Staff added recordkeeping requirements for repairs of any liquid leak, visible tear, or crack detected in a remote reservoir cleaner solvent cleaner container. The recordkeeping is needed to ensure the existing requirements to repair any liquid leak, visible tear, or crack detected is conducted within one calendar day.

Test Methods [Subdivision (h)]

This provision specifies the approved test methods for determining the VOC content of solvent cleaning materials, to quantify amounts of exempt perfluorocarbon compounds in solvent cleaning materials, and efficiency of emission control systems.

Staff removed an outdated test method that is no longer used by the South Coast AQMD laboratory and corrected a separate referenced test method name. The structure and numbering has been amended and streamlined.

Subparagraph (h)(1)(D) – Determining VOC Content by Thermogravimetric Analysis

Subparagraph (h)(1)(D) includes an additional test method in which VOC content may be determined using thermogravimetric analysis according to ASTM Standard Test Method E 1868-Standard Test Method for Loss-On-Drying by Thermogravimetry. This method is being included to provide greater flexibility for cleaning solvents that contain semi-volatile compounds which are not well characterized by Reference Test Method 24. Anyone using this method to determine the VOC of their cleaning solvent must also follow the quality assurance and quality control procedures using South Coast AQMD Additional Requirements to ASTM Standard Test Method E 1868-10 for Metalworking Fluids and Direct-Contact Lubricants. For cleaning solvents that contain VOC levels less than 150 g/L, South Coast AQMD Test Method 313 – Determination of Volatile Organic Compounds (VOC) by Gas Chromatography/Mass Spectrometry/Flame Ionization Detection (GC/MS/FID) provides the most accurate results and will be used for compliance determinations at the South Coast AQMD laboratory.

Rule 442 Applicability [Subdivision (i)]

This provision clarifies that any solvent cleaner, solvent cleaning material that is exempt pursuant to subdivision (j) from all or a portion of the VOC limits of subdivision (d), shall comply with Rule 442 – Usage of Solvents. This subdivision was not changed other than to capitalize defined terms and amend a reference that changed.

Exemptions [Subdivision (j)]

This subdivision provides conditional exemptions to various provisions of PAR 1171.

Paragraph(j)(1) - Record keeping Exemption

Paragraph (j)(1) outlines the conditions in which a person conducting solvent cleaning activities shall not be subject to the recordkeeping provisions in subdivision (g). Staff made no significant changes to this paragraph, but did reword the paragraph to provide greater clarity.

Paragraph (j)(2) – Exempt Solvent Cleaning Activities

Paragraph (j)(2) lists various solvent cleaning activities exempt from all provisions of this rule. Most of these exempted solvent cleaning activities are subject to separate rules. Staff made minor edits to this paragraph and moved an exemption that was previously listed in a paragraph (j)(10) to subparagraph (j)(2)(H). Staff added subparagraph (j)(2)(I) to include a conditional exemption for cleaning of high voltage cables during cable splicing activities where the VOC content of the solvent cleaning materials used does not exceed 790 g/L. The cleaning activity involves the use of individually wrapped saturated towelettes out in the field for specific cable splicing activities on high voltage lines. The cleaning activity using the towelettes occurs in high above ground locations or underground locations. The use of the towelettes is preferred over the use of an aerosol since

maintenance time is limited and each towelette is premeasured with the correct amount of solvent for necessary cleaning.

Paragraph (j)(3) – Exemptions from VOC Limits

Paragraph (j)(3) lists solvent cleaning activities that are exempt from the VOC limits in paragraph (d)(1).

Staff removed conditionally exempt solvent cleaning activities, which the exemption status is contingent on the use of a solvent cleaning material that complies with a maximum VOC content limit. Staff moved these solvent cleaning activities and the respective VOC limits to paragraph (d)(1) to be consistent with other solvent cleaning activities with an applicable VOC limit.

<u>Paragraph (j)(4) – Aerosol Atomization Exemption</u>

Paragraph (j)(4) maintains the exemption of the use of aerosol solvent cleaning products that have a VOC content that complies with the VOC limits in Table 1 from paragraph (f)(1), which prohibits solvent cleaning materials from being atomized unless they are vented to emission control equipment. Staff removed language limiting the volume of aerosol solvent cleaning products that contain VOC in excess of Table 1 VOC limits that can be used and revised and relocated the language to subdivision (e).

<u>Paragraph (j)(5) – Exemptions of Various Cleaning of Coatings or Adhesives Application</u> Equipment

Paragraph (j)(5) lists specific solvent cleaning activities for coating or adhesive application equipment that are exempted from the VOC limits in subparagraph (d)(1)(C).

Staff revised subparagraph (j)(5)(C) to remove the conditional VOC limit of 900 g/L for solvent cleaning materials used for the cleaning of solvent-based fluoropolymer coating application equipment and is proposing to replace the VOC limit with a volumetric usage limit of one gallon per day.

<u>Paragraph (j)(7) and Paragraph (j)(8) – On-Press Screen Cleaning and UV/EB Ink Application and Curing Equipment Cleaning</u>

Paragraph (j)(7) outlined an exemption for the use of solvent cleaning materials used for the cleaning of on-press screen printing equipment from VOC limits listed in clause (c)(1)(D)(v). Paragraph (j)(8) outlined an exemption for the use of solvent cleaning materials used for cleaning of UV/EB ink application and curing equipment from VOC limits listed in clause (c)(1)(D)(vi). Both of the exemptions were allowed until January 1, 2010. Staff has removed these two paragraphs as they are both now obsolete.

<u>Paragraph (j)(10) – Printing and Film Operation Exemption</u>

Paragraph (j)(10) was removed and added to paragraph (j)(2) as subparagraph (j)(2)(H) to streamline the listing of solvent cleaning activities exempt from all provisions of this rule.

CHAPTER 4: IMPACT ASSESSMENT

INTRODUCTION

EMISSIONS INVENTORY AND

CONTROL TECHNOLOGY

EMISSION REDUCTIONS

COST-EFFECTIVENESS AND INCREMENTAL COST-EFFECTIVENESS

SOCIOECONOMIC IMPACT ASSESSMENT

CALIFORNIA ENVIRONMENTAL QUALITY ACT (CEQA)

DRAFT FINDINGS UNDER THE HEALTH AND SAFETY CODE

COMPARATIVE ANALYSIS

Chapter 4 Impact Assessment

Emission Inventory

To estimate the VOC emissions inventory for PAR 1171, staff reviewed the rule factors associated with the 2009 rule amendment. The rule factors from the 2009 amendment impacted 3 Source Classification Codes (SCC) for point sources and 13 Category Emission Source (CES) codes for area sources. The category for area sources includes chemical evaporation of organic solvents relating to cold solvent cleaning or stripping, general thinning solvents, printing and publishing, solvent degreasing, tank truck and railcar cleaning, graphic arts, and surface coating operations. Categories for point sources include industrial solvent use, cold cleaning and degreasing, and hand wiping with solvents. Staff then ran a query of Annual Emissions Reporting (AER) SIP inventory for compliance year 2023 using the SSC and CES codes. Based on the evaluation, PAR 1171 point sources account for approximately 0.003 tons per day whereas area sources accounts for approximately 3.6 tons per day; the main contributor to the VOC baseline emissions are area sources. PAR 1171 has an estimated 2023 VOC baseline emissions inventory of approximately 3.6 tons per day.

Control Technology

Compliance with PAR 1171 is expected to be met through the use of aqueous solvent cleaning material or by substituting solvent cleaning materials with other chemicals that contain less VOCs, non-toxics solvents, and no stratospheric ozone-depleting compounds. The manufacturers will have flexibility to use any compliant alternative reformulation to meet the VOC limits in PAR 1171. Some end-users may comply with the rule using alternative options such as control devices (e.g., emission collection systems or thermal oxidizer). The latter options may be cost prohibitive for most facilities, so it is anticipated that most will comply with existing VOC limits with existing products or commercially available replacement products.

Emission Reductions

Staff's proposed prohibition of pCBtF and t-BAc does not impact existing VOC emissions for the solvent cleaning activities subject to the rule since alternative pCBtF-free formulations are currently available that meet existing limits. The prohibition will not require any changes to existing VOC limits and will be maintained at current levels. In addition, staff's proposed change to the current aerosol exemption for electricity and water distribution utilities will not impact VOC emissions since the overall usage amounts will not change; the change is simply an alternative usage allowance for the use of liquid alcohol rather than aerosol alcohol. Similarly, changes to the aerosol exemption by including a usage limit for specific operations related to cleaning of automotive parts or battery terminal cleaning at battery manufacturing facilities will not impact exiting aerosol usage and will remain unchanged. Therefore, staff will not be considering any associated emission reductions with the proposed amendments to PAR 1171.

Cost-Effectiveness and Incremental Cost-Effectiveness

Cost-Effectiveness

Staff does not anticipate any cost associated with the proposed changes to PAR 1171 since only a few solvent cleaning materials use pCBtF in their formulations and most solvent cleaning materials already have direct replacements-; thus, a cost-effectiveness and incremental cost-effectiveness analysis was not conducted.

Socioeconomic Impact Assessment

The proposed amendments to Rule 1171 do not <u>significantly</u> affect air quality or emission limitations, and thus, will not result in socioeconomic impacts. Therefore, a socioeconomic impact assessment is not required by Health and Safety Code Sections 40440.8 and 40728.5.

California Environmental Quality Act

Pursuant to the California Environmental Quality Act (CEQA) Guidelines Sections 15002(k) and 15061, the proposed project (PAR 1171) is exempt from CEQA pursuant to CEQA Guidelines Sections 15061(b)(3) and 15308. Further, there is no substantial evidence indicating that the exceptions set forth in CEQA Guidelines Section 15300.2 apply to the proposed project. A Notice of Exemption will has been prepared pursuant to CEQA Guidelines Section 15062, and if the proposed project is approved, the Notice of Exemption will be filed with the county clerks of Los Angeles, Orange, Riverside, and San Bernardino counties, and with the State Clearinghouse of the Governor's Office of Planning and Research.

Draft Findings Under the Health and Safety Code

Health and Safety Code Section 40727 requires that prior to adopting, amending, or repealing a rule or regulation, the South Coast AQMD Governing Board shall make findings of necessity, authority, clarity, consistency, nonduplication, and reference, as defined in that section, based on relevant information presented at the Public Hearing, this written analysis, and the rulemaking record. The draft findings are as follows:

Necessity – PAR 1171 is needed to phase out two exempt compounds, pCBtF and t-BAc, to address their toxic risk as by proposed by 2022 AQMP Control Measure CTS-01.

Authority - The South Coast AQMD Governing Board obtains its authority to adopt, amend, or repeal rules and regulations from Health and Safety Code Sections 39002, 40000, 40001, 40440, 40441, 40702, 40725 through 40728.5, 40920.6, and 41508 as well as the federal Clean Air Act.

Clarity - PAR 1171 is written and displayed so that the meaning can be easily understood by persons directly affected by it.

Consistency - PAR 1171 is in harmony with, and not in conflict with or contradictory to, existing statutes, court decisions, or federal and state regulations.

Nonduplication - PAR 1171 does not impose the same requirement as any existing state or federal regulation, and the proposed amendments are necessary and proper to execute the powers and duties granted to, and imposed upon, the South Coast AQMD.

Reference - In amending Rule 1171, the South Coast AQMD Governing Board references the following statutes which the South Coast AQMD hereby implements, interprets, or makes specific: Health and Safety Code Sections 39002, 40000, 40001, 40406, 40702, 40440(a), 40725 through 40728.5, 40920.6, 41508 and 40702 federal Clean Air Act Sections 110, 172, and 182(e).

Comparative Analysis

Under Health and Safety Code Section 40727.2, the South Coast AQMD is required to perform a comparative analysis when adopting, amending, or repealing a rule or regulation. The comparative

Chapter 4 Impact Assessment

analysis is relative to existing federal requirements, existing or proposed South Coast AQMD rules and air pollution control requirements and guidelines which are applicable to VOC regulations for solvent cleaning operations. There are no other existing or proposed South Coast AQMD rules and air pollution control requirements and guidelines which are applicable to VOC regulations for solvent cleaning operations.

<u>Chapter 4</u> <u>Impact Assessment</u>

Rule Element	PAR 1171	U.S. EPA Control Techniques Guidelines: Industrial Cleaning Solvents	California Air Districts
Applicability	 Any person who uses solvent cleaning materials in solvent cleaning operations or solvent cleaning activities during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or general work areas as a part of a business or public service within the South Coast AQMD All persons who store and dispose of solvent cleaning materials used in solvent cleaning activities All solvent cleaner suppliers who supply, sell, or offer for sale solvent cleaning materials for use in solvent cleaning operations or solvent cleaning activities within the South Coast AQMD 	Any industry that uses organic solvents for cleaning operations where a facility emits at least 15 lbs/day of VOC before consideration of controls in an ozone nonattainment area	 Any process, including wipe cleaning, used to clean or dry metal and non-metal surfaces typically using a cold, vapor or conveyorized solvent cleaner (BAAQMD) Any organic solvent cleaning performed outside a degreaser during the production, repair, maintenance, or servicing of parts, products, tools, machinery, equipment, or in general work areas at stationary sources; storage and disposal of all solvents and waste solvent materials at stationary sources (SJVAPCD)
Requirements	VOC limits for solvent cleaning activity categories: product cleaning during manufacturing process, or surface preparation for coating adhesive, or ink application; repair and maintenance cleaning; cleaning of coatings or adhesives application equipment; cleaning of ink application equipment; and cleaning of polyester resin application equipment Alternative VOC limit applicable to all solvent cleaning activities Alternative volumetric material usage limits coupled with alternative VOC limits Sell through and use through for products on shelf prior to effective date of rule Solvent cleaning method requirements Alternative Compliance option using emission control system	 Work practices to reduce VOC emissions from the use, handling, storage, and disposal of cleaning solvents VOC content limit of 50 g/L for general purpose cleaning solvents Alternative composite vapor pressure limit of 8.0 mmHg at 20 degrees Celsius, or an alternative limit that may be used in lieu of the 50 g/L VOC content limit 	VOC content limit of 50 g/L for cold cleaners used for general repair and maintenance cleaning (BAAQMD) Identical VOC limits to PAR 1171 (SJVAPCD)

<u>Chapter 4</u> <u>Impact Assessment</u>

Rule Element	PAR 1171	U.S. EPA Control Techniques Guidelines: Industrial Cleaning Solvents	California Air Districts
Prohibition	 Prohibition of the atomization of solvent cleaning materials unless vented to emission control equipment Prohibition of sale and use of products containing specified exempt compounds Prohibition of sale and use of carcinogenic material Prohibition of sale and use of solvent cleaning materials containing pCBtF and t-BAc at a future date 	None	Prohibition of the atomization of solvent cleaning materials unless vented to emission control equipment (SJVAPCD)
Recordkeeping	Daily usageMaterial data	None	 Monthly usage, Material data (BAAQMD) Daily usage, Material data (SJVAPCD)
Administrative	Container labeling of VOC content	None	Container labeling of VOC content (BAAQMD) Container labeling of VOC content (SJVAPCD)
Exemptions	 Exemption for solvent cleaning activities subject to other source specific rules Exemption for solvent cleaning materials containing less than 25 grams per liter of VOC Exemption for specified cleaning activities 	Cleaning operations listed for regulation under CAA Section 183(e)	Similar to PAR 1171 (BAAQMD) Similar to PAR 1171 (SJVAPCD)

APPE	NDIX A: RESP	ONSES TO C	COMMENTS	

Public Workshop Comments

Staff held a Public Workshop on March 28, 2025, to provide a summary of PAR 1171. The following is a summary of the verbal comments received on PAR 1171 and staff's responses.

Commentor #1 Doug Raymond – W.M. Barr

Doug Raymond expressed support of staff's change of the unit of measurement used from fluid ounces to ounces to limit the usage of aerosol solvent cleaning products that contain VOC in excess of applicable Table 1 VOC limits. Mr. Raymond also expressed support for staff's change from a daily aerosol product allowance of 160 ounces to a monthly allowance of 160 ounces; however, Mr. Raymond expressed concern that the monthly limit may still be too stringent. Mr. Raymond suggested a weekly limit of 160 ounces or a monthly limit of 640 ounces. Mr. Raymond expressed concern regarding the proposed definition of solvent cleaning activity and whether residential use of household consumer products may be subsequently subject to PAR 1171. Mr. Raymond requested clarity regarding the alternative compliance option for electricity generating and distribution equipment, and the general alternative PW-MIR limit proposed for all solvent cleaning activities. Mr. Raymond expressed concern regarding the proposed prohibition of volatile methylated siloxanes (VMS)-containing solvent cleaning materials, stating that certain solvent cleaning activities rely on VMS, and that a prohibition of VMS compounds would be premature due to the lack of conclusive toxicity data. Mr. Raymond concluded by stating that the June Governing Board meeting for PAR 1171 was too soon and that more time is needed for rule development.

Staff Response to Commentor #1:

Staff acknowledged the commentor's concerns regarding the proposed aerosol allowance revisions made and revised the proposal to allow 1,750 ounces per month of aerosol solvent cleaning products that contain VOC in excess of Table 1 limits to be used. Staff clarified that the alternative compliance options for electricity generating and distribution equipment and water distribution equipment require compliance with both the proposed applicable volumetric usage limit and PW-MIR limit. Staff also clarified that the proposed general alternative PW-MIR limit of $0.38~g~O_3/g~VOC$ is an alternative compliance option for all solvent cleaning activities. Staff acknowledged commentor's concerns regarding the prohibition of VMS and agreed to maintain the current allowance and continue to further assess its potential toxicity and consider revising the allowance in the future.

Commentor #2 Nicholas Georges – Household and Commercial Products Association (HCPA)

Mr. Georges expressed concern regarding the proposed prohibition of VMS-containing solvent cleaning materials and stated that a prohibition would be premature due to inconclusive toxicity data.

Staff Response to Commentor #2:

Staff acknowledged the commentor's concerns regarding the prohibition of VMS and agreed to maintain the current allowance and continue to further assess its potential toxicity and consider revising the allowance in the future.

Commentor #3 Bill Pearce – Boeing

Mr. Pearce expressed concern regarding the revised definition of *non-leaking container*, stating that the criteria to meet the revised definition may not be feasible. Mr. Pearce also expressed concern regarding the proposed prohibition of possession of non-compliant solvent cleaning materials and recordkeeping requirements. Mr. Pearce explained that facilities may receive solvent materials that are not intended for use within South Coast AQMD and store them until they are shipped to their next destination.

<u>Staff Response to Commentor #3:</u>

Staff acknowledged the commentor's concerns regarding the mentioned definition and proposed prohibition of possession of non-compliant solvent cleaning materials and agreed to revised both to address the commentor's concerns. While staff acknowledges the commentor's concerns regarding recordkeeping requirements, the proposed additions to the recordkeeping requirements are required of solvent cleaner suppliers.

Commentor #4 Rita Loof – RadTech

Mrs. Loof expressed appreciation for the inclusion of a definition for energy curable inks in PAR 1171 and suggested incorporating ASTM D7767-11 into the test methods subdivision for UV/EB/LED materials. Mrs. Loof stated that more time was needed for rule development and suggested delaying the Governing Board meeting. Mrs. Loof expressed concern regarding the proposed recordkeeping requirements.

Staff Response to Commentor #4:

Staff acknowledged the commentor's concerns regarding recordkeeping requirements, the proposed additions to the recordkeeping requirements are required of solvent cleaner suppliers. ASTM International D7767-11 "Standard test Method to Measure Volatiles from Radiation Curable Acrylate Monomers, Oligomers and Blends and Thin Coatings Made from Them" is not a U.S. EPA approved test method and cannot be used to enforce a SIP approved rule, therefore will not be added to PAR 1171.

Commentor #5 Jay Parepally – Communities for a Better Environment

Mr. Parepally expressed concern regarding fugitive solvent vapors and inspection frequency and suggested requiring signage at facilities conducting solvent cleaning operations warning the public of potential solvent vapors.

Staff Response to Commentor #5:

Staff acknowledged the commentor's concerns and clarified that while South Coast AQMD inspectors routinely conduct compliance inspections of facilities, the frequency of inspections conducted at each facility can vary for a variety of reasons, including but not limited to staffing. In regard to signage, Rule 1171 covers a large variety of facilities, some using water based cleaning materials with detergent. Requiring warning signs at every facility would be overly burdensome and could cause undue concern by the public. Further, California's Proposition 65 already requires signage to warm the public when businesses use chemicals that could cause cancer, birth defects or other reproductive harm.

Commentor #6 Katy Wolf - IRTA

Ms. Wolf requested clarity regarding the general alternative PW-MIR limit for all solvent cleaning activities and if the limit is tied to a usage limit. Ms. Wolf expressed support of a prohibition of VMS-containing solvent cleaning materials, specifically D5.

Staff Response to Commentor #6:

Staff clarified that the general alternative PW-MIR limit of $0.38 \text{ g O}_3/\text{g VOC}$ is not tied to any volumetric usage limit. Staff acknowledged the commentor's support of a prohibition of VMS but will wait to make changes in the prohibition until more definitive information is known.

<u>Commentor #7 Rita Loof – RadTech</u>

Mrs. Loof suggested taking into consideration medical sterilization facilities transitioning away from ethylene oxide equipment to UV light treatment equipment and granting regulatory relief in regard to PAR 1171 recordkeeping requirements.

Staff Response to Commentor #7:

Staff acknowledged commentor's suggestion; however, no additional recordkeeping requirements are being proposed for facilities conducting solvent cleaning activities.

Commentor #8 Cindy Parsons – LADWP

Ms. Parsons requested clarity whether facilities must maintain all records on-site at the facility where solvent cleaning activities are conducted or if records can be maintained at a central location. Ms. Parsons inquired about the proposed changes in the period of time required for records to be maintained.

Staff Response to Commentor #8:

Staff clarified that records may be maintained electronically or at a central location. Staff has revised the recordkeeping requirements to remove language requiring records to be maintained onsite. Staff clarified that South Coast AQMD rules generally require records to be maintained for a period of five years and that the proposed changes are consistent with other similar rules.

Commentor #9 Jay Parepally – Communities for a Better Environment

Mr. Parepally requested clarity regarding VOC limits in Table 1, specifically if the solvent cleaning activities listed also had associated volumetric usage limits. Mr. Parepally also inquired about different types of emission control systems, and the varying control and capture efficiency requirements for emission control systems. Mr. Parepally inquired about the time required for solvent cleaning material manufacturers to disclose if materials contain exempt perfluorocarbon compounds listed in the test methods subdivision.

Staff Response to Commentor #8:

Staff clarified that the VOC limits in Table 1 are not tied to a volumetric usage limit. Staff explained that various equipment associated with emission control systems used for various industrial processes, materials, other equipment, and types of resulting emissions may have varying physical limitations in capture and control efficiencies. Staff clarified that manufacturers generally will list the composition of solvent cleaning materials on safety data sheets (SDS) and that manufacturers aren't required to have products analyzed for the presence of exempt

perfluorocarbon compounds unless the manufacturer chooses to utilize the compounds to comply with Table 1 VOC limits pursuant to paragraph (h)(2).

Comment Letter #1



March 27, 2025

Mr. Christopher Bradley South Coast Air Quality Management District 21865 Copley Drive Diamond Bar, CA 91765

RE: South Coast Air Quality Management District Proposed Amended Rule 1171 – Cleaning Operations

Dear Mr. Bradley:

The W.M. Barr & Company, Inc. appreciates the opportunity to comment on the South Coast Air Quality Management District (SCAQMD) proposed amendments to Rule 1171 Cleaning Coating Operations. The W.M. Barr & Company, Inc. is a major supplier of Multipurpose Solvents and Paint Thinners to the retail market under our Klean-Strip® brand. Our family of brands supports consumers in their efforts to maintain clean and well-maintained homes.

W. M. Barr has worked with SCAQMD in the past to provide comments and demonstrations that have assisted in developing rule which are better for the environment and for Industry.

Our comments are mainly focused in two sections of the regulations. These two sections are the (d) (3) Alternative limits for Aerosol Cleaners and (f) (3) General Prohibitions that deal with metholated siloxanes (VMS).

Aerosol Products

The SCAQMD Rule has a long history with regulating Aerosol Products. Consumer Products, including Aerosol Products were first regulated in the early nineties by the California Air Resources (CARB). At that time some limits were significantly higher, especially on Carb and Choke products and Brake Cleaners. Since that time CARB has reregulated numerous categories and the VOC limits have been reduced significantly. Today the limits have been reduced to the lowest point that is technologically feasible per the State law that governs the CARB regulation.

Thus, there is little need for SCAQMD to continue to regulate the Aerosol products. W.M. Barr is proposing the SCAQMD simply propose to amend Rule 1171 to state that any cleaning product used under Rule 1171 needs to comply with CARB. This will regulate any products that are used in a manufacturing setting which is currently the only sector not currently subject to the CARB regulations all other uses are currently regulated and enforced by CARB.

W.M. Barr & Company, Inc.

1715 Aaron Brenner Dr., Suite 200, Memphis, TN 38120 www.wmbarr.com 1-1

1



If SCAQMD does not agree to simple regulate Aerosol Cleaners in this manner, then additional changes need to be made to section (d) (3). The current list of Solvent Cleaning Activities is grossly understated in Table 3. The activities listed in Table 3 ignore numerous uses of cleaning products such as General-Purpose Cleaners, General Purpose Degreaser, Glass Cleaners and other types of surface cleaners routinely used in manufacturing and maintenance of products and components. Replacing 160 ounces per day with 160 ounce per month is not feasible. We would request at least 160 ounces per week or 640 ounces per month to cover other solvent cleaning activities that SCAQMD has not specifically detailed.

1-1 Cont.

VMS

Volatile Methylated Siloxanes (VMS) particularly Octamethyl Cyclotetrsiloxane CAS #556-67-2 (04) is used for a wide variety of consumer and industrial applications. SCAQMD has proposed to virtually ban the use of this compound in the amendments. This compound has been used to replace the use of PCBTF in specialty cleaners which SCAQMD has also proposed to ban in this amendment. In fact, D4 is the only known viable replacement for PCBTF in specific solvent-based cleaning applications other than VOC organic solvents. SCAQMD has stated that numerous other alternatives are available to replace VMS or PCBTF. W.M. Barr would like to request a list of these other alternatives to be used. Our searches have not yielded any replacements for these compounds in cleaning applications for plastic automotive body surfaces.

SCAQMD should revisit the proposal of the ban on D4. The VMS ban is under subsection (f) (3) (B) Carcinogenic Materials and Exempt Compounds. While D4 is exempt it is not carcinogenic. In fact, this compound has not even been listed on the Proposition 65 list by the Office of Environmental Health Hazard Assessment (OEHAA). Thus, we do not understand the reason to ban this important chemical. W.M. Barr has prepared the attached summary on D4 to explain how toxicity of this compound does not support the need for a ban on use of the compound. Specifically, D4 is a critical tool to provide crucial cleaning efficacy needed in solvent cleaning operation. In addition to the summary paper, attached is the full draft risk evaluation on the toxicity of D4 and a representative supplier material Safety Data Sheet. W.M. Barr respectfully request SCAQMD reconsider a ban on D4.

1-2

Summary

W.M. Barr & Company again appreciates the opportunity to comment on the amendments to Rule 1171.

In summary, SCAQMD should consider using the CARB regulation for regulating Cleaning Products. If not SCAQMD needs to allow for the use of other solvent cleaning applications

W.M. Barr & Company, Inc.

1715 Aaron Brenner Dr., Suite 200, Memphis, TN 38120 www.wmbarr.com 2



that to date SCAQMD has not considered, such as cleaning of surface areas in manufacturing or just general cleaning.

Next, SCAQMD should remove the ban on VMS particularly D4. After SCAQMD reviews the attached data of the toxicity of D4, the ban should be removed.

W. M. Barr respectfully requests the above issues be reviewed; in addition, W.M. Barr would like to meet with SCAQMD staff to discuss these important amendments in Rule 1171 in further detail.

Thank you for your consideration to these comments and we look forward to working with you on these amendments. Any questions or comments please contact our consultant Doug Raymond at diraymond@me.com or at 440-339-4539.

Sincerely,

Amanda Burwell

Amanda Burwell Director of Regulatory Affairs | W.M. Barr C: (901) 426-0958 1715 Aaron Brenner Dr. l Suite 600 l Memphis, TN 38120 www.wmbarr.com

cc: Heather Farr cc. Michael Morris cc: Doug Raymond

W.M. Barr & Company, Inc.

1715 Aaron Brenner Dr., Suite 200, Memphis, TN 38120 www.wmbarr.com 3

Response to Comment 1-1

Staff appreciates W.M. Barr's feedback and participation throughout the rule development. Staff acknowledges that the VOC content in aerosol products regulated by CARB have been significantly reduced since the early nineties. CARB's regulation pertaining to Antiperspirants and deodorants, consumer products, and aerosol coatings have set limits for 129 consumer product categories. According to CARB, once these three regulations are fully implemented, VOC emissions will be reduced by about 50 percent compared to 1990 levels. However, despite the progress, CARB also predicted that consumer products will become the largest source category of VOC emissions in the South Coast Air Basin by 2020. The South Coast Air Basin is classified as an "extreme" nonattainment area for the following National Ambient Air Quality Standards (NAAQS): 1979 1-hour ozone, 1997 8-hour ozone, 2008 8-hour ozone and the 2015 ozone NAAQS. Therefore, South Coast AQMD must look at all feasible measures to reduce ozone and does not agree with the statement that there is little need for South Coast AQMD to continue to regulate aerosol products in PAR 1171. The aerosol allowance is currently for "non-complaint" products was included to address specialized cleaning operations that cannot comply with the VOC limits. The VOC limits for aerosol products regulated by CARB remain higher than those in PAR 1171, so it is necessary to regulate or limit the amount of aerosol products that can be used to minimize excess emissions. However, additional stakeholders raised a similar concern regarding the 160 ounces per month will be challenging. To address the specific concerns from several operations, staff revised the aerosol solvent cleaner usage limit from 160 ounces per month to 1,750 ounces per month.

Response to Comment 1-2

Thank you for providing the documents and information regarding the use of volatile methylated siloxanes (VMS). Staff is aware that VMS is currently used in a variety of consumer and industrial applications such as solvent cleaning. The VMS alternatives mentioned by staff was in regard to a specialty solvent used for automotive parts cleaning; the manufacturer indicated that they currently have a replacement product for the VMS containing solvent. Staff was only aware of VMS use for automotive parts cleaning and not aware of its use for cleaning of automotive body surfaces.

Staff's initial proposal to prohibit VMS along with pCBtF and t-BAc was because cyclic, branched, or linear, completely methylated siloxanes (VMS) were added to the list of defined Group II exempt compounds in South Coast AQMD Rule 102 – Definition of Terms in 1995. Rule 102 states that the use of Group II compounds may be restricted in the future because they are either toxic, potentially toxic, upper-atmosphere ozone depleting substances, or cause other environmental impacts. The Office of Environmental Health Hazard Assessment (OEHHA) reviewed VMS but ultimately could not make a conclusive determination on their toxicity. Based on the review OEHHA conducted for CARB, staff initially decided to take a precautionary approach and include VMS as part of the pCBtF and t-BAc prohibition. However, after careful review of the study provided and additional evaluations-conducted, staff concluded that additional information and data related to VMS are still needed to make a final determination on toxicity. As result, staff is not proposing to prohibit VMS compounds in PAR 1171 at this time but will continue to monitor their status and any future evaluations from OEHHA.

Comment Letter #2



Southern California Edison COMMENTS and Request for Clarification Proposed Amended Rule 1171. Solvent Cleaning Operations

April 8, 2025

Southern California Edison (SCE) appreciates the opportunity to present comments and requests for clarification for Proposed Amended Rule 1171, Solvent Cleaning Operations. to the South Coast Air Quality Management District. Below is a summary of our comments and requested revisions.

Requirements

1. Table 2 - Alternative Usage and MIR Limits. There seems to be a disconnect between the discussion in the staff report regarding the use of denatured alcohol (DA) and the MIR limit included in Table 2 for Electricity Generating or Distribution Equipment. The staff report acknowledges the need to use DA to clean components. However, Table 2 PW-MIR limit of 0.61 appears to align with current alcohol-based products. SCE must use straight DA at our facilities. Studies have shown various product combinations are not as effective as DA alone. As of now, Mitsubishi Electric Power Products (MEPPI) has not yet completed the testing of IPA but has already stated that IPA is not an acceptable alternative for some components that make up a significant part of SCE's inventory. SCE will switch to IPA where MEPPI supports its use. However, until then, we will need to use straight DA on many of our components. As such, a PW-MIR limit of 0.61 for Electricity Generating or Distribution Equipment is not a feasible limit for SCE. We request this limit be revised to 1.7 to allow us to continue our cleaning operations until a lower MIR product is approved.

2-2

2-1

2. Alternative Limits for Aerosol Cleaning, Thank you for increasing the Aerosol Solvent Cleaner Usage Limit for "All Others Solvent Cleaning Activities" to 160 ounces per month. Based on our current operations and input from our field personnel, SCE respectfully requests that this limit be further increased to 640 ounces per month or 160 ounces per week. A higher monthly limit would be preferrable as it would provide the flexibility we need for our operations and lessen the recordkeeping requirements.

2-3

3. It is our understanding that we can use both alternative compliance options (liquid and aerosol) at the same facility (a substation) for a combined use of 160 (640) ounces/month of aerosol and 70 gallons/yr of liquid. Please confirm. Different components need wipe cleaning using liquid solvents and other components need the aerosol pressurized stream. SCE needs the flexibility to use both alternative compliance options at the same facility.

Page 1 of 2

4. Please confirm that hand-held spray bottles that use atomized air (see example) do not meet the definition of Aerosol in the rule (Rule 117 (c)(1)) and the material used via this mechanism falls under the 70 gallons per year limit per facility. Our interpretation is consistent with the federal and state definitions of "Aerosol product", both of which exclude pump sprays (40 CFR \$ 59.202 – Definitions and CCR Title 17, 94508(a)(5)). Please clarify this distinction in the rule definition of "Aerosol Product".

2-4

Recordkeeping

1. Section (g)(2)(c) requires dates and quantities of use. This requirement is extremely challenging for our unmanned locations, the vast number of locations we services, and the nature of our field work. Since the rule's solvent usage limits are either monthly or annual, recording the daily usage of material seems unnecessary. We request that the rule allow for monthly recordkeeping and alternative recordkeeping approaches such as a central record keeping log where operators can input their solvent usage on a monthly basis by location, or use of purchase records without having to log daily usage at each location.

Thank you again for the opportunity to provide these comments. My contact information is

Carol Cauthen

below.

Environmental Advisor, Air Quality

Environmental, Health, Safety & Quality| Environmental Department

T. 626-302-5073 | M. 626-407-1360

2244 Walnut Grove Ave, Rosemead, CA 91770

2-5

Page 2 of 2

Response to Comment 2-1

Staff appreciates the clarification on the uses of denatured and isopropyl alcohol in solvent cleaning activities for electricity generating and distributing equipment. Staff's proposal of 0.61 was based on information provided to staff that isopropyl alcohol (IPA) was the approved cleaning solvent. Based on feedback, staff will revise the MIR limits in Table 2 to 1.7 to allow for the usage of denatured alcohol.

Response to Comment 2-2

Staff acknowledges that solvent cleaning covers many industries, many of which rely on the aerosol product allowance to comply with Rule 1171. Similar concerns were raised by other stakeholders. Staff will revise the aerosol solvent cleaning usage limit to 1,750 ounces per month for the "other solvent cleaning activities" category.

Response to Comment 2-3

Facilities can comply via both alternative compliance options (usage with MIR limits in Table 2 and aerosol usage limits in Table 3) at the same facility.

Response to Comment 2-4

Staff agrees to align the definition of an aerosol product with the federal and state definition to exclude "pump sprays." The definition of a pump spray in the Federal Code of Regulation is:

Pump spray means a packaging system in which the product ingredients are expelled only while a pumping action is applied to a button, trigger, or other actuator. Pump spray product ingredients are not under pressure.

As defined, the ingredients in a pump spray are not under pressure and do not include the device pictured in the comment letter. That device operated by pressurizing the ingredients and would qualify as an aerosol product.

Response to Comment 2-5

Staff acknowledges and understands the challenges in recordkeeping for operations at unmanned locations and revised the proposed rule language to remove the mention of "onsite" and require records be maintained and made available upon request. This allows for centralized recordkeeping and for records to be maintained electronically. Staff also revised subparagraph (g)(2)(C) to require quantities of each solvent cleaner's usage during the time period specified by the Executive Officer which means that South Coast AQMD can request the dates and quantities for any specified timeframe deemed necessary to determine compliance.

Comment Letter #3



Outlook

[EXTERNAL] Proposed Amended Rule 1171

From Kathleen Wolf <katywolfirta@gmail.com> Date Tue 4/8/2025 2:41 PM

Christopher Bradley <cbradley@agmd.gov>

1 attachment (25 KB) P1004S1S.pdf;

I am writing with comments on proposed amended Rule 1171 "Solvent Cleaning Operations." During the workshop, one participant urged the District staff to remove the restriction for the Volatile Methyl Siloxanes (VMS) under (f) (3). I strongly urge you to keep the restriction in place.

OEHHA performed a review of the toxicity of D5, the VMS used in cleaning and dry cleaning applications, and they concluded that they had concerns about D5 toxicity and could not conclude that D5 is not toxic. A link to this document can be accessed at https://ww2.arb.ca.gov/sites/default/files/classic//toxics/dryclean/oehhad5review.pdf

EPA received the results of a cancer study on rodents and concluded that there may be a cancer hazard associated with D5. That document is attached to this email.

I am also providing a link to a report on tests of alternatives to D5 in cleaning applications that was performed several years ago by the Institute for Research and Technical Assistance (IRTA). The project was sponsored by HESIS and EPA and, although the report is very old, many of the conclusions on alternatives should still stand. The link to the report

is https://www.irta.us/reports/Five%20Emerging%20Chemicals.pdf.

D5 did give a positive carcinogenicity result in an animal study. Although the results are not definitive, it is good public policy to err on the side of caution. Additional toxicity information may be available in the future that would resolve the issue. Until then, however, I would urge you to keep the restriction of VMS in the rule. It's worth noting that there was no definitive toxicity data on PCBTF until the last several years. Had the District exercised caution many years ago when exempting PCBTF, the action to ban it now may not have been necessary. PCBTF's structure, a benzene ring with a chlorine substituent, was indicative that it was likely to be a carcinogen.

The District has done excellent work on PAR1171 and I support your efforts strongly. If you have questions about these comments, please feel free to call me at (818) 371-9260

Katy Wolf, Ph.D. Consultant

Katy Wolf, Ph.D. Phone: (818) 371-9260 3-1

Response to Comment 3-1

Please see response to comment 1-2. As more toxicity data regarding D5 and other VMS compounds becomes available, staff will reassess whether to prohibit the use of solvent cleaning materials that contain VMS compounds.

Comment Letter #4



International Ultraviolet Association

6935 Wisconsin Avenue, Suite 207, Chevy Chase, MD 20815

April 11, 2025

Mr. Michael Morris Planning and Rules Manager South Coast Air Quality Management District mmorris@aqmd.gov

Re: Proposed Amended Rule 1171 (Solvent Cleaning Operations)

Dear Mr. Morris:

The International Ultraviolet Association (IUVA) is pleased to provide comments on the South Coast Air Quality Management District's Proposed Amended Rule (PAR) 1171—Solvent Cleaning Operations. IUVA is a nonprofit dedicated to the advancement of ultraviolet technology for public health and the environment, with over 500 members worldwide. Ultraviolet disinfection is a key technology in water treatment and is currently used by public agencies in Southern California because it is a chemical-free alternative that offers advantages such as the ability to inactivate difficult to eliminate pathogens. Our specific comments on the staff proposal follow:

Definitions (c)42

The current definition for Ozone Generators in PAR 1171 states that Ozone is produced by applying an electric potential to oxygen but makes no mention of Ultraviolet Ozone Generators. Ozone can also be generated by using UV light to convert oxygen molecules into ozone. We urge the district to include Ultraviolet Ozone Generators in the definition section (c)(42) of the rule.

Alternative Limits for Electricity and Water Equipment (e) (2)

Our comments in Section (e)(2) are specific to Ultraviolet Light Treatment Systems and Ozone generation via exposure to UV light, in water treatment/distribution equipment [Table 2-- B(ii) Ozone Generators and B(iii) Ultraviolet Light Treatment Systems]. The preliminary staff report recognizes the challenges faced by water distribution and water treatment facilities in meeting the requirements of PAR 1171. The staff report mentions that various public agencies currently use denatured alcohols & Isopropyl alcohol to clean specific equipment such as ozone generators, UV sterilization systems and electrical components associated with the UV equipment. While we appreciate the consideration for an allowance of 16 gallons per day per facility for Ultraviolet Light Treatment Systems and 30 gallons per year per facility for Ozone generators, we would urge the district to provide a total exemption for UV equipment.

According to the Los Angeles Department of Water and Power (LADWP), "UV technology is ideal for treating chlorine-resistant micro-organisms like Cryptosporidium and Giardia. UV treatment will provide essential disinfection while minimizing disinfection by-products, reducing the need for the required

www.iuva.org info@iuva.org

4-1

4-2



International Ultraviolet Association

6935 Wisconsin Avenue, Suite 207, Chevy Chase, MD 20815

Page 2

chlorine doses." LADWP is currently completing the construction of a new Ultraviolet (UV) Disinfection Facility at the Los Angeles Reservoir. This UV plant will treat water leaving the reservoir and entering LA's water distribution system. The new state-of-the-art LA Reservoir UV Disinfection Plant is an important investment in the reliability and safety of LA's drinking water infrastructure, greatly enhancing LADWP's mission to deliver pure, clean refreshing tap water in an efficient and publicly responsible manner.

UV water disinfection units inactivate target pathogens to produce safe water. UV is used as one of the vital safety barriers in water disinfection processes. When UV is absorbed by the DNA in microorganisms; it is damaged so that the microorganism cannot reproduce. Cells that cannot reproduce cannot cause disease.

Keeping UV lamps and sleeves clean is essential for optimal proper performance. Dust, dirt, and residue can accumulate on the lamp and sleeve surface, reducing its efficiency, and potentially leading to device overheating or other cleanness-related issues. Non-alcohol based cleaners may leave residues behind. While some industry sectors may be able to deal with the risk of UV equipment not operating at peak performance and cleanliness issues associated with lower VOC solvents--Water treatment agencies simply cannot take the risk to public health lightly. Requiring water agencies like LADWP to switch from conventional alcohol-based solvents to new solvents that have not been fully validated and approved may result in damage to UV disinfection performance, leading to regulatory compliance and public health issues. We respectfully request that water treatment agencies using UV for water disinfection operations be allowed to use denatured alcohol and/or Isopropyl alcohol to ensure proper operation of their systems.

We appreciate your consideration of the concerns we have raised and look forward to a collaborative rulemaking effort.

Regards,

Ted Mao President IUVA

Per V

www.iuva.org info@iuva.org

4-2

Response to Comment 4-1

Staff agrees and has added ultraviolet to the definition.

Response to Comment 4-2

Staff acknowledges and understands the critical role ultraviolet light treatment and ozone generating equipment play in water treatment and distribution, and to provide clean and safe drinking water. Staff also understands the importance of using the correct cleaning solvents specified by the manufacturer and intends to allow water treatment and distribution facilities to use denatured alcohol or isopropyl alcohol to meet their needs. The proposed volumetric usage limits for denatured alcohol or isopropyl alcohol are based on industry feedback which reflect their current operation and use.

Comment Letter #5



April 11, 2025

Mr. Chris Bradley Air Quality Specialist South Coast Air Quality Management District 21865 Copley Drive Diamond Bar, California 91765

Dear Mr. Bradley,

Thank you for the opportunity to provide input on the possible proposed revisions to SCAQMD's rule 1171. PRINTING United Alliance (Alliance) appreciates the willingness of the District to work with industry experts in the development of these important requirements. The Alliance hopes that the comments contained herein will prove useful and we stand ready to continue to work with the District in the further development of the requirements.

As background, the Alliance represents the interests of facilities engaged in producing a wide variety of products through screen printing, digital imaging, flexographic, and lithographic print processes. The print industry is comprised primarily of small businesses, with approximately 95 percent of the printing industry falling under the definition of a small business as described by the Small Business Administration.

There has been a long history associated with the cleaning solvent limits for printing operations in Rule 1171. When Rule 1171 was last revised in 1999 for cleaning solvent limits used in the printing industry with the phased in effective dates that extended to January 1, 2010, there was considerable effort invested by the printing industry, solvent suppliers, and the District to find materials that could meet the 100 gram/liter limit and be effective.

As outlined in our letter dated August 21, 2024, this goal has not been achieved. The printing industry and its suppliers have been continuously searching to find blends of chemicals that will meet the cleaning needs of the printing industry and so far, it has not met with satisfactory results.

We are encouraged that an alternative approach using Maximum Incremental Reactivity (MIR) as a parameter to limit the formation of ozone has been included in the proposed revisions to Rule 1171. MIR provides an opportunity to not just rely on VOC content, but to focus on the reactivity of chemicals used to formulate cleaning solution blends. Reactivity-based limits could provide more formulation flexibility while efficiently reducing the ozone formed from these products.

MIR values have been adopted by CARB and the SCAQMD in several rules and allow for flexibility for regulated sources to reduce VOC emissions and reduce emissions of the more reactive VOCs. In reviewing several of these rules, it is apparent that different MIR values have been set based on the type of material, application, and other performance characteristics. These are all critical aspects that need to be considered when setting an MIR value.

5-1

In fact, the proposed MIR limits in Rule 1171 reflect the needs of various cleaning applications and there is not a "one size fits all" approach. It is for these reasons why the proposed alternative MIR limit in 1171 (e)(4) would not be appropriate for the printing industry. Here is the draft provision:

(4) Alternative MIR Limit In lieu of complying with the requirements in paragraph (d)(1), a Person may elect to supply for use within South Coast AQMD or use Solvent Cleaning Materials that comply with a PW-MIR limit of 0.38 g O3/g VOC for any Solvent Cleaning Activity.

The printing industry continues to support efforts to reduce ozone precursors and improve regional air quality. However, the proposed MIR limit of 0.38 g O3/g significantly undercuts what is technologically feasible, even when using the most advanced low-reactivity formulations currently available. We received information from several cleaning solution vendors who evaluated the MIR values of their current products they are selling into the District. They reported back that the MIR values were in the 0.51-1.58 g O3/g VOC range. Therefore, the proposed value of 0.38 g O3/g is too low to provide an equivalent level of reactivity and Rule 1171 compliant cleaning solutions.

Furthermore, with acetone having a MIR value of 0.36 g O3/g, it was pointed out that the proposed 0.38 g O3/g limit does not provide for any formulation flexibility. As discussed in the August 21, 2024 letter acetone is not a printing process friendly chemical, so it is not a viable option. This extremely low threshold does not provide for the necessary ingredients that are required to clean the variety of inks and coatings required for quality products produced in the commercial and packaging printing industry. In addition, cleaning printing equipment requires the use of materials that do not damage critical components such as plates, blankets, rollers, screens, bearers, and other key press components. Cleaning solutions that meet the 100 gram/liter limit do not fulfill these requirements.

In looking at the ingredients necessary to prepare cleaning solutions that are effective and meet the demands required for effective cleaning, several of the cleaning solution vendors have reported that a MIR value range of 0.86-0.89 g O3/g. This MIR range provides the opportunity to formulate cleaning solutions that are effective and would avoid problems with ink and coating removal as well as other key press components. Plus, this value is consistent with other SCAQMD and CARB regulations where MIR is being used to control the emissions of VOC.

To ensure that VOC emissions from cleaning activities are reduced to the lowest level possible while maintaining the integrity of the printing process, it can be coupled with a limit on the VOC composite vapor pressure. As described in the August 21, 2024 letter, vapor pressure is a viable VOC control strategy. While the District is not necessarily in favor of using vapor pressure alone as a control strategy, coupling it with a low MIR value ensures that materials with a high vapor pressure will not be used to formulate cleaning solutions that quickly evaporate allowing for their recovery or destruction during the laundering process.

As indicated in the July 20, 2015 report *Environmental Fate of Low Vapor Pressure – Volatile Organic Compounds from Consumer Products: A Modeling Approach* by Deborah H. Bennett, once a low vapor pressure VOC makes it to a wastewater treatment facility, it is removed and not released. USEPA has stated in the Control Techniques Guidelines for Offset Lithographic Printing and Letterpress Printing (EPA-453/R-06-002) low vapor pressure solvents used in conjunction with wipes are assigned a 50% retention factor. EPA defines low vapor pressure as 10 mm Hg at 20°C (68°F). This means that at least 50% of low vapor pressure emissions are captured and destroyed.

5-1 Cont.

5-2

Combining the low MIR with a low vapor pressure limit, provides for a very effective VOC emission control strategy. Setting an alternative limit of 5 mm Hg at 68°F, which is one-half of the limit set by USEPA, in conjunction with an MIR value of 0.89 g O3/g in Rule 1171 would significantly reduce emissions and would represent state of the art for cleaning solutions for the printing industry. This combination would result in the least amount of emissions and those that would occur would be VOCs that are less reactive. It would also provide much needed operational flexibility at a reduced cost for the printing industry.

The printing industry continues to support efforts to reduce ozone precursors and improve regional air quality. The District has historically recognized the need for flexibility and category-specific limits based on performance requirements and material availability. Setting an MIR limit of 0.89 g O3/g with a vapor pressure limit of 5 mm Hg at 68oF for the printing industry would maintain consistency with prior rulemaking for other industrial categories while still significantly reducing ozone-forming emissions compared to historical solvent use. We firmly believe that our suggestion control strategy would lead to the establishment of a mutually beneficial set of conditions that are both technically and economically feasible while reducing VOC emissions.

We would be willing to meet with representatives from the District to discuss our concerns with the current draft of the proposed regulation. Please feel free to contact Gary Jones, Vice President of Environmental, Health and Safety Affairs, at (703) 359-1363 with any questions you may have or to arrange a meeting time that is convenient for you and the appropriate staff involved in the development of the regulation.

Sincerely,

Gary A. Jones

Vice President EHS Affairs gjones@printing.org

Lay a Jones

703-359-1363

5-2 Cont.

3

Response to Comment 5-1

Staff appreciates the comment and considerable efforts undertaken by the printing industry to find suitable compliant material that meets the current 100 g/L limit in the rule. Staff conducted site visits to several printing operations to gain a better understanding of the solvent cleaning materials used by the industry. The printing operations visited have indicated that they have several low VOC compliant options such as soy-based or water-based alternatives that have been effective with satisfactory results. The same facilities have also indicated that these same alternatives can be used as alternatives to pCBtF-containing solvent cleaners. The proposed MIR limit of 0.38 g O₃/g VOC is an alternative limit for all solvent cleaning activities in Table 1 and is not intended to be a substitute for the VOC limits in the Table of Standards. The alternative MIR limit is intentionally set low near that to acetone to prevent VOC emissions backsliding since acetone is an exempt solvent and has a lower potential for ozone formation. Staff understands the importance of formulation flexibility when there are no other options available; several printing operations have indicated that they have suitable effective cleaning solvent options because of the large research and development efforts undertaken over 15 years ago.

Staff understands PW-MIR limits can provide additional flexibility without resulting in more regional ozone formation. For the alternative PW-MIR limit for cleaning lithographic and screen printing ink application equipment, staff consulted with several solvent cleaning manufacturers to determine the PW-MIR limits that would have equivalent or less ozone formation potential than the current 100 g/L VOC limit. Existing solvent cleaning materials were not formulated with the goal of reducing reactivity, so some existing cleaning materials have a very high PW-MIR; however, some solvent cleaners have been formulated to reduce reactivity. Looking at the range of solvents used for cleaning printing equipment and considering what the manufacturers think can be formulated to efficiently clean the equipment, staff is proposing a 0.70 g O₃/g VOC limit. The proposed limit is an alternative limit so facilities can continue to use the 100 g/L mass-based VOC limit that has been in place for 15 years. The alternative is meant to provide flexibility without increasing the ozone formation potential of the cleaning solvents.

Response to Comment 5-2

Staff acknowledges the benefits of having additional flexibility in solvent formulation when limited compliant solvent options are available and is proposing an alternative limit of 0.70 g O₃/g VOC. However, staff does not recommend using vapor pressure as a means by which to limit potential VOC emissions due to findings that some low-vapor pressure VOCs have been found to evaporate nearly as rapidly as the traditional high-volatility solvents and thus can be additional contributors to ozone formation depending on their emission rate, the portion remaining in the gas phase, and their reactivity.

Comment Letter #6



April 11, 2025

Sent via email to: Chris Bradley cbradley@aqmd.gov

South Coast Air Quality Management District Attn: Planning, Rule Development, and Implementation 21865 Copley Drive Diamond Bar, CA 91765

Re: PROPOSED AMENDED RULE 1171 - SOLVENT CLEANING OPERATIONS

Clean Water SoCal appreciates the opportunity to comment on the Proposed Amended Rule 1171 – Solvent Cleaning Operations.

Clean Water SoCal represents over 80 public water/wastewater agencies in Southern California. Clean Water SoCal members provide essential water supply, wastewater treatment and water disinfection for approximately 20 million people in San Diego, Orange, Los Angeles, Santa Barbara, Riverside, San Bernardino, and Ventura counties. Our members provide environmentally sound, cost-effective management of more than two billion gallons of wastewater each day and, in the process, convert wastewater into resources for beneficial uses such as recycled water and renewable energy.

We respectfully request that essential public water treatment facilities be exempt from this rule.

The amount of solvents needed to clean water disinfection systems vary widely with the size (capacity) of the treatment facility and the amount of water disinfected. This is not a one size fits all application. Water disinfection system operators need to use alcohols to clean ultraviolet bulbs and ozone generators. They are not able to use low VOC solvents like acetone or waterborne materials. This means that these agencies who are using ultraviolet systems for water disinfection to protect public health and the environment would either not be able to reliably provide regulatory required disinfection or not be able to comply with the district rule. Furthermore, to ensure a drought proof long term water supply for Southern California, several agencies are constructing water recycling facilities that must meet new stringent potable reuse treatment and disinfection requirements to protect public health. These facilities will rely on ultraviolet systems to meet these disinfection requirements. The proposed solvent limits in Table 2 of PAR 1171 may not provide sufficient quantities for effective cleaning of ultraviolet systems limiting much needed recycled water production and stranding expensive public assets.

6-1

P.O Box 231565 Encinitas, CA 92024 email: info@cleanwatersocal.org phone: 760.415.4332



Beyond water disinfection, Clean Water SoCal members operate and maintain critical infrastructure to provide safe and reliable water and wastewater services to the customers and communities we serve. Agencies utilize aerosol solvents to maintain equipment such as pumps, piping, and engines, at various facilities throughout their service areas. Clean Water SoCal members have voiced concerns about the significant reduction in the proposed rule for the aerosol solvent cleaner's usage limits (PAR Rule 1171 Table 2.) Our members remain concerned with the potential unintended consequences this reduction could have on the maintenance and repair activities of infrastructure and equipment at essential public services. Many maintenance activities at essential public services require the use of aerosols. Aerosols are commonly used because they are quick dry, leave no residue which is critical for proper gasket adhesion and replace effectiveness, and they can reach small inaccessible areas of mechanical components, such as engines and pumps. Non aerosols solvents are typically not conducive to these work environments and equipment types.

6-2

We appreciate the opportunity to provide comments on the proposed amended Rule 1171 and for your consideration of our comments.

Clean Water SoCal supports the SCAQMD mission to clean the air and protect the health of all residents in the South Coast Air District. We have a similar goal and obligation to the public and the environment. As such, we would welcome the opportunity to meet to discuss and develop a solution that meets the public's needs.

If there are any questions regarding these comments, please contact the Clean Water SoCal Air Quality Manager, David Rothbart directly at (714) 878-9655 drothbart@cleanwatersocal.org or contact me directly at (760) 415-4332 siepsen@cleanwatersocal.org

Sincerely,

Steve Jepsen

Executive Director - Clean Water SoCal

cc: Clean Water SoCal Air Quality Committee

P.O Box 231565 Encinitas, CA 92024 email: <u>info@cleanwatersocal.org</u> phone: 760.415.4332

Response to Comment 6-1

Staff acknowledges and understands the critical role ultraviolet light treatment and ozone generating equipment play in water treatment and distribution, and to provide clean and safe drinking water. Staff also understands the importance of using the correct cleaning solvents specified by the manufacturer and intends to allow water treatment and distribution facilities to use denatured alcohol or isopropyl alcohol. The proposed volumetric usage limits for denatured alcohol or isopropyl alcohol are based on industry feedback from large water facilities, which reflect their current operation and use. Furthermore, because there are currently existing usage limits for solvent cleaning materials used at public water and wastewater agencies, the requested exemption would result in a backsliding of emissions. If necessary, staff is open to revisiting the issue if the potential need to increase usage arises due to growth or expansion of facilities.

Response to Comment 6-2

Staff acknowledges and understands the critical role public water and wastewater agencies play in providing clean and safe drinking water. Staff has revised the prior proposed allowance of aerosol solvent cleaning products that contain VOC in excess of VOC limits from 160 ounces per day to 1,750 ounces per month. The proposed allowance is based on industry feedback from various stakeholders who stated that they would be able to comply with the latest proposed allowance. Staff is open to meeting and discussing these concerns further.

Comment Letter #7



AIR QUALITY COALITION

April 11, 2025

South Coast Air Quality Management Committee Stationary Source Committee

RE: COMMENTS ON PAR 1171

Coalition Members

Dear Chairman Larry McCallon and Members of the Committee:



The Construction Industry Air Quality Coalition (CIAQC) would like to express our serious reservations about the proposed amendments to rule 1171 - Solvent Cleaning Operations.



We wish that the staff had done outreach to our specific industry before the proposed amendments had reached this level of completion.

The use of effective solvents for cleaning parts and equipment used in the construction industry is an integral part of assuring that our equipment is fully operational and in full compliance with the many regulations that govern the use and operation of our unique, on-road, off-road and portable equipment fleets. Much of this equipment is maintained in the field, on a job site, and away from a better equipped maintenance facility where there may be more options for cleaning parts and tools.





Building Industry Association of Southern California

Under the existing rule there are very limited aerosol options that can meet the current 25 g/l VOC emission limits. Further there is also an existing 160 oz/day aerosol limitation which has been challenging to meet when servicing multiple locations simultaneously.


Proposed Rule 1171 will be eliminating the aerosol spray solvent exemption. Currently, SCAQMD Rule 1171 requires the use of solvents for repair and maintenance with a very low VOC content to 25 g/l or less. Those solvent are not



California Construction Trucking

effective on the grease and grime

Engineering Contractors Association





Southern California Contractors Association We have identified several other specific concerns that we would like to address with the staff as soon as possible.

- 1. Cleaning Effectiveness: Removing proven solvents risks reducing cleaning performance-especially for grease, oil, and other contaminants-which can significantly impact equipment maintenance and lead to increased failures overall, particularly in emissions-related components.
- Productivity & Cost Impact: Alternative methods often take longer and require more labor, increasing downtime and repair costs.

7-1

7-2

- Compliance Burden: New requirements may force additional costly repairs to equipment, training, and documentation—disproportionately affecting smaller operations.
- Field Service Limitations: Effective, portable solvents are essential for remote repairs. Restrictions could leave no viable options for field work.
- Safety & Reliability Risks: Residual buildup from weaker cleaners can compromise equipment safety, performance, and reliability.
- Insufficient Alternatives & Timeline: Fast-tracking changes without viable substitutes in place risks noncompliance and operational disruption across the industry.

Our industry discussions with solvent suppliers lead us to believe that there may not be an <u>effective</u> compliant alternative available on the schedule established by this proposed amendment.

Finally, if an aerosol solvent is ultimately found that is effective and meets the 25 g/l low VOC requirement for general maintenance, does the 160 oz/day still apply? We would expect that there would be no limit, but this is not stated in the proposed regulation.

CIAQC has several experts available who can speak about these issues and we look forward to the opportunity to address them with your staff.

Sincerely,

Michael Lewis Senior Vice President mike@lewisandco.net

Michael W Luis

951-206-4420

7-2 Cont.

Response to Comment 7-1

Staff appreciates the comment and understands the commenter's concerns regarding PAR 1171. To clarify, staff is not proposing to remove the aerosol allowance in PAR 1171, the provision has been relocated from the exemption subdivision to the alternative compliance options subdivision and made some adjustments to the exemption amounts. Further, staff would like to clarify that the usage limits are for each individual facility or work site; the total cumulative usage between all facilities or work sites does *not* have to be less than the usage limits.

Response to Comment 7-2

Staff acknowledges and understands the challenges in transitioning away from commonly used solvents and understands all the concerns stated in the comment letter. As previously mentioned, staff is not removing the aerosol exemption and just revising it based on stakeholders' request for usage flexibility from a daily to monthly limit. Furthermore, the aerosol allowance applies to aerosol solvent cleaning products that contain VOC in excess if applicable VOC limits listed in Table 1. If an aerosol solvent is used that complies with the 25 g/L VOC limit, there is no restriction on the amount that can be used.

Comment Letter #8



April 11, 2025

Mr. Michael Morris South Coast Air Quality Management District 21865 Copley Drive, Diamond Bar, CA 91765

Email: mmorris@aqmd.gov

Re: Public Comments -- Proposed Amended Rule 1171 - Solvent Cleaning Operations -- OPPOSE

Dear Mike:

RadTech International is pleased to comment on the proposed amendments to Rule 1171—Solvent Cleaning Operations. RadTech is the premier trade association in North America for Ultraviolet/Electron Beam/Light Emitting Diode (UV/EB/LED) technology. We speak on behalf of our over 800 members who are involved in a myriad of industry sectors ranging from printing and packaging to nail polish. UV/EB/LED processes are all electric, eliminating the need for add-on control devices thereby preventing emissions of criteria pollutants (Nitrogen Oxides) and Greenhouse Gases. Our products are not formulated with conventional solvents and therefore the emissions of Volatile Organic Contaminants (VOCs) are negligible. Energy curable materials are free of toxic materials and are considered "super-compliant" as they go above and beyond current rule requirements and provide the district with excess emission reductions. Transitioning to these cleaner materials help the district achieve its clean air goals. PAR 1171 will impact every single one of our market sectors.

Unfortunately, we cannot support the current rule proposal as it needlessly saddles our industry with burdensome requirements that do not result in any benefit to air quality. On the contrary, these overly prescriptive requirements act as a barrier to the implementation of clean technology. We urge the district to provide incentives in the form of regulatory flexibility, to companies who invest in UV/EB/LED technology. Our suggested changes are as follows:

Request for Exemption

Comment 8-1

As mentioned during the public workshop, RadTech urges the district to provide regulatory flexibility to UV/EB/LED processes. We cannot support the limit of 100 grams per liter for UV/EB/LED operations. Our members and customers have tried to use low VOC cleaners at their facilities for years only to find that acetone based cleaners leave residue on UV lamps and reflectors, thereby compromising the optical efficiency of the system. Additionally, acetone-based cleaners are highly flammable and since UV/EB/LED equipment is electrical, any spark can lead to devastating fires not only for the facility but for the community at large. Waterborne materials also have safety issues associated with their use around electrical equipment. This presents a risk to workers

We request an allowance to use alcohol-type cleaners which, generally have a Volatile Organic Compound (VOC) content of 800 grams per liter. Our materials are typically well below 50 grams/liter in VOC content and are already providing the district with emission reductions above and beyond those called for in district coating rules. Therefore, we humbly ask that you take those reductions into consideration as a mitigating factor in any potential increase in emissions that may result from using alcohol-based cleaners.

Comment 8-1 Cont.

We propose that Section (j)(2)(H) be modified as follows:

Cleaning operations in Printing pre-press or Graphic Arts pre-press and energy curing areas, including the cleaning of film processors, color scanners, plate processors, film cleaning, plate cleaning and UV/EB/LED curing equipment.

Recordkeeping

Comment 8-2

We strongly oppose the new additional requirements for reporting, recordkeeping and labeling in the latest R1171 proposal under Section (g)(2). The current Rule 109 requirements cover UV/EB/LED materials and sufficiently provide the district with compliance verification. PAR 1171 creates a whole host of mandates on businesses, which will not result in any emission reductions such as:

- (A) Product name of each Solvent Cleaner used;
- (B) Name and address of the supplier for each Solvent Cleaner used;
- (C) Dates and quantities in which each Solvent Cleaner was used during the time period specified by the Executive Officer; and
- (D) VOC content of each Solvent Cleaner as used.

In fact, these additional requirements will deter businesses from investing in clean technologies like UV/EB/LED. Businesses who are willing to invest in clean technologies should be encouraged to do so and saddling with added regulatory costs will be counterproductive to the District's mission.

<u>Definition</u>

Comment 8-3

We appreciate the inclusion of a definition for energy curable materials in PAR 1171 and would urge the inclusion of ASTM 7767-11 as a suitable test method. The Environmental Protection Agency and the SCAQMD have long recognized that EPA Method 24 is not suitable for thin film UV/EB/LED Materials. The Multiple Test Method Section of the rule, (h)(5), is problematic in that it acts as a "gotcha" to businesses who may be subject to fines by the district due to lack of clarity on which method to employ. Thus, RadTech urges the inclusion of ASTM D7767-11 as suitable test method for UV/EB/LED materials. We propose the following language:

The VOC content of thin film Energy Curable Adhesives and Sealants may be determined by manufacturers using ASTM Test Method 7767-- Standard Test Method to Measure Volatiles from Radiation Curable Acrylate Monomers, Oligomers, and Blends and Thin Coatings Made from Them.

Thank you for your consideration of these issues and we hope we can work towards a resolution.

Sincerely,

Rita M. Loof Director, Environmental Affairs

Ce: SCAQMD Board

Response to Comment 8-1

Staff appreciates the comment letter and acknowledges the stakeholder's concerns. Energy curable printing cleaning operations have been successfully using 100 g/L cleaning products for decades, but staff understands that lamp and reflector cleaning is a separate solvent cleaning activity than the ink application equipment. Several sources indicate the recommended cleaning of energy curable lamps and reflectors is to use a soft cloth and pure alcohol. Cleaning of the lamps and reflectors is not a frequently required cleaning activity and will require minimal solvent; therefore,

the VOC emissions are anticipated to be negligible. Staff included a separate limit for the cleaning of Energy curable lamps and reflectors with a VOC limit of 800 g/L.

Response to Comment 8-2

Staff acknowledges the stakeholder's concerns regarding recordkeeping and labeling. Staff would like to clarify that the amendments do not propose any reporting requirements, and that no new recordkeeping requirements for end-users are being proposed.

Response to Comment 8-3

ASTM International D7767-11 "Standard test Method to Measure Volatiles from Radiation Curable Acrylate Monomers, Oligomers and Blends and Thin Coatings Made from Them" is not a U.S. EPA approved test method and cannot be used to enforce a SIP approved rule, therefore will not be added to PAR 1171. Further, that test method is to estimate the VOC content of "acrylate monomers, oligomers, and blends and thin coatings made from them" and has no relevance to solvent cleaning materials.

Comment Letters Received After Close of Comment Period

The following letter was received after the close of comment period. The concerns regarding PAR 1171 have been addressed but due to the late submission, official responses have not been included.

Comment Letter 9



Doug Raymond 13808 Duncan Run Rd. Galena, Ohio 43021 djraymond@reg-resources.com 440-339-4539

April 28, 2025

Mr. Christopher Bradley South Coast Air Quality Management District 21865 Copley Drive Diamond Bar, CA 91765

RE: South Coast Air Quality Management District Proposed Amended Rule 1171 – Cleaning Operations.

Dear Mr. Bradley:

Raymond Regulatory Resources (3R) appreciates the opportunity to comment on the South Coast Air Quality Management District (SCAQMD) proposed amendments to Rule 1171 Cleaning Coating Operations. 3R Consults for numerous marketers and fillers in the Consumer Products arena. As well 3R is the consultant for the National Aerosol Association (NAA).

3R has worked with SCAQMD since the inception of Rule 1171 in the 1990's. Our collaboration in the past has been to provide the best possible regulation that benefits the environment and is clear and concise for Industry to comply.

Comments

Per discussions with Sarady Ka, 3R appreciates that SCAQMD is willing to delete the ban on Volatile Methylated Siloxanes (VMS) at this time. We understand that pending additional information or work performed by office of Environmental Health Hazard Assessment (OEHHA) this status may change. As well, 3R appreciates the additional ounces being provided for the general aerosol usage to 640 ounces per month. Also, the change from fluid ounce to weight ounces clarifies the usage properly, given aerosols are measured only in weight ounces.

Additional Comments

Several other additional changes are being offered for the amendments to add clarity to the existing rule.

Raymond Regulatory Resources (3R), LLC 13808 Duncan Run Rd. Galena, Ohio 43021

- Aerosol products 3R believes that some marketers may be unclear on the use of the Aerosol Products exemption, specifically as regards complying with the California Air Resources Board (CARB) VOC limits as stated in Article 2 of the Consumer Products Rule under CARB. To clarify this issue the following wording is suggested for (e)(3) C).
 - Such products are compliant with the California Consumer Products Regulations, including meeting the VOC content limit requirements of Article 2 or as allowed by Article 4.
- Alternative MIR Limit 3R applauds that SCAQMD is providing an MIR Reactivity
 Alternative limit in Rule 1171. Reactivity is the best science to be used to regulate
 VOC emissions. However, SCAQMD has Rule 1143 as well. Thus, a marketer may be
 able to produce a product using the MIR Alternative but still be restricted by Rule
 1143. Thus, to clarify this issue and not have to open up Rule 1143, the following
 wording should be added at the end of (e)(4) so that the entire paragraph reads as
 follows:
 - (4) Alternative MIR Limit In lieu of complying with the requirements in paragraph (d)(1), a Person may elect to supply for use within South Coast AQMD or use Solvent Cleaning Materials that comply with a PW-MIR limit of 0.38 g O3/g VOC for any Solvent Cleaning Activity. Solvent cleaners that comply with this alternative MIR limit will also be deemed compliant with SCAQMD Rule 1143.
 - This would provide clear wording for enforcement and Industry to follow.
- Clarity for Definition Definition (9) for Cured Coatings, Cured Ink or Cured Adhesive has been modified. This change effects certain adhesives that while cured may appear or feel tacky to the touch. This in no way means that the adhesive has not cured and is not releasing additional VOCs under normal conditions. For a manufacturer to prove that a tacky adhesive has indeed released all it's VOC would be incredibly difficult to prove. Thus, this wording could facilitate unwarranted enforcement actions. We request that this "tacky" status only be used to describe Coatings and Inks. If SCAQMD cannot make this distinction, then the following wording is suggested for definition (9).
 - Cured Coating, Cured Ink, or Cured Adhesive means a coating, ink, or adhesive, that is dry to the touch, and that has undergone a chemical or physical process to achieve its final state, where an adhesive may or may not still be tacky and does not release volatile components under normal use conditions.
- Lastly, 3R believes that the June 2025 board hearing date is too early to work through
 all the possible changes and requests. The board date should be delayed to have
 more time to completely review this regulation. This rule was last amended in 2009.
 In 2024 there were two work group meetings with an approximate year in between,

Raymond Regulatory Resources (3R), LLC 13808 Duncan Run Rd. Galena, Ohio 43021

then a workgroup and public workshop within a month. There has not been sufficient time to have a complete review. In addition, it has been 16 years since last amendments, what is the hurry? A few more months may provide a better rule.

Summary

Thank you for all of the changes made to date. Hopefully these additional suggestions will provide more clarity to this rule and avoid any misconceptions in the future.

3R again appreciates the opportunity to comment on the amendments to Rule 1171 and looks forward to working with you in the future. Any questions or comments please contact me at <u>diraymond@me.com</u> or at 440-339-4539.

Sincerely,

Douglas Raymond

Douglas Kaymond

cc: Heather Farr cc. Michael Morris cc: Sarady Ka

Raymond Regulatory Resources (3R), LLC 13808 Duncan Run Rd. Galena, Ohio 43021

A-32

Comment Letter 10

May 5, 2025

Heather Farr, Michael Morris, and Michael Krause Planning, Rule Development, and Implementation South Coast Air Quality Management District 21865 Copley Drive Diamond Bar, CA 91765



RE: Comments on Proposed Amended Rule 1171 – Solvent Cleaning Operations

Dear Proposed Rule 1171 Staff:

Communities for a Better Environment ("CBE") submits these comments on Proposed Rule 1171 ("Proposed Rule"). We appreciate staff's work on Rule 1171 but we remain concerned that the current language will not meaningfully regulate an industry that has been polluting our communities for years. We have some concerns that remain unresolved by the Proposed Rule and it is critical that the South Coast Air Quality Management District ("AQMD") do everything in authority to control pollution from solvent cleaning operations, specifically auto body shops. We understand the need for our local air district to do everything it can to ameliorate the air quality concerns for AB 617 communities in its jurisdiction.

CBE is a member of the Southeast Los Angeles AB 617 Community Steering Committee. We have participated in the Proposed Rule working groups and provided public comments during the April 18, 2025, Stationary Source Committee meeting. Our membership includes youth and adult members who live, work, learn, and play in homes and schools, at times, directly adjacent to industries who use solvent cleaners. Unequitable and racist policies like redlining have and continues to force communities to bear the brunt of potential VOC emissions. Stronger requirements under Rule 1171 could help address excessive air emissions and provide critical safety measures for Southeast Los Angeles communities. While we applaud AQMD for phasing out known carcinogens terfbutyl acetate ("TBAC") and para-chlorobenzotrifluoride ("PCBTF") from solvent cleaning operations, we urge AQMD staff to consider:

 Rule 1171 should include a signage provision that requires auto body shops to notify adjacent communities of potential VOC exposure

While we applaud AQMD for recommending the prohibited use of TBAC and PCBTF in the Proposed Rule, volatile organic compounds ("VOCs") exposure from solvent cleaning operations are still a concern for Southeast Los Angeles ("SELA") communities. Some VOCs are known to be highly toxic while other VOCs have been linked to an elevated risk of cancer and other health issues, which is alarming given that many SELA communities live adjacent or near auto body and repair shops that depend on solvent cleaning products. Additionally, AQMD staff are only recommending a 95% emission reduction for solvent cleaning products despite

Hussain MS, Gupta G, Mishra R, Patel N, Gupta S, Alzarea SI, Kazmi I, Kumbhar P, Disouza J, Dureja H, Kukreti N, Singh SK, Dua K. Unlocking the secrets: Volatile Organic Compounds (VOCs) and their devastating effects on lung cancer. Pathol Res Pract. 2024 Mar;255:155157. doi: 10.1016/j.prp.2024.155157. Epub 2024 Jan 26. PMID: 38320440.

some VOCs being labeled as hazardous.² The Proposed Rule should include a signage requirement like Rule 1460³ where residents can report air quality issues such as odors from facilities that use solvent cleaning products. VOCs can be colorless at room temperature but have strong odors that are either sweet or foul, making daily life uncomfortable for residents who live near auto body and repair shops. Including a signage requirement for residents to report any air quality issue not only protects residents from air pollution but holds facilities accountable to the adherence of Proposed Rule's provisions.

2) Additional provisions require regular facility inspection for rule 1171 compliance

Compared to the last amendment of Rule 1171, CBE supports the Proposed Rule's new provisions and stronger amendments that hold facilities accountable and transparent with their solvent cleaning operations. This includes additions to General Prohibitions, Alternative Compliance Options, and Test Methods. The updated language and tables for Alternative Compliance Options provides clarity for facilities who use solvent cleaning materials such as the Usage Limits and the Product-Weighted MIR ("PW-MIR"). This new provision, paired with the additional Test Methods amendments, ensures additional protections for communities living near or adjacent to auto body and repair shops.

We also applaud AQMD staff for finally adding a Recordkeeping Requirement. Record keeping is important to track and evaluate the operations of a business, and for solvent cleaning operations it's conducive to understand the types of solvent cleaners used, where the suppliers are, where the solvent supplies are going, and the amount that be is being supplied. Fecord keeping can also support a variety of initiatives that can support AQMD with strategic decision-making to further reduce emissions or research efforts that investigate the prevention of VOC exposures and/or the feasibility of safer cleaning alternatives. Lastly, we support section (f) (6) of General Prohibitions states that no solvent cleaner can be used without the proper documentation. While these additions are necessary and imperative to protecting human health, the Proposed Rule is only as strong as AQMD allows it. Meaning that these new amendments require regular facility inspection for the adherence of the Proposed Rule. AQMD staff needs to include language that specifies regular and consistent inspections of solvent cleaning operations to ensure communities are not exposed to VOC emissions.

3) Include language that protects impacted workers who use solvent cleaning materials

As previously mentioned, some VOCs are known to be hazardous and can have carcinogenic effects on the human body. While the Proposed Rule no longer includes solvents with TBAC or PCBTF, VOC exposure still poses a risk to communities and frontline workers. It's disappointing to see that the Proposed Rule exempts cleaning operations such as janitorial cleaning (including graffiti removal), cleaning operations from printing processes, and VOC limits to a variety of applications. Regardless of the solvent use, solvent cleaners that emit high VOCs can have short- and long-term effects on the human body. This is especially true for auto body and repair workers who use solvent cleaning materials daily. AQMD should coordinate

² Beyond the Label: Health Impacts of Harmful Ingredients in Cleaning Products.WVE. April 21, 2021. https://womensvoices.org/wp-content/uploads/2021/04/Beyond-the-Label-Report.pdf. Accessed May 1, 2025.
³ Rule 1460 – Control of Particulate Emissions from Metal Recycling and Shredding Operations.
SCAQMD. Pg. 9. https://www.aqmd.gov/home/rules-compliance/compliance/rule-1460. Accessed May 1, 2025.

⁴ Proposed Amended Rule 1171 - Solvent Cleaning Operations, SCAQMD, pg. 17.

https://www.aamd.gov/home/rules-compliance/rules/scaamd-rule-book/proposed-rules/rule-1171.

⁵ Ibid, pg. 20.

⁶ Ibid. Pg. 25.

with CalOSHA, Los Angeles Public Work and Planning Commissions to provide and require personal protective equipment and require ventilation controls to reduce VOC exposure.

4) Updating Rule 1171 when stronger emission control systems are feasible and safer alternatives are available given the range of solvent use cleaners

Even with the prohibition of TBAC and PCBTF from solvent cleaning operations, the Emission Control Systems in the Proposed Rule fail to protect frontline workers and communities who live near auto body and repair shops. Currently, the highest emission control system stands at 95% with the lowest at 70%. During the March 28, 2025 Public Workshop, AQMD shared that emission control systems are not 99% due to feasibility and operation type. No matter the use, frontline workers and communities must be protected from VOC exposures and that means implementing emission control systems close to 100% capture. AQMD should revisit and amend Rule 1171 when new technologies are available as well as when solvent cleaning materials with lower VOC emissions are available. Stronger requirements under Rule 1171 can help reduce VOC exposure and protect the health of frontline workers and communities living near or adjacent auto body and repair shops.

 Regular inspections of facilities using solvent cleaning materials can prevent VOC contamination onsite and offsite, avoiding the possibility of vapor intrusion into residential homes.

The former Central Metal Inc. ("CMI") site, now today's proposed U-HAUL facility, was a 12-acre scrap metal processing facility that dismantled metals as large as buses, house trailers, fire engines, and rail cars. CMI was located right next door to the residents of Walnut Park and two blocks away from homes in Florence-Firestone. CBE organizes residents in both the Walnut Park and Florence-Firestone areas who experience the cumulative impacts of countless polluting industries, of which CMI was one of the most egregious. According to EJ Screen, Walnut Park ranks in the 95-100th percentile nationally for Hazardous Waste Proximity and in the 80-90th percentile for the Superfund Proximity.

CMI had a history of violations noticed and documented by the Department of Toxic Substances Control ("DTSC"), the Los Angeles Regional Water Quality Control Board ("Water Board"), and the Planning Commission, and yet they were still allowed to operate over the years. Even the U.S. Environmental Protection Agency ("EPA") found that various scrap metal and debris were stored across exterior portions of the site in large, uncontained, and uncovered debris piles since the early 2000s. The piles were not covered to prevent rainwater intrusion, nor were they managed to prevent airborne releases, as required by their then-existing CUP. These soil waste piles were found to have hazardous levels of toxic metals such as lead and arsenic and other unidentified materials that compromised the piles. In 2011, DTSC and the South Coast Air Quality Management District ("SCAQMD") conducted air monitoring in and around the facility's perimeter and found exceedingly high lead levels in dust in several locations on the sidewalks outside the facility4, making it evident that CMI was a fugitive emission source into the communities.

⁷ Data + Screening Tools, "EJ Screen: Environmental Justice Screening & Mapping Tool." Public Environmental Data Partners. Accessed May 1, 2025. https://pedp-ejscreen.azurewebsites.net/.

⁸ Site Inspection Report: Central Metal, Huntington Park, Los Angeles County, California. EPA ID: No.: CAN000903324, September 2023.

⁹ Id. at 13

After community members shared concerns about contaminated soil from the former CMI site blowing onto their properties, CBE partnered with the EPA in 2018 to assess whether the site qualified for inclusion on the National Priorities List ("NPL") for Superfund cleanup. In 2019, the EPA initiated a Site Inspection and discovered elevated levels of lead, arsenic, and cobalt in the soil and groundwater, prompting further testing to determine if toxic metals had spread through the air to nearby homes. ¹⁰ Through the perseverance of community members - even with the challenges brought on by the COVID-19 pandemic - EPA began residential soil testing in 2022, sampling 63 properties in Walnut Park and 20 in Florence-Firestone. The results revealed lead levels exceeding the federal benchmark of 401 ppm at eight properties and arsenic levels above the 22 ppm threshold at three properties. However, the site was ultimately deemed ineligible for NPL listing due to "minimal screening level exceedances", inconsistent contamination levels, and the broader industrial pollution history of the Los Angeles area. To this day, residential homes have not been cleaned up, and residents continue to live with high levels of metal contamination.

During the EPA investigation to determine NPL eligibility, the former CMI parcels were sold to U-Haul in 2022 despite community members' active advocacy for reenvisioning the site and holding agencies accountable to the cleanup of both the site and residential homes. The County approved the Project ministerially, despite the severity of grading heavily contaminated soil, increase in air pollution from the additional truck traffic to and from the site and from extracting and transporting hazardous waste, and potential exposure to VOCs from vehicle repair operation. ¹¹ As mentioned previously, residential homes continue to live with metal contamination while the Project owners will have immunity from any wrongdoing because they entered into a California Land Reuse and Revitalization Act ("CLRRA") agreement. CLRRA's purpose to redevelop contaminated properties for industrial/commercial reuse fails to adequately protect residents that live near contaminated sites such as the Project, especially where it's evident that contamination is not only an onsite issue but a regional one as well.

Through the CLRRA investigation, DTSC shared that not only is there high metal contamination across the proposed U-Haul project ("Project") site, but so are VOCs. ¹² The Draft Response Plan ("Plan") for the proposed Project recommends an extensive soil vapor extraction system ("SVES") that could take years to mitigate and prevent potential vapor intrusion. There are 47 residences that live adjacent to the Project site [less than 5 ft away] ¹³ that might be susceptible to vapor intrusion due to the former CMI's operations, and the adjacent facility known as Jack

No Site Inspection Interim Sampling Report: Central Metal 8201 Santa Fe Avenue Huntington Park, Los Angeles County, California (EPA ID No.: CAN000903324), https://www.epa.gov/sites/default/files/2020-10/documents/can000903324_site_inspection_interim_sampling_report_central_metal_20074.067.024.0003.01_2020-05.pdf.

¹¹ Site Plan Review, Los Angeles County EPIC LA. Plan Number: RPPL2022007986. https://epicla.lacounty.gov/energov_prod/SelfService/#/plan/a2ed1c5e-6829-4d44-a8ba-af81cd2b30fc?tab=attachme

¹² EnviroStor, Department of Toxic Substances Control. Accessed May 1, 2025. https://www.envirostor.dtsc.ca.gov/public/profile_report?global_id=60002329

¹³ Distance Analysis, ArcGIS Pro Desktop. ESRI. Analysis performed on April 29, 2025.

Engle. He The Jack Engle ("JE") site has a 100-year history of industrial uses, most recently as a metal and scrap recycler. JE also has a history of operating with expired permits and providing illegal services such as heavy-duty truck storage. DTSC's Plan for the Project makes clear that the VOCs on the proposed Project site possibly originate from the JE site and could be the source of potential vapor intrusion of the residential homes next to the Project. No agency has yet to develop a clear and comprehensive plan on how to address the VOC contamination that crosses multiple parcels and impacts the residential homes living adjacent or close to heavily contaminated sites.

While CMI and JE were not solvent cleaners, it's clear that VOC contamination is a legacy issue. And now with the proposed U-Haul project, which will have auto body and repair services, solvent cleaning operations could potentially exacerbate the VOC contamination and exposures to residents and frontline workers. Community members should not have to wait for problems to be addressed one by one – environmental harm must be addressed from a broader perspective. This is why AQMD has the opportunity to prevent additional VOC exposures, contamination, and vapor intrusion into community member's homes – by strengthening Rule 1171 to prioritize community health over industry. AQMD should include language that requires regular facility inspections to ensure that solvent cleaning materials are not leaking, exposed, and are disposed of properly while ensuring that frontline workers have well-ventilated work areas and adjacent communities are not exposed to VOC emissions. The failure to include consistent facility inspections can result in unnecessary VOC contamination that can leak into the soil and groundwater and potentially migrate into people's homes. Walnut Park and Florence-Firestone communities are already exposed to countless polluting industries and AQMD can prevent one less polluting source.

Sincerely,

Ambar Rivera Staff Researcher Communities for a Better Environment

¹⁴ EnviroStor, Department of Toxic Substances Control. Accessed May 1, 2025. https://www.envirostor.dtsc.ca.gov/public/profile_report?global_id=60002329

¹⁵ Ashley Orona, "South Gate residents boo decision to delay illegal truck yard's possible closure." LA Public Press. April 23, 2025.

ATTACHMENT H



SUBJECT: NOTICE OF EXEMPTION FROM THE CALIFORNIA

ENVIRONMENTAL QUALITY ACT

PROJECT TITLE: PROPOSED AMENDED RULE 1171 - SOLVENT CLEANING

OPERATIONS

Pursuant to the California Environmental Quality Act (CEQA) Guidelines, the South Coast Air Quality Management District (South Coast AQMD), as Lead Agency, has prepared a Notice of Exemption pursuant to CEQA Guidelines Section 15062 – Notice of Exemption for the project identified above.

If the proposed project is approved, the Notice of Exemption will be filed for posting with the county clerks of Los Angeles, Orange, Riverside, and San Bernardino Counties. The Notice of Exemption will also be electronically filed with the State Clearinghouse of the Governor's Office of Planning and Research for posting on their CEQAnet Web Portal which may be accessed via the following weblink: https://ceqanet.opr.ca.gov/search/recent. In addition, the Notice of Exemption will be electronically posted on the South Coast AQMD's webpage which can be accessed via the following weblink: http://www.aqmd.gov/nav/about/public-notices/ceqanotices/notices-of-exemption/noe---year-2025.

NOTICE OF EXEMPTION FROM THE CALIFORNIA ENVIRONMENTAL QUALITY ACT (CEQA)

To: County Clerks for the Counties of Los From: South Coast Air Quality Management

Angeles, Orange, Riverside, and San District

Bernardino; and Governor's Office of 21865 Copley Drive Planning and Research – State Clearinghouse Diamond Bar, CA 91765

Project Title: Proposed Amended Rule 1171 – Solvent Cleaning Operations

Project Location: The proposed project is located within the South Coast Air Quality Management District's (South Coast AQMD) jurisdiction, which includes the four-county South Coast Air Basin (all of Orange County and the non-desert portions of Los Angeles, Riverside, and San Bernardino counties), and the Riverside County portion of the Salton Sea Air Basin and the non-Palo Verde, Riverside County portion of the Mojave Desert Air Basin.

Description of Nature, Purpose, and Beneficiaries of Project: Rule 1171 limits emissions of volatile organic compounds (VOC), toxic air contaminants, stratospheric ozone-depleting compounds, and globalwarming compounds from solvent cleaning materials used in solvent cleaning operations. The purpose of Proposed Amended Rule (PAR) 1171 is to reduce toxicity in formulations of certain solvent cleaning materials and to make other changes to limit the usage of certain solvent cleaning materials by: 1) prohibiting the use of parachlorobenzotrifluoride (pCBtF) and tert-Butyl Acetate (t-BAc) in solvent cleaning materials due to toxicity concerns effective January 1, 2026; 2) including a sell-through and use-through provision for solvent cleaning materials that include pCBtF and/or t-BAc and are manufactured prior to the proposed prohibition date of January 1, 2026; 3) prohibiting the possession of non-compliant solvent cleaning materials; 4) including alternative usage and product weighted-maximum incremental reactivity (PW-MIR) VOC limits for electricity and water distribution facilities to allow for the use of liquid denatured alcohol instead of denatured alcohol packaged as an aerosol product; 5) including alternative usage limits for solvent cleaning products packaged as an aerosol; 6) including a higher VOC limit to allow for the manufacturerrecommended use of alcohol-based solvent cleaning materials for cleaning energy curing lamps and reflectors used in the printing industry; 7) including an alternative PW-MIR VOC limit for solvent cleaning materials used for cleaning lithographic printing and screen printing equipment; 8) including an alternative PW-MIR VOC limit of 0.38 gram of ozone per gram of VOC for any solvent cleaning activity; and 9) updating the rule structure, adding new definitions, and removing outdated rule provisions. Implementation of the proposed project is not expected to result in a change in VOC emissions relative to baseline conditions because: 1) alternative formulations of cleaning solvents that do not contain pCBtF or t-BAc are currently available and capable of meeting the established VOC emission limits; 2) the use of liquid alcohol solvent cleaning materials in certain solvent cleaning activities at water and electric utilities are chemically equivalent to aerosol alcohol solvent cleaning materials; 3) only the VOC emission limit for solvent cleaning materials used for energy-curing lamps and reflectors is proposed to be increased, but the use of these materials is minimal and occurs infrequently; and 4) reduced usage limits for aerosol solvent cleaning products that contain VOC in excess of the proposed VOC emission limits are proposed for most solvent cleaning activities. The primary benefit of phasing out pCBtF and t-BAc will reduce the risk of exposure of these toxic chemicals to workers, nearby receptors and the public.

Public Agency Approving Project: Agency Carrying Out Project:

South Coast Air Quality Management District South Coast Air Quality Management District

Exempt Status:

CEQA Guidelines Section 15061(b)(3) – Common Sense Exemption

CEQA Guidelines Section 15308 – Actions by Regulatory Agencies for Protection of the Environment

Reasons why project is exempt: South Coast AOMD, as Lead Agency, has reviewed the proposed project (PAR 1171) pursuant to: 1) CEQA Guidelines Section 15002(k) – General Concepts, the three-step process for deciding which document to prepare for a project subject to CEQA; and 2) CEQA Guidelines Section 15061 – Review for Exemption, procedures for determining if a project is exempt from CEQA. Since PAR 1171 is not expected to result in a change in VOC emissions relative to baseline conditions, and the alternative compliant formulations that do not contain pCBtF and t-BAc are commercially available such that the sell-through and use-through provisions provide sufficient time to find suitable replacements which will prevent stranded assets and the generation of waste, it can be seen with certainty that there is no possibility that the proposed project may have a significant adverse effect on the environment. Therefore, the proposed project is exempt from CEQA pursuant to CEQA Guidelines Section 15061(b)(3) – Common Sense Exemption. The proposed project is also categorically exempt from CEOA pursuant to CEOA Guidelines Section 15308 – Actions by Regulatory Agencies for Protection of the Environment, because PAR 1171 is intended to further protect or enhance the environment by reducing the potential exposure to toxic chemicals. Further, there is no substantial evidence indicating that any of the exceptions to the categorical exemption set forth in CEQA Guidelines Section 15300.2 – Exceptions, apply to the proposed project.

Date When Project Will Be Considered for Approval (subject to change):

South Coast AQMD Governing Board Public Hearing: June 6, 2025

CEQA Contact Person: Sina Taghvaee, Ph.D.	Phone Number: (909) 396-2192	Email: staghvaee@aqmd.gov
PAR 1171 Contact Person: Christopher Bradley	Phone Number: (909) 396-2185	Email: cbradley@aqmd.gov

Date Received for Filing: Signature: (Signed and Dated Upon Board Approval)

Kevin Ni Program Supervisor, CEQA Planning, Rule Development, and Implementation

Proposed Amended Rule 1171 Solvent Cleaning Operations



GOVERNING BOARD PRESENTATION June 6, 2025

ATTACHMENT I

Rule 1171 Background

- Adopted in August 1991, most recently amended in 2009
 - Establishes VOC limits for solvent cleaning materials used as part of business or public service
 - Broad applicability and covers many industries
- Proposed amendments needed to:
 - Partially implement 2022 AQMP control measure by phasing out of pCBtF and t-BAc
 - Address concerns at water and electricity distribution operations regarding availability of aerosol denatured alcohol
- Public process began January 2024
 - Three Working Group Meetings
 - One Public Workshop



Phasing Out pCBtF and t-BAc in Solvent Cleaning Materials

- Some solvents are exempt under definition of VOC
 - Used to meet lower VOC limits
- pCBtF and t-BAc are exempt solvents determined to have high cancer potency
 - 2017 Stationary Source Committee directed staff to prioritize toxicity over VOC emissions
- Solvent cleaning formulations
 - No t-BAc use identified
 - Limited use of pCBtF identified and suitable alternatives widely available
- Proposing quick phase out due to limited use
 - Prohibition effective date January 1, 2026
 - One-and-a-half-year sell through in supply chain
 - Two-and-a-half-year use through at shop level





Other Proposed Revisions

Aerosol Exemption

- Changed to monthly allowance better fits industry needs
- Lowered some usage limits to reflect current needs

Cleaning at Utilities

- Allow limited use of liquid alcohol cleaning products instead of aerosols
- Usage threshold to reflect industry needs

Reactivity-based VOC limits

 Allowing alternative reactivity-based limits for printing industry and general cleaning to provide for formulation flexibility

Cleaning Energy Curable Lamps and Reflectors

Carved out a higher VOC limit to allow for limited use of alcohol wipe cleaning

Proposed changes will **Not** increase VOC emissions

Key Issue #1

Recordkeeping, labeling and reporting requirements are too burdensome

- PAR 1171 includes two new recordkeeping requirements to ensure enforceability
 - If a remote reservoir cleaning system is repaired, a record of the repair must be maintained
 - Operators maintain records of VOC content and usage quantities similar to Rule 109 requirements
- Streamlined recordkeeping requirements
- New labeling requirement for alternative Maximum Incremental Reactivity (MIR) VOC limit
 - Only applies if manufacturer opts to comply with alternative limit
- No new reporting requirements

Key Issue #2

Clean Water SoCal, an advocacy group for water agencies, and the International Ultraviolet Association, a non-profit that focuses on advancing UV technologies, requested a rule exemption for cleaning operations at essential public services and cleaning of UV equipment

- Staff worked directly with Los Angeles Department of Water and Power (LADWP) and Metropolitan Water District (MWD) to determine their cleaning needs
- Proposed changes to allow for liquid alcohol use is based on water treatment agencies' request
- Water treatment agencies support usage limits included in PAR 1171

CEQA and Socioeconomic Impact Assessment

California Environmental Quality Act (CEQA)

- Prohibition of pCBtF and t-BAc is health protective and alternative formulations are currently available
- No change in VOC emissions expected
- PAR 1171 qualifies for exemption from CEQA
- Notice of Exemption has been prepared

Socioeconomic Impact Assessment

- PAR 1171 does not significantly affect air quality or emission limitations
- No socioeconomic impact assessment is required pursuant to Health and Safety Code Sections 40440.8 and 40728.5

