

PROPOSED AMENDED RULE 462-

ORGANIC LIQUID LOADING

[Rule index to be added after Amendment]

(a) Purpose

This rule is intended to control emissions of ~~v~~Volatile ~~o~~Organic ~~e~~Compounds (VOC) from ~~f~~Facilities that load ~~o~~Organic ~~l~~Liquids with a True ~~v~~Vapor ~~p~~Pressure of 1.5 psia (77.5 mm Hg) or greater under actual loading conditions into any tank truck, trailer, or railroad tank car and establish Contingency Measures for applicable ozone standards for the reduction of VOC.

(b) Applicability

(1) The provisions of this rule shall apply to all the Organic Liquid loading Facilities that are defined as Class A, B, or C Facilities pursuant to paragraphs (c)(2), (c)(3) and (c)(4), respectively, of this rule.

(2) Subdivision (i) shall not become applicable until the effective date of final and full approval by the United States Environmental Protection Agency (U.S. EPA) of the California State Implementation Plan as meeting the Contingency Measure requirements of the Clean Air Act Sections 172(c)(9) and 182(c)(9) for the Coachella Valley area regarding the 2008 and 2015 ozone National Ambient Air Quality Standards (NAAQS).

~~(b)~~(c) Definitions

For the purpose of this rule, the following definitions shall apply:

(1) BACKGROUND is the ambient concentration of organic vapors in the air measured according to the U.S. EPA Method 21-subsection 4.3.2.

(2) CLASS "A" FACILITY is any ~~f~~Facility which loads 20,000 gallons (75,700 liters) or more on any one day of ~~o~~Organic ~~l~~Liquids into any tank truck, trailer, or railroad tank car.

(3) CLASS "B" FACILITY is any ~~f~~Facility:

(A) which was constructed before January 9, 1976 and loads more than 4,000 gallons (15,140 liters) but not more than 20,000 gallons (75,700 liters) of ~~g~~Gasoline on any one day into any tank truck, trailer, or railroad tank car.

(B) which was constructed before January 9, 1976 and loads not more than 4,000 gallons (15,140 liters) of ~~g~~Gasoline on any one day, but more than

- 500,000 gallons (1,892,500 liters) of ~~g~~Gasoline in any one calendar year, into any tank truck, trailer, or railroad tank car.
- (C) which was constructed after January 9, 1976 and loads not more than 20,000 gallons (75,700 liters) of ~~g~~Gasoline on any one day into a tank truck, trailer or railroad tank car.
- (4) CLASS "C" FACILITY is any ~~f~~Facility existing before January 9, 1976 which loads not more than 4,000 gallons (15,140 liters) of ~~g~~Gasoline on any one day and not more than 500,000 gallons in any one calendar year, into any tank truck, trailer, or railroad tank car.
- (5) CONTINGENCY MEASURE is a control strategy to further reduce VOC emissions if the Coachella Valley area fails to comply with the requirements specified in Clean Air Act, Sections 172(c)(9) and 182(c)(9) regarding the 2008 and 2015 ozone NAAQS. These requirements are making reasonable further progress, attaining the applicable ozone NAAQS by a specified attainment date, and meeting any applicable milestones.
- (6) COUPLER is a component of Transfer Equipment at the interface between the end of the liquid loading line and the loading vessel.
- ~~(5)~~(7) EXEMPT COMPOUNDS are as defined in Rule 102 – Definition of Terms (Rule 102).
- ~~(6)~~(8) FACILITY is ~~an organic liquid or gasoline loading rack or set of such racks that load organic liquid or gasoline into tanks, trailers or railroad cars, which are located on one or more contiguous properties within the District, in actual physical contact or separated solely by a public roadway or other public right of way, and are owned or operated by the same person or persons under common control~~ as defined in Rule 1302 – Definitions.
- ~~(7)~~(9) FACILITY VAPOR LEAK is an escape of organic vapors from a source other than a tank truck, trailer or railroad tank car in excess of 3,000 ppm as methane above background when measured according to U.S. EPA Method 21. A ~~f~~Facility ~~v~~Vapor ~~l~~Leak source does not include liquid spillage or condensate resulting from "~~l~~Liquid ~~l~~Leaks".
- ~~(8)~~(10) GASOLINE is any petroleum distillate or petroleum distillate/alcohol blend or alcohol, except any liquefied petroleum gas (LPG), which has a True ~~v~~Vapor ~~p~~Pressure of 1.5 psia (77.5 mm Hg) or greater under actual loading conditions and is used as a fuel for internal combustion engines.
- (11) INACCESSIBLE COMPONENT is a component of Transfer Equipment located over five (5) meters above ground when access is required from the ground; or

located over two (2) meters away from a platform when access is required from the platform; or located at a position which would require the elevation of a monitoring personnel higher than two (2) meters above permanent support surfaces.

~~(9)~~(12) LIQUID LEAK is a dripping of liquid organic compounds at a rate in excess of three drops per minute from any single leak source other than the liquid fill line and vapor line of disconnect operations.

~~(10)~~(13) LIQUID LEAK FROM DISCONNECT OPERATIONS is defined as: (a) more than two milliliters of liquid drainage per disconnect from a top loading operation; or (b) more than ten milliliters of liquid drainage per disconnect from a bottom loading operation. Such liquid drainage shall be determined by computing the average drainage from three consecutive disconnects at any one loading arm.

(134) OPTICAL GAS IMAGING (OGI) DEVICE is an infrared camera with a detector capable of visualizing gases in the 3.2-3.4 micrometer waveband.

~~(11)~~(15) ORGANIC LIQUID is any liquid compound containing the element carbon that has a True ~~Vapor~~ pPressure of 1.5 psia (77.5 mm Hg) or greater under actual loading conditions excluding liquefied petroleum gases (LPG), methane, carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, ammonium carbonate, and ~~e~~Exempt eCompounds.

(156) RESIDUAL LIQUID is Organic Liquid remaining in the Coupler after disconnection.

~~(12)~~(17) SUBMERGED FILL LOADING is a type of ~~o~~Organic Hliquid loading operations where the discharge opening is completely submerged when the liquid level above the bottom of the vessel is eight centimeters (3.2 inches) or higher.

~~(13)~~(18) SWITCH LOADING is a transfer of ~~o~~Organic Hliquids with a True ~~Vapor~~ pPressure of less than 1.5 psia (77.5 mm Hg) under actual loading condition into any tank truck, trailer or railroad tank car that was loaded with an ~~o~~Organic Hliquid with a True ~~Vapor~~ pPressure of 1.5 psia (77.5 mm Hg) or greater immediately preceding the transfer.

~~(14)~~(19) TRANSFER EQUIPMENT shall consist of all the components of the liquid loading line between any storage tanks, the liquid pump and the transporting vessel, ~~and~~ the vapor return line from the transporting vessel to the storage tank, ~~or to~~ and ~~including~~ the vVapor rRecovery System and/or Vapor Disposal sSystem.

~~(15)~~(20) TRANSPORT VESSEL is a tank truck, trailer or railroad tank car that is equipped to receive and transport ~~o~~Organic Hliquid.

~~(16)~~(21) TRANSPORT VESSEL VAPOR LEAK is an escape of organic vapors from a ~~t~~Transport vVessel in excess of 100 percent of the ~~LEL~~ lower explosive

limit when monitored according to the California Air Resources Board (CARB) Vapor Recovery Test Procedure TP-204.3 – Determination of Leak(s).

(22) TRUE VAPOR PRESSURE is the vapor pressure of a liquid at the temperature at which a product is stored in a stationary container.

~~(17)~~(23) VAPOR DISPOSAL SYSTEM is a control equipment designed and operated to reduce VOC emissions into the atmosphere.

~~(18)~~(24) VAPOR RECOVERY SYSTEM is a vapor gathering system which is capable of collecting and returning discharged hydrocarbon vapors and gases during loading of ~~o~~Organic Liquids into ~~t~~Transport vessels, back to a stationary storage container, or into an enclosed process system.

(25) VISIBLE VAPORS are any VOC vapors detected with an OGI Device, when operated and maintained in accordance with manufacturer training or certification, or equivalent CARB training, user manuals, specifications, and recommendations. Visible Vapors do not include liquid spillage or condensate resulting from Liquid Leaks.

~~(19)~~(26) VOLATILE ORGANIC COMPOUND (VOC) is ~~any volatile compound containing the element carbon, excluding methane, carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, ammonium carbonate, and exempt compounds as defined in Rule 102.~~

~~(e) —~~ Applicability

~~The provisions of this rule shall apply to all the organic liquid loading facilities that are defined as Class A, B or C facilities pursuant to paragraphs (b)(2), (b)(3) and (b)(4) of this rule.~~

(d) Requirements

(1) Loading Requirements at Class A Facilities

(A) Each Class A fFacility shall be equipped with

(i) a CARB certified vVapor ~~r~~Recovery System and/or Vapor dDisposal ~~s~~System, or;

(ii) a ~~District~~South Coast AQMD- approved vVapor ~~r~~Recovery System and/or Vapor dDisposal ~~s~~System only when such system does not require CARB certification pursuant to Health and Safety Code 41954.

(B) Each vVapor ~~r~~Recovery System and/or Vapor dDisposal ~~s~~System at a Class A fFacility shall be equipped with a continuous monitoring system (CMS)

that is installed, operated, and maintained according to the manufacturer's specifications and is approved by the Executive Officer ~~or designee~~.

- (C) The transfer of ~~o~~Organic Liquids shall be accomplished in such a manner that the displaced organic vapors and air are vented under design conditions to the ~~v~~Vapor ~~r~~Recovery System and/or Vapor ~~d~~Disposal system.
 - (D) Each ~~v~~Vapor ~~r~~Recovery System and/or Vapor ~~d~~Disposal system shall reduce the emissions of VOCs to ~~0.080.04~~ pound or less per thousand gallons (~~405~~ grams per 1,000 liters) of ~~o~~Organic Liquid transferred, and shall demonstrate compliance with the VOC emission limit by conducting periodic source testing every 60 months pursuant to the requirements in paragraphs (f)(1) and (f)(8).
 - (E) Any Class A ~~f~~Facility transferring ~~g~~Gasoline into any truck, trailer, or railroad tank car shall be designed and operated for bottom loading only.
 - (F) The ~~t~~Transfer ~~e~~Equipment shall be operated and maintained so that there are no overfills, ~~f~~Facility ~~v~~Vapor Leaks, Liquid Leaks, or Liquid Leaks from disconnect operations.
 - (G) Effective August 1, 2026, the Transfer Equipment shall be operated and maintained so that there are no Visible Vapors.
 - ~~(G)~~(H) The backpressure in the ~~v~~Vapor ~~r~~Recovery System and/or Vapor ~~d~~Disposal system shall not exceed 18 inches of water column pressure.
- (2) Loading Requirements at Class B Facilities
- (A) Each Class B ~~f~~Facility shall be equipped with
 - (i) a CARB certified ~~v~~Vapor ~~r~~Recovery System and/or Vapor ~~d~~Disposal system, or;
 - (ii) a ~~District~~South Coast AQMD- approved ~~v~~Vapor ~~r~~Recovery System and/or Vapor ~~d~~Disposal system only when such system does not require CARB certification pursuant to Health and Safety Code 41954.
 - (B) Such system shall be designed and operated to recover at least 90 percent of the displaced vapors.
 - (C) The backpressure in the ~~v~~Vapor ~~r~~Recovery system and/or Vapor Disposal System shall not exceed 18 inches of water column pressure.
 - (D) Any Class B ~~f~~Facility transferring ~~g~~Gasoline into any truck, trailer, or railroad tank car, shall be designed for bottom loading only.

- (E) The ~~Transfer~~ Equipment shall be operated and maintained so that there are no overfills, ~~Facility~~ Vapor Leaks, Liquid Leaks, or Liquid Leaks from disconnect operations.
- (F) Effective August 1, 2026, the Transfer Equipment shall be operated and maintained so that there are no Visible Vapors.
- (3) Loading Requirements at Class C Facilities
 - (A) Each Class C ~~Facility~~ shall be equipped and operated for ~~Submerged~~ Fill Loading or bottom fill loading. All ~~Gasoline~~ or equivalent True Vapor ~~Pressure~~ Organic Liquids shall be transferred in this manner.
 - (B) The ~~Transfer~~ Equipment shall be operated and maintained so that there are no overfills, Liquid Leaks, or Liquid Leak from disconnect operations.
 - ~~(C) Effective July 1, 2026, the Transfer Equipment shall be operated and maintained so that there are no Visible Vapors.~~
- (4) Loading Requirements for Transport Vessels
 - (A) ~~No person~~ The owner or operator shall not allow loading or unloading of ~~Organic~~ Liquid or other use or operation of any ~~Transport~~ Vessel unless the vessel has a valid certification of vapor integrity as defined by the applicable ~~Air Resources Board~~ CARB Certification and Test Procedures, pursuant to Health and Safety Code Section 41962(g).
 - (B) Transport Vessel Vapor Leaks from dome covers, pressure vacuum vents or other sources shall be determined in accordance with the CARB Vapor Recovery Test Procedure TP-204.3 – Determination of Leak(s).
 - (C) The ~~Transport~~ Vessel shall be operated so that there are no ~~Transport~~ Vessel Vapor Leaks or Liquid Leaks.
- (5) Switch Loading
Uncontrolled ~~Switch~~ Loading is prohibited except at Class C ~~Facilities~~.
- (6) Leak Inspection Requirements
 - (A) The owner ~~and or~~ operator of any Class A, B, or C ~~Facility~~ shall be required to perform an inspection of ~~the vapor collection system, the vapor disposal system, and each loading rack~~ the Transfer Equipment handling ~~Organic Liquids~~; for ~~Facility~~ Vapor Leaks, ~~or~~ Liquid Leaks, ~~of volatile organic compounds or Visible Vapors~~ on one of the following schedules:
 - (i) monthly if sight, sound, and smell are used as detection methods and additionally, effective August 1, 2026, monthly using an OGI Device in accordance with paragraph (d)(7); or-

(ii) quarterly if an organic vapor analyzer (OVA) is used to monitor for ~~f~~Facility ~~v~~Vapor ~~H~~Leaks, and additionally, effective August 1, 2026, monthly using an OGI Device in accordance with paragraph (d)(7).

(B) Each detection of a Facility Vapor HLeak, Liquid Leak, or Visible Vapors shall be repaired or replaced within ~~72 hours~~ three (3) calendar days. The repaired or replacement component shall be reinspected the first time the component is in operation after the repair or replacement.

(7) Optical Gas Imaging Inspections

(A) The owner or operator conducting an OGI inspection shall complete a manufacturer's certification or training program, or equivalent CARB training for the OGI Device used to conduct the inspection.

(B) The owner or operator conducting OGI inspections shall operate and maintain the OGI Device in accordance with the manufacturer's specifications and recommendations.

(C) In lieu of an OGI inspection, the owner or operator may elect to use an alternative inspection method approved in writing by U.S. EPA that is equivalent or more stringent than a monthly OGI inspection. The owner or operator seeking to use an alternative inspection method shall submit the written approval from U.S. EPA to the Executive Officer for their review and independent approval.

(8) South Coast AQMD Inspection Procedures

(A) The owner or operator of a Facility may remove Residual Liquid from a Coupler prior to retesting by South Coast AQMD personnel for compliance determination with subparagraphs (d)(1)(F), (d)(1)(G), (d)(2)(E), (d)(2)(F), (d)(3)(B), and (d)(3)(C).

(B) Effective August 1, 2026, the owner or operator of a Facility shall be in violation of subparagraph (d)(1)(G); or (d)(2)(F), ~~or (d)(3)(C),~~ respectively, if South Coast AQMD personnel detect Visible Vapors unless the owner or operator concurrently demonstrates, or no later than one (1) calendar day after detection for an Inaccessible Component, using an appropriate analyzer in accordance with the test method in paragraph (f)(4) that the Visible Vapors are not a Facility Vapor Leak.

(e) Compliance Schedule

The owner ~~and~~or operator of any Class A, B, or C ~~f~~Facility subject to this rule shall comply with the requirements of subdivision (d) in accordance with the following schedule:

- (1) For Class A ~~f~~Facilities subject to paragraph (d)(1):
- (A) ~~By July 1, 1996, submit an application to the Executive Officer or designee for permit to construct a new or modified vapor recovery and/or disposal system where applicable.~~
- (B) ~~By February 1, 1997, submit a Continuous Monitoring System (CMS) Plan to the Executive Officer or designee for the approval.~~
- (C) ~~By February 1, 1998, demonstrate compliance with the organic vapor emission limit of 0.08 pound per thousand gallons of organic liquid transferred.~~
- ~~(D)~~(A) If required by Health and Safety Code 41954 to equip a Facility with a CARB certified Vapor Recovery System and/or Vapor Disposal System, Within within 30 calendar days after completing construction of a new or modified ~~v~~Vapor ~~r~~Recovery System and/or Vapor dDisposal sSystem, a written request shall be submitted to CARB for certification of the new or modified ~~v~~Vapor ~~r~~Recovery System and/or Vapor dDisposal sSystem.
- ~~(E) CARB Certification or District Approval~~
- ~~(i) Any vapor recovery and/or disposal system subject to clause (d)(1)(A)(i) shall meet the following requirements:~~
- ~~(I) By February 1, 1999, the existing or modified vapor recovery and/or disposal system shall be CARB-certified.~~
- ~~(II) No later than 180 calendar days after completion of construction, any vapor recovery and/or disposal system installed after May 14, 1999 shall be CARB-certified, or;~~
- ~~(ii) By December 31, 1999 or 180 calendar days after completing construction, whichever is later, the vapor recovery and/or disposal system subject to Clause (d)(1)(A)(ii) shall be District approved.~~
- (B) No later than 180 calendar days after completion of construction, any Vapor Recovery System and/or Vapor Disposal System shall be CARB certified or South Coast AQMD approved pursuant to clauses (d)(1)(A)(i) or (d)(1)(A)(ii), respectively.
- (C) No later than February 1, 2027, Title V facilities with a remaining permit term of 3 or more years as of [Date of Amendment], or non-Title V ~~F~~facilities, that do not have an existing permit condition that complies with subparagraph (d)(1)(D), shall submit a permit modification to indicate a VOC emission limit per (d)(1)(D).

- (D) For a new or modified CMS, submit a CMS Plan to the Executive Officer or designee for approval prior to operation.
- (2) For Class B ~~f~~Facilities subject to paragraph (d)(2):
 - ~~(A) — Any vapor recovery and/or disposal system subject to clause (d)(2)(A)(i) shall meet the following requirements:~~
 - (A) If required by Health and Safety Code 41954 to equip a Facility with a CARB certified Vapor Recovery System and/or Vapor Disposal System, within 30 calendar days after completing construction of a new or modified Vapor Recovery System and/or Vapor Disposal System, a written request shall be submitted to CARB for certification of the new or modified Vapor Recovery System and/or Vapor Disposal System.
 - ~~(i) — By February 1, 1999, the existing or modified vapor recovery and/or disposal system shall be CARB-certified.~~
 - ~~(ii) — No later than 180 calendar days after completion of construction, any vapor recovery and/or disposal system installed after May 14, 1999 shall be CARB-certified, or;~~
 - ~~(B) — By December 31, 1999 or 180 calendar days after completion of construction, whichever is later, the vapor recovery and/or disposal system subject to clause (d)(2)(A)(ii) shall be District approved.~~
 - (B) No later than 180 calendar days after completion of construction, any Vapor Recovery System and/or Vapor Disposal System shall be CARB certified or South Coast AQMD approved, pursuant to clauses (d)(2)(A)(i) or (d)(2)(A)(ii), respectively.
- (3) ~~For Class B facilities that were Class C facilities prior to June 9, 1995 and now are subject to paragraph (d)(2):~~
 - ~~(A) — By January 1, 1996, submit an application to the Executive Officer or designee for permit to construct and permit to operate a vapor recovery system where applicable.~~
 - ~~(B) — By February 1, 1998, demonstrate compliance with the requirement of 90 percent recovery of displaced vapors.~~
 - ~~(C) — Within 30 calendar days after completing construction of a new or modified vapor recovery system, a written request shall be submitted to CARB for certification of the new or modified vapor recovery and/or disposal system.~~
 - ~~(D) — CARB Certification or District Approval~~
 - ~~(i) — Any vapor recovery and/or disposal system subject to clause (d)(2)(A)(i) shall meet the following requirements:~~

~~(I) — By February 1, 1999, the existing or modified vapor recovery and/or disposal system shall be CARB certified.~~

~~(II) — No later than 180 calendar days after completion of construction, any vapor recovery and/or disposal system installed after May 14, 1999 shall be CARB certified, or;~~

~~(ii) — By December 31, 1999 or 180 calendar days after completion of construction, whichever is later, the vapor recovery and/or disposal system subject to clause (d)(2)(A)(ii) shall be District approved.~~

(f) Compliance Determination/Test Methods

(1) Compliance with the emission limit of organic vapors as specified in the subparagraph (d)(1)(D) shall be determined according to U.S. EPA Method 25A, 25B or SCAQMD South Coast AQMD Method 501.1, as applicable.

(2) Continuous Monitoring System required pursuant to subparagraph (d)(1)(B) shall be in compliance with Code of Federal Regulations Title 40 Part 63 Subpart R Section 63.427 and Code of Federal Regulations Title 40 Part 60 Appendix B, as applicable.

(3) Compliance with the vapor recovery efficiency as specified in the subparagraph (d)(2)(B) shall be determined according to the CARB Vapor Recovery Certification Procedure CP-202 – Certification Procedure for Vapor Recovery Systems of Bulk Plants or, for the ~~∅~~Vapor ~~∅~~Recovery System and/or Vapor ∅Disposal ~~∅~~System subject to ~~∅~~clause (d)(2)(A)(ii), the ~~SCAQMD South Coast AQMD Approval Procedure for Vapor Recovery Systems of Bulk Plants dated May 14, 1999.~~

(4) Determinations of ~~∅~~Facility ~~∅~~Vapor ~~∅~~Leaks as defined in the paragraph ~~(b)(7)~~ shall be conducted according to U.S. EPA Method 21.

(5) Compliance with the requirements of ~~District South Coast AQMD~~ approval for ~~∅~~Vapor ~~∅~~Recovery System and/or Vapor ∅Disposal ~~∅~~Systems as specified in subparagraphs (d)(1)(A) and (d)(2)(A) shall be determined according to the ~~District South Coast AQMD Approval Procedure for Vapor Recovery Systems for Bulk Plants dated May 14, 1999.~~ All testing required in the ~~District South Coast AQMD Approval Procedure for Vapor Recovery and/or Disposal System~~ shall be conducted by testing firms/laboratories that have been approved by the ~~District South Coast AQMD~~ for the specific tests under the Laboratory Approval Program.

(6) Any other alternative test method approved in writing by the ~~District South Coast AQMD~~, CARB, and U.S. EPA may be used only when none of the test methods identified in this subdivision are applicable.

- (7) When more than one test method or set of test methods are specified for any testing, a violation of any requirements of this rule established by any one of the specified test methods or set of test methods shall constitute a violation of the rule.

(8) Source Testing

The owner or operator of a Facility required to conduct source testing shall:

- (A) Prior to conducting source testing to demonstrate compliance, submit a source test protocol for approval to the Executive Officer;
- (B) Submit an updated or new source test protocol if there are any modifications to the Vapor Recovery System and/or Vapor Disposal System or if the Executive Officer requests an updated or new source test protocol;
- ~~(C) Report the source testing schedule to the Executive Officer at least 10 calendar days prior to the start of any source testing;~~
- ~~(D) Report any changes to the source testing schedule no later than 24 hours prior to the start of source testing or within one (1) hour of discovery of a change in the source testing schedule;~~
- (C) Submit a source test protocol for facilities that have not already been conducting periodic source testing by August 1, 2026, and conduct the source test by August 1, 2027;
- (D) Conduct source testing pursuant to the most recent source test protocol approved by the Executive Officer; and
- (E) Submit the source testing report to the Executive Officer within 60 days of completing all sampling for source testing.
- (9) The True Vapor Pressure of Organic Liquid shall be determined by ASTM Method D-323 for Reid vapor pressure, or ASTM Method D-6377 correlated to ASTM D-323, and converted to True Vapor Pressure using applicable nomographs in EPA AP-42 or South Coast AQMD and EPA approved nomographs. The actual storage temperature used for determining True Vapor Pressure shall be 70 degrees Fahrenheit for Organic Liquids that are stored at ambient temperatures, and actual storage temperature for Organic Liquids that are stored at above ambient temperatures.

(g) Recordkeeping Requirements

- (1) The owner ~~and~~or operator of any Class A, B, or C ~~Facility~~, in order to verify the classification of such ~~Facility~~, shall maintain a daily log of the throughput and a summary of the throughput for the calendar year to date, of the liquid organic

compounds subject to the provisions of this rule. A log showing daily compliance shall suffice to satisfy this requirement.

- (2) The owner ~~and~~or operator of any Class A, B, or C ~~f~~Facility shall maintain records for verification of compliance with the requirements in paragraphs (d)(6) and (d)(7). The records shall include, ~~but are not limited to~~, inspection dates, description of leaks detected, repair/replacement dates, and reinspection dates.
- (3) All records shall be maintained at the ~~f~~Facility for at least two years or a period of five years for a Title V Facility and shall be made available to the Executive Officer ~~or designee~~ upon request.

(h) Distribution of Responsibilities

- (1) The owner and operator of any Class A, B, or C ~~f~~Facility shall be responsible and liable for complying with the provisions of paragraphs (d)(1), (d)(2), (d)(3), ~~and (d)(6), (d)(7), and (f)(8)~~ and subdivisions (e) and (g) of this rule, and for maintaining the equipment at the ~~f~~Facility in such condition that it can comply with the requirements of this rule if properly operated. If employees of the owner or operator of the ~~f~~Facility supervise or affect the transfer operation, the owner or operator of the ~~f~~Facility shall be responsible for ensuring that the transfer operation complies with all requirements of this rule and that the ~~t~~Transfer ~~e~~Equipment is properly operated.
- (2) The owner, operator, and driver of a ~~t~~Transport ~~v~~Vessel shall be responsible and liable for complying with paragraphs (d)(4) and (d)(5) of this rule.

(i) Ozone Contingency Measure

- (1) On and after 60 days following the effective date of a final rule by U.S. EPA that the conditions described in Clean Air Act Sections 172(c)(9) and 182(c)(9) have occurred in the Coachella Valley area regarding the 2008 or 2015 ozone NAAQS, the Contingency Measure specified in paragraph (i)(2) shall be implemented.
- (2) The owner or operator of any Class A, B, or C Facility shall be required to perform an inspection of Transfer Equipment for Visible Vapors at least once every two (2) calendar weeks using an OGI Device in accordance with paragraph (d)(7).

~~(i)~~(j) Exemptions

- (1) The provisions of subparagraphs (d)(1)(F), ~~(d)(1)(G)~~, (d)(2)(E), ~~(d)(2)(F)~~ and (d)(3)(B), ~~and (d)(3)(C)~~ shall not apply to components found in violation of ~~f~~Facility ~~v~~Vapor Hleaks, ~~or H~~liquid Hleaks, ~~either of which is or~~ Visible Vapors detected and recorded originally by the owner or operator, provided the repair or

replacement of applicable equipment is completed within the specified period as given in subparagraph (d)(6)(B).

- (2) The provisions of subparagraphs (d)(1)(A), and (d)(1)(B) shall not apply to ~~v~~Vapor ~~r~~Recovery Systems and/or Vapor ~~d~~Disposal sSystems which vent displaced hydrocarbon vapors to an adjacent refinery flare or other combustion device that receives gaseous streams from other refinery sources.
- ~~(3) The provisions of subparagraph (d)(6)(A) for the monthly usage of an inspection using an OGI Device shall not apply to Class C F facilities.~~
- ~~(4) The provisions of Rules 466 and 466.1 shall not apply to F facilities subject to this rule.~~
- ~~(5) The provisions of subparagraphs (d)(6), (d)(7), and (d)(8) of this rule shall not apply to equipment subject to the requirements of Rule 1173.~~